

Network Architecture and Security

ECAM STRASBOURG-EUROPE 2018-2019

LECTURER: ROMAIN ORHAND (ROMAIN.ORHAND@ECAM-STRASBOURG.EU)

OSI Model, DHCP and DNS

OSI Model

The **Open Systems Interconnection model** is a conceptual model that **characterizes and standardizes** the different abstraction layers required for enabling communication between computers over a network.

- 7. Application
- 6. Presentation
- 5. Session
- 4. Transport
- 3. Network
- 2. Data-link
- 1. Physical layer

OSI Model – The layers in detail

7. Application

6. Presentation

5. Session

4. Transport

3. Network

2. Data-link

1. Physical layer

OSI Model – The layers in detail

7. Application

6. Presentation

5. Session

4. Transport

3. Network

2. Data-link

1. Physical layer

OSI Model – The layers in detail

7. Application

6. Presentation

5. Session

4. Transport

3. Network

2. Data-link

1. Physical layer

OSI Model – The layers in detail

7. Application

6. Presentation

5. Session

4. Transport

3. Network

2. Data-link

1. Physical layer

OSI Model – The layers in detail

7. Application

6. Presentation

5. Session

4. Transport

3. Network

2. Data-link

1. Physical layer

OSI Model – The layers in detail

7. Application

6. Presentation

5. Session

4. Transport

3. Network

2. Data-link

1. Physical layer

OSI Model – The layers in detail

7. Application

6. Presentation

5. Session


4. Transport

3. Network


2. Data-link

1. Physical layer


OSI Model and Addressing




Encapsulation




Encapsulation – dealing with addresses



Internet – A Little Reminder



Internet – A Little Reminder



Remember « I want to read my mails ? » use case

OKAY, SO KEEP ALSO IN MIND THE OSI LAYERS ;)

HTTP



We need to retrieve a web page. So we will use the **Hypertext Transfer Protocol (HTTP)**.

Some request methods : GET, POST, PUT, DELETE, ...

Example : GET <http://www.ecam-strasbourg.eu/> HTTP/1.1

Domain Name Service

The DNS protocol **enables to retrieve the IP address** of machine, **given its hostname**.

Given this URL from the previous example, <http://www.ecam-strasbourg.eu/>

We can divide it in :


A Protocol	The hostname	The file name
<u>http</u>	<u>:// www.ecam-strasbourg.eu</u>	<u>/ index.html</u>

Domain Name Service


Two types of request :

- Recursive request : request processed by the DNS cache
- Iterative request : request forwarded to the DNS server hierarchy


Domain Name Service – Recursive Request



Domain Name Service – Iterative Request




Dynamic Host Configuration Protocol




DHCP is a protocol triggered by client computer **to get an IP address lease** from a computer serving as a DHCP server.


Dynamic Host Configuration Protocol




Dynamic Host Configuration Protocol



Dynamic Host Configuration Protocol



Dynamic Host Configuration Protocol




Dynamic Host Configuration Protocol

50% of the lease time

If failure:
87,5% of the lease time

If failure:
At 100% of the lease time,
Full DHCP lease process





Any questions ?

Exercise 1

What is the meaning of the OSI acronym? Explain what OSI is.

Exercise 1

What is the meaning of the OSI acronym? Explain what OSI is.

The OSI is the Open System Interconnection. It characterizes and standardizes the different abstraction layers required for enabling communication between computers over a network.

Exercise 2

Name the seven layers of the OSI model.

Exercise 2

Name the seven layers of the OSI model.

Application – Presentation – Session – Transport – Network – DataLink - Physical

Exercise 3

Make the bound between the OSI Model and the following devices : a hub, a switch and a router.

Exercise 3

Make the bound between the OSI Model and the following devices : a hub, a switch and a router.

A hub will operate on the Physical layer (first one).

A switch will operate on the DataLink layer (second one).

A router will operate on the Network layer (third one).

Exercise 4

Name and explain the four primitives of a DHCP request.

Exercise 4

Name and explain the four primitives of a DHCP request.

DHCP DISCOVER: broadcast message sent by the client to the network to discover DHCP servers

DHCP OFFER: sent by the server to the client to offer its service as a DHCP server

DHCP REQUEST: sent by the client to the server to ask for a DHCP lease

DHCP ACK: confirmation sent by the server to the client to confirm lease is successful and to give the lease IP address to the client.

Exercise 5


What happens when no DHCP server is available at lease time?

Make a paquet-exchange diagram.

Exercise 5

What happens when no DHCP server is available at lease time?

Make a paquet-exchange diagram.




Exercice 6

What happens when a client A requests the IP address for hostname 'www.ecam-rennes.fr' ?
Draw the packet-exchange diagram.

Exercise 6

What happens when a client A requests the IP address for hostname 'www.ecam-rennes.fr' ?
Draw the packet-exchange diagram.

An iterative DNS request is performed.



Exercise 6

Right after request defined just previously, a client B requests for the same hostname.

Draw the packet-exchange diagram.

Exercise 6

Right after request defined just previously, a client B requests for the same hostname.
Draw the packet-exchange diagram.

A recursive DNS request is performed.

