

# Performance Analysis of MySQL, Neo4j, and Postgres

Performance Analysis of MySQL, Neo4j, and Postgres using Different Data Scenarios


**Institute:** Eastern Switzerland University of Applied Science  
**Program:** MSc Computer Science  
**Course:** DB Seminar  
**Author:** Roman Bögli  
**Supervisor:** Prof. Stefan F. Keller  
**Stage:** *interim*  
**Date:** 14. April 2023

# Content

- Relational DBMS vs. Graph-Based DBMS
- Tool gobench
- Synthetic Script & Substitution
- Custom Scripts ( merchant , employees , friends )
- Automation
- Result Analysis
- Open Work


# Relational DBMS

- Tables are entities
- Relationships using keys
- Homogenous data through schema



# Graph-Based DBMS

- Attributed nodes and edges
- Relationships are first class elements
- Heterogenous data (schema-less)



# Query Languages

Query adult customers

```
-- SQL
SELECT * FROM Customer c WHERE c.Age >= 18

-- Cyper
MATCH (c:Customer) WHERE c.Age > 18 RETURN c;
```


Show top clients based on revenue

```
-- SQL
SELECT c.CustomerId, c.Name, SUM(p.Total) FROM Customer c
INNER JOIN Purchase p on c.CustomerId = p.CustomerId
GROUP BY c.CustomerId, c.Name ORDER BY SUM(p.Total) DESC

-- Cyper
MATCH (c:Customer)-[:MAKES]->(p:Purchase)
RETURN c.Name, SUM(p.Total) AS TotalOrderValue ORDER BY TotalOrderValue DESC
```

# System Setup

- Requirements:
  - Docker
  - Go
  - gobench



# Command Line Interface (CLI)

- Open terminal and navigate to the location of `main.go`

```
$ cd ~/path/to/gobench/cmd
```

- Interact with `go run main.go` to see flags

```
► go run main.go -h
Available subcommands:
    mysql | postgres | neo4j | mergecsv | createcharts
    Use 'subcommand --help' for all flags of the specified command.
pflag: help requested
exit status 2
```

# Possilbe CLI Commands

```
# run synthetic INSERT and SELECT statements against MySQL, each 100x
$ go run main.go mysql --host 127.0.0.1 --port 3306 --user "root" \
    --pass "password" --iter 100 --run "inserts selects"
```

```
# run statemets of custom script against Postgres, save results in file
$ go run main.go postgres --host 127.0.0.1 --port 5432 --user "postgres" \
    --pass "password" --iter 100 --script "./path/to/mysql.sql" \
    --writecsv "./path/to/results/mysql.csv"
```

```
# merge serveral result files
$ go run main.go mergecsv \
    --rootDir "~/path/with/csv-files/to-be-merged"
    --targetFile "~/anypath/allresults.csv"
```

```
# visualize the benchmarking results
$ go run main.go createcharts \
    --dataFile "~/anypath/allresults.csv" --charttype "line"
```



# Custom Script (merchant)

```
-- INIT
\benchmark once \name initialize
DROP SCHEMA IF EXISTS gobench CASCADE;
CREATE SCHEMA gobench;
CREATE TABLE gobench.Customer (CustomerId INT PRIMARY KEY, Name VARCHAR(10), ... );
CREATE TABLE gobench.order (OrderId INT PRIMARY KEY, CustomerId INT NOT NULL, ... );

-- INSERTS
\benchmark loop 1.0 \name inserts
INSERT INTO gobench.Customer (CustomerId, Name, Birthday)
VALUES ( {{.Iter}}, '{{call .RandString 3 10 }}', '{{call .RandDate }}');

INSERT INTO gobench.Order (OrderId, CustomerId, CreationDate, Comment)
VALUES( {{.Iter}}, (SELECT CustomerId FROM gobench.Customer ORDER BY RANDOM() LIMIT 1),
        '{{call .RandDate }}', '{{call .RandString 0 50 }}');

-- SELECTS
\benchmark loop 1.0 \name select_simple
SELECT * FROM gobench.Customer WHERE CustomerId = {{.Iter}}

-- CLEAN
\benchmark once \name clean
DROP SCHEMA IF EXISTS gobench CASCADE;
```

# Statement Substitutions

Sequences of the following patterns will be substituted before the statement is executed:

`{{.Iter}}` --> The iteration counter. Will return 1 when `\benchmark` once .

`{{call .RandIntBetween 1 100}}` --> Random integer between `1` and `100` .

`{{call .RandFloatBetween 0 1}}` --> Random float between `0` and `1` .

`{{call .RandString 3 15}}` --> Random string with length between `3` and `15` .

`{{call .RandDate}}` --> Random date.


# Custom Script (employees)

Show all subordinates of an employee (tree queries)

```
-- use WITH RECURSION notation in Postgres (similar in MySQL)
WITH RECURSIVE hierarchy AS (
    SELECT employeeId, firstname, boss_id, 0 AS level
    FROM gobench.employee
    WHERE employeeId = {{.Iter}}
    UNION ALL
    SELECT e.employeeId, e.firstname, e.boss_id, hierarchy.level + 1 AS level
    FROM gobench.employee e JOIN hierarchy ON e.boss_id = hierarchy.employeeId
)
SELECT * FROM hierarchy;

-- simpler query using Cypher
MATCH (boss)-[:BOSS_OF*1..]->(sub) WHERE boss.employeeId={{.Iter}} RETURN sub;
```

see example graph on next slide ...



# Custom Script ( **friends** )

Show the shortest acquaintance path of two people (cyclic graph queries)

```
*****  
***** `WORK IN PROGRESS` *****  
*****
```

# Automation

```
$ bash bashscript.sh
```

```
start_time=`date +%s`  
echo -e "\nSTART BENCHMARKING...\n"  
for MULT in "${MULTIPLICITIES[@]}"; do  
    echo $(for i in $(seq 1 50); do printf "_"; done)  
    echo -e "\nITERATIONS: ${MULT}"  
  
    echo -e "\nTEST MYSQL"  
    go run $gobench_main_path mysql \  
        --host $db_host \  
        --port $mysql_port \  
        --user $mysql_user \  
        --pass $mysql_pass \  
        --iter $MULT \  
        --threads $threads \  
        --script "${script_base_path}/${script_set}/mysql.sql" \  
        --writecsv "${result_base_path}/${script_set}/mysql_${MULT}.csv"
```

see demo on next slide...


```
~/documents/gits
```



# Result Analysis

Generating a `chart.html` file to visualize


- average amount of microseconds (  $\mu s$  ) per benchmark (the lower the better)
- operations per second (the higher the better)
- microseconds per operation (the lower the better)



1 second (s) = 1'000'0000 microseconds ( $\mu s$ )




Chart 3.0: (loop) select\_before\_index



1 second (s) = 1'000'0000 microseconds (μs)

Chart 3.0: (loop) select\_before\_index



1 second (s) = 1'000'0000 microseconds (μs)

# Open Work

| CLI Tool   | Custom Scripts   | Writing  |
|--|--|--|
| <ul style="list-style-type: none"><li>✓ Benchmarking</li><li>✓ Result consolidation</li><li>✓ Chart generation</li></ul> | <ul style="list-style-type: none"><li>✓ merchant</li><li>✓ employees</li><li>○ friends</li></ul> | <ul style="list-style-type: none"><li>✓ Abstract</li><li>✓ Intro</li><li>○ System specs &amp; setup</li><li>○ Benchmarking approaches</li><li>○ Result analysis &amp; conclusion</li></ul> |

# References

- Chauhan, C., & Kumar, D. (2017). PostgreSQL High Performance Cookbook: Mastering query optimization, database monitoring, and performance-tuning for PostgreSQL. Packt Publishing.
- Codd, E. F. (2002). A Relational Model of Data for Large Shared Data Banks. In M. Broy & E. Denert (Eds.), Software Pioneers (pp. 263–294). Springer Berlin Heidelberg. [https://doi.org/10.1007/978-3-642-59412-0\\_16](https://doi.org/10.1007/978-3-642-59412-0_16)
- Elmasri, R., & Navathe, S. (2011). Fundamentals of Database Systems (6th ed). Addison-Wesley.
- Gregg, B. (2020). Systems Performance: Enterprise and the Cloud (Second). Addison-Wesley.
- Needham, M., & Hodler, A. E. (2019). Graph Algorithms: Practical Examples in Apache Spark and Neo4j (First edition). O'Reilly Media.
- Peixoto, T. P. (n.d.). What is graph-tool? Graph-Tool. Retrieved 20 March 2022, from <https://graph-tool.skewed.de/>
- Robinson, I., Webber, J., & Eifrem, E. (2015). Graph Databases: New Opportunities for Connected Data.
- Stopford, B. (2012, August 17). Thinking in Graphs: Neo4J. <http://www.benstopford.com/2012/08/17/thinking-in-graphs-neo4j/>

**Thanks**