

Deploy Storefront Next to Managed Runtime (MRT)

Contents

[Prerequisites](#)[Steps](#)[See Also](#)

To redeploy a storefront that was created in Business Manager after initial deployment, use the Storefront Next CLI and the autogenerated MRT project and environment.

Prerequisites

- Node Package Manager (pnpm) version 10.28.0 or later. See [Installation](#) on the pnpm site.
- Node.js version 24.13.0 or later. See [Download Node.js](#) on the Node.js site.
- To install Storefront Next dependencies specified in `package.json`, run the `pnpm install` command.

Steps

1. In Business Manager, navigate to your storefront. Click App Launcher , then select **Administration > Sites > Storefronts > New**, and click your storefront.
2. In the storefront detail page, click your environment, and then next to Deployments, click **Manage**.
3. Log in to Runtime Admin.
4. Take note of the project ID and environment ID.
5. To authenticate the CLI to Managed Runtime, use an API key. Get the Managed Runtime API key in Managed Runtime Admin. In Account Settings, under Personal API Key, do one of these steps.
 - a. If you haven't yet created an API key, click **Generate**.

[Try for free](#)

6. From your local storefront folder, use this command to create a bundle and deploy it to your Managed Runtime environment. Replace the placeholders with the MRT project ID, target environment, and the API key you got earlier.



```
1 pnpm sfnext push --project {m
2 --message "Deploying quick st
```



```
push command from
another folder outside your
storefront, use pnpm dlx
@salesforce/storefront
-next-dev push instead
and pass in the storefront
folder path with --
project-directory
{sfnext-project-
folder}.
```

**Note**

The `.env` file in your Storefront Next project folder contains environment variables that the Storefront Next CLI uses. You can set the project ID in the `SFCC_MRT_PROJECT` variable (or `MRT_PROJECT`), the target environment in the `SFCC_MRT_ENVIRONMENT` variable (or `MRT_TARGET`), and the API key in the `SFCC_MRT_API_KEY` variable instead of specifying them on the command line. If you specify these values in both the command line and the `.env` file, the command line arguments are used. To upload only the bundle to MRT and not deploy it, don't specify the `--environment` option and remove the `SFCC_MRT_ENVIRONMENT` and `MRT_TARGET` variables from the `.env` file.

7. Verify that the bundle was deployed to the target environment. In Managed Runtime Admin, in Projects, click your project and then your environment.

See Also

- [CLI Reference](#)
- [B2C DX CLI Documentation on GitHub: Storefront Next](#)