

Automate Environment Administration with the Managed Runtime API

Use the Managed Runtime API to automate the administration tasks in your app. The API offers similar capabilities like the Runtime Admin, in addition to administration options.

Considerations for Using Managed Runtime API

 Warning

The Managed Runtime API is for administration purposes only. Do *not* make requests to the API in your storefront code. Requests that exceed [Managed Runtime API Rate Limits](#) are

[Considerations for Using Managed Runtime API](#)

- [Before You Begin](#)
- [List Environments](#)
- [Create an Environment](#)
- [Modify Proxy Configuration](#)
- [Set Up Automation Users](#)
- [Managed Runtime API Rate Limits](#)
- [Projects and Environments](#)
- [Cache Invalidations](#)
- [Default Rate Limits](#)
- [Next Steps](#)
- [See Also](#)



section doesn't list the B2C CLI. We recommend creating an environment in Business Manager in **Administration > Storefronts > {Your Storefront}**.

- To read [environment variables](#) from the storefront, use `process.env` [↗](#).
- To read and load [redirects](#) use the managed endpoint `/mobify/redirects/$path`.

Before You Begin

Note

The Mobify brand name still appears in the `mobify.com` domain in the base URL for the Managed Runtime API. Although new Salesforce domains will eventually take the place of the Mobify domain, support for the Mobify domain will continue.

To make API requests, you must include an API key in the HTTP request `Authorization` header with the value, `Bearer $API_KEY`. To find your API key, log in to the [Runtime Admin](#) [↗](#) tool and go to the [Account Settings](#) [↗](#) page.



password because it allows scripts to perform operations on your behalf.

This tutorial uses sample curl requests. Before running the commands, replace any placeholders with actual values. Placeholders are formatted as `$PLACEHOLDER`. Replace `$PROJECT_ID` with your actual project ID. To get the project ID, see [Find a Project](#).

Project IDs can be up to 20 characters long and must be unique globally.

List Environments

Call the [projects_target_list](#) API endpoint to list the environments (called “targets” in the API) for a project:

```
</> | [icon]
1 curl "https://cloud
2 --header "Authori
```

Create an Environment

Create a `staging` environment to verify changes before deploying to `production`.



Important

Environments created via the Managed Runtime API



[projects_target_create](#) API endpoint. If you're also creating a project, call the [projects_create](#) API endpoint to create an environment:

```
</> 1 curl "https://cloud
2 --request 'POST'
3 --header 'Authori
4 --header 'Content
5 --data '{"name":
```

Then call the [cc_b2c_target_info_update](#) API endpoint to connect a B2C Commerce instance and one or more sites to the environment.

```
</> 1 curl "https://cloud
2 --request 'PUT' \
3 --header 'Authori
4 --header 'Content
5 --data '{"instanc
```

To use your new environment, [deploy a bundle](#) to it.

Call the [projects_target_retrieve](#) API endpoint to review the `staging` environment:

```
</> 1 curl "https://cloud
2 --header "Authori
```

Modify Proxy Configuration

Call the [projects_target_partial_update](#) API endpoint to modify the proxy configuration for `staging`:

```
</> |
```



```
5 --data '{"ssr_pro
```

Changing the configuration redeploys the deployed bundle so that the configuration update takes effect.

Troubleshoot the Managed Runtime API Requests

If you're having trouble using the API, try these troubleshooting steps.

- Add the `--fail` argument to your `curl` command.
- Check your API key.
- Check your project's ID.

The API endpoints also work in a browser. Log in to the [Runtime Admin](#) tool, and then open the endpoint in your browser.

Set Up Automation Users

To support continuous integration and deployment using the Managed Runtime API, create an Account Manager user for automation:

- Create a user account in Account Manager using a shared email address such as a Google Group. Store the associated credentials and MFA code in a password manager such as LastPass.
- Give the user the `Managed Runtime`



The user's Managed Runtime API key can only access what the user's permissions allow. Keep it specific to the projects that CI/CD needs to interact with.

- Create the API key for the user and save it in your continuous integration system.

To keep the Managed Runtime API key active, update the related Account Manager account password as required by your organization's Account Manager configuration. If the user is deactivated, reset the password to reactivate the account and re-enable the API key.

Managed Runtime API Rate Limits

The Managed Runtime API has rate limits in place for the number of requests allowed per unit of time. Rate limits are applied on a per-user basis, and help ensure fair access for all users.

If your request exceeds a rate limit, the API returns an HTTP 429 Too Many Requests error, and a Retry-After HTTP header that indicates the number of seconds to wait until you can retry. API rate limits can't be adjusted.

These tables list the rate limits for different API families.



Important

Some endpoints have cumulative



cumulative rate limits throttle the combined number of requests across multiple endpoints. All GET requests have a cumulative rate limit. Similarly, all POST, PATCH, and DELETE requests for endpoints that are not individually called out in the following tables have a cumulative rate limit. These limits are described in [Default Rate Limits](#).

Projects and Environments

Method	Endpoint
POST	/api/projects
PATCH	/api/projects
DELETE	/api/projects
POST	/api/projects
POST	/api/projects
PATCH	/api/projects
DELETE	/api/projects
POST	/api/projects