

Launch Your Storefront Next

Launch your new storefront and make it accessible from its official, public web address.

Before running the commands, replace any placeholders with actual values.

Contents

Before You Begin

Launching an Environment

1. Import the Storefront to the Staging or Production Instance
2. Perform the Cutover
3. Monitor the Site

Before You Begin

- To perform administrative tasks, you must have one of these roles and permissions:
 - Managed Runtime roles: **Managed Runtime User** or **Managed Runtime Admin**. To request access, contact your B2C Commerce administrator and ask them to add one of these roles to your account in Account Manager.
 - Business Administrator role in Account Manager or a role for the Business Manager Module and Organization context with read-write access to storefronts. See [Create a Role in B2C Commerce](#)  in *Salesforce Help*.
- To make requests to the [Managed Runtime API](#), you must include an API key in the HTTP request `Authorization` header with the value, `Bearer $API_KEY`. For all the sample requests provided, replace `$API_KEY` with your actual API key. To find your API key, log in to [Runtime Admin](#)  and go to the [Account Settings](#)  page.



Important

Treat your API key like a password because it allows scripts to complete operations on your behalf.

- Have access to your DNS provider to create and update CNAME records, and access to your third-party CDN provider (as applicable).



production. The only difference is the domain name and Managed Runtime environment.

 Warning

We strongly recommend going through the launch process on a staging environment before running it on production. Complete these steps as soon as you start a Storefront Next project and at least two weeks before your launch date.

1. Import the Storefront to the Staging or Production Instance

Before you can launch the storefront in another instance, export it from the sandbox or development instance, and then import it to the staging or production instance. The storefront import creates an initial environment that you can deploy a bundle to from the sandbox or development instance.

 Note

You can only export, and therefore import, one storefront at a time. Repeat these steps for each storefront, if necessary.

1. Export the storefront and its associated data, such as sites, catalogs, and price books. Follow the steps in [Site Import/Export to Copy Instances and Development Testing in B2C Commerce](#)  in *Salesforce Help*.
2. In the staging or production instance, import the exported archive file. After the storefront import process finishes, the `sfcc-post-import-setup-storefront` job starts. It sets up an Account Manager API client, a SLAS client, a default environment, and an eCDN default domain. Then it deploys an initial bundle. If errors occur for this job, check the job logs in **Administration > Operations > Jobs**. See [Managing Jobs](#)  in *Salesforce Help*.
3. After import, deploy the storefront bundle to the staging or production environment.



production, configure eCDN routing only for vanity domains or for new zones.

Default Domain

Default domains and default zones don't require eCDN configuration. Environments created in Storefront Next are preconfigured with eCDN and a default domain, which is routed to the Managed Runtime domain.

Vanity Domain or New Zone

If you're using a vanity domain or a new zone:

1. Update your eCDN routing rules to route traffic to your Managed Runtime environment. For more information, see [Traffic Routing for PIG Instances with eCDN](#), or [configure MRT Routing Rules in Business Manager](#).
2. Update access control headers to allow only trusted traffic from eCDN to your MRT origin. That way, bots and crawlers can't access your MRT origin and negatively impact SEO.

Set the MRT Access Control Header

Set an environment's access control header using Runtime Admin's Access Control Settings or the [access_control_header](#) API.

In this example, we use the Managed Runtime API to set an access control header with the header value `25pn5dec7f1c` :

```
1 curl "https://cloud.mobify.com/api/pr
2   --header "Authorization: Bearer $AP
3   --header 'Content-Type: application
4   --data '{ "value" : "25pn5dec7f1c"
```

Send the Access Control Header from eCDN to the MRT Origin

Use the [upsertOriginHeaderModification](#) API in B2C Commerce API (SCAPI) to set the headerValue. This example shows how to call this SCAPI endpoint to set an access control header with the header value `25pn5dec7f1c` :

```
1 curl "https://$CODE.api.commerceclou
2   --method 'PUT' \
```

[Try for free](#)

3. Monitor the Site

Salesforce Customer Success monitors the site's traffic to confirm that the launch succeeded. After launch, customers with a Signature Success Plan receive proactive site monitoring. To use this monitoring service, mark your environment as `production`. For more information, see the section on [environments](#) in Managed Runtime Overview. Also, monitor the eCDN and MRT metrics in Log Center, in the [Metrics Dashboard](#). See [Embedded Content Delivery Network \(eCDN\) Metrics](#) and [Managed Runtime Metrics](#) in *Salesforce Help*.

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)

DEVELOPER CENTERS

[Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)

POPULAR RESOURCES

[Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[AppExchange](#)

COMMUNITY

[Trailblazer Comrn](#)
[Events and Caler](#)
[Partner Commun](#)
[Blog](#)
[Salesforce Admir](#)
[Salesforce Archit](#)

© Copyright 2026 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#)

[Use of Cookies](#) [Cookie Preferences](#) [Your Privacy Choices](#)

