

Project Structure Differences with PWA Kit

PWA Kit organizes most app code under `app/` with centralized route definitions and explicit runtime entry files. Storefront Next shifts to `src/`, file-based routes, and framework conventions around root and route modules. The outcome is a more convention-driven layout with clearer boundaries for routes, providers, middleware, and adapters.

Contents

Directory Structure

[Entry Points](#)[Configuration Approach](#)[Key Differences](#)[Storefront Conversion Considerations](#)[References](#)

Directory Structure

Aspect	PWA Kit	Storefront Next
Source Directory	<code>app/</code>	<code>src/</code>
Page Components	<code>app/pages/</code>	<code>src/routes/</code>
Configuration	<code>config/</code> (JS)	<code>config.server.ts</code> file
Translations	<code>translations/</code> (JSON)	<code>src/locales/</code>
Static Assets	<code>app/static/</code> , <code>app/assets/</code>	<code>public/</code>
Theme/Styles	<code>app/theme/</code> (Chakra)	<code>src/app.css</code> (Tailwind)
Type Definitions	N/A (JavaScript)	<code>types/</code>

Entry Points

Aspect	PWA Kit	Storefront Next
Client Entry	<code>app/main.jsx</code> (explicit)	<code>entry.client</code> (hidden, revealed)

[Try for free](#)

Root Layout	app/components/_app/	src/root.tsx
Routes	app/routes.jsx (array)	src/routes.t src/routes/
Config	config/default.js	config.serve

Configuration Approach

PWA Kit uses CommonJS modules:

```
1 // config/default.js
2 module.exports = {
3   app: {
4     url: { site: "path", locale: "path" },
5     commerceAPI: { clientId: "...", organizationId: "..." },
6   },
7 };
```

Storefront Next uses TypeScript with `defineConfig`:

```
1 // config.server.ts
2 import { defineConfig } from "@salesforce/storefront-next";
3
4 export default defineConfig({
5   app: {
6     commerce: {
7       api: { clientId: "...", organizationId: "..." },
8     },
9   },
10 });
```

Key Differences

1. Language: PWA Kit uses JavaScript. Storefront Next uses TypeScript throughout.
2. Build Tool Integration: PWA Kit has separate config files for each tool. Storefront Next centralizes build config in `vite.config.ts`.
3. Server Architecture: PWA Kit uses Express with explicit route handlers. Storefront Next uses React Router's middleware pattern.
4. Entry Point Pattern: PWA Kit has separate client/server entry files. Storefront Next consolidates into `root.tsx` with exports.
5. Asset Handling: PWA Kit uses `getAssetUrl()` helper. Storefront Next uses Vite's native import system.

[Try for free](#)

directories for cleaner separation.

Storefront Conversion Considerations

1. Move source code from `app/` to `src/`.
2. Convert pages from `app/pages/` to file-based routes in `src/routes/`.
3. Migrate configuration from `config/default.js` to `config.server.ts`.
4. Update translations from `translations/*.json` to `src/locales/`.
5. Convert JavaScript to TypeScript-add type annotations throughout.
6. Replace Express routes with middleware exports in `root.tsx` or resource routes.
7. Update static asset imports to use Vite's import system instead of `getAssetUrl()`.
8. Entry file customization: If needed, run `npx react-router reveal` to customize client/server entry points.

References

- [React Router entry.client.tsx](#)
- [React Router entry.server.tsx](#)
- [React Router root.tsx](#)

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)

DEVELOPER CENTERS

Heroku
MuleSoft
Tableau
Commerce Cloud
Lightning Design System

POPULAR RESOURCES

Documentation
Component Library
APIs
Trailhead
Sample Apps

COMMUNITY

Trailblazer Community
Events and Calendar
Partner Community
Blog
Salesforce Admins



Try for free



© Copyright 2026 Salesforce, Inc. [All rights reserved.](#) Various trademarks held by their respective owners. Salesforce, Inc.
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#) [Use of Cookies](#)

[Cookie Preferences](#)  [Your Privacy Choices](#)