

Project Configuration Differences with PWA Kit

PWA Kit uses JavaScript configuration with looser runtime validation and flatter structures. Storefront Next introduces typed config definitions, structured namespaces, and an environment-variable override model designed for safer server-client separation. Access patterns also become more context-aware on the server and hook-based in React components.

Configuration Definition

Aspect	PWA Kit	Storefront Next
Language	JavaScript	TypeScript
Type Safety	None (runtime)	Full type defini
Location	<code>config/default.js</code>	<code>config.serv</code>
Helper Function	None	<code>defineConfi</code> for IDE autocomplete
Multi-site Config	Separate <code>sites.js</code> file	Simplified (sing locale and curi

Environment Variable Support

Aspect	PWA Kit	Storefront Next
Override System	Limited (specific vars only)	Full path-based override system
Naming Convention	Custom per variable	<code>PUBLIC__path__to__confi</code>

Contents

Configuration Definition

[Environment Variable Support](#)[Accessing Configuration](#)[Configuration Scope](#)[Example: Accessing Commerce API Config](#)[Example: Feature Flag Check](#)[Key Differences](#)[Storefront Conversion Considerations](#)[Configuration File Changes](#)[Code Conversion](#)[Environment Variables](#)[Server-Only Secrets](#)

[Try for free](#)

Validation	None	Strict schema validation
Client Exposure	N/A	<code>PUBLIC__</code> prefix = client-saf

Accessing Configuration

Aspect	PWA Kit	Storefront Next
Server Access	<code>getConfig()</code>	<code>getConfig(context)</code>
Client Access	<code>getConfig()</code>	<code>getConfig()</code> or <code>useConfig()</code>
React Components	<code>getConfig()</code>	<code>useConfig()</code> hook required
Type Inference	None	Full TypeScript types
Context Required	No	Yes (server-side)

Configuration Scope

Feature	PWA Kit	Storefront Next
Commerce API	<code>app.commerceAPI.parameters</code>	app.commerceAPI
Feature Flags	Top-level booleans	app.featureFlags
Analytics	<code>app.einsteinAPI</code> , <code>app.dataCloudAPI</code>	app.einsteinAPI, app.dataCloudAPI
UI Settings	N/A	app.uiSettings
Performance	N/A	app.performance
i18n	In <code>sites.js</code>	app.i18n

[Try for free](#)

```
1 import { getConfig } from "@salesforce/pwa-  
2  
3 const { clientId, siteId } = getConfig().ap
```

Storefront Next:



```
1 import { getConfig } from "@config";  
2  
3 // In a loader  
4 export function loader({ context }: Loaderf  
5   const { clientId, siteId } = getConfig(cc  
6 }  
7  
8 // In a component  
9 function MyComponent() {  
10   const { clientId, siteId } = useConfig()  
11 }
```

Example: Feature Flag Check

PWA Kit:



```
1 const storeLocatorEnabled = getConfig()?.ap  
2 const { passwordless = {} } = getConfig().a
```

Storefront Next:



```
1 const config = useConfig();  
2 const passwordlessEnabled = config.site.fe  
3 const socialLoginProviders = config.site.fe
```

Key Differences

1. Type Safety: Storefront Next provides full TypeScript type definitions, while PWA Kit uses plain JavaScript with no type checking.
2. Environment Variables: Storefront Next has a sophisticated environment variable override system with validation, while PWA Kit relies on hardcoded values or manually-implemented env var handling.
3. Context Requirement: Storefront Next requires passing router context to access config in server-



(proper React Context pattern), while PWA Kit allows calling `getConfig()` anywhere.

5. Configuration Scope: Storefront Next organizes configuration into clear namespaces (`pages` , `commerce` , `site` , `global` , `performance` , `engagement`), while PWA Kit uses a flatter structure with mixed concerns.
6. Multi-Site: PWA Kit has built-in multi-site configuration in `sites.js` with complex locale and currency mappings. Storefront Next simplifies this with single locale and currency values. Multi-site can be handled differently.

Storefront Conversion Considerations

Configuration File Changes

PWA Kit	Storefront Next
<code>config/default.js</code>	<code>config</code>
<code>config/sites.js</code>	Locale and currency mappings in <code>app.site.js</code>
<code>app.commerceAPI.parameters.clientId</code>	<code>app.config.commerceAPI.parameters.clientId</code>
<code>app.storeLocatorEnabled</code>	Move to <code>app.config.site.storeLocatorEnabled</code>
<code>app.multishipEnabled</code>	Move to <code>app.config.site.multishipEnabled</code>

Code Conversion

Before (PWA Kit):

```
1 import { getConfig } from "@salesforce/pwa-kit-runtime";
2
3 function ProductDetail() {
4   const storeLocatorEnabled = getConfig()?.storeLocatorEnabled;
5   const { clientId } = getConfig().app.commerceAPI.parameters;
6   // ...
7 }
```

After (Storefront Next):

```
1 import { getConfig } from "@salesforce/pwa-kit-runtime";
2
3 function ProductDetail() {
4   const storeLocatorEnabled = getConfig()?.storeLocatorEnabled;
5   const { clientId } = getConfig().app.config.commerceAPI.parameters;
6   // ...
7 }
```

[Try for free](#)

```
5 // ...  
6 // storeLocatorEnabled is now in extensio  
7 // ...  
8 }
```

Environment Variables

Before (PWA Kit):

```
1 # Limited environment variable support  
2 # Most values hardcoded in config/default.j
```

After (Storefront Next):

```
1 # Required Commerce API credentials  
2 PUBLIC__app__commerce__api__clientId=your-c  
3 PUBLIC__app__commerce__api__organizationId=  
4 PUBLIC__app__commerce__api__siteId=your-sit  
5 PUBLIC__app__commerce__api__shortCode=your-  
6  
7 # Optional feature toggles  
8 PUBLIC__app__site__features__socialLogin__e  
9 PUBLIC__app__pages__cart__maxQuantityPerIte
```

Server-Only Secrets

In Storefront Next, server-only secrets (like SLAS private key) should NOT use the `PUBLIC__` config system:

```
1 // In server-side code only  
2 const slasSecret = process.env.COMMERCE_API
```

**DID THIS ARTICLE SOLVE
YOUR ISSUE?**

Let us know so we can
improve!

[Share your feedback](#)

[Try for free](#)[Tableau](#)[Commerce Cloud](#)[Lightning Design System](#)[Einstein](#)[Quip](#)[APIs](#)[Trailhead](#)[Sample Apps](#)[AppExchange](#)[Partner Community](#)[Blog](#)[Salesforce Admins](#)[Salesforce Architects](#)

© Copyright 2026 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc.
Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#)[Terms of Service](#)[Privacy Information](#)[Responsible Disclosure](#)[Trust](#)[Contact](#)[Use of Cookies](#)[Cookie Preferences](#)[Your Privacy Choices](#)