

Deployment Differences with PWA Kit

PWA Kit uses Webpack with a single-command deployment that can auto-build. Storefront Next uses Vite with React Router 7, requiring separate build and push steps but providing more granular control over bundle sizes. Both deploy to the same Managed Runtime infrastructure, but Storefront Next offers more sophisticated bundle analysis and chunk splitting strategies for better performance optimization.

Contents

- [Key Differences](#)
- [Build Output](#)
- [Bundle Size Strategy](#)
- [Deployment Process](#)
- [Key Similarities](#)
- [Storefront Conversion Considerations](#)

Key Differences

Aspect	PWA Kit	Storefront Next
Build Tool	Webpack	Vite + React Router
Build Command	<code>pwa-kit-dev build</code>	<code>react-router build</code>
Push Command	<code>pwa-kit-dev push</code>	<code>sfnext push</code>
Analysis Tool	Webpack Bundle Analyzer	Rollup Visualizer
Config Format	JavaScript	TypeScript

Build Output

PWA Kit:

```
</> | 
1 build/
2 |─ main.js          (max 84 kB)
3 |─ vendor.js        (max 335 kB)
4 |─ ssr.js
5 |─ static/
```

Storefront Next:

```
</> | 
1 build/
2 |─ client/
```

[Try for free](#)

```
8 | ...js (max 5 MB total)
9 | static/
```

Bundle Size Strategy

PWA Kit:

```
</> 1 // Two main bundles with global limits
2 "bundlesize": [
3   {"path": "build/main.js", "maxSize": "84 kB"},
4   {"path": "build/vendor.js", "maxSize": "335 kB"}
5 ]
```

Storefront Next:

```
</> 1 // Granular per-chunk limits
2 "bundlesize": {
3   "client": [
4     {"name": "commerce-sdk-*", "limit": "454 kB"},
5     {"name": "-root.*", "limit": "110 kB"},
6     {"name": "**/*", "limit": "50 kB"} // Default
7   ]
8 }
```

Deployment Process

PWA Kit:

```
</> 1 npm run build      # Build first
2 npm run push       # Then deploy
3 # OR
4 pwa-kit-dev push   # Auto-builds if needed
```

Storefront Next:

```
</> 1 pnpm build      # Build first
2 pnpm push       # Deploy built bundle
3 # Separate steps required
```

Key Similarities

1. MRT Target: Both deploy to Managed Runtime.
2. Credentials: Same `~/mobify` file format.
3. Node.js Version: Both use Node.js 22.x.
4. SSR Parameters: Same configuration structure.
5. Proxy Config: Same proxy path patterns.

[Try for free](#)

- Replace `npm run build` with `pnpm build`.
- Update CI/CD scripts for new commands.

2. Bundle Size Monitoring

- Convert bundlesize config to new format.
- Add granular chunk limits.

3. Deployment Scripts

- Update from `pwa-kit-dev push` to `sfnext push`.
- Ensure build runs before push.

4. Configuration Files

- Migrate SSR config to `config.server.ts`.
- Update environment variable format.

DID THIS ARTICLE SOLVE YOUR ISSUE?

Let us know so we can improve!

[Share your feedback](#)

DEVELOPER CENTERS

[Heroku](#)
[MuleSoft](#)
[Tableau](#)
[Commerce Cloud](#)
[Lightning Design System](#)
[Einstein](#)
[Quip](#)

POPULAR RESOURCES

[Documentation](#)
[Component Library](#)
[APIs](#)
[Trailhead](#)
[Sample Apps](#)
[AppExchange](#)

COMMUNITY

[Trailblazer Community](#)
[Events and Calendar](#)
[Partner Community](#)
[Blog](#)
[Salesforce Admins](#)
[Salesforce Architects](#)

© Copyright 2026 Salesforce, Inc. [All rights reserved](#). Various trademarks held by their respective owners. Salesforce, Inc. Salesforce Tower, 415 Mission Street, 3rd Floor, San Francisco, CA 94105, United States

[Legal](#) [Terms of Service](#) [Privacy Information](#) [Responsible Disclosure](#) [Trust](#) [Contact](#) [Use of Cookies](#)

[Cookie Preferences](#)  [Your Privacy Choices](#)

