

Sequence design ID	Mutations	Tm [°C]	Yield [mg]	Conversion [%]	EE [%]
WT	—	47.5	27.0	16.5	17.0
F85L	F85L	47.5	27.0	22.4	25.6
1	T41S, F85L, H109E, M272T	50.9	10.0	29.2	37.8
2	N9T, F85L, S92P, M272T	53.2	21.0	23.9	28.2
3	F85L, S92P, R184K, M272T	52.9	32.5	25.8	31.4
4	F85L, H109E, K207E, M272T	50.4	32.0	23.2	27.6
5	N46G, F85L, H109E, M272T, V275I, N289K	53.7	15.8	24.0	28.2
6	N9T, E42K, F85L, K207E, M272T, K320S	49.6	26.8	24.1	27.8
7	N39Q, F85L, H109E, A152S, N289K, R341K	47.3	33.0	26.8	31.8
8	F85L, H109E, K174R, K207E, K311S, F338Y	46.9	33.0	37.3	51.6
9	F85L, H109E, R184K, V275I, N289K, D329A	46.8	9.9	23.9	26.4
10	N9T, T41I, F85L, D91N, K207E, M272N	44.7	46.0	25.0	28.4
11	T41L, F85L, H109E, F132Y, C166R, R256D	45.5	35.0	23.0	26.0
12	F85L, S92Y, H109E, C166H, K207E, D329T	48.9	32.1	14.9	14.2
13	F85L, H109E, R256E, A268E	45.1	20.6	25.4	28.4
14	K49N, F85L, H109E, E137Y, K207E, A268G	47.1	24.8	27.0	29.2
15	F85L, H109E, R184K, M272T	50.5	14.7	23.4	26.0