

Compression of jazz chord sequences

Romain VERSAEVEL

Tutored by Pr. David MEREDITH

13 août 2015

Contents

Motivation, definitions

Compression algorithms

Similarity measures

Results

Contents

Motivation, definitions

Compression algorithms

Similarity measures

Results

Chords


Definition

A *chord* is a set of at least three notes.

Chords

Definition

A *chord* is a set of at least three notes.



My data

A Child Is Born :

B \flat M7; E \flat m; B \flat M7; E \flat m6; B \flat M9; E \flat m; A halfdim7; D7 \sharp 9...

My data

A Child Is Born :

B \flat M7; E \flat m; B \flat M7; E \flat m6; B \flat M9; E \flat m; A halfdim7; D7 \sharp 9...



Mathematical chords

Notes are numbers.

Mathematical chords

Notes are numbers.

<i>A</i>	<i>A#</i>	<i>B</i>	<i>C</i>	<i>C#</i>	<i>D</i>	<i>D#</i>	<i>E</i>	<i>F</i>	<i>F#</i>	<i>G</i>	<i>G#</i>
0	1	2	3	4	5	6	7	8	9	10	11

Mathematical chords

Notes are numbers.

<i>A</i>	<i>A#</i>	<i>B</i>	<i>C</i>	<i>C#</i>	<i>D</i>	<i>D#</i>	<i>E</i>	<i>F</i>	<i>F#</i>	<i>G</i>	<i>G#</i>
0	1	2	3	4	5	6	7	8	9	10	11

$$\underbrace{B\flat}_1 \quad + \quad \underbrace{M7}_{\{0;4;7;10\}}$$

Contents


Motivation, definitions

Compression algorithms

Similarity measures

Results

Lempel-Ziv 77



LZ77 : example

Input

$I = ABCABCABD$

Output

$(0, 0, A), (0, 0, B), (0, 0, C), (3, 5, D)$

LZ77 : example

Input

$I = ABCABCABD$

Step	Buffer								Input (« preview »)								
0									A	B	C	A	B	C	A	B	D

Output

$(0,0,A), (0,0,B), (0,0,C), (3,5,D)$

LZ77 : example

Input

$I = ABCABCABD$

Step	Buffer								Input (« preview »)									
0									A	B	C	A	B	C	A	B	D	
1								A	B	C	A	B	C	A	B	D		

Output

$(0, 0, A), (0, 0, B), (0, 0, C), (3, 5, D)$

LZ77 : example

Input

$I = ABCABCABD$

Step	Buffer								Input (« preview »)								
0									A	B	C	A	B	C	A	B	D
1								A	B	C	A	B	C	A	B	D	
2							A	B	C	A	B	C	A	B	D		

Output

$(0, 0, A), (0, 0, B), (0, 0, C), (3, 5, D)$

LZ77 : example

Input

$I = ABCABCABD$

Step	Buffer									Input (« preview »)								
0										A	B	C	A	B	C	A	B	D
1									A	B	C	A	B	C	A	B	D	
2								A	B	C	A	B	C	A	B	D		
3							A	B	C	A	B	C	A	B	D			

Output

$(0, 0, A), (0, 0, B), (0, 0, C), (3, 5, D)$

Input

$I = ABCABCABD$

Decompression	Output
	$(0, 0, A)$
	$(0, 0, B)$
	$(0, 0, C)$
	$(3, 5, D)$

Input

$I = ABCABCABD$

Decompression	Output
	(0,0,A)
	(0, 0, <i>B</i>)
	(0, 0, <i>C</i>)
	(3, 5, <i>D</i>)

Input

$I = ABCABCABD$

Decompression	Output
A	$(0, 0, A)$
	$(0, 0, B)$
	$(0, 0, C)$
	$(3, 5, D)$

Input

$I = ABCABCABD$

Decompression	Output
A	$(0, 0, A)$
	$(0, 0, B)$
	$(0, 0, C)$
	$(3, 5, D)$

Input

$I = ABCABCABD$

Decompression	Output
<i>A</i>	(0, 0, <i>A</i>)
<i>B</i>	(0, 0, <i>B</i>)
	(0, 0, <i>C</i>)
	(3, 5, <i>D</i>)

Input

$I = ABCABCABD$

Decompression	Output
A	$(0, 0, A)$
B	$(0, 0, B)$
	$(0, 0, C)$
	$(3, 5, D)$

Input

$I = ABCABCABD$

Decompression	Output
A	$(0, 0, A)$
B	$(0, 0, B)$
C	$(0, 0, C)$
	$(3, 5, D)$

Input

$I = ABCABCABD$

Decompression	Output
<i>A</i>	(0, 0, <i>A</i>)
<i>B</i>	(0, 0, <i>B</i>)
<i>C</i>	(0, 0, <i>C</i>)
	(3, 5, <i>D</i>)

Input

$I = ABCABCABD$

Decompression	Output
<i>A</i>	(0, 0, <i>A</i>)
<i>B</i>	(0, 0, <i>B</i>)
<i>C</i>	(0, 0, <i>C</i>)
<i>A</i>	(3, 5, <i>D</i>)
<i>B</i>	
<i>C</i>	

Input

$I = ABCABCABD$

Decompression	Output
<i>A</i>	(0, 0, <i>A</i>)
<i>B</i>	(0, 0, <i>B</i>)
<i>C</i>	(0, 0, <i>C</i>)
<i>A</i>	(3, 5, <i>D</i>)
<i>B</i>	
<i>C</i>	
<i>A</i>	
<i>B</i>	

Input


$I = ABCABCABD$

Decompression	Output
<i>A</i>	(0, 0, <i>A</i>)
<i>B</i>	(0, 0, <i>B</i>)
<i>C</i>	(0, 0, <i>C</i>)
<i>A</i>	(3, 5, <i>D</i>)
<i>B</i>	
<i>C</i>	
<i>A</i>	
<i>B</i>	
<i>D</i>	


Diagonal patterns (1)

	B	D7	G	Bb7	Eb	A m7	D7	G	Bb7	Eb	F#7	B	F m7	Bb7	Eb
B															
D7															
G															
Bb7															
Eb															
A m7															
D7															
G															
Bb7															
Eb															
F#7															
B															
F m7															
Bb7															
Eb															

Diagonal patterns (1)



Diagonal patterns (1)



Diagonal patterns (2)

Step 1 Identify the patterns

Step 2 Find a (small) cover

Diagonal patterns (3)

Input

$\mathbb{I} = B; D7; G; B\flat7; E\flat; Am7; D7; G; B\flat7; E\flat; F\sharp7; B; Fm7; B\flat7; E\flat$

Diagonal patterns (3)

Input

$\mathcal{I} = B; D7; G; B\flat7; E\flat; Am7; D7; G; B\flat7; E\flat; F\sharp7; B; Fm7; B\flat7; E\flat$

Patterns

- ▷ $B — \{0; 11\};$
- ▷ $B\flat7; E\flat — \{3; 8; 13\};$
- ▷ $D7; G; B\flat7; E\flat — \{1; 6\};$

Diagonal patterns (3)

Input

$\mathcal{I} = B; D7; G; B\flat7; E\flat; Am7; D7; G; B\flat7; E\flat; F\sharp7; B; Fm7; B\flat7; E\flat$

Patterns

- ▷ $B — \{0; 11\};$
- ▷ $B\flat7; E\flat — \{3; 8; 13\};$
- ▷ $D7; G; B\flat7; E\flat — \{1; 6\};$
- ▷ $D7 — \{1; 6\}, G — \{2; 7\} \dots$

Diagonal patterns (3)

Input

$I = B; D7; G; B\flat7; E\flat; Am7; D7; G; B\flat7; E\flat; F\sharp7; B; Fm7; B\flat7; E\flat$

Patterns

- ▷ $B — \{0; 11\};$
- ▷ $B\flat7; E\flat — \{3; 8; 13\};$
- ▷ $D7; G; B\flat7; E\flat — \{1; 6\};$
- ▷ $D7 — \{1; 6\}, G — \{2; 7\} \dots$


Output

- ▷ $B — \{0; 11\};$
- ▷ $B\flat7; E\flat — \{13\};$
- ▷ $D7; G; B\flat7; E\flat — \{1; 6\};$
- ▷ $Am7 — \{5\}, F\sharp7 — \{10\}, Fm7 — \{12\}$

Diagonal patterns (4)

B D7 G Bb7 Eb Am7 D7 G Bb7 Eb F#7 B Fm7 Bb7 Eb

Diagonal patterns (4)



Contents

Motivation, definitions

Compression algorithms

Similarity measures

Results

The magical ingredient

$$C = C'$$

The magical ingredient

$$C = C'$$

↓

$$C \sim C'$$

All measures

- ▷ root note equivalence ;
- ▷ transposition equivalence ;
- ▷ PCS-Prime equivalence ;
- ▷ the F1-score ;
- ▷ Isaacson's similarity index ;
- ▷ Lewin's measure ;
- ▷ Morris' measure ;
- ▷ Rahn's measure ;
- ▷ Teitelbaum's measure.

Thresholds



Contents

Motivation, definitions

Compression algorithms

Similarity measures

Results

Evaluation

Compression factor

Recovery factor

Evaluation

Compression factor

$$\frac{|\text{Input}|}{|\text{Output}|}$$

Recovery factor


$$\frac{|\{i \mid \text{DECOMPRESS}(\text{COMPRESS}(\text{Input}))[i] = \text{Input}[i]\}|}{|\text{Input}|}$$

Comparison between measures (1)



« Similarity measures are similar. »

Comparison between measures (1)


« Similarity measures are similar. »




Comparison between measures (2)





Comparison between measures (2)




Comparison between measures (2)




Comparison between algorithms (1)





Comparison between algorithms (1)




Comparison between algorithms (1)



Comparison between algorithms (2)



Comparison between algorithms (2)



Comparison between algorithms (2)

