

Layer Name	Type	Material	Thickness (mm)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Liquid Photo	0 mm	White	1	0
F.Paste	Top Solder Paste		0 mm		1	0
F.Mask	Top Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
F.Cu	copper		0.0432 mm		1	0
Dielectric 1	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
In1.Cu	copper		0.0175 mm		1	0
Dielectric 2	core	FR408-HR	0.9906 mm	FR4 natural	3.64	0.0098
In2.Cu	copper		0.0175 mm		1	0
Dielectric 3	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
B.Cu	copper		0.0432 mm		1	0
B.Mask	Bottom Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
B.Paste	Bottom Solder Paste		0 mm		1	0
B.Silkscreen	Bottom Silk Screen	Liquid Photo	0 mm	White	1	0

BOARD CHARACTERISTICS

Copper Layer Count:	4	Board Thickness:	1.5670 mm
Board overall dimensions:	52.5000 mm x 40.5000 mm		
Min track/spacing:	0.0000 mm / 0.0000 mm	Min hole diameter:	0.3000 mm
Copper Finish:	ENIG	Impedance Control:	Yes
Castellated pads:	No	Plated Board Edge:	No
Edge card connectors:	No		

Notes:
LNA footprint is pin-compatible with PMA2-123LN+.

Remy Nguyen

Sheet:
File: 002.35.20.15.20-001-PCB-LNA.kicad_pcb


Title: RF-DFS Gain Circuit

Size: A4 Date: 1/23/2024

KiCad E.D.A. kicad 7.0.5

Rev: B

Id: 1/1



Layer Name	Type	Material	Thickness (mm)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Liquid Photo	0 mm	White	1	0
F.Paste	Top Solder Paste		0 mm		1	0
F.Mask	Top Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
F.Cu	copper		0.0432 mm		1	0
Dielectric 1	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
In1.Cu	copper		0.0175 mm		1	0
Dielectric 2	core	FR408-HR	0.9906 mm	FR4 natural	3.64	0.0098
In2.Cu	copper		0.0175 mm		1	0
Dielectric 3	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
B.Cu	copper		0.0432 mm		1	0
B.Mask	Bottom Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
B.Paste	Bottom Solder Paste		0 mm		1	0
B.Silkscreen	Bottom Silk Screen	Liquid Photo	0 mm	White	1	0

BOARD CHARACTERISTICS

Copper Layer Count:	4	Board Thickness:	1.5670 mm
Board overall dimensions:	52.5000 mm x 40.5000 mm		
Min track/spacing:	0.0000 mm / 0.0000 mm	Min hole diameter:	0.3000 mm
Copper Finish:	ENIG	Impedance Control:	Yes
Castellated pads:	No	Plated Board Edge:	No
Edge card connectors:	No		

Notes:
LNA footprint is pin-compatible with PMA2-123LN+.

Remy Nguyen

Sheet:
File: 002.35.20.15.20-001-PCB-LNA.kicad_pcb

Title: RF-DFS Gain Circuit

Size: A4 Date: 1/23/2024

KiCad E.D.A. kicad 7.0.5

Rev: B

Id: 1/1

[illegible]

Layer Name	Type	Material	Thickness (mm)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Liquid Photo	0 mm	White	1	0
F.Paste	Top Solder Paste		0 mm		1	0
F.Mask	Top Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
F.Cu	copper		0.0432 mm		1	0
Dielectric 1	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
In1.Cu	copper		0.0175 mm		1	0
Dielectric 2	core	FR408-HR	0.9906 mm	FR4 natural	3.64	0.0098
In2.Cu	copper		0.0175 mm		1	0
Dielectric 3	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
B.Cu	copper		0.0432 mm		1	0
B.Mask	Bottom Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
B.Paste	Bottom Solder Paste		0 mm		1	0
B.Silkscreen	Bottom Silk Screen	Liquid Photo	0 mm	White	1	0

Copper Layer Count:	4	Board Thickness:	1.5670 mm
Board overall dimensions:	52.5000 mm x 40.5000 mm		
Min track/spacing:	0.0000 mm / 0.0000 mm	Min hole diameter:	0.3000 mm
Copper Finish:	ENIG	Impedance Control:	Yes
Castellated pads:	No	Plated Board Edge:	No
Edge card connectors:	No		

Remy Nguye

Sheet:
File: 002.35.20.15.20-001-PCB-LNA.kicad_pcb

Title: RF-DFS Gain Circuit

Size: A4	Date: 1/23/2024
----------	-----------------

Rev: B

KiCad E.D.A. kicad 7.0.5

Id: 1/1

Layer Name	Type	Material	Thickness (mm)	Color	Epsilon R	Loss Tangent
F.Silkscreen	Top Silk Screen	Liquid Photo	0 mm	White	1	0
F.Paste	Top Solder Paste		0 mm		1	0
F.Mask	Top Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
F.Cu	copper		0.0432 mm		1	0
Dielectric 1	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
In1.Cu	copper		0.0175 mm		1	0
Dielectric 2	core	FR408-HR	0.9906 mm	FR4 natural	3.64	0.0098
In2.Cu	copper		0.0175 mm		1	0
Dielectric 3	prepreg	FR408HR 2113	0.2021 mm	FR4 natural	3.6	0.01
B.Cu	copper		0.0432 mm		1	0
B.Mask	Bottom Solder Mask	Liquid Ink	0.0254 mm	Purple	3.3	0
B.Paste	Bottom Solder Paste		0 mm		1	0
B.Silkscreen	Bottom Silk Screen	Liquid Photo	0 mm	White	1	0

BOARD CHARACTERISTICS

Copper Layer Count:	4	Board Thickness:	1.5670 mm
Board overall dimensions:	52.5000 mm x 40.5000 mm		
Min track/spacing:	0.0000 mm / 0.0000 mm	Min hole diameter:	0.3000 mm
Copper Finish:	ENIG	Impedance Control:	Yes
Castellated pads:	No	Plated Board Edge:	No
Edge card connectors:	No		

Notes:
LNA footprint is pin-compatible with PMA2-123LN+.

Remy Nguyen

Sheet:
File: 002.35.20.15.20-001-PCB-LNA.kicad_pcb

Title: RF-DFS Gain Circuit

Size: A4	Date: 1/23/2024
----------	-----------------

Rev: B

KiCad E.D.A.	kicad 7.0.5
--------------	-------------

Id: 1/1