

## Lecture 17. Predicate Logic and Quantifiers (§1.5)

## Predicates

- In previous lectures, we mentioned how sentences that involve a variable, such as  $x$ , need not be statements.
  - For example, the sentence “**The number  $x + 2$  is an even integer**” is not necessary true or false unless we know what value is substituted for  $x$ .
  - If we restrict our choices to integers, then when  $x$  is replaced by  $-7$ ,  $1$ , or  $5$ , for instance, the resulting statement is false.
  - When an even integer is substituted for  $x$ , however, the resulting proposition is true.

---

<sup>1</sup>Also, called as a [first-order logic](#).

## Predicates

- In previous lectures, we mentioned how sentences that involve a variable, such as  $x$ , need not be statements.
  - For example, the sentence “**The number  $x + 2$  is an even integer**” is not necessary true or false unless we know what value is substituted for  $x$ .
  - If we restrict our choices to integers, then when  $x$  is replaced by  $-7$ ,  $1$ , or  $5$ , for instance, the resulting statement is false.
  - When an even integer is substituted for  $x$ , however, the resulting proposition is true.
- We can denote the sentence “The number  $x + 2$  is an even integer” by  $P(x)$ , which is called a **propositional function** at  $x$ .

---

<sup>1</sup>Also, called as a **first-order logic**.

## Predicates

- In previous lectures, we mentioned how sentences that involve a variable, such as  $x$ , need not be statements.
  - For example, the sentence “**The number  $x + 2$  is an even integer**” is not necessary true or false unless we know what value is substituted for  $x$ .
  - If we restrict our choices to integers, then when  $x$  is replaced by  $-7$ ,  $1$ , or  $5$ , for instance, the resulting statement is false.
  - When an even integer is substituted for  $x$ , however, the resulting proposition is true.
- We can denote the sentence “The number  $x + 2$  is an even integer” by  $P(x)$ , which is called a **propositional function** at  $x$ .
- **Definition** A **predicate logic**<sup>1</sup> is a declarative sentence whose truth value depends on one or more variables that becomes a statement when the variables in it are replaced by certain allowable choices. We will say **predicate logic** as just **predicate**.
- In the example above,  $P(3)$  is false and  $P(2)$  is true.

---

<sup>1</sup>Also, called as a **first-order logic**.

**Example 17.1.** Predicate  $Q(x, y) =$  “ $x$  is heavier than  $y$ ”. Then the statement  $Q(\text{feather}, \text{brick})$  is false.

**Example 17.1.** Predicate  $Q(x, y) = \text{"}x \text{ is heavier than } y\text{"}$ . Then the statement  $Q(\text{feather}, \text{brick})$  is false.

**Example 17.2.** Equations are predicates: If  $E(x)$  stands for the equation

$$x^2 - x - 6 = 0,$$

then  $E(3)$  is true and  $E(4)$  is false.

## Quantifiers

We need **quantifiers** to express the meaning of English words including **all** and **some**:

- “**All** men are Mortal.”
- “**Some** cats do not have fur.”

# Quantifiers

We need **quantifiers** to express the meaning of English words including **all** and **some**:

- “**All** men are Mortal.”
- “**Some** cats do not have fur.”

The two most important quantifiers are:

- **Universal Quantifier**, “For All”, symbol:  $\forall$
- **Existential Quantifier**, “There Exists”, symbol:  $\exists$



# Quantifiers

We need **quantifiers** to express the meaning of English words including **all** and **some**:

- “**All** men are Mortal.”
- “**Some** cats do not have fur.”

The two most important quantifiers are:

- **Universal Quantifier**, “For All”, symbol:  $\forall$
- **Existential Quantifier**, “There Exists”, symbol:  $\exists$

We write as in  $\forall x \in D, P(x)$  and  $\exists x \in D, P(x)$ :

# Quantifiers

We need **quantifiers** to express the meaning of English words including **all** and **some**:

- “**All** men are Mortal.”
- “**Some** cats do not have fur.”

The two most important quantifiers are:

- **Universal Quantifier**, “For All”, symbol:  $\forall$
- **Existential Quantifier**, “There Exists”, symbol:  $\exists$

We write as in  $\forall x \in D, P(x)$  and  $\exists x \in D, P(x)$ :

- $\forall x \in D, P(x)$  = “For all  $x$  in the domain  $D$ ,  $P(x)$  is true”; i.e.,  $P(x)$  is true for **every**  $x$  in  $D$ .

## Quantifiers

We need **quantifiers** to express the meaning of English words including **all** and **some**:

- “**All** men are Mortal.”
- “**Some** cats do not have fur.”

The two most important quantifiers are:

- **Universal Quantifier**, “For All”, symbol:  $\forall$
- **Existential Quantifier**, “There Exists”, symbol:  $\exists$

We write as in  $\forall x \in D, P(x)$  and  $\exists x \in D, P(x)$ :

- $\forall x \in D, P(x)$  = “For all  $x$  in the domain  $D$ ,  $P(x)$  is true”; i.e.,  $P(x)$  is true for **every**  $x$  in  $D$ .
- $\exists x \in D, P(x)$  = “There exists an  $x$  in the domain  $D$  such that  $P(x)$  is true”; i.e.,  $P(x)$  is true for **some**  $x$  in  $D$ .

**Universal Quantifier:**  $\forall x \in D, P(x)$  is read as “For all  $x$  in the domain  $D$ ,  $P(x)$  is true”

**Example 17.3.**

- 1 If  $P(x)$  denotes “ $x > 0$ ” and its domain  $D$  is the integers, then the statement  $[\forall x \in D, P(x)]$  is false.

**Universal Quantifier:**  $\forall x \in D, P(x)$  is read as “For all  $x$  in the domain  $D$ ,  $P(x)$  is true”

**Example 17.3.**

- ① If  $P(x)$  denotes “ $x > 0$ ” and its domain  $D$  is the integers, then the statement  $[\forall x \in D, P(x)]$  is false.
- ② If  $P(x)$  denotes “ $x > 0$ ” and  $D$  is the positive integers, then the statement  $[\forall x \in D, P(x)]$  is true.

**Universal Quantifier:**  $\forall x \in D, P(x)$  is read as “For all  $x$  in the domain  $D$ ,  $P(x)$  is true”

**Example 17.3.**

- ① If  $P(x)$  denotes “ $x > 0$ ” and its domain  $D$  is the integers, then the statement  $[\forall x \in D, P(x)]$  is false.
- ② If  $P(x)$  denotes “ $x > 0$ ” and  $D$  is the positive integers, then the statement  $[\forall x \in D, P(x)]$  is true.
- ③ If  $P(x)$  denotes “ $x$  is even” and  $D$  is the integers, then the statement  $[\forall x \in D, P(x)]$  is false.

**Existential Quantifier:**  $\exists x \in D, P(x)$  is read as “There exists an  $x$  in the domain  $D$  such that  $P(x)$  is true”

**Example 17.4.**

- ① If  $P(x)$  denotes “ $x > 0$ ” and  $D$  is the integers, then  $[\exists x \in D, P(x)]$  is true. It is also true if  $D$  is the positive integers.

**Existential Quantifier:**  $\exists x \in D, P(x)$  is read as “There exists an  $x$  in the domain  $D$  such that  $P(x)$  is true”

**Example 17.4.**

- ① If  $P(x)$  denotes “ $x > 0$ ” and  $D$  is the integers, then  $[\exists x \in D, P(x)]$  is true. It is also true if  $D$  is the positive integers.
- ② If  $P(x)$  denotes “ $x < 0$ ” and  $D$  is the positive integers, then  $[\exists x \in D, P(x)]$  is false.



**Existential Quantifier:**  $\exists x \in D, P(x)$  is read as “There exists an  $x$  in the domain  $D$  such that  $P(x)$  is true”

**Example 17.4.**

- ① If  $P(x)$  denotes “ $x > 0$ ” and  $D$  is the integers, then  $[\exists x \in D, P(x)]$  is true. It is also true if  $D$  is the positive integers.
- ② If  $P(x)$  denotes “ $x < 0$ ” and  $D$  is the positive integers, then  $[\exists x \in D, P(x)]$  is false.
- ③ If  $P(x)$  denotes “ $x$  is even” and  $D$  is the integers, then  $[\exists x \in D, P(x)]$  is true

The truth value of  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  depend on both the propositional function (or predicate)  $P(x)$  and on the domain  $D$ .

The truth value of  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  depend on both the propositional function (or predicate)  $P(x)$  and on the domain  $D$ .

**Example 17.5.**

- 1 If  $D$  is the positive integers and  $P(x)$  is the statement " $x < 2$ ", then  $\exists x \in D, P(x)$  is true, but  $\forall x \in D, P(x)$  is false.

The truth value of  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  depend on both the propositional function (or predicate)  $P(x)$  and on the domain  $D$ .

**Example 17.5.**

- ① If  $D$  is the positive integers and  $P(x)$  is the statement " $x < 2$ ", then  $\exists x \in D, P(x)$  is true, but  $\forall x \in D, P(x)$  is false.
- ② If  $D$  is the negative integers and  $P(x)$  is the statement " $x < 2$ ", then both  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  are true.

The truth value of  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  depend on both the propositional function (or predicate)  $P(x)$  and on the domain  $D$ .

**Example 17.5.**

- ① If  $D$  is the positive integers and  $P(x)$  is the statement " $x < 2$ ", then  $\exists x \in D, P(x)$  is true, but  $\forall x \in D, P(x)$  is false.
- ② If  $D$  is the negative integers and  $P(x)$  is the statement " $x < 2$ ", then both  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  are true.
- ③ If  $D$  consists of 3, 4, and 5, and  $P(x)$  is the statement " $x > 2$ ", then both  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  are true. But if  $P(x)$  is the statement " $x < 2$ ", then both  $\exists x \in D, P(x)$  and  $\forall x \in D, P(x)$  are false.

**Practice 17.6** Consider the predicate  $R(x, y) : 2x + y = 0$ , where the domain of  $x$  and  $y$  is all rational numbers. True or False?

(a)  $R(0, 0)$    (b)  $R(2, -1)$    (c)  $R(\frac{1}{5}, -\frac{2}{5})$    (d)  $\exists y, R(0.2, y)$    (e)  $\forall y, R(7, y)$

## Precedence of Quantifiers

The quantifiers  $\forall$  and  $\exists$  have higher precedence than all the logical operators.

- For example,  $\forall x P(x) \vee Q(x)$  means  $(\forall x P(x)) \vee Q(x)$ .
  - Note: Here we omitted the domain  $D$  assuming we already know what the domain is.

## Precedence of Quantifiers

The quantifiers  $\forall$  and  $\exists$  have higher precedence than all the logical operators.

- For example,  $\forall x P(x) \vee Q(x)$  means  $(\forall x P(x)) \vee Q(x)$ .
  - Note: Here we omitted the domain  $D$  assuming we already know what the domain is.
- $\forall x (P(x) \vee Q(x))$  means something different.



## Precedence of Quantifiers

The quantifiers  $\forall$  and  $\exists$  have higher precedence than all the logical operators.

- For example,  $\forall x P(x) \vee Q(x)$  means  $(\forall x P(x)) \vee Q(x)$ .
  - Note: Here we omitted the domain  $D$  assuming we already know what the domain is.
- $\forall x (P(x) \vee Q(x))$  means something different.
- To avoid any confusion just put brackets right after every quantifier you use; i.e.,  $\forall x \in D, [P(x) \vee Q(x)]$  or  $\forall x [P(x) \vee Q(x)]$ .

**Example 17.7.** Translate the following sentence into predicate logic:

*“Every student in this class has taken a course in Java.”*

**Example 17.7.** Translate the following sentence into predicate logic:

*“Every student in this class has taken a course in Java.”*

- **Solution 1** If  $D$  is all students in this class, define a predicate  $J(x)$  denoting “ $x$  has taken a course in Java” and translate as  $\forall x \in D, J(x)$ .

**Example 17.7.** Translate the following sentence into predicate logic:

*“Every student in this class has taken a course in Java.”*

- **Solution 1** If  $D$  is all students in this class, define a predicate  $J(x)$  denoting “ $x$  has taken a course in Java” and translate as  $\forall x \in D, J(x)$ .
- **Solution 2** But if  $D$  is all people, also define a predicate  $S(x)$  denoting “ $x$  is a student in this class” and translate as  $\forall x \in D, [S(x) \rightarrow J(x)]$ .

## Negating Quantified Expressions

- Consider  $\forall x J(x)$ :  
“Every student in your class has taken a course in Java.”  
Here  $J(x)$  is “ $x$  has taken a course in Java” and the domain is students in your class.
- Negating the original statement gives

## Negating Quantified Expressions

- Consider  $\forall x J(x)$ :  
“Every student in your class has taken a course in Java.”  
Here  $J(x)$  is “ $x$  has taken a course in Java” and the domain is students in your class.
- Negating the original statement gives  
“It is not the case that every student in your class has taken Java.”  
This implies that “There is a student in your class who has not studied Java.”
- Symbolically,  $\neg [(\forall x) J(x)] \Leftrightarrow$

## Negating Quantified Expressions

- Consider  $\forall x J(x)$ :  
“Every student in your class has taken a course in Java.”  
Here  $J(x)$  is “ $x$  has taken a course in Java” and the domain is students in your class.
- Negating the original statement gives  
“It is not the case that every student in your class has taken Java.”  
This implies that “There is a student in your class who has not studied Java.”
- Symbolically,  $\neg [(\forall x) J(x)] \Leftrightarrow (\exists x) (\neg J(x))$

- Now consider  $\exists x J(x)$   
“There is a student in this class who has taken a course in Java.”  
where  $J(x)$  is “ $x$  has taken a course in Java” and the domain is students in this class.
- Negating the original statement gives



- Now consider  $\exists x J(x)$   
“There is a student in this class who has taken a course in Java.”  
where  $J(x)$  is “ $x$  has taken a course in Java” and the domain is students in this class.
- Negating the original statement gives  
“It is not the case that there is a student in this class who has taken Java.”  
This implies that “Every student in this class has not studied Java.”
- Symbolically,  $\neg [(\exists x) J(x)] \Leftrightarrow$

- Now consider  $\exists x J(x)$   
“There is a student in this class who has taken a course in Java.”  
where  $J(x)$  is “ $x$  has taken a course in Java” and the domain is students in this class.
- Negating the original statement gives  
“It is not the case that there is a student in this class who has taken Java.”  
This implies that “Every student in this class has not studied Java.”
- Symbolically,  $\neg [(\exists x) J(x)] \Leftrightarrow (\forall x) (\neg J(x))$

## Negation Rules for Quantifiers

$$\neg[(\forall x) P(x)] \Leftrightarrow (\exists x)(\neg P(x)) \quad (\text{universal negation})$$

$$\neg[(\exists x) P(x)] \Leftrightarrow (\forall x)(\neg P(x)) \quad (\text{existential negation})$$

**Example 17.8.** Express the statement in predicate logic and find its negation.

“There does not exist anyone who likes skiing over magma.”

## Negation Rules for Quantifiers

$$\neg[(\forall x) P(x)] \Leftrightarrow (\exists x)(\neg P(x)) \quad (\text{universal negation})$$


$$\neg[(\exists x) P(x)] \Leftrightarrow (\forall x)(\neg P(x)) \quad (\text{existential negation})$$

**Example 17.8.** Express the statement in predicate logic and find its negation.

“There does not exist anyone who likes skiing over magma.”

**Practice 17.9** Show that  $\neg(\forall x[P(x) \rightarrow Q(x)])$  and  $\exists x[P(x) \wedge \neg Q(x)]$  are logically equivalent.

**Practice 17.10.** Let the domain be all faces of the following truncated **icosahedron**.<sup>2</sup>



Consider the following predicates:

- $P(x)$  = “ $x$  is a pentagon”
- $H(x)$  = “ $x$  is a hexagon”
- $B(x, y)$  = “ $x$  borders  $y$ ”

Here we say that two polygons **border each other** if they share an edge. Confirm that the following observations are true for any truncated icosahedron.

- No two pentagons border each other.
- Every pentagon borders some hexagon.
- Every hexagon borders another hexagon.

Write these statements in predicate logic, and negate them. Simplify the negated statements so that no quantifier or connective lies within the scope of a negation. Translate your negated statement back into English.

---

<sup>2</sup>A solid figure having 20 faces.