

Lecture 21. Recursively Defined Structures

Recursive Definition

- Recursion is also useful for many problems that do not involve numbers.
- In general, a **recursive definition** of a given *object*¹ is made up of two parts:
 - B. Base step** defines the simplest possible object that doesn't depend on anything else, and
 - R. Recursive step** defines more complicated objects recursively that depend on simpler cases.

¹An object could be a number, a mathematical structure, a function, or almost anything else we want to describe.

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.
 - B1.** λ is a palindrome. (Why do we need to define this? Think about forming 'otto')
 - B2.** Any symbol **a** is a palindrome.
 - R.** If **x** and **y** are palindromes, then **xyx** is a palindrome.
- We can build up the palindrome **racecar** from the definition as follows.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.
 - B1.** λ is a palindrome. (Why do we need to define this? Think about forming 'otto')
 - B2.** Any symbol **a** is a palindrome.
 - R.** If **x** and **y** are palindromes, then **xyx** is a palindrome.
- We can build up the palindrome **racecar** from the definition as follows.
 - ① Since it is a symbol, **e** is a palindrome by **B2**.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.
 - B1.** λ is a palindrome. (Why do we need to define this? Think about forming 'otto')
 - B2.** Any symbol **a** is a palindrome.
 - R.** If **x** and **y** are palindromes, then **xy** is a palindrome.
- We can build up the palindrome **racecar** from the definition as follows.
 - ① Since it is a symbol, **e** is a palindrome by B2.
 - ② Similarly, **c** is a palindrome.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.
 - B1.** λ is a palindrome. (Why do we need to define this? Think about forming 'otto')
 - B2.** Any symbol **a** is a palindrome.
 - R.** If **x** and **y** are palindromes, then **xyx** is a palindrome.
- We can build up the palindrome **racecar** from the definition as follows.
 - ① Since it is a symbol, **e** is a palindrome by B2.
 - ② Similarly, **c** is a palindrome.
 - ③ Using R, **cec** is a palindrome.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.
 - B1.** λ is a palindrome. (Why do we need to define this? Think about forming 'otto')
 - B2.** Any symbol **a** is a palindrome.
 - R.** If **x** and **y** are palindromes, then **xyx** is a palindrome.
- We can build up the palindrome **racecar** from the definition as follows.
 - ① Since it is a symbol, **e** is a palindrome by **B2**.
 - ② Similarly, **c** is a palindrome.
 - ③ Using **R**, **cec** is a palindrome.
 - ④ By **B2**, **a** is a palindrome.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.
 - B1.** λ is a palindrome. (Why do we need to define this? Think about forming 'otto')
 - B2.** Any symbol **a** is a palindrome.
 - R.** If **x** and **y** are palindromes, then **xyx** is a palindrome.
- We can build up the palindrome **racecar** from the definition as follows.
 - ① Since it is a symbol, **e** is a palindrome by **B2**.
 - ② Similarly, **c** is a palindrome.
 - ③ Using **R**, **cec** is a palindrome.
 - ④ By **B2**, **a** is a palindrome.
 - ⑤ By **R**, **aceca** is a palindrome.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.
 - B1.** λ is a palindrome. (Why do we need to define this? Think about forming 'otto')
 - B2.** Any symbol **a** is a palindrome.
 - R.** If **x** and **y** are palindromes, then **xyx** is a palindrome.
- We can build up the palindrome **racecar** from the definition as follows.
 - ① Since it is a symbol, **e** is a palindrome by **B2**.
 - ② Similarly, **c** is a palindrome.
 - ③ Using **R**, **cec** is a palindrome.
 - ④ By **B2**, **a** is a palindrome.
 - ⑤ By **R**, **aceca** is a palindrome.
 - ⑥ By **B2**, **r** is a palindrome.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

- **Example 21.1.** A sequence of symbols written together in some order is called a **string**. λ represents the **empty string**, and we do not write λ after it has been introduced with another string; for example, **cubs** λ = **cubs**. A special kind of string called a **palindrome**² can be defined as follows.

B1. λ is a palindrome. (Why do we need to define this? Think about forming 'otto')

B2. Any symbol **a** is a palindrome.

R. If **x** and **y** are palindromes, then **xyx** is a palindrome.

- We can build up the palindrome **racecar** from the definition as follows.

① Since it is a symbol, **e** is a palindrome by **B2**.

② Similarly, **c** is a palindrome.

③ Using **R**, **cec** is a palindrome.

④ By **B2**, **a** is a palindrome.

⑤ By **R**, **aceca** is a palindrome.

⑥ By **B2**, **r** is a palindrome.

⑦ Using **R**, **racecar** is a palindrome.

²Any word that is the same forward as backward, such as **racecar** or **HANNAH**

Activity 21.2. Define a set (or collection) X of strings in the symbols 0 and 1 as follows.

B. 0 and 1 are in X .

R1. If x and y are in X , so is $xyyy$.

R2. If x and y are in X , so is xyx .

- (a) Explain why the string $01001011 \in X$ using the definition. Build up the string step by step, and justify each step by referring to the appropriate part of the definition.
- (b) Use the induction method to prove that, if x is in X , then x has exactly the same number of 0s and 1s.
- (c) Find a string in the symbols 0 and 1 that has the same number of 0s and 1s, but is not in X .

Python Code for Palindrome Testing

- B1. λ is a palindrome.
- B2. Any symbol a is a palindrome.
- R. If x and y are palindromes, then xyx is a palindrome.

```
def isPalindrome(s):
    """Assume s is a string
    Returns True if s is a palindrome; False otherwise.
    Punctuation marks, blanks, and capitalization are
    ignored."""

    def toChars(s):
        s = s.lower()
        letters = ''
        for c in s:
            if c in 'abcdefghijklmnopqrstuvwxyz':
                letters = letters + c
        return letters

    def isPal(s):
        print (' isPal called with', s)
        if len(s) <= 1:
            print (' About to return True from base case')
            return True
        else:
            answer = s[0] == s[-1] and isPal(s[1:-1])
            print (' About to return', answer, 'for', s)
            return answer

    return isPal(toChars(s))
```

```
def testIsPalindrome():
    print ('Try racecar')
    print (isPalindrome("racecar"))
    print(' ')

    print ('Try AURAK')
    print (isPalindrome('AURAK'))
    print(' ')

    print ("Doc Note: I dissent. A fast never prevents a fatness.I diet on cod.")
    print (isPalindrome("Doc Note: I dissent. A fast never prevents a fatness.I diet on cod."))

testIsPalindrome()
```

Recursive Geometry

Example 21.3. The Koch snowflake fractal. Define a sequence of shapes as follows.

B. $K(1)$ is an equilateral triangle.

R. For $n > 1$, $K(n)$ is formed by replacing each line segment



of $K(n - 1)$ with the shape



Construct $K(1)$, $K(2)$, $K(3)$, etc.




Figure 3.7 The curves $K(1)$, $K(2)$, and $K(3)$.




Figure 3.8 The Koch snowflake fractal.