

Design, model and build a USAR robot platform

Mechatronic Project 478 Final Report

Author: Ronan Wells 22961305

Supervisor: Mr. Wayne Swart

2023/03/17

Department of Mechanical and Mechatronic Engineering Stellenbosch University Private Bag X1, Matieland 7602, South Africa.

Plagiarism declaration

I have read and understand the Stellenbosch University Policy on Plagiarism and the definitions of plagiarism and self-plagiarism contained in the Policy [Plagiarism: The use of the ideas or material of others without acknowledgement, or the re-use of one's own previously evaluated or published material without acknowledgement or indication thereof (self-plagiarism or text-recycling)].

I also understand that direct translations are plagiarism, unless accompanied by an appropriate acknowledgement of the source. I also know that verbatim copy that has not been explicitly indicated as such, is plagiarism.

I know that plagiarism is a punishable offence and may be referred to the University's Central Disciplinary Committee (CDC) who has the authority to expel me for such an offence.

I know that plagiarism is harmful for the academic environment and that it has a negative impact on any profession.

Accordingly all quotations and contributions from any source whatsoever (including the internet) have been cited fully (acknowledged); further, all verbatim copies have been expressly indicated as such (e.g. through quotation marks) and the sources are cited fully.

I declare that, except where a source has been cited, the work contained in this assignment is my own work and that I have not previously (in its entirety or in part) submitted it for grading in this module/assignment or another module/assignment. I declare that have not allowed, and will not allow, anyone to use my work (in paper, graphics, electronic, verbal or any other format) with the intention of passing it off as his/her own work.

I know that a mark of zero may be awarded to assignments with plagiarism and also that no opportunity be given to submit an improved assignment.

Signature:	•••••		
Name:		Student no:	
Date:			

Executive summary

Title of Project

Design, model and build a USAR robot platform

Objectives

Create a model to describe the kinematics of a Load Intuitive Module (LIM). Build a prototype Urban Search and Rescue (USAR) device which uses LIMs to climb stairs.

Validate the model using the prototype.

What is current practice and what are its limitations?

The current practice for USAR platform ranges widely, but the most successful platforms use tracks with paddles for locomotion. These devices are effective but very expensive, there is a need for low cost expendable USAR robots.

What is new in this project?

This project will introduce a model to describe a cheaper stair climbing robot platform using LIMs.

If the project is successful, how will it make a difference?

The model developed in this project can be used to inform future USAR designs.

What are the risks to the project being a success? Why is it expected to be successful?

...

What contributions have/will other students made/make?

In 2013, Matthew Wilson developed the LIM system as a masters project at the University of Cape Town (UCT).

Further development on the system was done in final year projects at UCT by students Jordan Haskel, Murray Buchanan, and Richard Daniel Powrie in 2017, 2018, and 2019 respectively.

Which aspects of the project will carry on after completion and why?

USAR devices using LIMs as a platform can be designed, built and tested.

What arrangements have been/will be made to expedite continuation?

...

Table of contents

Ρl	agiar	ism declaration	ii
Ex	ecuti	ve summary	iii
Ta	ble o	f contents	v
Li	st of	figures	vi
Li	st of	tables	vii
1	1.1 1.2	oduction Background	
Li	st of	references	4

List of figures

1.1	Systems layout of Wilson's LIM device (Wilson, 2013)	1
1.2	Powrie's "Di-Wheel" robot (Powrie, 2019)	2

List of tables

Chapter 1

Introduction

1.1 Background

During disasters such as earthquakes, Urban Search And Rescue (USAR) robots are used to detect victims in hazardous environments where first responders would otherwise be put at risk. More advanced USAR robots can explore and map the environment while overcoming obstacles, and deliver supplies to victims who cannot be immediately evacuated. USAR robots were first used in the aftermath of the September 11 attacks on the World Trade Centre, where they had limited success as they would frequently get stuck or broken. Since then, designs for USAR robots with many different locomotion methods have been considered and compared in competitions such as the RoboCup Rescue Robot League and the DARPA Robotics Challenge. At present USAR robots are typically only successful at surveillance, due to the extreme conditions in disaster zones and the urgency of rescue operations, first responders will rarely consider using USAR robots.

Another problem limiting the use of USAR robots is cost, USAR robots are prohibitively expensive so rescue organisations use them sparingly. There is a need for low cost, expendable USAR robots. In 2013, Matthew Wilson proposed an automatically-shape-shifting platform that uses a Load Intuitive Module (LIM) in the place of regular wheels, shown in Figure 1.1 (Wilson, 2013). The LIM system uses a two outer "minor wheels" placed on a central hub that can be rotated as a "major wheel". The minor wheels are geared to the central hub such that the they drive the vehicle, however if they experiences high resistance,




Figure 1.1: Systems layout of Wilson's LIM device (Wilson, 2013)

for example from hitting an obstacle, the torque will cause the major wheel to rotate instead, flipping one of the minor wheels over the obstacle to automat-

ically climb it. This is an adaptation of a similar system that uses three minor wheels called a "Tri-star" developed for Lockheed in 1967 (Forsyth and Forsyth, 1965). Using only two wheels gives the system a lower profile for exploring disaster environments while maintaining the ability to climb obstacles. This is a strong concept for a cheap stair climbing robot as it only uses a single motor for both normal driving and climbing obstacles.

LIMed robot platforms were built individually by four final year students at UCT (Wilson, 2013), (Haskel, 2017), (Buchanan, 2018), and (Powrie, 2019), one of these robots is shown in Figure 1.2. These platforms show some success in climbing a single step, albeit inconsistently. Powrie noted that a mathematical model that accurately describes the kinematics of the system could be developed to optimise the design of LIMed robots. This project is a continuation of these students' work.




Figure 1.2: Powrie's "Di-Wheel" robot (Powrie, 2019)

1.2 Objectives

The aim of this project is to create a model that can be used to inform future USAR designs. The following objectives were identified to meet this aim:

- 1. Create a model to describe the kinematics of a LIM.
- 2. Build a prototype USAR device which uses LIMs to climb stairs.
- 3. Validate the model using the prototype.

1.3. MOTIVATION 3

This project does not intend to create a fully functioning USAR robot, but rather a prototype of the platform that a USAR robot may use.

1.3 Motivation

Future designers can use the model produced in this report to design and optimise LIMed USAR robots. These robots use fewer actuators so could be cheaper than existing USAR robots. Lowering the cost of USAR robots is a priority as it makes them more accessible to rescue organisations.

List of references

Buchanan, M. (2018). Ascender.

Forsyth, R. and Forsyth, J. (1965). Amphibious star-wheeled vehicle.

Haskel, J. (2017). A cost effective, tele-operated observation search and rescue robot.

Powrie, R. (2019). Di-wheel robot.

Wilson, M. (2013). Development of a low-cost, mid-sized, tele-operated, wheeled robot for rescue reconnaissance.