

Microsoft Identity platform


Developer training



Ronny Hansen

Ronny.Hansen@microsoft.com

Cloud Solution Architect



Irina Kostina


Irina.Kostina@Microsoft.com

Cloud Solution Architect

~~Protecting an API~~

Let's talk about Authorization

RFC 6749 - The OAuth 2.0 Authorization Framework



The screenshot shows a web browser window with the address bar displaying <https://tools.ietf.org/html/rfc6749>. The page content includes navigation links at the top: [Docs], [txt|pdf], [draft-ietf-oaut...], [Tracker], [Diff1], [Diff2], [IPR], and [Errata]. Below these, the document is identified as 'Updated by: 8252' and 'PROPOSED STANDARD'. It is attributed to the 'Internet Engineering Task Force (IETF)' and 'D. Hardt, Ed.' with a 'Request for Comments: 6749' and a date of 'October 2012'. The category is 'Standards Track' and the ISSN is '2070-1721'. The main title is 'The OAuth 2.0 Authorization Framework'. The 'Abstract' section states that the framework enables a third-party application to obtain limited access to an HTTP service, either on behalf of a resource owner or by allowing the application to obtain access on its own behalf, replacing and obsoleting the OAuth 1.0 protocol from RFC 5849. The 'Status of This Memo' section notes it is an Internet Standards Track document, a product of the IETF, and has been approved for publication by the IESG. It also provides a URL for current status and feedback: <http://www.rfc-editor.org/info/rfc6749>. The 'Copyright Notice' section states copyright (c) 2012 IETF Trust and the persons identified as the document authors, with all rights reserved. It also mentions that the document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

[\[Docs\]](#) [\[txt|pdf\]](#) [\[draft-ietf-oaut...\]](#) [\[Tracker\]](#) [\[Diff1\]](#) [\[Diff2\]](#) [\[IPR\]](#) [\[Errata\]](#)

Updated by: [8252](#) PROPOSED STANDARD
Errata Exist

Internet Engineering Task Force (IETF) D. Hardt, Ed.
Request for Comments: 6749 Microsoft
Obsoletes: [5849](#) October 2012
Category: Standards Track
ISSN: 2070-1721

The OAuth 2.0 Authorization Framework

Abstract

The OAuth 2.0 authorization framework enables a third-party application to obtain limited access to an HTTP service, either on behalf of a resource owner by orchestrating an approval interaction between the resource owner and the HTTP service, or by allowing the third-party application to obtain access on its own behalf. This specification replaces and obsoletes the OAuth 1.0 protocol described in [RFC 5849](#).

Status of This Memo

This is an Internet Standards Track document.

This document is a product of the Internet Engineering Task Force (IETF). It represents the consensus of the IETF community. It has received public review and has been approved for publication by the Internet Engineering Steering Group (IESG). Further information on Internet Standards is available in [Section 2 of RFC 5741](#).


Information about the current status of this document, any errata, and how to provide feedback on it may be obtained at <http://www.rfc-editor.org/info/rfc6749>.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD license text as described in Section 4.e of

Protecting an API



Protecting an API with Azure AD

- Register the API as an app in Azure AD
 - Define the **delegated** permissions your API exposes in the App Reg portal
 - Help developers using your API to keep to least-privilege
 - Avoid “do everything” permissions where possible
 - Be conservative with permissions users can consent to
- Validate received access tokens in your API
 - Use existing libraries and middleware. They exist for most platforms.
- Apply and enforce permissions!
 - Delegated permissions must not exceed what the signed-in user is allowed to do.

Access tokens

- An API secured with Azure AD will require a valid access token.
- Microsoft issues access tokens in the JSON Web Token (JWT) format.
 - [RFC 7519 JSON Web Token \(JWT\)](#)
 - Structure of a JWT:
 - **Header**: token metadata
 - Provides information needed for token verification
 - **Payload**: claims asserted by token issuer
 - Identifies the authenticated user (if there is one)
 - Includes roles and scopes to be used in authorization
 - **Signature**: created with issuer's private key
 - MUST be verified!
 - Decode and view JWT tokens: <https://jwt.ms>

Validating access tokens

Use a library for signature verification and JWT decoding.

Attempting to implement this yourself is a security risk.

General guidelines

The audience (aud) must identify the service reading the token

The issuer (iss) must be the trusted issuer (e.g. an Azure AD tenant).

The token must be valid ($\text{nbf} < \text{now}$) and not expired ($\text{exp} > \text{now}$).

Use *immutable* unique identifiers to identify subjects.

Object ID (oid) or the subject (sub) claim are good options. Email and UPN can change.

Do *not* accept the “none” signature algorithm.

More details in the documentation

<https://docs.microsoft.com/azure/active-directory/develop/v2-id-and-access-tokens>

Demo

Application Permissions (for daemons)

- Apps do not authenticate as a user
- Apps authorize using "Client Credentials"
- Returned in the "role" claim
- App Roles with "allowedMemberTypes" of Application

App Permissions Demo

<https://github.com/azure-samples/active-directory-dotnetcore-daemon-v2>

```
8      "appRoles": [  
9      {  
10         "allowedMemberTypes": [  
11             "Application"  
12         ],  
13         "description": "Allow the application to read all todo items as itself.",  
14         "displayName": "Read all todo items",  
15         "id": "f8d39977-e31e-460b-b92c-9bef51d14f98",  
16         "isEnabled": true,  
17         "lang": null,  
18         "origin": "Application",  
19         "value": "Todo.Read.All"  
20     }  
21 ],
```

Cactus API example

What does this Access token allow?

eyJ0eXAiOiJKV1QiLCJhbGciOiJSUzI1NiIsImtpZCI6InU0T2ZORlBld0VCb3NIanRyYXVPYiY4NExuWSJ9.eyJhdWQiOiI0MTY2ODRhNy0wYjUyLTRmYTMtOTkxOC1InzZkMTY1NDJiZTliLCJpc3MiOiJodHRwczovL2xvZ2luLm1pY3Jvc29mdG9ubGluZS5jb20vYzcyYTI5NWQtZDdhNS00MwVhLWEzNTEtYjE1ZGQ5ZjY3MjE1L3YyLjAiLCJpYXQiOiE1NjM4ODMzMzYsIm5iZil6MTU2Mzg4MzMzMzNiwiZXhwljoxNTYzODg3MjM2LCJhaW8iOiJBVFFBeS84TUFBQUFhTHRBLzNNb2R4K09OK1FNaTUwMnZycFdiY0h6c253akNxYmladU9qcTE2bFkxelU3YkVNdDIIUW90NXJGcDVqIiwiaXpwIjoiYml3NjRjMjE1NDJiZTliOC00OWRILWFhMjQtNmM3NmQ3ZGM4MDBmliwiYXpwYWNYljoiiMCIslm5hbWUiOiJNZWdhbiBCb3dibilslm9pZCI6IjBINzQ4Y2QwLTVhMmEtNDkxOC1hMzUxLTk1NDIiInzVmZDFkZCIsInByZWZlcnJlZi91c2VybmFtZSI6IjE1Z2FuQkBaWNYb3NvZnRpZGVudGI0eS5kZXkiLCJyaCI6Ikk1LCJyb2xlcyI6IjYyLjBZG1pbjIjLCJzY3AiOiJkYXRhbG9nLlZpZXcuQWxsIENhdGFsb2cuVmllZy5QdWJsaXNoZWQiLCJzdWliOiIiwWdDQdkVUNG9ySFJuUlllZE12QTRDWWxZeGdfQ293c0UxQkdUSUFLNmhfliwidGkljoiYzcyYTI5NWQtZDdhNS00MwVhLWEzNTEtYjE1ZGQ5ZjY3MjE1liwidXRpljoia2FIRkNSR3dtMFNPd01Obmp2SUhBQSIsInZlcil6IjluMCJ9.gdp_cBRgJhfDo7d8_ooG1d41NCfLmLLwNxFTQI-_hhskeHXg45DMFBTCyxBv1Kt5ggrxxKgfkAZTdrM01mzpw-DhA8TX7xi7altJJ-iljNMrRQVJI8F6UVZxMetgN_20184Ry9IbBDDOI0Ac6A8UnpV8uUbV08Aii3ecjpX3vAaaTKuOQsdmzZEh9CK1REvxn6ospUTkL2wzqMQ-E4h-wb30-NpCqLuuaGItqpw45Sunn1hoq8flZyzgCkVz65V_Udw4eTbKA1FGOG7nXiN_Pp0EKy1O6qiN77BQENA5PQOIcgRaOedQ1N9eH6_qT4AavHKMkqrxfcFp2QAD-UR

Cactus API example

What does this Access token allow?

```
[Header].{  
  "aud": "416684a7-0b52-4fa3-9918-e76d16542be2",  
  "iss": "https://login.microsoftonline.com/c72a295d-d7a5-41ea-a351-b15dd9f67215/v2.0",  
  "iat": 1563883336,  
  "nbf": 1563883336,  
  "exp": 1563887236,  
  "aio": "ATQAY/8MAAAAaLtA/3Modx+ON+QMi502vrpWboHzsnwjCqbiZuOjq16lY1zU7bEMt9HQot5rFp5j",  
  "azp": "bb764c21-49b8-49de-aa24-6c76d7dc800f",  
  "azpacr": "0",  
  "name": "Megan Bowen",  
  "oid": "0e748cd0-5d2a-4918-a351-9549e75fd1dd",  
  "preferred_username": "MeganB@microsoftidentity.dev",  
  "rh": "I",  
  "roles": [  
    "Admin"  
  ],  
  "scp": "Catalog.View.All Catalog.View.Published",  
  "sub": "0X7PvET4orHRnRYndMvA4CYIYxg_CowsE1BGTIAK6hE",  
  "tid": "c72a295d-d7a5-41ea-a351-b15dd9f67215",  
  "uti": "kaeFCRGwm0SOwMnNjvIHAA",  
  "ver": "2.0"  
}.[Signature]
```

Cactus API example

What does this Access token allow?

```
[Header].{
  "aud": "416684a7-0b52-4fa3-9918-e76d16542be2",
  "iss": "https://login.microsoftonline.com/c72a295d-d7a5-41ea-a351-b15dd9f67215/v2.0",
  "iat": 1563883336,
  "nbf": 1563883336,
  "exp": 1563887236,
  "aio": "ATQAY/8MAAAAaLtA/3Modx+ON+QMi502vrpWboHzsnwjCqbiZuOjq16lY1zU7bEMt9HQot5rFp5j",
  "azp": "bb764c21-49b8-49de-aa24-6c76d7dc800f",
  "azpacr": "0",
  "name": "Megan Bowen",
  "oid": "0e748cd0-5d2a-4918-a351-9549e75fd1dd",
  "preferred_username": "MeganB@microsoftidentity.dev",
  "rh": "I",
  "roles": [
    "Admin"
  ],
  "scp": "Catalog.View.All Catalog.View.Published",
  "sub": "0X7PvET4orHRnRYndMvA4CYIYxg_CowsE1BGTIAK6hE",
  "tid": "c72a295d-d7a5-41ea-a351-b15dd9f67215",
  "uti": "kaeFCRGwm0SOwMnNjvIHAA",
  "ver": "2.0"
}.[Signature]
```

Cactus API example

What does this Access token allow?

```
[Header].{  
  "aud": "416684a7-0b52-4fa3-9918-e76d16542be2",  
  "iss": "https://login.microsoftonline.com/c72a295d-d7a5-41ea-a351-b15dd9f67215/v2.0",  
  "iat": 1563882662,  
  "nbf": 1563882662,  
  "exp": 1563886562,  
  "aio": "42FgYBBvuZbJnh7xs0l8YXcOy7nLAA==",  
  "azp": "bf9b8d73-dc3f-4c03-a928-7529d3cc3fd4",  
  "azpacr": "1",  
  "oid": "7d655a98-843c-4337-ad24-3a4b0922179e",  
  "roles": [  
    "Catalog.View.All"  
  ],  
  "sub": "7d655a98-843c-4337-ad24-3a4b0922179e",  
  "tid": "c72a295d-d7a5-41ea-a351-b15dd9f67215",  
  "uti": "pPPIBgD_AUqWqKVYHTUQAA",  
  "ver": "2.0"  
}.[Signature]
```

Cactus API example

What does this Access token allow?

```
[Header].{  
  "aud": "416684a7-0b52-4fa3-9918-e76d16542be2",  
  "iss": "https://login.microsoftonline.com/c72a295d-d7a5-41ea-a351-b15dd9f67215/v2.0",  
  "iat": 1563882662,  
  "nbf": 1563882662,  
  "exp": 1563886562,  
  "aio": "42FgYBBvuZbJnh7xs0l8YXcOy7nLAA==",  
  "azp": "bf9b8d73-dc3f-4c03-a928-7529d3cc3fd4",  
  "azpacr": "1",  
  "oid": "7d655a98-843c-4337-ad24-3a4b0922179e",  
  "roles": [  
    "Catalog.View.All"  
  ],  
  "sub": "7d655a98-843c-4337-ad24-3a4b0922179e",  
  "tid": "c72a295d-d7a5-41ea-a351-b15dd9f67215",  
  "uti": "pPPIBgD_AUqWqKVYHTUQAA",  
  "ver": "2.0"  
}.[Signature]
```


Cactus API example

What does this Access token allow?

```
[Header].{  
  "aud": "416684a7-0b52-4fa3-9918-e76d16542be2",  
  "iss": "https://login.microsoftonline.com/c72a295d-d7a5-41ea-a351-b15dd9f67215/v2.0",  
  "iat": 1563882662,  
  "nbf": 1563882662,  
  "exp": 1563886562,  
  "aio": "42FgYBBvuZbJnh7xs0l8YXcOy7nLAA==",  
  "azp": "bf9b8d73-dc3f-4c03-a928-7529d3cc3fd4",  
  "azpacr": "1",  
  "oid": "7d655a98-843c-4337-ad24-3a4b0922179e",  
  "roles": [  
    "Catalog.View.All"  
  ],  
  "sub": "7d655a98-843c-4337-ad24-3a4b0922179e",  
  "tid": "c72a295d-d7a5-41ea-a351-b15dd9f67215",  
  "uti": "pPPIBgD_AUqWqKVYHTUQAA",  
  "ver": "2.0"  
}.[Signature]
```

More tokens

Human Identities

Enterprise - Single Tenant for LOB Apps

```
{
  "typ": "JWT",
  "alg": "RS256",
  "kid": "1LTMzakihiRla_8z2BEJvXewMqo"
}.{
  "ver": "2.0",
  "iss": "https://login.microsoftonline.com/fa15d692-e9c7-4460-a743-29f2956fd429/v2.0",
  "sub": "AAAAAAAAAAAAAAAAAAAAAAIkzqFvRsaSaFHy782bbtaQ",
  "aud": "6cb04018-a3f5-46a7-b995-940c78f5aef3",
  "exp": 1536361411,
  "iat": 1536274711,
  "nbf": 1536274711,
  "name": "Abe Lincoln",
  "preferred_username": "AbeLi@microsoft.com",
  "oid": "00000000-0000-0000-66f3-3332eca7ea81",
  "tid": "fa15d692-e9c7-4460-a743-29f2956fd429",
  "nonce": "123523",
  "aio": "Df2UVXL1ix!lMCWMS0JBcFatzcGfvFGhjKv8q5g0x732dR5MB5BisvGQ07YWByjd8iQDLq!eGbIDakyp5mn0rcdqHeYSnltepQmRp6AIz8jY"
}.[Signature]
```

Human Identities

Enterprise – Multi Tenant for LOB Apps

```
{
  "typ": "JWT",
  "alg": "RS256",
  "kid": "1LTMzakihiRla_8z2BEJvXewMqo"
}.{
  "ver": "2.0",
  "iss": "https://login.microsoftonline.com/9188040d-6c67-4c5b-b112-36a304b66dad/v2.0",
  "sub": "BBBBBBBBBBBBBBBBBBBBBBBBBBIkzqFvRsaSaFHy782bbtaQ",
  "aud": "6cb04018-a3f5-46a7-b995-940c78f5aef3",
  "exp": 1536361411,
  "iat": 1536274711,
  "nbf": 1536274711,
  "name": "Matthijs Hoekstra",
  "preferred_username": "matthijs@contoso.com",
  "oid": "12345678-0000-0000-66f3-3332eca550ab",
  "tid": "9188040d-6c67-4c5b-b112-36a304b66dad",
  "nonce": "123523",
  "aio": "Df2UVXL1ix!lMCWMS0JBcFatzcGfvFGhjKv8q5g0x732dR5MB5BisvGQ07YWByjd8iQDLq!eGbIDakyp5mn0rcdqHeYSnltepQmRp6AIZ8jY"
}.[Signature]
```

Human Identities

Enterprise - External B2B User from another tenant

```
{
  "typ": "JWT",
  "alg": "RS256",
  "kid": "1LTMzakihiRla_8z2BEJvXewMqo"
}.{
  "ver": "2.0",
  "iss": "https://login.microsoftonline.com/9188040d-6c67-4c5b-b112-36a304b66dad/v2.0",
  "sub": "AAAAAAAAAAAAAAAAAAAAAAIkzqFVrSaSaFHy782bbtaQ",
  "aud": "6cb04018-a3f5-46a7-b995-940c78f5aef3",
  "exp": 1536361411,
  "iat": 1536274711,
  "nbf": 1536274711,
  "idp": "https://login.microsoftonline.com/3338040d-6c67-4c5b-b112-36a304b66dad/v2.0",
  "name": "Abe Lincoln",
  "preferred_username": "AbeLi@microsoft.com",
  "oid": "00000000-0000-0000-66f3-3332eca7ea81",
  "tid": "9188040d-6c67-4c5b-b112-36a304b66dad",
  "nonce": "123523",
  "aio": "Df2UVXL1ix!lMCWMS0JBcFatzcGfvFGhjKv8q5g0x732dR5MB5BisvGQ07YWByjd8iQDLq!eGbIDakyp5mn0rcdqHeYSnltepQmRp6AIZ8jY"
}.[Signature]
```

Human Identities

Enterprise - External B2B User from gmail

```
{
  "typ": "JWT",
  "alg": "RS256",
  "kid": "1LTMzakihiRla_8z2BEJvXewMqo"
}.{
  "ver": "2.0",
  "iss": "https://login.microsoftonline.com/9188040d-6c67-4c5b-b112-36a304b66dad/v2.0",
  "sub": "AAAAAAAAAAAAAAAAAAAAAAIkzqFvRsaSaFHy782bbtaQ",
  "aud": "6cb04018-a3f5-46a7-b995-940c78f5aef3",
  "exp": 1536361411,
  "iat": 1536274711,
  "nbf": 1536274711,
  "idp": "gmail.com",
  "name": "Matthijs",
  "email": "matthijs@gmail.com",
  "oid": "00000000-0000-0000-66f3-3332eca7ea81",
  "tid": "9188040d-6c67-4c5b-b112-36a304b66dad",
  "unique_name": "google.com#matthijs@gmail.com",
  "nonce": "123523",
  "aio": "Df2UVXL1ix!lMCWMS0JBcFatzcGfvFGhjKv8q5g0x732dR5MB5BisvGQ07YWByjd8iQDLq!eGbIDakyp5mn0rcdqHeYSnltepQmRp6AIZ8jY"
}
```

24

[Signature]


Human Identities

External identities - identity in B2C app


```
{
  "typ": "JWT",
  "alg": "RS256",
  "kid": "1LTMzakihiRla_8z2BEJvXewMqo"
}.{
  "ver": "2.0",
  "iss": "https://mahoekestb2c.b2clogin.com/fa15d692-e9c7-4460-a743-29f2956fd429/v2.0",
  "sub": "AAAAAAAAAAAAAAAAAAAAAAIkzqFvRsaSaFHy782bbtaQ",
  "aud": "5cf15118-a3f5-46a7-b995-940c78f5aef3",
  "exp": 1536361411,
  "iat": 1536274711,
  "nbf": 1536274711,
  "idp": "facebook.com",
  "name": "Matthijs",
  "emails": [
    "matthijs@hoekstraonline.net"
  ],
  "oid": "00000000-0000-0000-66f3-3332eca7ea81",
  "tid": "fa15d692-e9c7-4460-a743-29f2956fd429",
  "unique_name": "google.com#matthijs@gmail.com",
  "customclaimsareawesomeinb2c": "TechoramaNL",
```

**What happens when one API
needs to call another API?**


App has an authenticated user and a token to call API




Call the API




Call the API




Call the API




Call the API




Call the API




Call the API




Call the API



Call the API



Call the API



Call the API



Call the API



Coding OBO (On Behalf Of)

```
app = ConfidentialClientApplicationBuilder.Create(config.ClientId)  
    .WithClientSecret(config.ClientSecret) //TODO do this with cert ;)  
    .Build();
```

Coding On Behalf Of (OBO)

```
X509Certificate2 certificate = ReadCertificate(config.CertificateName);  
application = ConfidentialClientApplicationBuilder.Create(config.ClientId)  
    .WithCertificate(certificate)  
    .Build();
```

```
var result = await application.AcquireTokenOnBehalfOf(scopes, new  
    UserAssertion(accesstoken))  
    .ExecuteAsync()  
    .ConfigureAwait(false);
```

But wait, there is more

User roles and groups.....

Please join the Authorization Session

Next Session:
Authorization
WEWC589 Thursday June 4th 14:00-15:00

Sign up for the webinar at
<http://aka.ms/modernIdentityForDevelopers>

Homework

Protecting API

Protecting your own API

Web => WebAPI on .NET Core

1. Go to: <https://aka.ms/APILabCore>
2. Download the whole repo and go to folder: 4-WebApp-your-API
3. Choose the 4-1-MyOrg (For Azure AD integration)

WPF Desktop Client => WebAPI on .NET Full Framework

1. Go to: <https://aka.ms/APILabFull>
2. Follow the instructions

Self Study to learn more

Scenario: Protected web API

- <https://docs.microsoft.com/en-us/azure/active-directory/develop/scenario-protected-web-api-overview>

How to: Sign in any Azure Active Directory user using the multi-tenant application pattern

- <https://docs.microsoft.com/en-us/azure/active-directory/develop/howto-convert-app-to-be-multi-tenant>

