

# RookDB – API Documentation

## Index of Existing APIs

1. Init Catalog
  2. Load Catalog
  3. Create Database
  4. Show Databases
  5. Select Database
  6. Show Tables
  7. Save Catalog
  8. Create Table
  9. Init Table
  10. Init Page
  11. Page Count
  12. Create Page
  13. Read Page
  14. Write Page
  15. Page Free Space
  16. Add Tuple to Page
  17. Read Item / Get Tuple
- 

## API Descriptions

### 0. init\_catalog API

#### Description:

Creates catalog.json if it doesn't exist and initializes it with an empty catalog (`{"databases": {}}`).

#### Function:

```
pub fn init_catalog()
```

#### Implementation:

1. Check if database/global/catalog.json exists.
  2. If not, create parent directories and an empty file with data `{"databases": {}}`.
- 

### 1. load\_catalog API

#### Description:

- Loads the catalog table metadata into memory as a **Catalog struct**.

#### Function:

```
pub fn load_catalog() -> Catalog
```

#### Ouput:

- Returns a valid Catalog struct containing table metadata.

#### Implementation:

- Reads the catalog file, validates its contents, and deserializes it into a Catalog struct.

## 2. create\_database API

#### Description:

- Creates a new database in the catalog.

#### Function:

```
pub fn create_database(catalog: &mut Catalog, db_name: &str) -> Result<(), StorageError>
```

#### Input:

- **catalog**: in-memory catalog metadata.
- **db\_name**: Name of the new database to be created.

#### Output:

- Returns Ok on success or an error if creation fails.

#### Implementation:

1. Check if the database already exists; if not, insert a new empty entry into catalog.databases.
2. Serialize the updated Catalog and write it to database/global/catalog.json.
3. Create a new directory at database/base/{db\_name} for the database's physical storage.

## 2. save\_catalog API

#### Description:

- Writes the in-memory Catalog structure (containing table metadata) back to disk in JSON format.

#### Function:

```
pub fn save_catalog(catalog: &Catalog)
```

#### Input:

- **catalog**: A reference to a Catalog struct in memory that holds all table definitions.

#### Output:

- Writes the catalog data to CATALOG\_FILE.

#### Implementation:

- Serializes the given Catalog struct into a JSON string and writes it to the catalog file path.

---

## 3. create\_table API

#### Description:

- Creates a new table entry in the in-memory Catalog with the provided table name and column definitions.
- If the table does not already exist, it is added to the catalog and the updated catalog is written to disk in JSON format.

#### Function:

```
pub fn create_table(catalog: &mut Catalog, table_name: &str, columns: Vec<Column>)
```

#### Input:

- catalog: A mutable reference to the in-memory Catalog structure that holds metadata for all tables.
- table\_name: A string slice representing the name of the new table to be created.
- columns: A vector of Column structs, where each struct contains the column name and data type for the new table.

#### Output:

- Updates the in-memory Catalog by inserting the new table.
- Persists the updated catalog to disk by writing to the CATALOG\_FILE in JSON format using **save\_catalog** API.

#### Implementation:

- Checks if a table with the given name already exists in the catalog.
- If not, creates a new Table struct using the provided columns.
- Inserts the table into the catalog.tables HashMap.
- Calls save\_catalog(catalog) to serialize and write the updated catalog to disk.
- Creates a new data file for the table in {TABLE\_DIR}/{table\_name}.dat.
- Initializes the table file header by writing TABLE\_HEADER\_SIZE bytes of zeros using init\_table().

## 4. init\_table API

#### Description:

- Initializes the **Table Header** by writing the **first page** (8192 bytes) into the table file with 0's. The first 4 bytes represent the **Page Count** (1).

#### Function:

```
pub fn init_table(file: &mut File)
```

#### Input:

file: File pointer to update Table Header.

#### Output:

Table header (first page) initialized with page\_count = 1 in the first 4 bytes and remaining bytes set to zero.

#### Implementation:

1. Move the file cursor to the beginning of the file.
2. Allocate a buffer of 8192 bytes (**TABLE\_HEADER\_SIZE**) initialized to zero.
3. Write the entire 8192-byte buffer (including the page count) to disk, marking the creation of the first table page.
4. Write another 8192-byte buffer to disk to initialize the first data page along with page headers using

create\_page API (Page 1), which will store table tuples.

---

## 5. init\_page API

### Description:

- Initializes the **Page Header** with two offset values for **In Memory Page**:
  - **Lower Offset** (PAGE\_HEADER\_SIZE) → bytes 0..4
  - **Upper Offset** (PAGE\_SIZE) → bytes 4..8

### Function:

```
pub fn init_page(page:&mut Page)
```

### Input:

page: **In Memory Page** to set Header - Lower and Upper Offsets.

### Output:

Page header updated with lower and upper offsets.

### Implementation:

1. Write the lower offset (PAGE\_HEADER\_SIZE) into the first 4 bytes of the page header (0..4).
  2. Write the upper offset (PAGE\_SIZE) into the next 4 bytes of the page header (4..8).
- 

## 6. page\_count API

### Description:

To get total number of pages in a file

### Function:

```
pub fn page_count(file: &mut File)
```

### Input:

file: file to calculate number of pages.

### Output:

Total number of pages present in the file.

### Implementation:

1. Use the **read\_page()** function to read the first page (page ID 0) from the file into memory.
  2. Extract the **first 4 bytes** from the in-memory page buffer — these bytes represent the page count stored in the table header.
  3. Return the first 4 bytes as page count.
- 

## 7. create\_page API

### Description:

Create a page in disk for a file.

**Function:**

```
pub fn create_page(file: &mut File)
```

**Input:**

file: file to create to a file

**Output:**

1. Create a page at the end of the file.
2. Update the File Header with **Page Count**.

**Implementation:**

1. Initializes a new page **in memory** using **init\_page** API (update page header - lower and upper).
  2. Reads the **current page count** from the file using the **page\_count** API.
  3. Moves the file cursor to the end of the file.
  4. Writes the initialized in-memory page to the file and **updates the file header** by incrementing the page count stored in the first 4 bytes.
- 

## 8. read\_page API

**Description:**

Reads a page from a disk/file into memory.

**Function:**

```
pub fn read_page(file: &mut File, page: &mut Page, page_num: u32)
```

**Input:**

file: file to read from,  
page: memory page to fill,  
page\_num: page number to read

**Output:**

Populates the given memory page with data read from the file.

**Implementation:**

1. Calculates the **offset** as **(page\_num \* PAGE\_SIZE)** and moves the file cursor to the correct position.
2. Reads data from that offset position up to **offset + PAGE\_SIZE** and copies it into the page memory.

**Cases Handled:**

1. Checks the file size and returns an error if the requested page does not exist in the file.
- 

## 9.write\_page API

**Description:**

Write a page from memory to disk/file.

**Function:**

```
pub fn write_page(file: &mut File, page: &mut Page, page_num: u32)
```

**Input:**

file: file to write,  
page: memory page to copy from,  
page\_num: page number to write

**Output:**

Writes the contents of the given memory page to the file at the specified page offset.

**Implementation:**

1. Calculates the **offset** as  $\text{page\_num} * \text{PAGE\_SIZE}$  and moves the file cursor to the correct position.
  2. copy the contents of the given memory page from offset to offset + PAGE\_SIZE positions to the file.
- 

## 10. page\_free\_space API

**Description:**

To calculate the total amount of free space left in the page.

**Function:**

```
pub fn page_free_space(page: &Page)
```

**Input:**

page: page to calculate the free space.

**Output:**

Total amount of freespace left in the page.

**Implementation:**

1. Read the lower pointer from the first 4 bytes of the page.
  2. Read the upper pointer from the next 4 bytes of the page.
  3. Calculate free space = upper - lower.
  4. Return the free space.
- 

## 11. Add Tuple

**Description:**

Adds raw data to the file.

**Function:**

- In the buffer manager load\_csv\_into\_pages function.

**Output:**

Data inserted in the file.

**Implementation:**

1. Get the **total number of pages** in the file using [page\\_count](#) API.
2. Read the **last page** into memory using [read\\_page](#) API.
3. Check **free space** in the page using [page\\_free\\_space](#) API.

4. If the last page has enough free space to store the data and its ItemId (i.e., if `free_space >= data.size() + ITEM_ID_SIZE`):
    - a. Calculate the **insertion offset** from the upper pointer.  
`start = upper - data.len()`
    - b. Copy the data bytes into the page buffer starting at this offset.
    - c. Update the **upper pointer** in the page header to the new start of free space.
    - d. Write the **ItemId entry** (offset and length of the data) at the position indicated by the lower pointer.
    - e. Update the **lower pointer** in the page header to account for the newly added ItemId (`lower += ITEM_ID_SIZE`).
    - f. Write the updated page back to disk using [write\\_page](#) API.
  5. If the last page does not have enough free space:
    - a. Create a new page in the file and add the tuple in the new page.
- [Code Documentation \(https://hemanth-sunkireddy.github.io/Storage-Manager/storage\\_manager/all.html\)](https://hemanth-sunkireddy.github.io/Storage-Manager/storage_manager/all.html)
  - **Reference:** [Postgres Internals – Page Layouts & Data \(https://www.postgresql.org/docs/current/storage-page-layout.html\)](https://www.postgresql.org/docs/current/storage-page-layout.html)

**Note:** Some APIs have undergone slight implementation changes during development. So, some of the implementation steps might not aligned with the actual code functions.