

NAME

0x0 - interface with **https://0x0.st**

SYNOPSIS

0x0 file [-nv] *filename*

0x0 url [-nv] *URL*

DESCRIPTION

The **0x0** utility is an interface to the **https://0x0.st** file hosting.

The command modifiers are as follows.

file *filename*

Upload the local file *filename*. If *filename* is a directory, a tarball of the directory is uploaded. If *filename* is -, stdin is uploaded. *URL* when opened. Supported protocols are http and https.

url *URL*

Upload the remote file at *URL*. Supported protocols are http and https.

The options are as follows:

-n Do not execute the curl(1) or tar(1) commands.

-v Output the curl(1) and tar(1) commands that are executed, or would be if **-n** was not passed.

ENVIRONMENT

NULLPOINTERINSTANCE Any non-empty value of the environment variable
NULLPOINTERINSTANCE is used instead of the standard 0x0 instance
https://0x0.st. See the *INSTANCES* section for a list of known working instances.

INSTANCES

https://0x0.st, **https://ttm.sh**, **https://envs.sh**

EXIT STATUS

The **0x0** utility exits 0 on success, and >0 if an error occurs.

EXAMPLES

Upload the source code of

```
$ 0x0 file "$(which 0x0)"  
https://0x0.st/iU8B.bin
```

Output the curl(1) command **0x0** uses in the previous example without executing it:

```
$ 0x0 file -nv "$(which 0x0)"  
curl -Ss -w status_code=%{http_code} https://0x0.st "-Ffile=@"/usr/local/bin/0x0""
```

Upload a diff:

```
$ diff old new | 0x0 file -  
https://0x0.st/iU8L.txt
```

Upload a remote file:

```
$ 0x0 url http://www.openbsd.org/art/puffy/ppuf800X725.gif  
https://0x0.st/iU8n.gif
```

SEE ALSO

curl(1), tar(1)

<https://0x0.st>, <https://ttm.sh>, <https://envs.sh>, <https://github.com/rooyca/0x0>

AUTHORS

Olav Fosse <post@olavfosse.no>

rooyca <blog.png8n@slmail.me>