

Kingsgate API Documentation

Base URL: `https://api.kingsgate-dev.kg91.pro`

Environments: `sandbox, live`

1. Payins: Integrate Kingsgate payments in your website

To enable payment services through Kingsgate on your website, follow the below steps :

Step 1: Get Merchant Access Token

Authenticates a merchant and returns a JWT access token required for all subsequent API requests.

Endpoint: `POST /api/merchant/auth`

Headers:

Content-Type	application/json
--------------	------------------

Body:

```
{
  "api_key": "<YOUR_MERCHANT_API_KEY>",
  "integration_id": "<YOUR_MERCHANT_INTEGRATION_ID>"
}
```

Sample Example:

```
curl --location 'https://api.kingsgate-dev.kg91.pro/merchant/auth' \
--header 'Content-Type: application/json' \
```

```
--data '{
  "integration_id": "your_integration_id",
  "api_key": "your_api_key"
}'
```

Sample Response:

```
{
  "status": 200,
  "accessToken": "<JWT_ACCESS_TOKEN>"
}
```

HTTP Status Codes -

HTTP Status	Description
200	success
500	Internal Server Error
400	Bad Request Error (Invalid or missing request parameters)

Step 2: Create Order and Generate Payment Link

Creates a new payment order and returns a hosted payment page URL.

Endpoint: **POST /api/payment/get-payment-page**

Headers:

Content-Type	application/json
Authorization	Bearer

Body:

```
{
  "amount": <AMOUNT>,
  "orderId": "<ORDER_ID>",
  "user": {
    "id": "<USER_ID>",
    "name": "<USER_NAME>",
    "email": "<USER_EMAIL>",
    "mobileNumber": "<USER_MOBILE>"
  },
  "paymentMethod": "<PAYMENT_METHOD>",
  "environment": "<ENVIRONMENT>",
  "paymentGateway": "<PAYMENT_GATEWAY_IF_REQUIRED>",
  "successUrl": "<SUCCESS_URL>",
  "failureUrl": "<FAILURE_URL>",
  "webhookUrl": "<Server_TO_SERVER_CALLBACK>"
}
```

Field Descriptions:

Field	Type	Required	Description
<code>amount</code>	Number	Yes	Amount in INR
<code>orderId</code>	String	Yes	Unique order identifier
<code>user.id</code>	String	Yes	Unique user ID
<code>user.name</code>	String	Yes	Name of the user
<code>user.email</code>	String	No	Email of the user
<code>user.mobileNumber</code>	String	No	Mobile number of the user
<code>paymentMethod</code>	String	Yes	Payment type. Options: <code>UPI</code> , <code>E_WALLET</code> , <code>NET_BANKING</code>
<code>environment</code>	String	Yes	Payment environment: <code>sandbox</code> or <code>live</code>
<code>paymentGateway</code>	String	Conditional	Required only if <code>environment = sandbox</code> . Options: <code>PAYU</code> ,


```
}  
'
```

Sample Response:

```
{  
  "status": 201,  
  "data": {  
    "url": "<CHECKOUT_PAGE_URL>"  
  }  
}
```

HTTP Status Codes -

HTTP Status	Description
201	success
500	Internal Server Error
400	Bad Request Error (Invalid or missing request parameters)
403	Forbidden (auth token missing or invalid)

Request Body Parameters for `webhookUrl` Invocation

Below is a sample request body that will be sent via an HTTP `POST` to the configured `webhookUrl` when a payin is either **successful** or **failed**

```
{  
  "signature": "<JWT_TOKEN>",  
  "orderId": "<MERCHANT_ORDER_ID>",  
  "kgOrderId": "<KINGSGATE_ORDER_ID>",  
}
```

```

"status": "COMPLETE",
"user": {
  "id": "<USER_ID>",
  "name": "<USER_NAME>",
  "mobile": "<USER_MOBILE>",
  "email": "<USER_EMAIL>"
},
"transactionDetails": {
  "id": "<TRANSACTION_ID>",
  "amount": <AMOUNT>,
  "paymentMethod": "<PAYMENT_METHOD>",
  "time": "<TIMESTAMP>"
}
}

```

Order Status Values:

INITIATED	Order is created but payment not started
ASSIGNED	Gateway assigned
SUBMITTED	Payment submitted
COMPLETE	Payment successful
FAILED	Payment failed

Verifying Signature for Webhook

The `signature` is a JWT (JSON Web Token) that is signed using your Merchant API Key. To verify the authenticity of the request, you should decode and verify the JWT using your own API key as the secret.

Example

```

import jwt from "jsonwebtoken";
const signature = req.body.signature;
const merchantApiKey = process.env.MERCHANT_API_KEY;
try {
  const payload = jwt.verify(signature, merchantApiKey);

```

```
console.log("Verified payload:", payload);
} catch (err) {
  console.error("Invalid signature", err);
}
```

Check Payin Status API

Endpoint: **GET /api/payment/order-status/:orderId**

Query Parameters:

environment	"sandbox" or "live"
-------------	---------------------

Headers:

Authorization	Bearer
---------------	--------

Sample Request:

GET /api/payment/order-status/ORDER-XYZ-001?environment=sandbox

Sample Response:

```
{
  "httpStatus": 200,
  "data": {
    "orderId": "<MERCHANT_ORDER_ID>",
    "kgOrderId": "<KINGSGATE_ORDER_ID>",
    "status": "COMPLETE",
    "user": {
      "id": "<USER_ID>",
      "name": "<USER_NAME>",
      "mobile": "<USER_MOBILE>",
      "email": "<USER_EMAIL>"
    },
    "transactionDetails": {
      "id": "<TRANSACTION_ID>",
```

```
"amount": <AMOUNT>,  
"paymentMethod": "<PAYMENT_METHOD>",  
"time": "<TIMESTAMP>"  
}  
}  
}
```

HTTP Status Codes -

HTTP Status	Description
200	success
500	Internal Server Error
400	Bad Request Error (Invalid or missing request parameters)

Order Status Values:

INITIATED	Order is created but payment not started
ASSIGNED	Gateway assigned
SUBMITTED	Payment submitted
COMPLETE	Payment successful
FAILED	Payment failed

2. Payouts: Use Kingsgate APIs to pay your website users

Step 1: Get Merchant Access Token

Authenticates a merchant and returns a JWT access token required for all subsequent API requests.

Endpoint: **POST /api/merchant/auth**

Headers:

Content-Type	application/json
--------------	------------------

Body:

```
{
  "api_key": "<YOUR_MERCHANT_API_KEY>",
  "integration_id": "<YOUR_MERCHANT_INTEGRATION_ID>"
}
```

Sample Example:

```
curl --location 'https://api.kingsgate-dev.kg91.pro/merchant/auth' \
--header 'Content-Type: application/json' \
--data '{
  "integration_id": "your_integration_id",
  "api_key": "your_api_key"
}'
```

Sample Response:

```
{
  "status": 201,
  "accessToken": "<JWT_ACCESS_TOKEN>"
}
```

Step 2: Initiate Payout

Initiates a payout request using one of the supported payment methods: UPI, Net Banking, or E-Wallet.

Endpoint: POST /api/payout

Body:

Common Fields:

Field	Required	Description
amount	Yes	The amount to be paid
paymentMethod	Yes	One of UPI , NET_BANKING , E_WALLET
user	Yes	Information about the user
webhookUrl	No	The URL that will receive an HTTPS POST request when a payout either succeeds or fails . This endpoint should be configured to handle the payout result notification accordingly. The request body will follow the same structure as the sample response from the Check Payout Status API.

user Object

Field	Required	Description
id	Yes	Unique user identifier
name	Yes	Full name of the user
email	No	Email address
mobile	No	Mobile number

Sample Example:

```
curl --location 'https://api.kingsgate-dev.kg91.pro/api/payout' \
--header 'Content-Type: application/json' \
--header 'Authorization: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpZCI6NSwiZW1haWwiOiAhYmhpbnVwQHlvcG1haWwuO29tliwidHlwZSI6Pk1FUkNlQU5UPiwiWF0ljoXNzUxNDM1NzM5fQ.QOYoEKnrIMvYObDIwfiyp6r1RRLF-rtWT6oehSbooSg' \
--data-raw '{
"amount": 1,
```

```
"orderId": "CT_TEST_PAYOUT_33",
"paymentMethod": "UPI",
"upiDetails": {
  "upId": "usera0012@okhdfcbank",
  "mobileNumber": "9812122217"
},
"user": {
  "id": "NEW_USER2",
  "name": "USER",
  "email": "user@catalyst.sh",
  "mobile": "9816221247"
}
}'
```

Sample Response:

```
{
  "status": 201,
  "data": {
    "orderId": "<MERCHANT_ORDER_ID>",
    "kgOrderId": "<KINGSGATE_ORDER_ID>",
    "status": <STATUS>,
    "message": <MESSAGE>,
  }
}
```

HTTP Status Codes -

HTTP Status	Description
201	success
500	Internal Server Error

400	Bad Request Error (Invalid or missing request parameters)
403	Forbidden (auth token missing or invalid)

Payment Method-Specific Examples

1. UPI Payment

```
{
  "amount": <number>,
  "paymentMethod": "UPI",
  "user": {
    "id": "<user_id>",
    "name": "<user_name>",
    "email": "<user_email>",
    "mobile": "<user_mobile>"
  },
  "upiDetails": {
    "upild": "<upi_id>",
    "mobileNumber": "<linked_mobile_number>"
  }
}
```

Field	Required	Description
<code>upild</code>	Yes	UPI ID of the recipient
<code>mobileNumber</code>	Yes	Mobile number linked to UPI

2. Net Banking Payment

```
{
  "amount": <number>,
  "paymentMethod": "NET_BANKING",
  "user": {
    "id": "<user_id>",
```

```

    "name": "<user_name>",
    "email": "<user_email>",
    "mobile": "<user_mobile>"
  },
  "netBankingDetails": {
    "beneficiaryName": "<name>",
    "bankName": "<bank_name>",
    "accountNumber": "<account_number>",
    "ifscCode": "<ifsc_code>"
  }
}

```

Field	Required	Description
beneficiaryName	Yes	Name of the account holder
bankName	Yes	Bank name
accountNumber	Yes	Bank account number
ifscCode	Yes	IFSC code of the bank branch

3. E-wallet Payment

```

{
  "amount": <number>,
  "paymentMethod": "E_WALLET",
  "user": {
    "id": "<user_id>",
    "name": "<user_name>",
    "email": "<user_email>",
    "mobile": "<user_mobile>"
  },
  "eWalletDetails": {
    "appName": "<wallet_app_name>",
    "mobileNumber": "<linked_mobile_number>"
  }
}

```

Field	Required	Description
appName	Yes	Name of the wallet application
mobileNumber	Yes	Mobile number linked to the wallet

Request Body Parameters for `webhookUrl` Invocation

Below is a sample request body that will be sent via an HTTP `POST` to the configured `webhookUrl` when a payout is either **successful** or **failed**.

```
{
  "signature": "<JWT_TOKEN>",
  "orderId": "<MERCHANT_ORDER_ID>",
  "kgOrderId": "<KINGSGATE_ORDER_ID>",
  "status": "<STATUS>",
  "user": {
    "id": "<USER_ID>",
    "name": "<USER_NAME>",
    "mobile": "<USER_MOBILE>",
    "email": "<USER_EMAIL>"
  },
  "transactionDetails": {
    "id": "<TRANSACTION_ID or null>",
    "amount": <AMOUNT>,
    "paymentMethod": "<PAYMENT_METHOD>",
    "time": "<TIMESTAMP_ISO8601>",
    "utr": "<UNIQUE_TRANSACTION_REFERERFERNCE>"
  },
}
```

Order Status Values:

Status	Description
INITIATED	Order is created but not yet assigned to a payment gateway.
ASSIGNED	A payment gateway has been assigned to the order.

SUBMITTED	Payout initiated; verification is pending.
COMPLETE	Payout is verified and the payout has been successfully completed.
FAILED	Payout attempt failed.

Verifying Signature for Webhook

The `signature` is a JWT (JSON Web Token) that is signed using your Merchant API Key. To verify the authenticity of the request, you should decode and verify the JWT using your own API key as the secret.

Example

```
import jwt from "jsonwebtoken";
const signature = req.body.signature;
const merchantApiKey = process.env.MERCHANT_API_KEY;
try {
  const payload = jwt.verify(signature, merchantApiKey);
  console.log("Verified payload:", payload);
} catch (err) {
  console.error("Invalid signature", err);
}
```

Check Payout Status API

Endpoint: `GET /api/payout/order-status/:orderId`

Headers:

Authorization	Bearer
---------------	--------

Sample Request:

```
GET /api/payout/PAYOUT-XYZ12345
```

Sample Response:

```

{
  "httpStatus": 200,
  "data": {
    "orderId": "<MERCHANT_ORDER_ID>",
    "kgOrderId": "<KINGSGATE_ORDER_ID>"
    "status": "<STATUS>",
    "user": {
      "id": "<USER_ID>",
      "name": "<USER_NAME>",
      "mobile": "<USER_MOBILE>",
      "email": "<USER_EMAIL>"
    },
    "transactionDetails": {
      "id": "<TRANSACTION_ID or null>",
      "amount": <AMOUNT>,
      "paymentMethod": "<PAYMENT_METHOD>",
      "time": "<TIMESTAMP_ISO8601>"
    }
  }
}

```

HTTP Status Codes -

HTTP Status	Description
200	success
500	Internal Server Error
400	Bad Request Error (Invalid or missing request parameters)
403	Forbidden (auth token missing or invalid)

Order Status Values:

Status	Description
INITIATED	Order is created but not yet assigned to a payment gateway.
ASSIGNED	A payment gateway has been assigned to the order.
SUBMITTED	Payout initiated; verification is pending.
COMPLETE	Payout is verified and the payout has been successfully completed.
FAILED	Payout attempt failed.

3. Utility APIs

Get Balance API

Endpoint: **GET /api/merchant/balance**

Headers:

Authorization	Bearer
---------------	--------

Sample Response:

```
{
  "status": 200,
  "data": {
    "balance": 1037.49
  }
}
```

HTTP Status Codes -

HTTP Status	Description
200	success
500	Internal Server Error

400	Bad Request Error Invalid or missing request parameters)
403	Forbidden (auth token missing or invalid)

Get Payment Methods API

Endpoint: **GET /api/merchant/payment-methods**

Headers:

Authorization	Bearer
---------------	--------

Sample Response:

```
{
  "status": 200,
  "data": {
    "payins": {
      "UPI": true,
      "E_WALLET": true,
      "NET_BANKING": true
    },
    "payouts": {
      "UPI": true,
      "E_WALLET": true,
      "NET_BANKING": true
    }
  }
}
```

HTTP Status Codes -

HTTP Status	Description
-------------	-------------

200	success
500	Internal Server Error
400	Bad Request Error Invalid or missing request parameters)
403	Forbidden (auth token missing or invalid)