

## Reading from a File

### Creating an Adjacency List from an Edge List

The goal of this assignment is to write the **R** function `edge2adj.r` that constructs an adjacency list for a graph given the list of edges in the graph.

**Input:** *myfilename*, a text string that contains the name of the file containing the list of edges of a graph.

**Output:** *adjlist*, an **R** list of all the edges of a graph, in which the  $i^{th}$  component of the list contains a vector of all the vertices adjacent to edge  $i$ .

For example, here is a graph:




Figure 1: Graph with Six Vertices

The edge list associated with this graph is shown in Figure 2.

1	2
1	5
2	3
2	5
3	4
4	5
4	6

Figure 2: Edge List Associated with Figure 1

We want to turn this edge list into the associated adjacency list shown in Figure 3.

The first component contains the numbers 2 and 5, because Vertex 1 is adjacent to Vertices 2 and 5. The second component contains the numbers 1, 3, and 5 because Vertex 2 is adjacent to Vertices 1, 3, and 5. Etc.

There are several new **R** commands that you will need for this assignment.

1. **read.table.** Table-format files are best thought of as plain-text files with three key features that fully define how **R** should read the data.

1	2	5	
2	1	3	5
3	2	4	
4	3	5	6
5	1	2	4
6	4		

Figure 3: Adjacency List Associated with Figure 1

- (a) **Header.** If a *header* is present, it's always the first line of the file. This optional feature is used to provide names for each column of data. When importing a file into **R**, you need to tell the software whether a header is present so that it knows whether to treat the first line as variable names or, alternatively, observed data values.
- (b) **Delimiter.** The *delimiter* is the character that is used to separate the entries in each line. The delimiter cannot be used for anything else in the file. This tells **R** when a specific entry begins and ends.
- (c) **Missing Values.** This is another unique character string used exclusively to denote a missing value. When reading the file, **R** will turn these entries into the form it recognizes: NA.

Here's the plain-text file `MyFirstDataFile.txt`.

```
name age.years gender entertaining age.months
Peter * M High 504
Lois 40 F * 480
Meg 17 F Low 204
Chris 14 M Med 168
Steve 1 M High *
Brian * M Med *
```

**R** will now read this in as a matrix.

```

> mydatafile <- read.table(file = "MyFirstDataFile.txt", header = TRUE,
                           sep = ' ', na.strings = "*",
                           stringsAsFactors = FALSE)

> mydatafile
  name age.years gender entertaining age.months
1 Peter      NA      M      High      504
2 Lois      40      F      NA      480
3 Meg       17      F      Low      204
4 Chris     14      M      Med      168
5 Steve      1      M      High      NA
6 Brian     NA      M      Med      NA
> mydatafile[1,2]
[1] "NA"
> mydatafile[2,3]
[1] "F"
> mydatafile[1,4]
[1] "High"
> mydatafile[4,2]
[1] "14"
> mydatafile[4,2] + 3
Error in mydatafile[4, 2] + 3 : non-numeric argument to binary operator

```

Note that numeric values are read as characters here.

For this assignment, there will be no header, the delimiter will be a space, and `na.strings` and `stringsAsFactors` do not have to be in the command.

Here are several examples.

```
> edge2adj("Edgelist01.txt")
```

```
[[1]]
```

```
[1] 2 3 4
```

```
[[2]]
```

```
[1] 1 3 7
```

```
[[3]]
```

```
[1] 1 2 4 6
```

```
[[4]]
```

```
[1] 1 3 5
```

```
[[5]]
```

```
[1] 4 6 9
```

```
[[6]]
```

```
[1] 3 5 7 8 9
```

```
[[7]]
```

```
[1] 2 6 8
```

```
[[8]]
```

```
[1] 6 7 9 10
```

```
[[9]]
```

```
[1] 5 6 8 10
```

```
[[10]]
```

```
[1] 8 9
```

```
> edge2adj("Edgelist02.txt")
```

```
[[1]]
```

```
[1] 2 7 9
```

```
[[2]]
```

```
[1] 1 5 7 10
```

```
[[3]]
```

```
[1] 5 7
```

```
[[4]]
```

```
[1] 5 6 9
```

```
[[5]]
```

```
[1] 2 3 4 6 10
```

```
[[6]]
```

```
[1] 4 5
```

```
[[7]]
```

```
[1] 1 2 3
```

```
[[8]]
```

```
[1] 9 10
```

```
[[9]]
```

```
[1] 1 4 8
```

```
[[10]]
```

```
[1] 2 5 8
```

```
> edge2adj("Edgelist03.txt")
```

```
[[1]]
```

```
[1] 2 3
```

```
[[2]]
```

```
[1] 1 3 4 5
```

```
[[3]]
```

```
[1] 1 2 4 5
```

```
[[4]]
```

```
[1] 2 3 5 6
```

```
[[5]]
```

```
[1] 2 3 4 6
```

```
[[6]]  
[1] 4 5 8 11 12
```

```
[[7]]  
[1] 8
```

```
[[8]]  
[1] 6 7 9 10
```

```
[[9]]  
[1] 8 10
```

```
[[10]]  
[1] 8 9
```

```
[[11]]  
[1] 6
```

```
[[12]]  
[1] 6
```