Example API

Note 1: This API is only for the example you are going to use as basis for the project. For the project itself, you are going to use another API with different documentation.

Note 2: All requests to the API must include the group key as a query (URL-variable), e.g.:

https://sukkergris.onrender.com/webshop/testdummy/categories?key= ABCDEF01

Replace *ABCDEF01* with your group key.

Note 2. When you list products, each item will have a filename for a thumb image (100 x 100 pixels). Use this URL to retrieve the image:

- https://sukkergris.onrender.com/images/*ABCDEF01*/dummies/*filename.png*

Replace **ABCDEF01** with your group key and **filename.png** with the filename you retrieve from the server.

Note 3. To prevent Do S attacks, the server has a restriction of 300 requests per 10 minutes for each unique IP-address. If you exceed the limit, you will receive a CORS-error and denied access until the average is below 300.

Note 4. Data that is sent to the server is sanitized (on the server) to prevent XSS attacks.

Note 5. Any errors sent from the server will contain a corresponding HTTP status code and a status text with the error description. In addition, most errors will also result in response data that contain JSON in this format:

```
{
    "msg" : "Error description",
    "code" : "Error code",
    "http_code" : The HTTP code
}
```

Content

Sukkergris dummy API 1
Info lists 3
1. List product categories 3
Products 4
2. List products 4
3. Add a product 5
4. Delete a product 6

Info lists

1. List product categories

GET to https://sukkergris.onrender.com/webshop/testdummy/categories

Request data

Queries (URL-variables)	
Name	**Value**
key (required)	Your group key

Example: https://sukkergris.onrender.com/webshop/testdummy/categories?key=ABCDEF01

Response data

JSON formatted array with product categories ordered by *id*.

Products

2. List products

GET to https://sukkergris.onrender.com/webshop/testdummy/products

Request data

Queries (URL-variables)	
Name	**Value**
key (required)	Your group key
category_id	Category ID, lists all the products in the given category. If not supplied, lists all products.
id	A product ID. Lists the product that has the given ID. If not supplied, lists all products.

Examples:

https://sukkergris.onrender.com/webshop/testdummy/products?category_id=2&key=ABCDEF01

https://sukkergris.onrender.com/webshop/testdummy/products?id=12&key=ABCDEF01

https://sukkergris.onrender.com/webshop/testdummy/products?key=ABCDEF01

Response data

JSON formatted array with products ordered by *name*.

3. Add a product

POST to https://sukkergris.onrender.com/webshop/testdummy/products

Note: Each project group can only add 30 new products. If you want to add more, you must delete some of the old ones.

Request data

Queries (URL-variables)	
Name	**Value**
key (required)	Your group key

Formdata (enctype=multipart/form-data) in body	
Fields (name)	**Value**
name (required)	The name of the product. Must be unique.
description	A short description/heading for the product
category_id	The category ID. If not supplied, it is set to 1 (the 'Special' category)
details	More details about the product
thumb	An image file (PNG or JPG). Max size is 1MB. If not supplied a default image is used. The image is resized to a 300 x 300 pixels image, and a 100 x 100 pixels thumb image on the server.
price	The price of the product. If not supplied, it is set to 0

Response data

The data (JSON) for the product that was added. The data also includes a unique product number that is generated on the server.

4. Delete a product

DELETE to https://sukkergris.onrender.com/webshop/testdummy/products

Note: You can only delete products that you have added yourself (with your group key).

Request data

Queries (URL-variables)	
Name	**Value**
key (required)	Your group key
id	The ID of the product that should be deleted

Response data

The data (JSON) for the product that was deleted.