

Ex. 7 Inter Process Communication Using Semaphores

```
roshan@localhost:~ — vi sender.c
#include<stdio.h>
#include<sys/ipc.h>
#include<sys/shm.h>
#include<string.h>
int main(){
    key_t key=1234;
    int shmid;
    shmid=shmget(key,1024,0666|IPC_CREAT);
    char*str=(char*)shmat(shmid,(void*)0,0);
    printf("Enter message: ");
    scanf("%[^\n]", str);
    printf("Data written to shared memory:%s\n",str);
    return 0;
}
-- INSERT --
```

```
roshan@localhost:~ — vi receiver.c
#include<stdio.h>
#include<sys/ipc.h>
#include<sys/shm.h>
int main(){
    key_t key=1234;
    int shmid;
    shmid=shmget(key,1024,0666);
    char*str=(char*)shmat(shmid,(void*)0,0);
    printf("Data read from shared memory:%s\n",str);
    shmdt(str);
    return 0;
}
```

```
roshan@localhost:~  
[roshan@localhost ~]$ gcc sender.c  
[roshan@localhost ~]$ ./a.out  
Enter message: Hello  
Data written to shared memory:Hello  
[roshan@localhost ~]$ gcc receiver.c  
[roshan@localhost ~]$ ./a.out  
Data read from shared memory:Hello  
[roshan@localhost ~]$
```