

Ex. 10 a: First Fit Contiguous Memory Allocation

FACE Prep

Operating System - Coding | REC | 3 Feb

Course Progress

Go Back

Back To Practice

Save

Completed

First Fit Contiguous Memory Allocation

Write a C program to implement the First Fit contiguous memory allocation technique. The program should take the sizes of various memory blocks and the sizes of processes as input. For each process, search through the memory blocks sequentially and allocate the first block that meets the size requirement. If no such block exists, indicate that the process cannot be allocated. Finally, display the allocation details and calculate internal fragmentation.

Input Format

- The first line contains an integer m representing the number of memory blocks.
- The next line contains m integers representing the sizes of each memory block.
- The next line contains an integer n representing the number of processes.
- The next line contains n integers representing the sizes of each process.

Output Format

- For each process, the program prints whether the process is allocated or not.
- If allocated, it displays the process number, process size, block number, block size, and the internal fragmentation (block size minus process size).
- If not allocated, it indicates that the process cannot be allocated.

Sample Input 1

```
5
100 500 200 300 600
```

Select Language: C (GCC 9.2.0)

```
1 #include <stdio.h>
2
3 int main() {
4     int m, n, i, j;
5
6     printf("Enter number of memory blocks:\n");
7     scanf("%d", &m);
8
9     int blockSize[m], originalBlock[m];
10
11     printf("Enter size of each block:\n");
12     for(i = 0; i < m; i++) {
13         scanf("%d", &blockSize[i]);
14         originalBlock[i] = blockSize[i];
15     }
16
17     printf("Enter number of processes:\n");
18     scanf("%d", &n);
19
20     int processSize[n];
21
22     printf("Enter size of each process:\n");
```

Test Cases 2

Run Sample Cases

Run All Cases

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

FACE Prep

Operating System - Coding | REC | 3 Feb

Course Progress

Go Back

Back To Practice

Save

- For each process, the program prints whether the process is allocated or not.
- If allocated, it displays the process number, process size, block number, block size, and the internal fragmentation (block size minus process size).
- If not allocated, it indicates that the process cannot be allocated.

Sample Input 1

```
5
100 500 200 300 600
4
212 417 112 426
```

Sample Output 1

```
Enter number of memory blocks:
Enter size of each block:
Enter number of processes:
Enter size of each process:

Process 1 of size 212 is allocated to Block 2 of size 500 with Fragment 288
Process 2 of size 417 is allocated to Block 5 of size 600 with Fragment 183
Process 3 of size 112 is allocated to Block 3 of size 200 with Fragment 88
Process 4 of size 426 is not allocated
```

Select Language: C (GCC 9.2.0)

```
22     printf("Enter size of each process:\n");
23     for(i = 0; i < n; i++) {
24         scanf("%d", &processSize[i]);
25     }
26
27     for(i = 0; i < n; i++) {
28         int allocated = 0;
29
30         for(j = 0; j < m; j++) {
31             if(blockSize[j] >= processSize[i]) {
32
33                 int fragment = blockSize[j] - processSize[i];
34
35                 printf("Process %d of size %d is allocated to Block %d of size %d with Fragment %d\n",
36                     i + 1, processSize[i], j + 1, originalBlock[j], fragment);
37
38                 blockSize[j] -= processSize[i];
39                 allocated = 1;
40                 break;
41             }
42         }
43     }
```

Test Cases 2

Run Sample Cases

Run All Cases

Custom Test Case

> Custom Test

Sample Test Case

> Test Case - 1

Operating System - Coding | REC | 3 Feb

Course Progress

Go Back

Back To Practice

- For each process, the program prints whether the process is allocated or not.
- If allocated, it displays the process number, process size, block number, block size, and the internal fragmentation (block size minus process size).
- If not allocated, it indicates that the process cannot be allocated.

Sample Input 1

```

5
100 500 200 300 600
4
212 417 112 426

```

Sample Output 1

```

Enter number of memory blocks:
Enter size of each block:
Enter number of processes:
Enter size of each process:
Process 1 of size 212 is allocated to Block 2 of size 500 with Fragment 288
Process 2 of size 417 is allocated to Block 5 of size 600 with Fragment 183
Process 3 of size 112 is allocated to Block 3 of size 200 with Fragment 88
Process 4 of size 426 is not allocated

```

```

29
30
31     for(j = 0; j < m; j++) {
32         if(blockSize[j] >= processSize[i]) {
33             int fragment = blockSize[j] - processSize[i];
34             printf("Process %d of size %d is allocated to Block %d of size %d with Fragment %d\n",
35                 i + 1, processSize[i], j + 1, originalBlock[j], fragment);
36             blockSize[j] -= processSize[i];
37             allocated = 1;
38             break;
39         }
40     }
41     if(!allocated) {
42         printf("Process %d of size %d is not allocated\n", i + 1, processSize[i]);
43     }
44     return 0;
45 }

```

Test Cases

Run Sample Cases

Run All Cases

Custom Test Case

Custom Test

Sample Test Case

Test Case - 1

Test Case - 2

Ex. 10 b: Best Fit Contiguous Memory Allocation

Operating System - Coding | REC | 3 Feb

Course Progress

Go Back

Back To Practice

Best Fit Contiguous Memory Allocation

Write a C program to implement the Best Fit Contiguous Memory Allocation technique. The program should accept the sizes of memory blocks and the sizes of processes as input.

For each process, the program searches all available memory blocks and allocates the smallest block that is sufficient to satisfy the process size. If no suitable block is available, the process is marked as not allocated. The program should display the allocation details for each process and calculate the internal fragmentation.

Input Format

- The first line contains an integer representing the number of memory blocks.
- The second line contains the sizes of the memory blocks.
- The third line contains an integer representing the number of processes.
- The fourth line contains the sizes of the processes.

Output Format

- For each process, display whether it is allocated or not.
- If allocated, display the block number, block size, and internal fragmentation.
- If not allocated, display that the process could not be allocated.

Example 1

Sample Input 1

```

5

```

Completed

Select Language: C (GCC 8.2.0)

```

1 #include <stdio.h>
2
3 int main() {
4     int m, n, i, j;
5
6     printf("Enter number of memory blocks:\n");
7     scanf("%d", &m);
8
9     int blockSize[m], originalBlock[m];
10
11     printf("Enter size of each block:\n");
12     for(i = 0; i < m; i++) {
13         scanf("%d", &blockSize[i]);
14         originalBlock[i] = blockSize[i];
15     }
16
17     printf("Enter number of processes:\n");
18     scanf("%d", &n);
19
20     int processSize[n];
21
22     printf("Enter size of each process:\n");

```

Test Cases

Run Sample Cases

Run All Cases

Custom Test Case

Custom Test

Sample Test Case

Test Case - 1

Operating System - Coding | REC | 3 Feb

Course Progress
Go Back

Back To Practice
Save

- If allocated, display the block number, block size, and internal fragmentation.
- If not allocated, display that the process could not be allocated.

Example 1

Sample Input 1

```

5
100 500 200 300 600
4
212 417 112 426

```

Sample Output 1

Enter number of memory blocks:

Enter size of each block:

Enter number of processes:

Enter size of each process:

Process 1 of size 212 is allocated to Block 4 of size 300 with Fragment 88

Process 2 of size 417 is allocated to Block 2 of size 500 with Fragment 83

Process 3 of size 112 is allocated to Block 3 of size 200 with Fragment 88

Process 4 of size 426 is allocated to Block 5 of size 600 with Fragment 174

Select Language: C (GCC 9.2.0)

```

22 printf("Enter size of each process:\n");
23 for(i = 0; i < n; i++) {
24     scanf("%d", &processSize[i]);
25 }
26
27 for(i = 0; i < n; i++) {
28     int bestIndex = -1;
29
30     for(j = 0; j < m; j++) {
31         if(blockSize[j] >= processSize[i]) {
32             if(bestIndex == -1 || blockSize[j] < blockSize[bestIndex]) {
33                 bestIndex = j;
34             }
35         }
36     }
37
38     if(bestIndex != -1) {
39         int fragment = blockSize[bestIndex] - processSize[i];
40
41         printf("Process %d of size %d is allocated to Block %d of size %d with Fragment %d\n",
42             i + 1, processSize[i], bestIndex + 1, originalBlock[bestIndex], fragment);
43     }
44 }

```

Test Cases
Run Sample Cases
Run All Cases

Custom Test Case
> Custom Test

Sample Test Case
> Test Case - 1

Operating System - Coding | REC | 3 Feb

Course Progress
Go Back

Back To Practice
Save

- If allocated, display the block number, block size, and internal fragmentation.
- If not allocated, display that the process could not be allocated.

Example 1

Sample Input 1

```

5
100 500 200 300 600
4
212 417 112 426

```

Sample Output 1

Enter number of memory blocks:

Enter size of each block:

Enter number of processes:

Enter size of each process:

Select Language: C (GCC 9.2.0)

```

31 if(blockSize[j] >= processSize[i]) {
32
33     if(bestIndex == -1 || blockSize[j] < blockSize[bestIndex]) {
34         bestIndex = j;
35     }
36 }
37
38
39 if(bestIndex != -1) {
40     int fragment = blockSize[bestIndex] - processSize[i];
41
42     printf("Process %d of size %d is allocated to Block %d of size %d with Fragment %d\n",
43         i + 1, processSize[i], bestIndex + 1, originalBlock[bestIndex], fragment);
44
45     blockSize[bestIndex] -= processSize[i];
46 } else {
47     printf("Process %d of size %d is not allocated\n", i + 1, processSize[i]);
48 }
49
50
51 return 0;
52 }

```

Test Cases
Run Sample Cases
Run All Cases