

Lab No: 3 Date: 2082/

Title: Write a program to calculate the number of page fault for user input reference

string and frame size using LRU page replacement algorithm.

LRU replaces the page that has not been used for the longest time in the past. It approximates the Optimal algorithm but works in real systems because it only relies on past

usage. It Uses the concept of recency to decide which page to replace. Can be implemented

using counters, stacks, or linked lists to track usage.

Algorithm:

Step 1: Initialize all frames as empty.

Step 2: Read the reference string.

Step 3: For each page request:

 $\circ$  If the page is already in frame  $\rightarrow$  Page Hit and update its recent usage.

○ If the page is not in frame  $\rightarrow$  Page Fault:

• If free space  $\rightarrow$  insert the page.

• Else  $\rightarrow$  find the page that was least recently used (used longest ago) and

replace it.

Step 4: Update page hit/fault counters after each request.

Step 5: Repeat Step 3 for all pages and display the results.

Language: C++

IDE: VS Code

```
Code:
#include <iostream>
#include <vector>
#include <iomanip>
using namespace std;
void lruPageReplacement(const string &referenceString, int frameSize) {
  vector<char> frames;
                          // store characters in frames
  vector<int> lastUsed; // parallel vector to store last used index
  int pageFaults = 0, pageHits = 0;
  cout << "\nStep-by-step Table (LRU Page Replacement):\n";</pre>
  cout << "-----\n";
  cout << setw(10) << "Page"
    << setw(20) << "Frames"</pre>
    << setw(15) << "Page Fault"</pre>
    << setw(10) << "Hit\n";</pre>
  cout << "-----\n";
  for (int i = 0; i < (int)referenceString.size(); i++) {
    char page = referenceString[i];
    bool found = false;
    // Check if page already in frames
    for (int j = 0; j < (int)frames.size(); j++) {
      if (frames[j] == page) {
        found = true;
        lastUsed[j] = i; // update last used index
```

```
break;
  }
}
if (!found) { // Page fault
  if ((int)frames.size() < frameSize) {</pre>
     frames.push_back(page);
     lastUsed.push_back(i);
  } else {
     // Find least recently used page
     int lruIndex = 0;
     for (int j = 1; j < frameSize; j++) {
        if (lastUsed[j] < lastUsed[lruIndex])</pre>
          lruIndex = j;
    }
     frames[lruIndex] = page;
     lastUsed[lruIndex] = i;
  }
  pageFaults++;
} else {
  pageHits++;
}
// Print current step
cout << setw(10) << page << setw(20);
for (char f : frames) cout << f << " ";
cout << setw(15) << (found ? "No" : "Yes")
```

```
<< setw(10) << (found ? "Yes" : "No") << "\n";</pre>
  }
  cout << "-----\n";
  cout << "Total Page Faults = " << pageFaults << endl;</pre>
  cout << "Total Page Hits = " << pageHits;</pre>
}
int main() {
  int frameSize, refSize;
  string referenceString;
  cout << "Enter reference string size: ";
  cin >> refSize;
  cout << "Enter reference string (length should be " << refSize << "): ";</pre>
  cin >> referenceString;
  cout << "Enter frame size: ";</pre>
  cin >> frameSize;
  if ((int)referenceString.size() != refSize) {
     cout << "Error: reference string size does not match input length!\n";
    return 1;
  }
  lruPageReplacement(referenceString, frameSize);
  return 0;
}
```

## **Output:**

```
Enter reference string size: 15
Enter reference string (length should be 15): ROSHANSAUDTEXAS
Enter frame size: 4
Step-by-step Table (LRU Page Replacement):
                     Frames Page Fault
     Page
                                              Hit
        R
                          R
                                       Yes
                                                 No
        0
                          R O
                                       Yes
                                                   No
        S
                          ROS
                                         Yes
        Н
                          ROSH
                                            Yes
                                                      No
        Α
                          A O S H
                                            Yes
                                                      No
                          ANSH
        Ν
                                            Yes
                                                      No
        S
                          ANSH
                                             No
                                                      Yes
                          ANSH
        Α
                                             No
                                                      Yes
        U
                          ANSU
                                            Yes
                                                      No
        D
                          ADSU
                                            Yes
                                                      No
        Т
                          ADTU
                                            Yes
                                                       No
        Ε
                          EDTU
                                            Yes
                                                      No
        Χ
                          E D T X
                                            Yes
                                                      No
        Α
                          EATX
                                            Yes
                                                       No
        S
                          EASX
                                            Yes
                                                       No
Total Page Faults = 13
Total Page Hits
c:\Users\Roshan\Desktop\Roshan os lab>
```

## **Conclusion:**

LRU effectively reduces page faults compared to FIFO by considering recent usage. While it may not always be as optimal as the theoretical Optimal algorithm, it is practical and widely used in real systems.