

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap

INTRODUCTION

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <!-- The above 3 meta tags *must* come first in the
head; any other head content must come *after* these tags
-->
    <title>
      Introduction
    </title>

    <!-- Bootstrap -->
    <link href="css/bootstrap.min.css" rel="stylesheet">

    <!-- HTML5 shim and Respond.js for IE8 support of
HTML5 elements and media queries -->
    <!-- WARNING: Respond.js doesn't work if you view the
page via file:// -->
    <!--[if lt IE 9]>
<script
src="https://oss.maxcdn.com/html5shiv/3.7.2/html5shiv.min.
js">
</script>
```

```
<script
src="https://oss.maxcdn.com/respond/1.4.2/respond.min.js">
</script>
<![endif]-->
</head>
<body>
  <div class="container-fluid">
    <h1>
      We are learning Bootstrap
    </h1>
    <p>
      Hello World!
    </p>
  </div>

  <!-- jQuery (necessary for Bootstrap's JavaScript
plugins) -->
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
  </script>
  <!-- Include all compiled plugins (below), or include
individual files as needed -->
  <script src="js/bootstrap.min.js">
  </script>
</body>
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Grid System
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>
      #deviceSize{
        margin-bottom: 30px;

      }
      .bluebox{
        background-color: #2fc5b8;
        height: 200px;
      }
      .greenbox{
        background-color: #8deb46;
        height: 200px;
      }
    </style>
```

```

</head>
<body>
  <div class="container-fluid">
    <div id="deviceSize">
      Device Size:
    </div>
    <div class="bluebox col-md-8 col-sm-6 col-xs-3 col-
lg-4">
      col-md-8 col-sm-6 col-xs-3 col-lg-4
    </div>
    <div class="greenbox col-md-4 col-sm-6 col-xs-9 col-
lg-8">
      col-md-4 col-sm-6 col-xs-9 col-lg-8
    </div>
  </div>
  <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
  </script>
  <script src="js/bootstrap.min.js">
  </script>
  <script>
    $(function(){
      $( window ).resize(function() {
        var windowWidth = $(window).width();
        if(windowWidth<768){
          $('#deviceSize').text('Device Size: ' +
windowWidth + 'px - Extra small devices (Phones)');
        }
        else if(windowWidth<992){
          $('#deviceSize').text('Device Size: ' +
windowWidth + 'px - Small devices (Tablets)');
        }
        else if(windowWidth<1200){
          $('#deviceSize').text('Device Size: ' +
windowWidth + 'px - Medium devices (Desktops)');
        }
        else{

```

```
        $('#deviceSize').text('Device Size: ' +  
windowWidth + 'px - Large devices (Desktops)');  
    }  
}  
);  
}  
);  
</script>  
</body>  
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap

TYPOGRAPHY

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Typography
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <h1>
        Bootstrap heading
      </h1>
      <h2>
        Bootstrap heading
      </h2>
      <h3>
        Bootstrap heading
      </h3>
```

```
<h4>
  Bootstrap heading
</h4>
<h5>
  Bootstrap heading
</h5>
<h6>
  Bootstrap heading
</h6>
<div class="h5">
  This is some text.
</div>
<p>
  Text can be
  <br />
  <mark>
    highlighted
  </mark>
  <br />
  <s>
    struck through
  </s>
  <br />
  <u>
    underlined
  </u>
  <br />
  <span class="small">
    de-emphasised
  </span>
  <br />
  <strong>
    made bold
  </strong>
  <br />
  or
  <em>
    emphasized with italics
  </em>
</p>

<p>
```

```
    This is a simple paragraph
</p>
<p class="lead">
    This paragraph stands out
</p>
<p class="small">
    This paragraph is made small
</p>
<p class="text-right">
    Text in this paragraph is right aligned
</p>
<p class="text-capitalize">
    Text in this paragraph is capitalized
</p>
<p class="text-primary">
    This text is emphasised
</p>
<p class="text-success">
    This text is emphasised
</p>
<p class="text-danger">
    This text is emphasised
</p>
<p class="text-warning">
    This text is emphasised
</p>
<p class="text-info">
    This text is emphasised
</p>
<ul class="list-unstyled list-inline">
    <li>
        HTML
    </li>

    <li>
        CSS
    </li>

    <li>
        JQuery
    </li>
```



```
</ul>
<div class="bg-primary">
  bg-primary
</div>
<div class="bg-success">
  bg-success
</div>
<div class="bg-danger">
  bg-danger
</div>
<div class="bg-warning">
  bg-warning
</div>
<div class="bg-info">
  bg-info
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
</body>
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap TABLES

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Tables
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <table class="table">
        <tr>
          <th>
            Phone Make
          </th>
          <th>
            Model
          </th>
          <th>
```

```

Storage
</th>
</tr>

<tr>
<td>
Apple Apple Apple Apple Apple Apple Apple
Apple Apple Apple Apple Apple
</td>
<td>
Iphone 6
</td>
<td>
32Go
</td>
</tr>
<tr>
<td>
Apple
</td>
<td>
Iphone 5
</td>
<td>
32Go
</td>
</tr>
<tr>
<td>
Apple
</td>
<td>
Iphone 5s
</td>
<td>
32Go
</td>
</tr>
<tr>
<td>
Apple
</td>

```

```

        <td>
            Iphone 4
        </td>
        <td>
            32Go
        </td>
    </tr>

</table>

<div class="table-responsive">
    <table class="table table-striped table-hover
table-condensed table-bordered">
        <tr>
            <th>
                Phone Make
            </th>
            <th>
                Model
            </th>
            <th>
                Storage
            </th>
        </tr>

        <tr>
            <td>
                Apple Apple Apple Apple Apple Apple Apple
                Apple Apple Apple Apple Apple Apple Apple Apple
                Apple Apple Apple Apple Apple
            </td>
            <td>
                Iphone 6
            </td>
            <td>
                32Go
            </td>
        </tr>
        <tr>
            <td>
                Apple
            </td>

```

```
        <td>
            Iphone 5
        </td>
        <td>
            32Go
        </td>
    </tr>
    <tr>
        <td>
            Apple
        </td>
        <td>
            Iphone 5s
        </td>
        <td>
            32Go
        </td>
    </tr>
    <tr>
        <td>
            Apple
        </td>
        <td>
            Iphone 4
        </td>
        <td>
            32Go
        </td>
    </tr>
</table>

</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
</body>
</html>
```


THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap FORMS (1)

APPLICATION: INLINE AND HORIZONTAL RESPONSIVE LOGIN FORMS

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap FORMS (2)

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

Bootstrap FORMS (3)

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      forms
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <form class="form-inline">
        <div class="form-group">
          <label for="email">
            Email:
          </label>
          <input type="email" id="email"
placeholder="Email" class="form-control">
        </div>
```



```

        <div class="form-group">
            <label for="password">
                Password:
            </label>

            <input type="password" id="password"
placeholder="Password" class="form-control">
        </div>

        <button type="submit" class="btn btn-default">
            Login
        </button>
    </form>
<br />
<hr>

<form class="form-horizontal">
    <div class="form-group">
        <label for="email" class="col-sm-2 control-
label">
            Email:
        </label>
        <div class="col-sm-10">
            <input type="email" id="email"
placeholder="Email" class="form-control">

        </div>
    </div>

    <div class="form-group">
        <label for="password" class="col-sm-2 control-
label">
            Password:
        </label>

        <div class="col-sm-10">
            <input type="password" id="password"
placeholder="Password" class="form-control">

        </div>
    </div>

```

```
<div class="col-sm-offset-2 col-sm-10">
  <button type="submit" class="btn btn-default">
    Login
  </button>

</div>
</form>
<br />
<hr>

<form>
  <label for="comments">
    Comments:
  </label>
  <textarea class="form-control" rows="5"
id="comments">
  </textarea>

  <div class="checkbox checkbox-inline">
    <label>
      <input type="checkbox" value="value1"
id="checkbox1">
      Checkbox1
    </label>

  </div>

  <div class="checkbox checkbox-inline disabled">
    <label>
      <input type="checkbox" value="value2"
id="checkbox2">
      Checkbox2
    </label>

  </div>
<br />

<br />
<hr>

<div class="radio radio-inline">
  <label>
```

```
        <input type="radio" name="radios" id="radio1"
value="option1">
        Radio Option 1
    </label>

</div>
<div class="radio radio-inline">
    <label>
        <input type="radio" name="radios" id="radio2"
value="option2">
        Radio Option 1
    </label>

</div>
<div class="radio radio-inline">
    <label>
        <input type="radio" name="radios" id="radio3"
value="option3" disabled>
        Radio Option 1
    </label>

</div>
<br />
<hr>
<select multiple class="form-control">
    <option>
        Option 1
    </option>

    <option>
        Option 2
    </option>

    <option>
        Option 3
    </option>

</select>

<br />
```

```
        <input type="text" class="form-control"
placeholder="Text Input" disabled>

    <br />
    <hr>

    <div class="row">
        <div class="form-group has-success col-xs-2">
            <label for="textInput1" class="sr-only">
                Text Input 1
            </label>

            <input type="text" class="form-control"
id="textInput1" placeholder="Text Input 1">

        </div>
        <div class="form-group has-error col-xs-6">
            <label for="textInput2" class="sr-only">
                Text Input 2
            </label>

            <input type="text" class="form-control input-
lg" id="textInput2" placeholder="Text Input 2">

        </div>
        <div class="form-group has-warning col-xs-4">
            <label for="textInput3" class="sr-only">
                Text Input 3
            </label>

            <input type="text" class="form-control input-
sm" id="textInput3" placeholder="Text Input 3">

        </div>

    </div>

    <br />
    <hr>

    <div class="form-group has-feedback has-warning">
        <label for="textInput4" class="sr-only">
```

```

        Text Input
    </label>

    <input type="text" class="form-control"
id="textInput4" placeholder="Text Input">
    <span class="glyphicon glyphicon-alert form-
control-feedback">
    </span>
    <span class="sr-only">
        warning
    </span>
</div>
<br />
<hr>

<div class="input-group has-feedback has-success">
    <label for="textInput4" class="sr-only">
        Text Input
    </label>
    <span class="input-group-addon">
        @
    </span>
    <input type="text" class="form-control"
id="textInput4" placeholder="Text Input">
    <span class="glyphicon glyphicon-ok form-
control-feedback">
    </span>
    <span class="sr-only">
        warning
    </span>
</div>

<br />
<hr>

<div class="input-group has-feedback has-success">
    <label for="textInput4" class="sr-only">
        Text Input
    </label>
    <span class="input-group-btn">
        <button type="button" class="btn btn-default">
            Submit

```

```
        </button>

        </span>
        <input type="text" class="form-control"
id="textInput4" placeholder="Text Input">
        <span class="glyphicon glyphicon-ok form-
control-feedback">
        </span>
        <span class="sr-only">
        warning
        </span>
    </div>
</form>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
</body>
</html>
```



Bootstrap

BUTTONS

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      buttons
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <a class="btn btn-link" href="#">
        Top of the page
      </a>
      <button class="btn btn-primary btn-lg"
type="submit">
        Reset
      </button>
      <input class="btn btn-info btn-sm active"
type="button" value="Cancel">
```

```

        <input class="btn btn-success btn-xs disabled"
type="button" value="Submit">

        <br />
        <br />
        <br />
        <div class="btn-group btn-group-justified"
role="group">
            <div class="btn-group">
                <button type="button" class="btn btn-default">
                    Left
                </button>

            </div>

            <div class="btn-group">
                <button type="button" class="btn btn-default">
                    Middle
                </button>

            </div>

            <div class="btn-group">
                <button type="button" class="btn btn-default">
                    Right
                </button>

            </div>

        </div>
        <br />
        <br />
        <br />
        <div class="btn-toolbar" role="toolbar">
            <div class="btn-group btn-group-vertical"
role="group">
                <button type="button" class="btn btn-default">
                    Left
                </button>

                <button type="button" class="btn btn-default">
                    Middle

```



```
        </button>

        <button type="button" class="btn btn-default">
            Right
        </button>

    </div>
    <div class="btn-group" role="group">
        <button type="button" class="btn btn-default">
            Left
        </button>

        <button type="button" class="btn btn-default">
            Middle
        </button>

        <button type="button" class="btn btn-default">
            Right
        </button>

    </div>
    <div class="btn-group" role="group">
        <button type="button" class="btn btn-default">
            Left
        </button>

        <button type="button" class="btn btn-default">
            Middle
        </button>

        <button type="button" class="btn btn-default">
            Right
        </button>

    </div>
</div>

</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
```

```
</script>  
<script src="js/bootstrap.min.js">  
</script>  
</body>  
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



APPLICATION: CREATE A CIRCULAR IMAGE

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      buttons
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      
    </div>
    <script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
    </script>
    <script src="js/bootstrap.min.js">
    </script>
```

```
</body>  
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap NAVS

APPLICATION: WEBSITE DESIGN USING NAV TABS AND NAV PILLS

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      navs
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <ul class="nav nav-tabs nav-justified">
        <li role="presentation" class="active">
          <a href="#">
            <span class="glyphicon glyphicon-home">
            </span>
            Home
          </a>
        </li>
```

```
<li role="presentation">
  <a href="#">
    <span class="glyphicon glyphicon-envelope">
    </span>
    Messages
    <span class="badge">
      3
    </span>
  </a>
</li>

<li role="presentation">
  <a href="#">
    Notifications
    <span class="badge">
      3
    </span>
  </a>
</li>

<li role="presentation">
  <a href="#">
    Contact us
  </a>
</li>

</ul>

<ul class="nav nav-pills nav-stacked">
  <li role="presentation" class="active">
    <a href="#">
      Home
    </a>
  </li>

  <li role="presentation">
    <a href="#">
      Page 1
    </a>
  </li>

  <li role="presentation">
```

```
        <a href="#">
            Page 2
        </a>
    </li>

    <li role="presentation" class="disabled">
        <a href="#">
            Page 3
        </a>
    </li>

</ul>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
</body>
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap

NAVBAR

APPLICATION: WEBSITE DESIGN USING A
RESPONSIVE/COLLAPSIBLE NAVIGATION BAR.

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      navbars
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <nav role="navigation" class="navbar navbar-inverse
navbar-fixed-top">
      <div class="container-fluid">
        <div class="navbar-header">
          <a class="navbar-brand">
            Store
          </a>
          <button type="button" class="navbar-toggle"
data-target="#navbarCollapse" data-toggle="collapse">
            <span class="sr-only">
```



```

        Toggle navigation
    </span>
    <span class="icon-bar">
    </span>
    <span class="icon-bar">
    </span>
    <span class="icon-bar">
    </span>
</button>
</div>
<div class="navbar-collapse collapse"
id="navbarCollapse">
    <ul class="nav navbar-nav">
        <li class="active">
            <a href="#">
                All Products
            </a>
        </li>
        <li>
            <a href="#">
                Help
            </a>
        </li>
        <li>
            <a href="#">
                Department
                <span class="caret">
                </span>
            </a>
        </li>
    </ul>
    <form class="navbar-form navbar-left"
role="search">
        <div class="input-group">
            <span class="input-group-btn">
                <button type="submit" class="btn btn-info">
                    Go
                </button>
            </span>
            <label for="search" class="sr-only">
                Search
            </label>

```

```
<input type="text" id="search" class="form-control" placeholder="Search">  
    <span class="glyphicon glyphicon-search form-control-feedback">  
    </span>  
  </div>  
</form>  
  
  <form class="navbar-form navbar-right">  
    <input class="btn btn-success" type="button"  
value="Login">  
  </form>  
</div>  
</nav>  
<div class="container-fluid" style="margin-top:60px">  
  <p>  
    Paragraph  
  </p>  
  
  <p>  
    Paragraph  
  </p>  
  
  <p>  
    Paragraph  
  </p>  
  
  <p>  
    Paragraph  
  </p>  
  
  <p>  
    Paragraph  
  </p>
```

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

<p>

Paragraph

</p>

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
<p>  
  Paragraph  
</p>
```

```
</div>
```

```
<script  
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j  
query.min.js">  
</script>  
<script src="js/bootstrap.min.js">  
</script>  
</body>  
</html>
```



Bootstrap PAGINATION

APPLICATION: CREATE PAGINATION AND PAGER
EXAMPLES SIMILAR TO GOOGLE OR EBAY.

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Pagination
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <nav>
        <ul class="pagination pagination-lg">
          <li class="disabled">
            <a href="#" aria-label="Previous">
              <span aria-hidden="true">
                &Laquo;
              </span>
            </a>
          </li>
```

```
<li class="active">
  <a href="#">
    1
  </a>
</li>
<li>
  <a href="#">
    2
  </a>
</li>
<li>
  <a href="#">
    3
  </a>
</li>
<li>
  <a href="#">
    4
  </a>
</li>
<li>
  <a href="#">
    5
  </a>
</li>
<li class="disabled">
  <a href="#">
    6
  </a>
</li>
<li>
  <a href="#">
    7
  </a>
</li>
<li>
  <a href="#">
    8
  </a>
</li>
<li>
  <a href="#">
```

```

        9
        </a>
    </li>
    <li>
        <a href="#">
            10
        </a>
    </li>
    <li>
        <a href="#" aria-label="Next">
            <span aria-hidden="true">
                &raquo;
            </span>
        </a>
    </li>
</ul>

</nav>

<nav>
    <ul class="pager">
        <li class="previous disabled">
            <a href="#">
                Previous
            </a>
        </li>
        <li class="next">
            <a href="#">
                Next
            </a>
        </li>
    </ul>
</nav>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
</body>

```



```
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap

JUMBOTRON

CALL EXTRA ATTENTION TO FEATURED CONTENT IN
YOUR WEBSITE

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Jumbotron
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>

    <div class="jumbotron">
      <div class="container-fluid">
        <h1>
          Welcome to our best selling app.
        </h1>
        <p>
          Our app will make your life easier.
        </p>
        <p>
```

```
        <a class="btn btn-success btn-lg" href="#">
            Find out more
        </a>
    </p>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
</body>
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap THUMBNAILS

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Thumbnails
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <div class="row">
        <div class="col-xs-6 col-md-4">
          <a href="#" class="thumbnail">
            
          </a>
        </div>
        <div class="col-xs-6 col-md-4">
          <a href="#" class="thumbnail">
            
          </a>
        </div>
      </div>
    </div>
  </body>
</html>
```

```

    </a>
</div>
<div class="col-xs-6 col-md-4">
    <a href="#" class="thumbnail">
        
    </a>
</div>
</div>

<div class="row">
    <div class="col-sm-6 col-md-4">
        <div class="thumbnail">
            
            <div class="caption">
                <h3>
                    Product title
                </h3>
                <p>
                    Product description
                </p>
                <p>
                    <a href="#" class="btn btn-primary"
role="button">
                        Add to watch List
                    </a>
                    <a href="#" class="btn btn-success"
role="button">
                        Add to Basket
                    </a>
                </p>
            </div>
        </div>
    </div>
    <div class="col-sm-6 col-md-4">
        <div class="thumbnail">
            
            <div class="caption">
                <h3>
                    Product title
                </h3>
                <p>
                    Product description

```

```

        </p>
        <p>
            <a href="#" class="btn btn-primary"
role="button">
                Add to watch List
            </a>
            <a href="#" class="btn btn-success"
role="button">
                Add to Basket
            </a>
        </p>
    </div>
</div>
</div>
<div class="col-sm-6 col-md-4">
    <div class="thumbnail">
        
        <div class="caption">
            <h3>
                Product title
            </h3>
            <p>
                Product description
            </p>
            <p>
                <a href="#" class="btn btn-primary"
role="button">
                    Add to watch List
                </a>
                <a href="#" class="btn btn-success"
role="button">
                    Add to Basket
                </a>
            </p>
        </div>
    </div>
</div>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">

```

```
</script>  
<script src="js/bootstrap.min.js">  
</script>  
</body>  
</html>
```



Bootstrap DROPDOWN MENUS

CREATE A DROPDOWN MENU WITH HEADERS

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Dropdown plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <div class="dropdown">
        <button class="dropdown-toggle btn btn-info"
type="button" id="dropdownMenu" data-toggle="dropdown">
          Dropdown plugin
          <span class="caret">
        </span>
        </button>
        <ul class="dropdown-menu" role="menu" aria-
labelledby="dropdownMenu">
```



```
<li role="presentation" class="dropdown-header">
  Header 1
</li>
<li role="presentation">
  <a role="menuitem" href="#">
    item
  </a>
</li>
<li role="presentation">
  <a role="menuitem" href="#">
    item
  </a>
</li>
<li role="presentation" class="divider">
</li>
<li role="presentation" class="dropdown-header">
  Header 2
</li>
<li role="presentation">
  <a role="menuitem" href="#">
    item
  </a>
</li>
<li role="presentation">
  <a role="menuitem" href="#">
    item
  </a>
</li>
<li role="presentation" class="disabled">
  <a role="menuitem" href="#">
    item
  </a>
</li>
</ul>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
```

```
</body>  
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap MODALS (1)

APPLICATION: I HAVE AN INQUIRY ABOUT MY ORDER!

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap MODALS (2)

APPLICATION: I HAVE AN INQUIRY ABOUT MY ORDER!

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Modal plugin
    </title>
```

```

<link href="css/bootstrap.min.css" rel="stylesheet">
<style>

</style>
</head>
<body>
  <div class="container-fluid">
    <button type="button" class="btn btn-primary" data-
target="#myInquiry" data-toggle="modal" data-
ordernumber="1122">
      Order Number: 1122 - Contact us
    </button>
    <div class="modal" id="myInquiry" role="dialog"
aria-labelledby="myModallLabel" aria-hidden="true">
      <div class="modal-dialog">
        <div class="modal-content">
          <div class="modal-header">
            <button class="close" data-dismiss="modal">
              &times;
            </button>
            <h4 id="myModallLabel">
              Thank you for contacting us:
            </h4>
          </div>
          <div class="modal-body">
            <label for="inquiry">
              Your inquiry:
            </label>
            <textarea class="form-control" rows="5"
id="inquiry">
            </textarea>
          </div>
          <div class="modal-footer">
            <button type="button" class="btn btn-default"
data-dismiss="modal">
              Close
            </button>
            <button type="button" class="btn btn-primary">
              Send
            </button>
          </div>
        </div>
      </div>
    </div>
  </div>

```

```
</div>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
    $('#myInquiry').on('hide.bs.modal',function(){
        //window.alert('Hi!');
    }
    );
    $('#myInquiry').on('show.bs.modal',function(event){
        var button = $(event.relatedTarget);
        var orderNumber = button.data('ordernumber');
        $(this).find('#myModalLabel').text('Order number: '
+ orderNumber);
    }
    )
</script>
</body>
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Scrollspy plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <nav role="navigation" class="navbar navbar-inverse
navbar-fixed-top" id="mynavBar">
      <div class="container-fluid">
        <div class="navbar-header">
          <a class="navbar-brand">
            Store
          </a>
          <button type="button" class="navbar-toggle"
data-target="#navbarCollapse" data-toggle="collapse">
            <span class="sr-only">
```

```

        Toggle navigation
    </span>
    <span class="icon-bar">
    </span>
    <span class="icon-bar">
    </span>
    <span class="icon-bar">
    </span>
    </button>
</div>
<div class="navbar-collapse collapse"
id="navbarCollapse">
    <ul class="nav navbar-nav">
        <li class="active">
            <a href="#allProducts">
                All Products
            </a>
        </li>
        <li>
            <a href="#help">
                Help
            </a>
        </li>
        <li>
            <a href="#department">
                Department
                <span class="caret">
                </span>
            </a>
        </li>
    </ul>
    <form class="navbar-form navbar-left"
role="search">
        <div class="input-group">
            <span class="input-group-btn">
                <button type="submit" class="btn btn-info">
                    Go
                </button>
            </span>
            <label for="search" class="sr-only">
                Search
            </label>

```

[illegible]


```
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<h4 id="help">
  Help
</h4>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
```

```
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<h4 id="department">
  Departments
</h4>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
```

```
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
<p>
  Some text
</p>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
  $('#mynavBar').on('activate.bs.scrollspy',function(){
    $('.btn-success').toggleClass('btn-warning');

  }

  );

</script>
```

```
</body>  
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap TABS

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Tabs plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <ul class="nav nav-tabs nav-justified" id="myTabs">
        <li role="presentation" class="active">
          <a href="#home" data-toggle="tab">
            <span class="glyphicon glyphicon-home">
            </span>
            Home
          </a>
        </li>
```

```
<li role="presentation">
  <a href="#messages" data-toggle="tab">
    <span class="glyphicon glyphicon-envelope">
    </span>
    Messages
    <span class="badge">
      3
    </span>
  </a>
</li>

<li role="presentation">
  <a href="#notifications" data-toggle="tab">
    Notifications
    <span class="badge">
      3
    </span>
  </a>
</li>

<li role="presentation">
  <a href="#contactUs" data-toggle="tab">
    Contact us
  </a>
</li>

</ul>

<div id="myTabContent" class="tab-content">
  <div class="tab-pane active fade in" id="home">
    <p>
      Home Content.
    </p>
    <p>
      Some text.
    </p>
    <p>
      Some text.
    </p>
    <p>
      Some text.
    </p>
```

```
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
</div>
<div class="tab-pane fade" id="messages">
  <p>
    Messages Content.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
</div>
<div class="tab-pane fade" id="notifications">
  <p>
    Notifications Content.
```

```
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
<p>
  Some text.
</p>
</div>
<div class="tab-pane fade" id="contactUs">
  <p>
    Contact us.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
  <p>
    Some text.
  </p>
```



```
        <p>
            Some text.
        </p>
        <p>
            Some text.
        </p>
    </div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
    $('#myTabs a:last').tab('show');
    $('a[data-
toggle="tab"]').on('shown.bs.tab',function(event){
        window.alert('The active tab is: ' +
$(event.target).text() + '. The previous tab is: ' +
$(event.relatedTarget).text());
    }
    );
</script>
</body>
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap TOOLTIPS

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Tooltip plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <div>
        <p>
          Paragraph.
        </p>
        <p>
          This is a
          <a href="http://www.google.com" title="Google"
data-toggle="tooltip" data-placement="right">
            link
```

```

        </a>
        .
    </p>
    <button type="button" class="btn btn-primary"
data-toggle="tooltip" title="button tooltip" data-
placement="bottom">
        Button
    </button>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
    $('[data-toggle="tooltip"]').tooltip();
    $('[data-toggle="tooltip"]').tooltip('show');
    $('[data-
toggle="tooltip"]').on('hidden.bs.tooltip',function(){
        window.alert("tooltip hidden!");
    }

)

</script>
</body>
</html>

```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED

Bootstrap POPOVERS

APPLICATION: CREATE A POPOVER JUST LIKE THE ONE
YOU SEE ON AN IPAD

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Popover plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <button type="button" class="btn btn-primary" data-
toggle="popover" data-content="
<h4>
Popover
</h4>
<p>
This is a popover just like the one you see on an ipad
</p>
" data-trigger="hover">
```

```
    Button
  </button>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
  </script>
  <script src="js/bootstrap.min.js">
  </script>
  <script>
    $(function(){
      $('[data-toggle="popover"]').popover({
        html : true,
        delay : {"show":1000, "hide": 300}
      }
    );

    $('[data-
toggle="popover"]').on('hidden.bs.popover',function(){
      window.alert('Popover hidden!');
    }
  );
  }
  );
</script>
</body>
</html>
```

Bootstrap ALERTS

APPLICATION: CREATE AN ALERT BOX TO SHOW
A WARNING OR SUCCESS MESSAGE

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Alert plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <div id="alert1" class="alert alert-warning">
        <a class="close" data-dismiss="alert">
          &times;
        </a>
        <strong>
          Warning!
        </strong>
        Your unsaved data was lost.
      </div>
```

```
<div id="alert2" class="alert alert-success">
  <a class="close" data-dismiss="alert">
    &times;
  </a>
  <strong>
    Success!
  </strong>
  File uploaded successfully.
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
  $(function(){
    $('.alert').on('closed.bs.alert',function(){
      window.alert('Alert message closed!');
    }

    );

    $('#alert1').alert('close');
  }
  );
</script>
</body>
</html>
```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap

BUTTON PLUGIN

APPLICATION: LOADING ... DOWNLOAD COMPLETE!

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Button plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <button type="button" class="btn btn-primary"
id="button1" data-loading-text="Loading...">
        Button1
      </button>

      <button type="button" class="btn btn-primary"
id="button2" data-loading-text="Loading..." data-complete-
text="Download complete!">
```



```

        Button2
    </button>

</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
    $(function(){
        $('#button1').click(function(){
$(this).button('loading').delay(1000).queue(function(){
    $(this).button('reset');
    });
        });

        $('#button2').click(function(){
$(this).button('loading').delay(1000).queue(function(){
    $(this).button('complete');
    });
        });
    });
</script>
</body>
</html>

```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap COLLAPSE PLUGIN

APPLICATION: WEBSITE DESIGN
USING A STYLED COLLAPSIBLE ACCORDION

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Collapse plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>

    </style>
  </head>
  <body>
    <div class="container-fluid">
      <a class="btn btn-primary" href="#collapse01" data-
toggle="collapse">
        Link
      </a>
      <button class="btn btn-primary" data-
target="#collapse02" data-toggle="collapse">
        Button
      </button>
      <div class="bg-danger collapse" id="collapse01">
```

```

    <p>
      Collapsible content 1.
    </p>
    <p>
      Collapsible content 1.
    </p>
    <p>
      Collapsible content 1.
    </p>
  </div>
  <div class="bg-warning collapse" id="collapse02">
    <p>
      Collapsible content 2.
    </p>
    <p>
      Collapsible content 2.
    </p>
    <p>
      Collapsible content 2.
    </p>
  </div>
<br />

<br />

<div id="accordion" class="panel-group">
  <div class="panel panel-warning">
    <div class="panel-heading">
      <h4 class="panel-title">
        <a href="#collapse1" data-toggle="collapse"
data-parent="#accordion">
          Section 1
        </a>
      </h4>
    </div>
    <div class="panel-collapse collapse in"
id="collapse1">
      <div class="panel-body">
        <p>
          Collapsible content 1.
        </p>
        <p>

```

```

        Collapsible content 1.
    </p>
    <p>
        Collapsible content 1.
    </p>
</div>
</div>
</div>
<div class="panel panel-success">
    <div class="panel-heading">
        <h4 class="panel-title">
            <a href="#collapse2" data-toggle="collapse" data-
parent="#accordion">
                Section 2
            </a>
        </h4>
    </div>
    <div class="panel-collapse collapse" id="collapse2">
        <div class="panel-body">
            <p>
                Collapsible content 2.
            </p>
            <p>
                Collapsible content 2.
            </p>
            <p>
                Collapsible content 2.
            </p>
        </div>
    </div>
</div>
<div class="panel panel-danger">
    <div class="panel-heading">
        <h4 class="panel-title">
            <a href="#collapse3" data-toggle="collapse" data-
parent="#accordion">
                Section 3
            </a>
        </h4>
    </div>
    <div class="panel-collapse collapse in"
id="collapse3">

```

```

    <div class="panel-body">
      <p>
        Collapsible content 3.
      </p>
      <p>
        Collapsible content 3.
      </p>
      <p>
        Collapsible content 3.
      </p>
    </div>
  </div>
</div>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
  $(function(){
    $('#collapse2').collapse('show');
    $('#collapse3').collapse('toggle');
    $('#collapse1').on('hidden.bs.collapse',function(){
      window.alert('Section 1 hidden!');
    }
      );
  }
  );
</script>
</body>
</html>

```

THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap CAROUSELS

APPLICATION: CREATE AN INTERACTIVE CAROUSEL SLIDER

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Carousel plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>
      .yellow{
        color: yellow;
      }
    </style>
  </head>
  <body>
    <div class="container-fluid">
      <div class="carousel slide" id="myCarousel" data-
ride="carousel">
        <ol class="carousel-indicators">
          <li data-target="#myCarousel" data-slide-to="0"
class="active">
          </li>
          <li data-target="#myCarousel" data-slide-to="1">
```

```

        </li>
        <li data-target="#myCarousel" data-slide-to="2">
        </li>
    </ol>
    <div class="carousel-inner">
        <div class="item active">
            
            <div class="carousel-caption">
                <p>
                    First Slide
                </p>
            </div>
        </div>
        <div class="item">
            
            <div class="carousel-caption">
                <p>
                    Second Slide
                </p>
            </div>
        </div>
        <div class="item">
            
            <div class="carousel-caption">
                <p>
                    Third Slide
                </p>
            </div>
        </div>
    </div>
    <a class="left carousel-control" href="#myCarousel"
data-slide="prev">
        <span class="glyphicon glyphicon-chevron-left">
        </span>
        <span class="sr-only">
            Previous
        </span>
    </a>
    <a class="right carousel-control" href="#myCarousel"
data-slide="next">
        <span class="glyphicon glyphicon-chevron-right">
        </span>

```

```
<span class="sr-only">
  Previous
</span>
</a>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
</script>
<script>
$(function(){
  $('.carousel').carousel({
    interval : 1000
  }
  );
  $('.carousel').on('slide.bs.carousel',function(){
    $('p').toggleClass('yellow');
  }
  );
  $('.carousel').hover(function(){
    $(this).carousel('pause');
  }
  ,function(){
    $(this).carousel('cycle');
  }
  );
});
</script>
</body>
</html>
```


THE COMPLETE WEB
DEVELOPMENT
COURSE

STEP BY STEP
WITH
NO STEP SKIPPED



Bootstrap AFFIX PLUGIN

APPLICATION: CREATE AN INTERACTIVE WEBSITE WITH
CONTENT AFFIXED TO A MENU

DEVELOPMENT ISLAND
help@completewebdevelopmentcourse.co.uk

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="utf-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width,
initial-scale=1">
    <title>
      Affix plugin
    </title>
    <link href="css/bootstrap.min.css" rel="stylesheet">
    <style>
      ul.nav-tabs{
        width: auto;
        border: 1px solid #9e60f0;
        border-radius: 3px;
      }
      ul.nav-tabs li.active a, ul.nav-tabs li.active
a:hover{
        color: white;
        background: #7628dc;
      }
    </style>

  </head>
  <body data-spy="scroll" data-target="#myScrollspy">
```

```
<div class="container-fluid">
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <p>
    Paragraph
  </p>
  <div class="row">
    <div class="col-xs-3" id="myScrollspy">
      <ul id="myAffix" class="nav nav-tabs nav-
stacked">
        <li>
          <a href="#section1">
            Section One
          </a>
        </li>
        <li>
          <a href="#section2">
            Section Two
          </a>
        </li>
      </ul>
    </div>
  </div>
</div>
```

[illegible]

```
</p>
<p>
  C1
</p>
<p>
  C1
</p>
<p>
  C1
</p>
<p>
  C1
</p>
<p>
  C1
</p>
<p>
  C1
</p>
<p>
  C1
</p>
<p>
  C1
</p>
<h2 id="section2">
  Section Two
</h2>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
```

```
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<p>
  C2
</p>
<h2 id="section3">
  Section Three
</h2>
<p>
  C3
</p>
<p>
  C3
</p>
<p>
  C3
</p>
<p>
  C3
</p>
<p>
  C3
</p>
<p>
  C3
```

[illegible]

[illegible]

```
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
<p>
  C5
</p>
</div>
</div>
</div>
<script
src="https://ajax.googleapis.com/ajax/libs/jquery/1.11.2/j
query.min.js">
</script>
<script src="js/bootstrap.min.js">
```



```
</script>
<script>
  $(function(){
    $('#myAffix').affix({
      offset: {
        top: 300}
    }
  });
});
</script>
</body>
</html>
```