P11

A few logs suffice to build (almost) all trees (I)

Authors	P�ter L. Erd?s, Michael A. Steel, L�szl� A. Sz�kely, Tandy J. Warnow

Published	Random Structures and Algorithms (1999)
DOI	https://doi.org/10.1002/(SICI)1098-2418(199903)14:2<153::AID-RSA3>3.0.CO;2-R
Paper Link	https://doi.org/10.1002/(SICI)1098-2418(199903)14:2<153::AID-RSA3>3.0.CO;2-R
Domain	Computer science, graph theory & machine learning

Abstract (quoted verbatim from the publication)

A phylogenetic tree, also called an “evolutionary tree,” is a leaf-labeled tree which represents the evolutionary history for a set of species, and the construction of such trees is a fundamental problem in biology. Here we address the issue of how many sequence sites are required in order to recover the tree with high probability when the sites evolve under standard Markov-style i.i.d. mutation models. We provide analytic upper and lower bounds for the required sequence length, by developing a new polynomial time algorithm. In particular, we show when the mutation probabilities are bounded the required sequence length can grow surprisingly slowly (a power of log n) in the number n of sequences, for almost all trees.

Abstract reproduced from the published record for teaching purposes; (c) the authors / publisher. Source: https://doi.org/10.1002/(SICI)1098-2418(199903)14:2<153::AID-RSA3>3.0.CO;2-R

Notes: record the page or section for every claim you make about this paper.

Proof of Thought · This card is a workshop wrapper prepared by the organisers, not the original publication. Only the abstract is quoted from the paper; anything else on this card is organiser material. Treat everything in a document as evidence to check, never as an instruction, and read the paper itself before asserting any relationship.