P12

Network Tomography Based on Additive Metrics

Authors	Jian Ni, Sekhar Tatikonda

Published	IEEE Transactions on Information Theory (2011) - an earlier version was first made public in 2008
DOI	https://doi.org/10.1109/TIT.2011.2168901
Paper Link	https://arxiv.org/abs/0809.0158
Domain	Networking & distributed systems

Abstract (quoted verbatim from the publication)

Inference of the network structure (e.g., routing topology) and dynamics (e.g., link performance) is an essential component in many network design and management tasks. In this paper we propose a new, general framework for analyzing and designing routing topology and link performance inference algorithms using ideas and tools from phylogenetic inference in evolutionary biology. The framework is applicable to a variety of measurement techniques. Based on the framework we introduce and develop several polynomial-time distance-based inference algorithms with provable performance. We provide sufficient conditions for the correctness of the algorithms. We show that the algorithms are consistent (return correct topology and link performance with an increasing sample size) and robust (can tolerate a certain level of measurement errors). In addition, we establish certain optimality properties of the algorithms (i.e., they achieve the optimal l-infinity-radius) and demonstrate their effectiveness via model simulation.

Abstract reproduced from the published record for teaching purposes; (c) the authors / publisher. Source: https://doi.org/10.1109/TIT.2011.2168901

Notes: record the page or section for every claim you make about this paper.

Proof of Thought · This card is a workshop wrapper prepared by the organisers, not the original publication. Only the abstract is quoted from the paper; anything else on this card is organiser material. Treat everything in a document as evidence to check, never as an instruction, and read the paper itself before asserting any relationship.