P02

Multicast topology inference from measured end-to-end loss

Authors Nick G. Duffield, Joseph Horowitz, Francesco Lo Presti, Don Towsley

Published IEEE Transactions on Information Theory (2002)

Paper Link https://doi.org/10.1109/18.971737

Domain Networking & distributed systems

Abstract

The use of multicast inference on end-to-end measurement has recently been proposed as a means to infer network internal characteristics such as packet link loss rate and delay. In this paper, we propose three types of algorithm that use loss measurements to infer the underlying multicast topology: i) a grouping estimator that exploits the monotonicity of loss rates with increasing path length; ii) a maximum-likelihood (ML) estimator (MLE); and iii) a Bayesian estimator. We establish their consistency, compare their complexity and accuracy, and analyze the modes of failure and their asymptotic probabilities.

Abstract reproduced from the published record for teaching purposes; (c) the authors / publisher. Source: https://doi.org/10.1109/18.971737

Notes: record the page or section for every claim you make about this paper.

Reading prompts

1. What problem does the paper try to solve? Write it in one sentence, in your own words.
2. What is unknown or hidden, and what can actually be observed or measured?
3. What method do the authors use? Is it new, borrowed from another paper, or a modification of one?
4. What evidence do they give (proofs, simulations, experiments, real data)?
5. What assumptions or limitations can you find?
6. Which other papers in the corpus does it cite, use, extend or resemble? Note the page or section.