

Catch-all route — `[...slug]`

Live demo: `/shop` , `/shop/men` , `/shop/men/shoes/blue` **Code:** `src/app/shop/`

What it is

A **catch-all** segment, written `[...slug]` , matches **one or more** path segments and gives you them as a **string array**.

Folder	URL	<code>params.slug</code>
<code>shop/[...slug]</code>	<code>/shop/men</code>	<code>["men"]</code>
<code>shop/[...slug]</code>	<code>/shop/men/shoes</code>	<code>["men", "shoes"]</code>
<code>shop/[...slug]</code>	<code>/shop/men/shoes/blue</code>	<code>["men", "shoes", "blue"]</code>

```
export default async function ShopCatchAll({
  params,
}): {
  params: Promise<{ slug: string[] }>;
} {
  const { slug } = await params; // string[]
}
```

The key gotcha: it does NOT match the base path

`[...slug]` matches `/shop/<something>` but **not** `/shop` itself. In this demo `/shop` only works because there's a separate `shop/page.tsx` . Remove that and `/shop` would 404.

➡ If you want **one file** to handle both `/shop` and `/shop/...` , use an **optional** catch-all `[...slug]` (see the `/docs` demo).

When to use

- Documentation trees, file browsers, category paths of unknown depth.
- Anywhere the number of segments isn't fixed.

Interview Q&A

- **Q: `[...slug]` vs `[...slug]` ?** Both capture multiple segments into an array. The double-bracket **optional** one *also* matches the parent/base path; the single-bracket one does not.
- **Q: What type is `params.slug` for a catch-all?** `string[]` (and the `params` object is a Promise you await).