

Certificate of Conformity (COC)

SGS

Certificate Holder : NingBo Deye Inverter Technology Co., Ltd.
No. 26 South Yongjiang Road, Daqi, Beilun, NingBo, China

Date of Original Issue : 2024-03-26
Date of Last Revision : --
Date of Expiry : 2027-03-25
Certificate Number : PCS-24-1022
Product : Grid-connected PV Inverter
Ratings : See appendix on page 2 to page 4
Brand/Trademark : **Deye**

Model : SUN-3K-G06P3-EU-AM2, SUN-4K-G06P3-EU-AM2, SUN-5K-G06P3-EU-AM2,
SUN-6K-G06P3-EU-AM2, SUN-7K-G06P3-EU-AM2, SUN-8K-G06P3-EU-AM2,
SUN-9K-G06P3-EU-AM2, SUN-10K-G06P3-EU-AM2, SUN-12K-G06P3-EU-AM2,
SUN-15K-G06P3-EU-AM2, SUN-3K-G06P3-EU-AM2-P1, SUN-4K-G06P3-EU-AM2-P1,
SUN-5K-G06P3-EU-AM2-P1, SUN-6K-G06P3-EU-AM2-P1, SUN-7K-G06P3-EU-AM2-P1,
SUN-8K-G06P3-EU-AM2-P1, SUN-9K-G06P3-EU-AM2-P1, SUN-10K-G06P3-EU-AM2-P1,
SUN-12K-G06P3-EU-AM2-P1, SUN-15K-G06P3-EU-AM2-P1

Test Laboratory : SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch
Testing Report : GZES220300424901, 2023-12-02, Amendment 01:2024-03-05
GZES220300424902, 2023-12-02, Amendment 01:2024-03-05

Test Standard : IEC 62116:2014 and IEC 61727:2004



This is to certify that the product has been tested and was found to comply with the requirements of the standard(s).
The above-mentioned product is certified according to the requirements of ISO/IEC 17065:2012.

Christopher Hee
Certification Officer



SGS Testing & Control Services Singapore Pte Ltd
30 Boon Lay Way #03-01 Singapore 609957



The use of this Certificate is subjected to the General Conditions for Certification Services accessible at <https://www.sgs.com/en/terms-and-conditions> and Certification Agreement for SGS Product Certification Scheme (PCS). Any unauthorised alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This Certificate is part of a full report and should be read in conjunction with it. This Certificate cannot be reproduced except in full, without prior approval of the Company. This Certificate remains the property of SGS Testing & Control Services Singapore Pte Ltd and shall be returned upon request.

APPENDIX

Certificate Number: PCS-24-1022

Model	SUN-3K-G06P3-EU-AM2-P1	SUN-4K-G06P3-EU-AM2-P1	SUN-5K-G06P3-EU-AM2-P1	SUN-6K-G06P3-EU-AM2-P1
Model (*)	SUN-3K-G06P3-EU-AM2	SUN-4K-G06P3-EU-AM2	SUN-5K-G06P3-EU-AM2	SUN-6K-G06P3-EU-AM2
PV Input				
Recommended Max. PV input power (kW)	3.9	5.2	6.5	7.8
Max. input voltage (V)	1100			
Start-up operating voltage (V)	140			
Rated input voltage (V)	600			
MPPT operating voltage range (V)	120-1000			
Full power MPPT voltage range (V)	350-850			
Max. input current (A)	20+20			
Max. short current (A)	30+30			
Max. input current (A) (*)	13+13			
Max. short current (A) (*)	19.5+19.5			
AC Output				
Nominal grid voltage (V)	3L/N/PE 230/400V			
Nominal grid frequency (Hz)	50/60			
Rated AC power (kW)	3	4	5	6
Max. AC power (kW)	3.3	4.4	5.5	6.6
Rated AC current (A)	4.4	5.8	7.3	8.7
Max. AC current (A)	4.8	6.4	8.0	9.6
Output power factor	0.8 leading~0.8 lagging			
General Data				
Operating temperature range	-25 ~ 60 °C, >45 °C derating			
Protection degree	IP65			
Protective class	Class I			
Cooling method	Free cooling			
Topology	Transformerless			

(*) The difference between the model suffixes AM2 and AM2-P1 is the maximum input current and the maximum short-circuit current, refer to the above parameter table of detailed information.



APPENDIX

Certificate Number: PCS-24-1022

Model	SUN-7K-G06P3-EU-AM2-P1	SUN-8K-G06P3-EU-AM2-P1	SUN-9K-G06P3-EU-AM2-P1	SUN-10K-G06P3-EU-AM2-P1
Model (*)	SUN-7K-G06P3-EU-AM2	SUN-8K-G06P3-EU-AM2	SUN-9K-G06P3-EU-AM2	SUN-10K-G06P3-EU-AM2
PV Input				
Recommended Max. PV input power(kW)	9.1	10.4	11.7	13
Max. input voltage(V)	1100			
Start-up operating voltage(V)	140			
Rated input voltage(V)	600			
MPPT operating voltage range(V)	120~1000			
Full power MPPT voltage range (V)	480~850			
Max. input current(A)	20+20			
Max. short current(A)	30+30			
Max. input current(A) (*)	13+13			
Max. short current(A) (*)	19.5+19.5			
AC Output				
Nominal grid voltage(V)	3L/N/PE 230/400V			
Nominal grid frequency (Hz)	50/60			
Rated AC power(kW)	7	8	9	10
Max. AC power(kW)	7.7	8.8	9.9	11
Rated AC current(A)	10.2	11.6	13.1	14.5
Max. AC current(A)	11.2	12.8	14.4	16.0
Output power factor	0.8 leading~0.8 lagging			
General Data				
Operating temperature range	-25 ~ 60 °C,>45 °C derating			
Protection degree	IP65			
Protective class	Class I			
Cooling method	Free cooling			
Topology	Transformerless			

(*) The difference between the model suffixes AM2 and AM2-P1 is the maximum input current and the maximum short-circuit current, refer to the above parameter table of detailed information.



APPENDIX

Certificate Number: PCS-24-1022

Model	SUN-12K-G06P3-EU-AM2-P1	SUN-15K-G06P3-EU-AM2-P1
Model (*)	SUN-12K-G06P3-EU-AM2	SUN-15K-G06P3-EU-AM2
PV Input		
Recommended Max. PV input power(kW)	15.6	19.5
Max. input voltage(V)	1100	
Start-up operating voltage(V)	140	
Rated input voltage(V)	600	
MPPT operating voltage range(V)	120~1000	
Full power MPPT voltage range (V)	480~850	
Max. input current(A)	20+20	20+26
Max. short current(A)	30+30	30+39
Max. input current(A) (*)	13+13	13+26
Max. short current(A) (*)	19.5+19.5	19.5+39
AC Output		
Nominal grid voltage(V)	3L/N/PE 230/400V	
Nominal grid frequency (Hz)	50/60	
Rated AC power(kW)	12	15
Max. AC power(kW)	13.2	16.5
Rated AC current(A)	17.4	21.8
Max. AC current(A)	19.2	24.0
Output power factor	0.8 leading~0.8 lagging	
General Data		
Operating temperature range	-25 ~ 60 °C,>45 °C derating	
Protection degree	IP65	
Protective class	Class I	
Cooling method	Free cooling	
Topology	Transformerless	

(*) The difference between the model suffixes AM2 and AM2-P1 is the maximum input current and the maximum short-circuit current, refer to the above parameter table of detailed information.

