

Experiment 1

Objective

Create an XML document to store information about a collection of books.

Code:

XML Code:

```
<?xml version="1.0"?>
<bookstore>
  <book>
    <title>The First Book</title>
    <author>Hightower, Kim</author>
    <genre>Fiction</genre>
    <year>2000</year>
  </book>
  <book>
    <title>Becoming Somebody</title>
    <author>Nagata, Suanne</author>
    <genre>Biography</genre>
    <year>2001</year>
  </book>
  <book>
    <title>The Poet's First Poem</title>
    <author>Oberg, Bruce</author>
    <genre>Poem</genre>
    <year>2002</year>
  </book>
</bookstore>
```

HTML Code:

```

<!DOCTYPE html>
<html>
<head>
<title>XML Book Collection</title>
<style>
table {
    border-collapse: collapse;
    width: 100%;
}
th, td {
    border: 1px solid black;
    padding: 8px;
    text-align: left;
}
th {
    background-color: #f2f2f2;
}
</style>
</head>
<body>
<h1>Book Collection</h1>
<table id="bookTable">
<thead>
<tr>
<th>Title</th>
<th>Author</th>
<th>Genre</th>
<th>Year</th>
</tr>
</thead>

```

```

<tbody></tbody>
</table>
<script>
function loadXMLDoc(filename) {
    var xhttp = new XMLHttpRequest();
    xhttp.open("GET", filename, false);
    xhttp.send();
    return xhttp.responseXML;
}
function displayBooks() {
    var xmlDoc = loadXMLDoc("exp1.xml");
    var books = xmlDoc.getElementsByTagName("book");
    var tableBody =
document.getElementById("bookTable").getElementsByTagName("tbody")[0];
    for (var i = 0; i < books.length; i++) {
        var book = books[i];
        var title =
book.getElementsByTagName("title")[0].textContent;
        var author =
book.getElementsByTagName("author")[0].textContent;
        var genre =
book.getElementsByTagName("genre")[0].textContent;
        var year =
book.getElementsByTagName("year")[0].textContent;
        var row = tableBody.insertRow();
        row.insertCell(0).innerHTML = title;
        row.insertCell(1).innerHTML = author;
        row.insertCell(2).innerHTML = genre;
        row.insertCell(3).innerHTML = year;
    }
}

```

```
    }  
  }  
  displayBooks();  
</script>  
</body>  
</html>
```

Output:

Book Collection

Title	Author	Genre	Year
The First Book	Hightower, Kim	Fiction	2000
Becoming Somebody	Nagata, Suanne	Biography	2001
The Poet's First Poem	Oberg, Bruce	Poem	2002

Experiment 2

Objective

Transform XML data into HTML table using XSLT.

Code:

XML Code:

```
<?xml version="1.0" encoding="UTF-8"?>
<employees>
  <employee><id>1</id><name>John
Doe</name><position>Developer</position><salary>70000<
/salary></employee>
  <employee><id>2</id><name>Jane
Smith</name><position>Manager</position><salary>85000<
/salary></employee>
</employees>
```

XSLT Code:

```
<?xml version="1.0" encoding="UTF-8"?>
<xsl:stylesheet version="1.0"
xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
<xsl:template match="/">
<html><body>
<h2>Employee Table</h2>
<table border="1">
<tr><th>ID</th><th>Name</th><th>Position</th><th>Salary
</th></tr>
<xsl:for-each select="employees/employee">
<tr>
<td><xsl:value-of select="id"/></td>
<td><xsl:value-of select="name"/></td>
```

```

<td><xsl:value-of select="position"/></td>
<td><xsl:value-of select="salary"/></td>
</tr>
</xsl:for-each>
</table>
</body></html>
</xsl:template>
</xsl:stylesheet>

```

HTML Code (loading XML and XSL):

```

<!DOCTYPE html>
<html>
<head><title>Transform XML</title></head>
<body>
<div id="example"></div>
<script>
if (window.ActiveXObject || "ActiveXObject" in window) {
    var xml = new ActiveXObject("Microsoft.XMLDOM");
    xml.async = false;
    xml.load("exp2.xml");
    var xsl = new ActiveXObject("Microsoft.XMLDOM");
    xsl.async = false;
    xsl.load("exp2.xsl");
    document.getElementById("example").innerHTML =
xml.transformNode(xsl);
} else {
    var xhttp = new XMLHttpRequest();
    xhttp.open("GET", "exp2.xml", false);
    xhttp.send();
    var xml = xhttp.responseXML;

```

```
xhttp.open("GET", "exp2.xsl", false);
xhttp.send();
var xsl = xhttp.responseXML;
var xsltProcessor = new XSLTProcessor();
xsltProcessor.importStylesheet(xsl);
var resultDocument =
xsltProcessor.transformToFragment(xml, document);

document.getElementById("example").appendChild(resultDoc
ument);
}
</script>
</body>
</html>
```

Output:

XML Data Transformed into an HTML Table

Employee Information

ID	Name	Position	Salary
1	John Doe	Software Engineer	70000
2	Jane Smith	Product Manager	80000
3	Sam Brown	Designer	65000

Experiment 3

Objective

Load employee data from XML and display using JavaScript.

Code:

XML Code:

```
<?xml version="1.0" encoding="UTF-8"?>
<employees>
  <employee><id>1</id><name>Alice
Smith</name><department>HR</department></employee>
  <employee><id>2</id><name>Bob
Johnson</name><department>Engineering</department></e
mployee>
</employees>
```

HTML Code:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8" />
  <title>Employee List</title>
  <style>
    body { font-family: Arial, sans-serif; }
  </style>
</head>
<body>
  <h2>Employee List</h2>
  <ul id="employeeList"></ul>

  <script>
```

```

var xhr = new XMLHttpRequest();
xhr.open("GET", "exp3.xml", true);
xhr.onload = function () {
    if (xhr.status === 200) {
        var xmlDoc = xhr.responseXML;
        var employees =
xmlDoc.getElementsByTagName("employee");
        var list = document.getElementById("employeeList");
        for (var i = 0; i < employees.length; i++) {
            var name =
employees[i].getElementsByTagName("name")[0].textContent;
            var department =
employees[i].getElementsByTagName("department")[0].textC
ontent;
            var li = document.createElement("li");
            li.textContent = name + " - " + department;
            list.appendChild(li);
        }
    }
};
xhr.send();
</script>
</body>
</html>

```

Output:



Experiment 4

Objective

AJAX Contact Form with PHP backend.

Code:

PHP Code:

```
<?php
if ($_SERVER["REQUEST_METHOD"] == "POST") {
    $name = htmlspecialchars($_POST["name"]);
    $email = htmlspecialchars($_POST["email"]);
    $message = htmlspecialchars($_POST["message"]);
    echo "Thank you, <strong>$name</strong>!  
<br>";
    echo "We received your message:<br>";
    echo "<em>$message</em><br>";
    echo "We will reply to <strong>$email</strong> soon.";
} else {
    echo "Invalid request.";
}
?>
```

HTML Code:

```
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8" />
    <title>Contact Form</title>
    <style>
        body { font-family: Arial; padding: 20px; }
        form { width: 300px; }
        input, textarea { width: 100%; margin-bottom: 10px;
```

```
padding: 8px; }
    #response { margin-top: 15px; color: green; }
</style>
</head>
<body>
    <h2>Contact Us</h2>
    <form id="contactForm">
        <input type="text" name="name" placeholder="Your
Name" required />
        <input type="email" name="email" placeholder="Your
Email" required />
        <textarea name="message" placeholder="Your Message"
rows="4" required></textarea>
        <button type="submit">Send</button>
    </form>
    <div id="response"></div>
    <script>
        const form = document.getElementById("contactForm");
        const responseDiv =
document.getElementById("response");
        form.addEventListener("submit", function (event) {
            event.preventDefault();
            const formData = new FormData(form);
            fetch("exp4.php", { method: "POST", body: formData })
                .then((response) => response.text())
                .then((data) => {
                    responseDiv.innerHTML = data;
                    form.reset();
                })
                .catch((error) => {
```

```
        responseDiv.innerHTML = "Error: " + error;
    });
});
</script>
</body>
</html>
```

Output:

Contact Us

Blaze

masternoob4000@gmail.com

This is experiment :)

Send

Contact Us

Your Name

Your Email

Your Message

Send

Thank you, **Blaze!**
We received your message:
This is experiment :)
We will reply to **masternoob4000@gmail.com** soon.

Experiment 5:

Objective

Write an Ajax script to get player details from an XML file when the user selects a player name in any game. Also, create an XML file to store details of the player (name, country, wickets, and runs).

XML Code:

```
<?xml version="1.0" encoding="UTF-8"?>
<players>
  <player>
    <name>Virat Kohli</name>
    <country>India</country>
    <wickets>4</wickets>
    <runs>12000</runs>
  </player>
  <player>
    <name>Joe Root</name>
    <country>England</country>
    <wickets>20</wickets>
    <runs>10500</runs>
  </player>
  <player>
    <name>Steve Smith</name>
    <country>Australia</country>
    <wickets>10</wickets>
    <runs>9500</runs>
  </player>
  <player>
    <name>Babar Azam</name>
```

```

    <country>Pakistan</country>
    <wickets>2</wickets>
    <runs>8000</runs>
  </player>
</players>

```

HTML Code:

```

<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width,
initial-scale=1.0" />
    <title>Player Details</title>
    <script>
      function getPlayerDetails() {
        let playerName =
document.getElementById("playerSelect").value;
        let xhr = new XMLHttpRequest();
        xhr.open("GET", "exp5.xml", true);
        xhr.onreadystatechange = function () {
          if (xhr.readyState == 4 && xhr.status == 200) {
            let xmlDoc = xhr.responseXML;
            let players = xmlDoc.getElementsByTagName("player");
            let output = "Player not found";

            for (let i = 0; i < players.length; i++) {
              let name =
players[i].getElementsByTagName("name")[0].textContent;

```

```

        if (name === playerName) {
            let country =
                players[i].getElementsByTagName("country")[0].textContent;
            let wickets =
                players[i].getElementsByTagName("wickets")[0].textContent;
            let runs =
                players[i].getElementsByTagName("runs")[0].textContent;

            output = `Name:</strong> ${name} <br>
                        <strong>Country:</strong> ${country}
<br>
                        <strong>Wickets:</strong> ${wickets}
<br>
                        <strong>Runs:</strong> ${runs}`;

            break;
        }
    }
    document.getElementById("playerDetails").innerHTML
= output;
    }
    };
    xhr.send();
}
</script>
</head>
<body>
    <h2>Select a Player</h2>

```

```
<select id="playerSelect" onchange="getPlayerDetails()">
  <option value="">--Select a Player--</option>
  <option value="Virat Kohli">Virat Kohli</option>
  <option value="Joe Root">Joe Root</option>
  <option value="Steve Smith">Steve Smith</option>
  <option value="Babar Azam">Babar Azam</option>
</select>

<h3>Player Details:</h3>
<div id="playerDetails">Select a player to view
details.</div>
</body>
</html>
```

Output:

Select a Player

--Select a Player-- ▾

--Select a Player--

Virat Kohli

Joe Root

Steve Smith

Babar Azam

ew details.

Select a Player

Virat Kohli ▾

Player Details:

Name: Virat Kohli

Country: India

Wickets: 4

Runs: 12000

Experiment 6:

Objective

Write an AJAX request to a URL that does not exist. Implement error handling to display a user-friendly message when the request fails.

HTML Code:

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width,
initial-scale=1.0" />
    <title>AJAX Error Handling</title>
    <script src="https://code.jquery.com/jquery-
3.6.0.min.js"></script>
  </head>
  <body>
    <button id="fetchData">Fetch Data</button>
    <p id="message"></p>

    <script>
      $(document).ready(function () {
        $("#fetchData").click(function () {
          $.ajax({
            url: "non_existing_url.php", // This URL does not exist
            type: "GET",
            success: function (response) {
              $("#message").text("Data fetched successfully!");
            },

```

```
error: function (xhr, status, error) {  
    $("#message").text(  
        "Error: Unable to fetch data. Please try again later."  
    );  
    console.log ("AJAX Error:", status, error); // Log details  
for debugging  
    },  
    });  
});  
});  
</script>  
</body>  
</html>
```

Output:

Fetch Data

Error: Unable to fetch data. Please try again later.

Experiment 7:

Objective

Write a jQuery code to select values from a JSON object. Also, write a jQuery code to remove all CSS classes from an application.

HTML Code:

```
<!DOCTYPE html>
<html>
  <head>
    <title>jQuery JSON Selector & Class Remover</title>
    <style>
      body {
        font-family: Arial, sans-serif;
        background-color: #f0f0f0;
        padding: 20px;
      }

      .container {
        background-color: white;
        border: 2px solid #ccc;
        padding: 20px;
        border-radius: 8px;
        box-shadow: 2px 2px 10px rgba(0, 0, 0, 0.1);
      }

      .header {
        font-size: 24px;
        font-weight: bold;
        color: #333;
      }
```

```
}
```

```
.user-info {  
  margin-top: 15px;  
  padding: 10px;  
  background-color: #e6f7ff;  
  border-left: 5px solid #1890ff;  
}
```

```
.highlight {  
  color: #d32f2f;  
  font-style: italic;  
}
```

```
.footer {  
  margin-top: 20px;  
  font-size: 14px;  
  color: #777;  
}
```

```
.button {  
  padding: 8px 16px;  
  background-color: #4caf50;  
  color: white;  
  border: none;  
  cursor: pointer;  
  margin-top: 10px;  
}
```

```
.button:hover {
```

```

        background-color: #45a049;
    }
</style>
<script src="https://code.jquery.com/jquery-
3.6.0.min.js"></script>
</head>
<body>
    <div id="app" class="container">
        <div class="header">User Profile</div>

        <div class="user-info">
            <p class="highlight">Name: <span id="user-
name"></span></p>
            <p>Age: <span id="user-age"></span></p>
            <p>City: <span id="user-city"></span></p>
        </div>

        <div class="footer">
            This is a demo of jQuery operations on JSON and CSS
            classes.
        </div>
    </div>

    <script>
    $(document).ready(function () {
        // JSON Object
        var jsonObj = {
            name: "Alice Johnson",
            age: 28,
            city: "Los Angeles",

```

```
};

// Extract values
var name = jsonObj.name;
var age = jsonObj.age;
var city = jsonObj.city;

// Log values
console.log("Name:", name);
console.log("Age:", age);
console.log("City:", city);

// Display values on the page
$("#user-name").text(name);
$("#user-age").text(age);
$("#user-city").text(city);

// Remove all CSS classes from elements inside #app on
button click
$("#app *").removeClass();
});
</script>
</body>
</html>
```

Output:

User Profile

Name: Alice Johnson

Age: 28

City: Los Angeles

This is a demo of jQuery operations on JSON and CSS classes.

Experiment 8:

Objective

Create a PHP script that defines variables of different data types (string, integer, float, boolean, array). Output the values and types of these variables using echo and var_dump.

PHP Code:

```
<?php
// String
$name = "John Doe";
echo "Name: " . $name . "<br>";
var_dump($name);
echo "<br><br>";

// Integer
$age = 25;
echo "Age: " . $age . "<br>";
var_dump($age);
echo "<br><br>";

// Float
$height = 5.9;
echo "Height: " . $height . "<br>";
var_dump($height);
echo "<br><br>";

// Boolean
$isStudent = true;
echo "Is Student: " . ($isStudent ? "true" : "false") . "<br>";
var_dump($isStudent);
```

```
echo "<br><br>";
```

```
// Array
```

```
$colors = array("Red", "Green", "Blue");
```

```
echo "Colors: ";
```

```
foreach ($colors as $color) {
```

```
    echo $color . " ";
```

```
}
```

```
echo "<br>";
```

```
var_dump($colors);
```

```
echo "<br><br>";
```

```
?>
```

Output:

Name: John Doe
`string(8) "John Doe"`

Age: 25
`int(25)`

Height: 5.9
`float(5.9)`

Is Student: true
`bool(true)`

Colors: Red Green Blue
`array(3) { [0]=> string(3) "Red" [1]=> string(5) "Green" [2]=> string(4) "Blue" }`

Experiment 9: File Upload Form

Objective: Develop an HTML form to upload a file. Write a PHP script to handle the file upload, save the file on the server, and display a message indicating the file upload status.

PHP Code (exp9.php):

```
<?php
if (isset($_POST['submit'])) {
    // Define target directory
    $targetDir = "uploads/";

    // Create directory if it doesn't exist
    if (!is_dir($targetDir)) {
        mkdir($targetDir, 0755, true);
    }

    $targetFile = $targetDir .
basename($_FILES["uploadedFile"]["name"]);
    $uploadOk = 1;
    $fileType = strtolower(pathinfo($targetFile,
PATHINFO_EXTENSION));

    // Check if file was uploaded without errors
    if ($_FILES["uploadedFile"]["error"] == 0) {
        if
(move_uploaded_file($_FILES["uploadedFile"]["tmp_name"],
$targetFile)) {
            echo "The file <strong>" .
htmlspecialchars(basename($_FILES["uploadedFile"]["name"]))
) . "</strong> has been uploaded successfully.";
        }
    }
}
```

```

    } else {
        echo "Sorry, there was an error uploading your file.";
    }
} else {
    echo "Error: " . $_FILES["uploadedFile"]["error"];
}
} else {
    echo "No file was submitted.";
}
?>

```

HTML Code (exp9.html):

```

<!DOCTYPE html>
<html>
  <head>
    <title>File Upload Form</title>
  </head>
  <body>
    <h2>Upload a File</h2>
    <form action="exp9.php" method="post"
    enctype="multipart/form-data">
      <label>Select file to upload:</label><br /><br />
      <input type="file" name="uploadedFile" required /><br
    /><br />
      <input type="submit" name="submit" value="Upload" />
    </form>
  </body> </html>

```

Output:

The file **official_logo-removebg-preview.avif** has been uploaded successfully.

Experiment 10: MySQL Database for User Registration

Objective: Create a MySQL database and table to store user information (name, email). Write a PHP script to connect to the database and insert a new user record. Display a success message upon successful insertion.

PHP Code (exp10.php):

```
<?php
// Database connection variables
$servername = "localhost";
$username = "root"; // Change if your MySQL user is
different
$password = ""; // Change if your MySQL password is set
$dbname = "user_db";

// Create connection
$conn = new mysqli($servername, $username, $password,
$dbname);

// Check connection
if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

// Get user input
$name = $_POST['name'];
$email = $_POST['email'];
```

```
// Prepare SQL statement
$sql = "INSERT INTO users (name, email) VALUES (?, ?)";
$stmt = $conn->prepare($sql);
$stmt->bind_param("ss", $name, $email);

// Execute and check
if ($stmt->execute()) {
    echo "✓ User <strong>$name</strong> registered successfully!";
} else {
    echo "✗ Error: " . $stmt->error;
}

// Close connection
$stmt->close();
$conn->close();
?>
```

SQL Code (Create Database and Table):

```
-- Create the database
CREATE DATABASE user_db;

-- Use the new database
USE user_db;

-- Create a table to store users
CREATE TABLE users (
    id INT AUTO_INCREMENT PRIMARY KEY,
```

```
name VARCHAR(100) NOT NULL,  
email VARCHAR(100) NOT NULL UNIQUE );
```

HTML Code (exp10.html):

```
<!DOCTYPE html>  
<html>  
  <head>  
    <title>User Registration</title>  
  </head>  
  <body>  
    <h2>Register User</h2>  
    <form action="exp10.php" method="post">  
      <label>Name:</label><br />  
      <input type="text" name="name" required /><br /><br />  
  
      <label>Email:</label><br />  
      <input type="email" name="email" required /><br /><br  
</>  
      <input type="submit" value="Register" />  
    </form>  
  </body>  
</html>
```

Output:

Register User

Name:

Email:



User **Noob master** registered successfully!

Experiment 11: Travel Agency Web Page

Objective: Create a web page for a Travel Agency using PHP.

PHP Code (Index Page - index.php):

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width,
initial-scale=1.0">
  <title>Travel Agency</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 0;
      padding: 0;
      background-color: #f4f4f4;
    }
    header {
      background-color: #333;
      color: white;
      text-align: center;
      padding: 1rem;
    }
    nav {
      text-align: center;
      background-color: #444;
      padding: 10px;
    }
```

```
nav a {
    color: white;
    text-decoration: none;
    margin: 0 15px;
}
footer {
    background-color: #333;
    color: white;
    text-align: center;
    padding: 10px;
    position: fixed;
    bottom: 0;
    width: 100%;
}
.main-content {
    padding: 20px;
}
.button {
    background-color: #007BFF;
    color: white;
    padding: 10px 20px;
    text-decoration: none;
    border-radius: 5px;
}
</style>
</head>
<body>
<header>
    <h1>Welcome to Our Travel Agency</h1>
</header>
```

```

<nav>
  <a href="index.php">Home</a>
  <a href="booking.php">Book a Trip</a>
  <a href="contact.php">Contact Us</a>
</nav>

<div class="main-content">
  <h2>Discover Amazing Destinations</h2>
  <p>Explore the world with our top travel packages.</p>
  <a href="booking.php" class="button">Book Your Trip
Now</a>
</div>

<footer>
  <p>&copy; 2025 Travel Agency. All rights reserved. </p>
</footer>
</body>
</html>

```

PHP Code (Booking Page - booking):

```

<?php
if ($_SERVER['REQUEST_METHOD'] == 'POST') {
  $name = $_POST['name'];
  $email = $_POST['email'];
  $destination = $_POST['destination'];
  $start_date = $_POST['start_date'];
  $end_date = $_POST['end_date'];

```

```

// Admin's email address to receive the booking details
$admin_email = "admin@travelagency.com";

// Subject and message for the email
$subject = "New Booking Request";
$message = "You have a new booking request:

";
    $message .= "Name: $name
";
    $message .= "Email: $email
";
    $message .= "Destination: $destination
";
    $message .= "Start Date: $start_date
";
    $message .= "End Date: $end_date
";

// Send the email
if (mail($admin_email, $subject, $message)) {
    $response = "✓ Your booking has been successfully
submitted!";
} else {
    $response = "✗ There was an error while processing your
booking.";
}
}
?>

```

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width,
initial-scale=1.0">
  <title>Book a Trip - Travel Agency</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 0;
      padding: 0;
      background-color: #f4f4f4;
    }
    header {
      background-color: #333;
      color: white;
      text-align: center;
      padding: 1rem;
    }
    nav {
      text-align: center;
      background-color: #444;
      padding: 10px;
    }
    nav a {
      color: white;
      text-decoration: none;
      margin: 0 15px;
```

```
}  
.main-content {  
  padding: 20px;  
}  
.form-container {  
  background-color: #fff;  
  padding: 20px;  
  border-radius: 5px;  
  box-shadow: 0 2px 5px rgba(0,0,0,0.1);  
  max-width: 500px;  
  margin: auto;  
}  
input[type="text"], input[type="email"],  
input[type="date"], select {  
  width: 100%;  
  padding: 10px;  
  margin-bottom: 15px;  
  border: 1px solid #ccc;  
  border-radius: 5px;  
}  
input[type="submit"] {  
  background-color: #007BFF;  
  color: white;  
  padding: 10px 20px;  
  border: none;  
  border-radius: 5px;  
}  
footer {  
  background-color: #333;  
  color: white;
```

```

        text-align: center;
        padding: 10px;
        position: fixed;
        bottom: 0;
        width: 100%;
    }
</style>
</head>
<body>
    <header>
        <h1>Book a Trip with Us</h1>
    </header>

    <nav>
        <a href="index.php">Home</a>
        <a href="booking.php">Book a Trip</a>
        <a href="contact.php">Contact Us</a>
    </nav>

    <div class="main-content">
        <div class="form-container">
            <h2>Fill in Your Booking Details</h2>
            <?php if (isset($response)) { echo
"<p>$response</p>"; } ?>
            <form method="POST" action="booking.php">
                <input type="text" name="name" placeholder="Your
Name" required>
                <input type="email" name="email" placeholder="Your
Email" required>
                <select name="destination" required>

```

```
        <option value="" disabled selected>Select
Destination</option>
        <option value="Paris">Paris</option>
        <option value="New York">New York</option>
        <option value="Tokyo">Tokyo</option>
        <option value="London">London</option>
        <option value="Sydney">Sydney</option>
        <option value="Dubai">Dubai</option>
    </select>
    <input type="date" name="start_date" required>
    <input type="date" name="end_date" required>
    <input type="submit" value="Submit Booking">
</form>
</div>
</div>

<footer>
    <p>&copy; 2025 Travel Agency. All rights reserved. </p>
</footer>
</body>
</html>
```

Output:

