Create and insert (Appendix C.2) Following C.2’s example, create a customers table with at least four columns (id, name, city, and one numeric column) using a SQL CREATE TABLE statement, then INSERT at least eight fictional rows. MySQL’s types map to SQLite almost directly: use INTEGER, TEXT, REAL. Deliverable: the CREATE and INSERT statements running via con.execute(), and a SELECT * proving the rows exist.

In [1]:
```
import sqlite3
import pandas as pd

con = sqlite3.connect('lab2.db')
cursor = con.cursor()

cursor.execute("DROP TABLE IF EXISTS customers;")

cursor.execute("""
CREATE TABLE customers (
    id INTEGER PRIMARY KEY,
    name TEXT,
    city TEXT,
    loyalty_score REAL
);
""")

fictional_customers = [
    (1, 'Caleb Hearon', 'Los Angeles', 4.8),
    (2, 'Michael Showalter', 'Santa Monica', 3.5),
    (3, 'Tim Robinson', 'San Francisco', 4.2),
    (4, 'Sam Richardson', 'Seattle', 4.9),
    (5, 'Evan Wright', 'Austin', 2.7),
    (6, 'Seth Rogen', 'Chicago', 3.9),
    (7, 'George Miller', 'New York', 4.1),
    (8, 'Jennifer Connolley', 'Boston', 4.6)
]

cursor.executemany("""
INSERT INTO customers (id, name, city, loyalty_score)
VALUES (?, ?, ?, ?);
""", fictional_customers)

con.commit()

df_lab2 = pd.read_sql("SELECT * FROM customers;", con)
df_lab2
```

Out[1]: <style scoped> .dataframe tbody tr th:only-of-type { vertical-align: middle; } .dataframe tbody tr th { vertical-align: top; } .dataframe thead th { text-align: right; } </style> <thead> <th> </th> <th>id</th> <th>name</th> <th>city</th> <th>loyalty_score</th> </thead> <tbody> <th>0</th> <th>1</th> <th>2</th> <th>3</th> <th>4</th> <th>5</th> <th>6</th> <th>7</th> </tbody> <tbody></tbody>

1	Caleb Hearon	Los Angeles	4.8
2	Michael Showalter	Santa Monica	3.5
3	Tim Robinson	San Francisco	4.2
4	Sam Richardson	Seattle	4.9
5	Evan Wright	Austin	2.7
6	Seth Rogen	Chicago	3.9
7	George Miller	New York	4.1
8	Jennifer Connolley	Boston	4.6