


Deferred Loading of Types

Ross Tate

Motivation



Scope

- Deferred loading of
 - Functionality (e.g. function definitions)
 - Data (and initialization)
 - Accessors (e.g. field offsets)
 - Types (e.g. struct definitions) ← today's focus

Example

```
package early;  
import later.Bar;
```

```
public class Foo {  
    private Bar b;  
    public Foo() { b = null; }  
    public Bar getb() { return this.b; }  
    public void setb(Bar b) { this.b = b; }  
}
```

- Desire
 - Load Foo early
 - Load Bar later
- Challenge
 - Definition of Foo's type uses Bar's type
- Observation
 - Foo's code does not use Bar's type's definition
 - Foo's code preserves Bar's invariants

Compilation

```
package early;
import later.Bar;

public class Foo {
    private Bar b;
    public Foo() { b = null; }
    public Bar getb() { return this.b; }
    public void setb(Bar b) { this.b = b; }
}
```

```
(module $Foo
  (type $Bar (import "later" "Bar"))
  (type $Foo (struct
    (field $vtable (ref $FooVTable))
    (field $b (mut (ref null $Bar)))
  ))
  (type $FooVTable (struct
    (field $getb (func (param $this (ref $Foo)) (result (ref null $Bar))))
    (field $setb (func (param $this (ref $Foo)) (param $b (ref null $Bar))))
  ))
  (func (export "__new_Foo") (result (ref $Foo)) (struct.new $Foo (global.get $__Foo_vtable) (ref.null $Bar)))
  (func $Foo.getb (param $this (ref $Foo)) (result (ref null $Bar)) (struct.get $b (local.get $this)))
  (func $Foo.setb (param $this (ref $Foo)) (param $b (ref null $Bar)) (struct.set $b (local.get $this) (local.get $b)))
  (global $__Foo_vtable (ref $FooVTable) (struct.new $FooVTable (ref.func $Foo.getb) (ref.func $Foo.setb)))
  ... ;; exports of the relevant field references for the methods $getb and $setb
)
```

Seems to require later.Bar to be loaded

Solution

- Separate type “declaration” and type “definition”
- (declare-type \$Bar)
 - Creates a new type \$Bar but does not define it
- (define-type \$Bar t)
 - Defines declared-but-not-yet-defined \$Bar to be type t
- Sound provided every declare-type has at most one define-type
- Loader can declare types for use by “early” modules
 - And “later” modules can establish their definitions when loaded
- Can we compile “early” and “later” modules in the same manner?

Compilation, Revised

```
package early;

import later.Bar;

public class Foo {
    private Bar b;

    public Foo() { b = null; }

    public Bar getb() { return this.b; }

    public void setb(Bar b) { this.b = b; }
}
```

Only change

Early Loading and Static Linking:

```
(module $__glue
  (declare-type $Foo)
  (declare-type $Bar)
  (instance $Foo (import "later" "Bar" (type $Bar))
                (import "early" "Foo" (type $Foo)))
  (instance $Bar (import "later" "Bar" (type $Bar)))
  ...
)
```

```
(module $Foo
  (type $Bar (import "later" "Bar"))
  (define-type $Foo (import "early" "Foo") (struct
    (field $vtable (ref $FooVTable))
    (field $b (mut (ref null $Bar)))
  ))
  (type $FooVTable (struct
    (field $getb (func (param $this (ref $Foo)) (result (ref null $Bar))))
    (field $setb (func (param $this (ref $Foo)) (param $b (ref null $Bar))))
  ))
  (func (export "__new_Foo") (result (ref $Foo)) (struct.new $Foo (global.get $__Foo_vtable) (ref.null $Bar)))
  (func $Foo.getb (param $this (ref $Foo)) (result (ref null $Bar)) (struct.get $b (local.get $this)))
  (func $Foo.setb (param $this (ref $Foo)) (param $b (ref null $Bar)) (struct.set $b (local.get $this) (local.get $b)))
  (global $__Foo_vtable (ref $FooVTable) (struct.new $FooVTable (ref.func $Foo.getb) (ref.func $Foo.setb)))
  ... ;; exports of the relevant field references for the methods $getb and $setb
)
```


Bonus: Mutual Recursion (without Inversion)

```
package later;
import early.Foo;

public class Bar {
    private Foo f;
    public Bar() { f = null; }
    public Foo getf() { return this.f; }
    public void setf(Foo f) { this.f = f; }
}
```

Same as Foo
(modulo renaming)

Early Loading and Static Linking:

```
(module $__glue
  (declare-type $Foo)
  (declare-type $Bar)
  (instance $Foo (import "later" "Bar" (type $Bar))
                (import "early" "Foo" (type $Foo)))
  (instance $Bar (import "early" "Foo" (type $Foo))
                (import "later" "Bar" (type $Bar)))
  ...)
```

```
(module $Bar
  (type $Foo (import "early" "Foo"))
  (define-type $Bar (import "later" "Bar")) (struct
    (field $vtable (ref $BarVTable))
    (field $f (mut (ref null $Foo)))
  ))
  (type $BarVTable (struct
    (field $getf (func (param $this (ref $Bar)) (result (ref null $Foo))))
    (field $setf (func (param $this (ref $Bar)) (param $f (ref null $Foo))))
  ))
  (func (export "__new_Bar") (result (ref $Bar)) (struct.new $Bar (global.get $__Bar_vtable) (ref.null $Foo)))
  (func $Bar.getf (param $this (ref $Bar)) (result (ref null $Foo)) (struct.get $f (local.get $this)))
  (func $Bar.setf (param $this (ref $Bar)) (param $f (ref null $Foo)) (struct.set $f (local.get $this) (local.get $f)))
  (global $__Bar_vtable (ref $BarVTable) (struct.new $BarVTable (ref.func $Bar.getf) (ref.func $Bar.setf)))
  ... ;; exports of the relevant field references for the methods $getf and $setf
)
```