

# Rajalakshmi Engineering College

Name: ROSSHNI PL  
Email: 240801279@rajalakshmi.edu.in  
Roll no: 240801279  
Phone: 9150237513  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 15

#### Section 1 : MCQ

1. Which of the following operations can be used to traverse a Binary Search Tree (BST) in ascending order?

**Answer**

Inorder traversal

**Status : Correct**

**Marks : 1/1**

2. Find the in-order traversal of the given binary search tree.

**Answer**

1, 2, 4, 13, 14, 18

**Status : Correct**

**Marks : 1/1**

3. The preorder traversal of a binary search tree is 15, 10, 12, 11, 20, 18, 16, 19. Which one of the following is the postorder traversal of the tree?

**Answer**

11, 12, 10, 16, 19, 18, 20, 15

**Status :** Correct

**Marks :** 1/1

4. Which of the following is the correct post-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

**Answer**

20, 32, 30, 52, 57, 55, 50

**Status :** Correct

**Marks :** 1/1

5. Which of the following is the correct pre-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

**Answer**

50, 30, 20, 32, 55, 52, 57

**Status :** Correct

**Marks :** 1/1

6. Find the pre-order traversal of the given binary search tree.

**Answer**

13, 2, 1, 4, 14, 18

**Status :** Correct

**Marks :** 1/1

7. Which of the following is the correct in-order traversal of a binary search tree with nodes: 9, 3, 5, 11, 8, 4, 2?

**Answer**

2, 3, 4, 5, 8, 9, 11

**Status :** Correct

**Marks :** 1/1

8. Find the post-order traversal of the given binary search tree.

**Answer**

10, 17, 20, 18, 15, 32, 21

**Status :** Correct

**Marks :** 1/1

9. While inserting the elements 5, 4, 2, 8, 7, 10, 12 in a binary search tree, the element at the lowest level is \_\_\_\_\_.

**Answer**

12

**Status :** Correct

**Marks :** 1/1

10. In a binary search tree with nodes 18, 28, 12, 11, 16, 14, 17, what is the value of the left child of the node 16?

**Answer**

14

**Status :** Correct

**Marks :** 1/1

11. Find the postorder traversal of the given binary search tree.

**Answer**

1, 4, 2, 18, 14, 13

**Status :** Correct

**Marks :** 1/1

12. While inserting the elements 71, 65, 84, 69, 67, 83 in an empty binary search tree (BST) in the sequence shown, the element in the lowest level is \_\_\_\_\_.

**Answer**

67

**Status :** Correct

**Marks :** 1/1

13. Which of the following is a valid preorder traversal of the binary search tree with nodes: 18, 28, 12, 11, 16, 14, 17?

**Answer**

18, 12, 11, 16, 14, 17, 28

**Status :** Correct

**Marks :** 1/1

14. How many distinct binary search trees can be created out of 4 distinct keys?

**Answer**

14

**Status :** Correct

**Marks :** 1/1

15. Find the preorder traversal of the given binary search tree.

**Answer**

9, 2, 1, 6, 4, 7, 10, 14

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: ROSSHNI PL  
Email: 240801279@rajalakshmi.edu.in  
Roll no: 240801279  
Phone: 9150237513  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Imagine you are tasked with developing a simple GPA management system using a singly linked list. The system allows users to input student GPA values, insertion should happen at the front of the linked list, delete record by position, and display the updated list of student GPAs.

##### ***Input Format***

The first line of input contains an integer  $n$ , representing the number of students.

The next  $n$  lines contain a single floating-point value representing the GPA of each student.

The last line contains an integer position, indicating the position at which a student record should be deleted. Position starts from 1.

### **Output Format**

After deleting the data in the given position, display the output in the format "GPA: " followed by the GPA value, rounded off to one decimal place.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 4

3.8

3.2

3.5

4.1

2

Output: GPA: 4.1

GPA: 3.2

GPA: 3.8

### **Answer**

```
// You are using GCC
```

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
typedef struct gpa{
```

```
    float value;
```

```
    struct gpa*next;
```

```
}Node;
```

```
Node*newnode(float value){
```

```
    Node*newgpa=(Node*)malloc(sizeof(Node));
```

```
    newgpa->value=value;
```

```
    newgpa->next=NULL;
```

```
    return newgpa;
```

```
}
```

```
Node*insertAtStart(Node*head,float value){
```

```
    Node*newgpa=newnode(value);
```

```
    newgpa->next=head;
```

```
    return newgpa;
```

```
}
```

```

void traverse(Node*head){
    while(head!=NULL){
        printf("GPA: %.1f\n",head->value);
        head=head->next;
    }
}

void deleteAtPosition(Node**head,int pos){
    pos-=1;
    Node*temp=*head;
    if(pos==0){
        *head=temp->next;
        free(temp);
        return;
    }
    while(--pos){
        temp=temp->next;
    }
    Node*temp1=temp->next;
    temp->next=temp->next->next;
    free(temp1);
}

int main()
{
    int n,pos;
    float value;
    scanf("%d",&n);
    Node*head=NULL;
    for(int i=0;i<n;i++){
        scanf("%f",&value);
        head=insertAtStart(head,value);
    }
    scanf("%d",&pos);
    deleteAtPosition(&head,pos);
    traverse(head);
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: ROSSHNI PL  
Email: 240801279@rajalakshmi.edu.in  
Roll no: 240801279  
Phone: 9150237513  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

John is learning about Binary Search Trees (BST) in his computer science class. He wants to create a program that allows users to delete a node with a given value from a BST and print the remaining nodes using an in-order traversal.

Implement a function to help him delete a node with a given value from a BST.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the BST nodes.



The third line consists of an integer V, which is the value to delete from the BST.

### **Output Format**

The output prints the space-separated values in the BST in an in-order traversal, after the deletion of the specified value.

If the specified value is not available in the tree, print the given input values in-order traversal.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5  
10 5 15 2 7  
15

Output: 2 5 7 10

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};
```

```
struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
// You are using GCC
```

```
struct TreeNode* insert(struct TreeNode* root, int key) {
    if(root==NULL){
```

```

        return createNode(key);
    }
    else if(key<root->data){
        root->left=insert(root->left,key);
    }
    else if(key>root->data){
        root->right=insert(root->right,key);
    }
    return root;
}

```

```

struct TreeNode* findMin(struct TreeNode* root) {
    //Type your code here
    if(root->left==NULL) return root;
    findMin(root);
}

```

```

struct TreeNode* deleteNode(struct TreeNode* root, int key) {
    //Type your code
    if(root==NULL) return NULL;
    if(key<root->data){
        root->left=deleteNode(root->left,key);
    }
    else if(key>root->data){
        root->right=deleteNode(root->right,key);
    }
    else{
        if(root->left&&root->right){
            struct TreeNode* temp=findMin(root->right);
            root->data=temp->data;
            root->right=deleteNode(root->right,temp->data);
        }
        else{
            struct TreeNode* temp=root;
            if(root->left==NULL){
                root=root->right;
            }
            else{
                root=root->left;
            }
            free(temp);
        }
    }
}

```

```

    }
    return root;
}

void inorderTraversal(struct TreeNode* root) {
    //Type your code here
    if(root==NULL) return;
    inorderTraversal(root->left);
    printf("%d ",root->data);
    inorderTraversal(root->right);
}

int main()
{
    int N, rootValue, V;
    scanf("%d", &N);
    struct TreeNode* root = NULL;
    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }
    scanf("%d", &V);
    root = deleteNode(root, V);
    inorderTraversal(root);
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: ROSSHNI PL  
Email: 240801279@rajalakshmi.edu.in  
Roll no: 240801279  
Phone: 9150237513  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Mike is learning about Binary Search Trees (BSTs) and wants to implement various operations on them. He wants to write a basic program for creating a BST, inserting nodes, and printing the tree in the pre-order traversal.

Write a program to help him solve this program.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of values to insert into the BST.

The second line consists of N space-separated integers, representing the values to insert into the BST.

##### ***Output Format***

The output prints the space-separated values of the BST in the pre-order traversal.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

3 1 5 2 4

Output: 3 1 2 5 4

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* left;
    struct Node* right;
};
```

```
struct Node* createNode(int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = value;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
// You are using GCC
```

```
// You are using GCC
```

```
struct Node* insert(struct Node* root, int key) {
    //Type your code here
    if(root==NULL) return createNode(key);
    if(key<root->data){
        root->left=insert(root->left,key);
    }
    else if(key>root->data){
        root->right=insert(root->right,key);
    }
    return root;
}
```

```
}
```

```
void printPreorder(struct Node* node) {
```

```
    if(node==NULL) return;  
    printf("%d ",node->data);  
    printPreorder(node->left);
```

```
    printPreorder(node->right);
```

```
}
```

```
int main() {
```

```
    struct Node* root = NULL;
```

```
    int n;  
    scanf("%d", &n);
```

```
    for (int i = 0; i < n; i++) {  
        int value;  
        scanf("%d", &value);  
        root = insert(root, value);  
    }
```

```
    printPreorder(root);  
    return 0;
```

```
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: ROSSHNI PL  
Email: 240801279@rajalakshmi.edu.in  
Roll no: 240801279  
Phone: 9150237513  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are required to implement basic operations on a Binary Search Tree (BST), like insertion and searching.

Insertion: Given a list of integers, construct a Binary Search Tree by repeatedly inserting each integer into the tree according to the rules of a BST.

Searching: Given an integer, search for its presence in the constructed Binary Search Tree. Print whether the integer is found or not.

Write a program to calculate this efficiently.

##### ***Input Format***

The first line of input consists of an integer n, representing the number of nodes

in the binary search tree.

The second line consists of the values of the nodes, separated by space as integers.

The third line consists of an integer representing, the value that is to be searched.

### **Output Format**

The output prints, "Value <value> is found in the tree." if the given value is present, otherwise it prints: "Value <value> is not found in the tree."

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 7

8 3 10 1 6 14 23

6

Output: Value 6 is found in the tree.

### **Answer**

```
struct Node* insertNode(struct Node* root, int value) {
    if (root == NULL) {
        return createNode(value);
    }
    if (value < root->data) {
        root->left = insertNode(root->left, value);
    } else if (value > root->data) {
        root->right = insertNode(root->right, value);
    }
    return root;
}
```

```
struct Node* searchNode(struct Node* root, int value) {
    if (root == NULL || root->data == value) {
        return root;
    }
    if (value < root->data) {
        return searchNode(root->left, value);
    } else {

```



```
    return searchNode(root->right, value);  
  }  
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: ROSSHNI PL  
Email: 240801279@rajalakshmi.edu.in  
Roll no: 240801279  
Phone: 9150237513  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

John, a computer science student, is learning about binary search trees (BST) and their properties. He decides to write a program to create a BST, display it in post-order traversal, and find the minimum value present in the tree.

Help him by implementing the program.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of elements to insert into the BST.

The second line consists of N space-separated integers data, which is the data to be inserted into the BST.

### **Output Format**

The first line of output prints the space-separated elements of the BST in post-order traversal.

The second line prints the minimum value found in the BST.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

5 10 15

Output: 15 10 5

The minimum value in the BST is: 5

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* left;  
    struct Node* right;  
};
```

```
struct Node* createNode(int data) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = data;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
// You are using GCC
```

```
struct Node* insert(struct Node* root, int data) {  
    //Type your code here  
    if(root==NULL){  
        return createNode(data);  
    }  
    if(data<root->data){  
        root->left=insert(root->left,data);  
    }
```

```

    }
    else if(data>root->data){
        root->right=insert(root->right,data);
    }
    return root;
}

void displayTreePostOrder(struct Node* root) {
    if(root==NULL) return ;
    displayTreePostOrder(root->left);
    displayTreePostOrder(root->right);
    printf("%d ",root->data);
}

int findMinValue(struct Node* root) {
    //Type your code here
    if(root->left==NULL){
        return root->data;
    }
    return findMinValue(root->left);
}

int main() {
    struct Node* root = NULL;
    int n, data;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        scanf("%d", &data);
        root = insert(root, data);
    }

    displayTreePostOrder(root);
    printf("\n");

    int minValue = findMinValue(root);
    printf("The minimum value in the BST is: %d", minValue);

    return 0;
}

```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: ROSSHNI PL  
Email: 240801279@rajalakshmi.edu.in  
Roll no: 240801279  
Phone: 9150237513  
Branch: REC  
Department: I ECE AF  
Batch: 2028  
Degree: B.E - ECE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In his computer science class, John is learning about Binary Search Trees (BST). He wants to build a BST and find the maximum value in the tree.

Help him by writing a program to insert nodes into a BST and find the maximum value in the tree.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the nodes to insert into the BST.

##### ***Output Format***

The output prints the maximum value in the BST.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

10 5 15 2 7

Output: 15

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};
```

```
struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
// You are using GCC
```

```
struct TreeNode* insert(struct TreeNode* root, int key) {
    //Type your code here
    if(root==NULL) return createNode(key);
    if(key<root->data){
        root->left=insert(root->left,key);
    }
    else if(key>root->data){
        root->right=insert(root->right,key);
    }
    return root;
}
```

```
int findMax(struct TreeNode* root) {
    //Type your code here
    if(root==NULL) return NULL;
    if(root->right==NULL){
        return root->data;
    }
    return findMax(root->right);
}

int main() {
    int N, rootValue;
    scanf("%d", &N);

    struct TreeNode* root = NULL;

    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }

    int maxVal = findMax(root);
    if (maxVal != -1) {
        printf("%d", maxVal);
    }

    return 0;
}
```

**Status :** Correct

**Marks :** 10/10