Two Clocks — liga de fotbal fictivă
12 tabele: 6 ancore + 3 versiuni + 3 tehnice

Legendă: PK = cheie primară; FK = cheie externă; UQ = unicitate
Capăt || = exact 1; cerc + crow foot = 0..N; cerc + bară = 0..1
Toate coloanele NOT NULL; FK: ON DELETE/UPDATE RESTRICT
Versiuni: VT și TT [from,to); tx_id se referă la registru
season și query_params nu au FK; cardinalitățile nu exprimă integritatea intervalelor

6 ancore de domeniu — non-temporal

season
non-temporal

season_id	BIGINT UNSIGNED	PK
season_name	VARCHAR(32)	UQ
period_start	DATE	
period_end	DATE	

player
non-temporal

player_id	BIGINT UNSIGNED	PK
player_code	VARCHAR(32)	UQ
full_name	VARCHAR(120)	
birth_date	DATE	

club
non-temporal

club_id	BIGINT UNSIGNED	PK
club_code	VARCHAR(32)	UQ

coach
non-temporal

coach_id	BIGINT UNSIGNED	PK
coach_code	VARCHAR(32)	UQ
full_name	VARCHAR(120)	
birth_date	DATE	

contract
non-temporal

contract_id	BIGINT UNSIGNED	PK
player_id	BIGINT UNSIGNED	FK
club_id	BIGINT UNSIGNED	FK

UQ(player_id, club_id)

head_coach_role
non-temporal

role_id	BIGINT UNSIGNED	PK
club_id	BIGINT UNSIGNED	FK

UQ(club_id)

3 tabele de versiuni — bitemporal (VT + TT)

contract_version
bitemporal

version_id	BIGINT UNSIGNED	PK
contract_id	BIGINT UNSIGNED	FK
agreement_kind	VARCHAR(9)	
salary_eur	DECIMAL(12,2)	
valid_from	DATE	
valid_to	DATE	
tx_from	DATETIME(6)	
tx_to	DATETIME(6)	
tx_id	BIGINT UNSIGNED	FK

head_coach_role_version
bitemporal

version_id	BIGINT UNSIGNED	PK
role_id	BIGINT UNSIGNED	FK
coach_id	BIGINT UNSIGNED	FK
valid_from	DATE	
valid_to	DATE	
tx_from	DATETIME(6)	
tx_to	DATETIME(6)	
tx_id	BIGINT UNSIGNED	FK

club_version
bitemporal

version_id	BIGINT UNSIGNED	PK
club_id	BIGINT UNSIGNED	FK
club_name	VARCHAR(120)	
budget_eur	DECIMAL(14,2)	
valid_from	DATE	
valid_to	DATE	
tx_from	DATETIME(6)	
tx_to	DATETIME(6)	
tx_id	BIGINT UNSIGNED	FK

3 auxiliare tehnice — non-temporal

query_params
non-temporal

params_id	TINYINT UNSIGNED	PK
valid_at	DATE	
known_at	DATETIME(6)	
period_start	DATE	
period_end	DATE	
subject_id	BIGINT UNSIGNED	

params_id = 1; subject_id fără FK

tx_registry
non-temporal

tx_id	BIGINT UNSIGNED	PK
tx_time	DATETIME(6)	
author	VARCHAR(128)	
reason	TEXT	

tx_event_tag
non-temporal

tx_id	BIGINT UNSIGNED	PK / FK
event_code	CHAR(2)	PK

PK(tx_id, event_code); E1…E9