

Lecture 7: Model Selection

Instructor: Naveen N. Narisetty

Scribe: Yutong Dai

Last Modified: 2018-05-07

Disclaimer: *These notes have not been subjected to the usual scrutiny reserved for formal publications, and they may contain factual and/or typographic errors.*

7.1 Criteria: AIC

Goal: Find the model that gives the best prediction without assuming the any candidate model is correct.

Setup: Suppose $x_i \stackrel{iid}{\sim} f_\theta$ and the candidate set is $\mathcal{M} = \{M_j | j = 1, 2, \dots, n\}$ where $M_j = \{p_{\theta_j}(x); \theta_j \in \Theta_j\}$. We want to minimize the loss

$$\min_j KL(f_\theta || p_{\hat{\theta}_j}) = \int (f_\theta \log f_\theta - f_\theta \log p_{\hat{\theta}_j}) d\theta,$$

where $p_{\hat{\theta}_j}$ is an estimate of p_{θ_j} ($p_{\hat{\theta}_j} = p_{\hat{\theta}_j}$). This is equivalent to

$$\min_j - \int f_\theta \log p_{\hat{\theta}_j} d\theta.$$

A good estimator of $\int f_\theta \log p_{\hat{\theta}_j} d\theta$ is

$$\bar{K}_j = \frac{1}{n} \sum_i \log p_{\hat{\theta}_j}.$$

7.2 Criteria: BIC