Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the append method.

Absolutely, Routh Kiran Babu! Let's break down the **append()** method in Python like a pro problem solver and Python expert. I'll keep it simple, detailed, and engaging with real-world-style examples.

## Definition of append() in Python

The append() method is used to **add a single element** to the **end** of a list. It modifies the original list **in place** and **does not return a new list**.

## Syntax

python CopyEdit

list\_name.append(element)

## Parameter

#### Parameter Description

element The item to be added at the end of the list.

The element can be of **any data type** — string, integer, float, list, tuple, dictionary, etc.

• If you append a **list**, it becomes a **nested list** (a list inside a list).

### Return Value

- Returns: None
- The list is modified in place.

## Examples with Creative Use Cases

## ✓ Example 1: Append student names to a class list

```
python
CopyEdit
class_students = ['Ravi', 'Anu']
class_students.append('Kiran')
print(class_students) # ['Ravi', 'Anu', 'Kiran']
```

## **Example 2: Append a number to a list of scores**

```
python
CopyEdit
scores = [80, 90]
scores.append(95)
print(scores) # [80, 90, 95]
```

## Example 3: Appending a list (Nested list)

```
python
CopyEdit
tools = ['Hammer', 'Wrench']
tools.append(['Screwdriver', 'Pliers'])
print(tools)
# Output: ['Hammer', 'Wrench', ['Screwdriver', 'Pliers']]
```

## Creative Real-world Use Cases

## ✓ Use Case 1: Building a dynamic to-do list from user input

```
python
CopyEdit
todo_list = []
todo_list.append("Write Cypress test case")
todo_list.append("Edit YouTube video")
todo_list.append("Practice Python array methods")
print(todo_list)
```

## 🏆 Use Case 2: Logging scores in a game

```
python
CopyEdit
game_scores = []
for round in range(3):
    score = (round + 1) * 10 # Dynamic score generation
    game_scores.append(score)
print(game_scores) # [10, 20, 30]
```

## William Use Case 3: Appending dictionaries for JSON-style data

```
python
CopyEdit
students = []
students.append({"name": "Routh", "score": 98})
students.append({"name": "Anu", "score": 91})
print(students)
# [{'name': 'Routh', 'score': 98}, {'name': 'Anu', 'score': 91}]
```

## Use Case 4: Appending functions or objects

python CopyEdit

```
def greet():
    return "Hello!"

items = []
items.append(greet)
print(items[0]()) # Output: Hello!
```

## Quick Recap

Feature Behavior

Type List method

Action Adds **one item** at the **end** 

Accepts Any data type as element

Return None

Creates nested V

list?

If you append another list

Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the extend() method.

Absolutely! Let's break down the extend() method in Python like an expert and problem solver, in a way that's beginner-friendly but deeply informative.

Method: list.extend()



The extend() method adds all elements of an iterable (e.g., list, tuple, set, string) to the end of the current list. It modifies the original list in-place and does not return a new list.

## Syntax:

python CopyEdit

list1.extend(iterable)

#### Parameters:

- **iterable**: Any iterable object (like list, tuple, set, string, dictionary, or even a generator) whose elements will be added to the list.
  - If a dictionary is passed, only the keys are added.

### Return Value:

Returns None — the original list is updated directly.

## 

Let's look at unique and creative examples so you fully **understand how extend() works** with different types of iterables:

## **Example 1: Extending a list of tasks with new tasks**

python CopyEdit

```
daily_tasks = ["Wake up", "Exercise", "Read"]
new_tasks = ["Code", "Cook", "Study"]
daily_tasks.extend(new_tasks)
```

```
print(daily_tasks)
# Output: ['Wake up', 'Exercise', 'Read', 'Code', 'Cook', 'Study']
```

Real-Life Use: You maintain a to-do list and want to add more tasks from another source.

## **Example 2: Extending with a string (each character gets added)**

```
python
CopyEdit
```

```
my_list = ["a", "b"]
my_list.extend("xyz")
print(my_list)
# Output: ['a', 'b', 'x', 'y', 'z']
```

*Insight*: Strings are iterables of characters. So each character is added individually.

## **Example 3: Extend using a tuple**

#### python

CopyEdit

```
ingredients = ["flour", "sugar"]
more_ingredients = ("eggs", "milk")
ingredients.extend(more_ingredients)

print(ingredients)
# Output: ['flour', 'sugar', 'eggs', 'milk']
```

• Real-Life Use: Mixing ingredients from a base recipe with additional ones.

## Example 4: Extend with a dictionary (only keys added)

### python

CopyEdit

```
tech_stack = ["Python", "Java"]
additional = {"JavaScript": 1, "C++": 2}
```

```
tech_stack.extend(additional)
print(tech_stack)
# Output: ['Python', 'Java', 'JavaScript', 'C++']
```

python

Important: Only keys (JavaScript, C++) are added, not values.

## Example 5: Extend using a generator expression

```
python
CopyEdit
nums = [1, 2, 3]
squares = (x**2 \text{ for } x \text{ in range}(4, 7)) # generator: 16, 25, 36
nums.extend(squares)
print(nums)
# Output: [1, 2, 3, 16, 25, 36]
```

Pro-level: You can efficiently add items from a generator to save memory.

## 🮨 Example 6: Extend a playlist of songs with trending ones

```
CopyEdit
playlist = ["Imagine", "Bohemian Rhapsody"]
trending = ["Blinding Lights", "Levitating"]
playlist.extend(trending)
print(playlist)
```

'Levitating']

# Output: ['Imagine', 'Bohemian Rhapsody', 'Blinding Lights',

Real-Life Use: You're managing a playlist and fetching songs from a trending list.

## Difference from append()

```
python
CopyEdit
a = [1, 2]
b = [3, 4]

a.append(b) # [1, 2, [3, 4]]
a = [1, 2]
a.extend(b) # [1, 2, 3, 4]
```

append() adds the whole object as a single element, extend() adds each element individually.

# Summary Table:

Feature extend()

Purpose Add each element of an iterable

Modifies list ✓ Yes (in-place)

Return None

Accepts List, Tuple, Set, String, Generator, Dict (keys only)

Use case Merging or combining lists or iterables

Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the insert method.

Absolutely! Let's dive deep into the insert() method in Python lists — with full definition, syntax, parameter explanation, and creative examples that help you **truly master** it.

## insert() Method in Python

## **Definition:**

The insert() method inserts an element at a specified position in a list. Unlike append() (which adds at the end), insert() gives you **full control** over where the new element should go.

## 🔣 Syntax:

python CopyEdit

list.insert(index, element)

### Parameters:

#### **Parameter**

#### **Description**

index

The position (integer) at which the element should be inserted. If the index is beyond the current list range, the item is appended. If it's negative, it's counted from the end.

element

The item you want to insert (could be any data type: number, string, list, object, etc.).

## Return Value:

None – It modifies the list in-place and returns nothing.

# 

## 1. Insert a Task in To-Do List Based on Priority

python CopyEdit

tasks = ["Buy groceries", "Clean room", "Exercise"]

```
tasks.insert(1, "Finish assignment") # Inserting at index 1 (high
priority)
print(tasks)
```

#### **Output:**

```
python
CopyEdit
['Buy groceries', 'Finish assignment', 'Clean room', 'Exercise']
```

#### 2. Insert Emoji at Specific Index in a Chat

```
python
CopyEdit
chat = ["Hey", "How are you?", "I'm good"]
chat.insert(2, "ee") # Add emoji before the response
print(chat)
```

#### **Output:**

```
python
CopyEdit
['Hey', 'How are you?', 'e', "I'm good"]
```

### • 3. Insert a Player into a Gaming Queue

```
python
CopyEdit
players = ["Alice", "Bob", "Charlie"]
players.insert(0, "VIP_Player") # VIP goes to the front
print(players)
```

#### **Output:**

```
python
CopyEdit
['VIP_Player', 'Alice', 'Bob', 'Charlie']
```

### 4. Inserting a Default Value at the End Using Large Index

```
python  
CopyEdit  
settings = ["Brightness", "Volume"]  
settings.insert(100, "Language")  # Index out of bounds \rightarrow goes to end print(settings)
```

#### **Output:**

```
python
CopyEdit
['Brightness', 'Volume', 'Language']
```

### 5. Using Negative Index to Insert Before Last Element

```
python
CopyEdit
colors = ["Red", "Blue", "Green"]
colors.insert(-1, "Yellow") # Insert before the last item
print(colors)
```

#### **Output:**

```
python
CopyEdit
['Red', 'Blue', 'Yellow', 'Green']
```

#### • 6. Insert a Sublist into a List

```
python
CopyEdit
shopping_list = ["Milk", "Eggs", "Bread"]
shopping_list.insert(2, ["Bananas", "Apples"]) # Sublist as item
print(shopping_list)
```

#### **Output:**

```
python
CopyEdit
['Milk', 'Eggs', ['Bananas', 'Apples'], 'Bread']
```

## 7. Insert a Dictionary to Represent an Object

```
python
CopyEdit
inventory = [{"item": "sword"}, {"item": "shield"}]
inventory.insert(1, {"item": "potion", "quantity": 3})
print(inventory)
```

#### **Output:**

```
python
CopyEdit
[{'item': 'sword'}, {'item': 'potion', 'quantity': 3}, {'item':
'shield'}]
```

## Summary:

Feature insert()

Returns value X No

Useful for Inserting at specific index

Supports Any data type

Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the remove method.

Absolutely! Let's dive deep into the remove() method in Python, especially for lists. I'll break everything down step by step with a clean structure.

remove() Method in Python (List Method)

## **Definition:**

The remove() method is used to delete the **first occurrence** of a specified element from a list. If the element is **not present**, it raises a ValueError.

## **Syntax:**

python CopyEdit

list\_name.remove(element)

### Parameters:

#### **Parameter**

#### **Description**

element

The value you want to remove from the list. Must exist in the list, otherwise ValueError is raised.

Note: This method does not return anything (None), it modifies the list in-place.

## Examples with Creative Arguments:

```
Example 1: Removing a Fruit from a Basket
python
CopyEdit
basket = ['apple', 'banana', 'orange', 'banana']
basket.remove('banana')
print(basket)

Output: ['apple', 'orange', 'banana']
    Removes the first occurrence of 'banana' from the basket.

Example 2: Removing a Student from a Roll List
```

```
python
CopyEdit
students = ['Alice', 'Bob', 'Charlie', 'Bob'
```

```
students = ['Alice', 'Bob', 'Charlie', 'Bob']
students.remove('Bob')
print(students)
```

- Output: ['Alice', 'Charlie', 'Bob']
  Removes the first 'Bob'. Useful when managing attendance or removals.
- # Example 3: Remove a Task from To-Do List
  python
  CopyEdit
  tasks = ['coding', 'gym', 'meditation', 'gym']
  tasks.remove('gym')
  print(tasks)

  Output: ['coding', 'meditation', 'gym']

  Use case: Remove completed task from the list.

```
Example 4: Trying to Remove an Item Not in List (Error Handling)

python

CopyEdit

numbers = [1, 2, 3]
```

```
numbers.remove(5)
except ValueError as e:
    print("Error:", e)

Output: Error: list.remove(x): x not in list
    Good practice to handle with try-except if you're unsure whether the element exists.

Example 5: Remove Using User Input
python
```

Output:['red', 'green', 'blue']

Interactive list modification based on user preference.

colors.remove(color\_to\_remove)

colors = ['red', 'blue', 'green', 'blue']

color\_to\_remove = 'blue'

if color\_to\_remove in colors:

## **Summary:**

print(colors)

try:

CopyEdit

Feature Description

Modifies List ✓ Yes (in-place)

Returns Value? ✓ No (returns None)

Removes All Matches ✓ No (only first occurrence)

Error on Not Found ✓ Yes (ValueError)

Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the pop method.

Absolutely! Let's dive deep into the **pop() method in Python**, with **clear explanations**, **creative examples**, and **real-world analogies** to make it easy to remember and use.



The pop() method **removes and returns the item at the specified index** from a list. If no index is specified, it removes and returns the **last item**.

It's like popping a balloon — once it's popped, it's gone!



python
CopyEdit
list.pop(index)

## Parameters:

#### **Parameter**

#### **Description**

index

(Optional) The position of the element to remove. If omitted, the last item is removed.

Note: If the index is out of range, it raises an IndexError.



# Usage Summary:

Case Result

No parameter Removes and returns last

element

Valid index provided Removes and returns that

element

Invalid index Raises IndexError



## Creative Examples:

### 1. Pop the last guest from a party list

```
python
CopyEdit
guests = ["Alice", "Bob", "Charlie", "Daisy"]
last_guest = guests.pop()
print("Last guest to leave:", last_guest)
print("Remaining guests:", guests)
```

#### **Output:**

```
CSS
```

#### CopyEdit

```
Last guest to leave: Daisy
Remaining guests: ['Alice', 'Bob', 'Charlie']
```

## 2. Pop a task from a to-do list (index-based)

```
python
CopyEdit
todo = ["Workout", "Study Python", "Clean Room", "Call Mom"]
done_task = todo.pop(1)
print("Completed:", done_task)
```

```
print("Tasks left:", todo)
```

#### **Output:**

less

CopyEdit

```
Completed: Study Python
Tasks left: ['Workout', 'Clean Room', 'Call Mom']
```

### 3. Simulating undo feature in a drawing app

```
python
CopyEdit
actions = ["Draw Line", "Draw Circle", "Fill Color"]
last_action = actions.pop()
print("Undo:", last_action)
print("Remaining Actions:", actions)
```

#### **Output:**

less

CopyEdit

```
Undo: Fill Color
Remaining Actions: ['Draw Line', 'Draw Circle']
```

### 4. Pop the first customer from a queue (like a bank counter)

```
python
CopyEdit
queue = ["Customer1", "Customer2", "Customer3"]
served = queue.pop(0)
print("Now serving:", served)
print("Queue left:", queue)
```

#### **Output:**

less

CopyEdit

Now serving: Customer1

```
Queue left: ['Customer2', 'Customer3']
```

#### 5. Removing an incorrect answer in a quiz app

```
python
CopyEdit
answers = ["A", "B", "C", "D"]
removed = answers.pop(2) # C is wrong
print("Removed wrong option:", removed)
print("Remaining options:", answers)
```

#### **Output:**

```
pgsql
CopyEdit
Removed wrong option: C
Remaining options: ['A', 'B', 'D']
```

## Common Errors:

```
python
CopyEdit
empty_list = []
empty_list.pop() # X IndexError: pop from empty list
```

Always check if the list has elements before popping.

## 🧠 Tips to Remember:

- No index = last element
- pop() is destructive it modifies the original list
- Use it when you need the removed value

Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the clear method.

Absolutely, let's break down the Python **clear()** method in a detailed and creative way to help you fully understand and master it.

Method Name: clear()

## **Definition:**

The clear() method is used to **remove all items** from a list (or other mutable data types like dictionaries and sets), leaving it **empty**, but not deleting the list itself.

### Syntax:

python
CopyEdit
list\_name.clear()

### Parameters:

None.

The clear() method does **not take any parameters**. It simply acts on the list (or set/dictionary) it's called on.

## Return Value:

• It returns None.

• It modifies the original list in place.



## Examples with Creative Use-Cases:

## Example 1: Cleaning up a list of completed tasks

```
python
CopyEdit
completed_tasks = ["Email client", "Fix bug #123", "Write report"]
print("Before clear:", completed_tasks)
# Clear the list after reporting
completed_tasks.clear()
print("After clear:", completed_tasks)
Output:
```

```
less
CopyEdit
Before clear: ['Email client', 'Fix bug #123', 'Write report']
After clear: []
```

Use Case: Once tasks are logged into a database, we reset the list for new tasks.

## Example 2: Resetting a shopping cart after order confirmation

```
python
CopyEdit
shopping_cart = ["Apples", "Bananas", "Toothpaste"]
print("Cart before clearing:", shopping_cart)
# Order placed successfully, clear the cart
shopping_cart.clear()
```

```
print("Cart after clearing:", shopping_cart)
```

#### **Output:**

```
less
```

CopyEdit

```
Cart before clearing: ['Apples', 'Bananas', 'Toothpaste']
Cart after clearing: []
```

**Use Case**: Post-checkout, the cart needs to be reset for the next session.

## Example 3: Memory-efficient real-time logging system

```
python
```

```
CopyEdit
```

```
log_buffer = ["Error: Disk Full", "Warning: CPU Overload", "Info:
Update Complete"]
print("Logs before archive:", log_buffer)
# After sending logs to server
log_buffer.clear()
print("Logs after archive:", log_buffer)
```

#### **Output:**

less

#### CopyEdit

```
Logs before archive: ['Error: Disk Full', 'Warning: CPU Overload',
'Info: Update Complete']
Logs after archive: []
```

**Solution** Use Case: To save memory after pushing logs to a remote server.

## Example 4: Tracking live visitors on a website

python

```
CopyEdit
```

```
live_visitors = ["user_102", "user_215", "user_889"]
print("Visitors before maintenance:", live_visitors)

# Clear the list during maintenance mode
live_visitors.clear()
print("Visitors after maintenance:", live_visitors)
```

#### **Output:**

#### less

#### CopyEdit

python

# vs

```
Visitors before maintenance: ['user_102', 'user_215', 'user_889']
Visitors after maintenance: []
```

**Use Case**: Resetting the visitor tracking system during site maintenance.

## Alternative (but not recommended):

```
CopyEdit

my_list = [1, 2, 3]

my_list = [] # Reassigning to a new empty list
```

```
my_list.clear() # Actually clears the original list in-place
```

Neassignment creates a **new list**; clear() modifies the **same object**, which is important when other references to the list exist.

## Summary Table:

**Feature** 

**Description** 

Method clear()

Purpose Removes all items from a list

Parameter None

S

Returns None

Modifies In-place

Use with list, set, dict

Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the index method.

Absolutely, Routh! Let's break down the index() method in Python in a comprehensive way so that you can understand it like an expert.



## **Definition:**

The index() method returns the **first index** at which a specified value is found in a list (or tuple or string).

If the value is **not found**, it raises a ValueError.

## 

python

CopyEdit

list.index(element, start, end)

### Parameters:

#### **Parameter**

#### **Description**

(Required) – The item you want to search for. element

(Optional) – The index position to start searching from. start

(Optional) – The index position to stop searching. (exclusive) end

### Exceptions:

• Raises ValueError if the element is not found in the specified range.

### Use-Case Scenarios with Creative Examples:

Let's explore creative and real-world-style arguments to solidify your understanding.

#### Example 1: Basic Use – Find Position of a Fruit

#### python

#### CopyEdit

```
fruits = ["apple", "banana", "cherry", "banana", "kiwi"]
print(fruits.index("banana"))
```

#### Output:

#### CopyEdit

right lt finds the first occurrence of "banana" at index 1.

#### Example 2: Use with Start and End – Skipping the First Match

#### python

#### CopyEdit

```
fruits = ["apple", "banana", "cherry", "banana", "kiwi"]
```

```
print(fruits.index("banana", 2)) # Start searching from index 2

Output:
CopyEdit
3

It skips the first "banana" and returns the next one.
```

Example 3: Working with Numbers – Find First Failing Student

```
python
CopyEdit
scores = [85, 90, 45, 60, 45, 70]
failing_score = 45
print(scores.index(failing_score))
```

#### Output:

CopyEdit

2

\* Helps to quickly identify the first failing student by score.

• Example 4: Search Within a Range – Birthday Months

```
python
CopyEdit
```

```
months = ["Jan", "Feb", "Mar", "Apr", "Feb", "May"]
print(months.index("Feb", 2, 5)) # Search only in a limited range
```

Output:

CopyEdit

4

Useful when you're trying to find repeated items within a particular timeframe.

#### Example 5: Raise Error Gracefully Using Try-Except

```
python
CopyEdit
colors = ["red", "green", "blue"]
try:
    print(colors.index("purple"))
except ValueError:
    print("Color not found!")
```

#### Output:

CSS

CopyEdit

Color not found!

Prevents crashing your code if the element is missing.

## Example 6: With Duplicates – Find the First Winner of a Game

python

CopyEdit

```
winners = ["Alice", "Bob", "Alice", "David"]
first_winner = winners.index("Alice")
print(f"The first person to win is: {winners[first_winner]}")
```

#### Output:

vbnet

CopyEdit

The first person to win is: Alice

Y Very helpful in ranking systems or game scores.

## Pro Tips:

- .index() is great when you want to know where something occurred.
- If unsure whether the element exists, always use try-except.
- Works on lists, tuples, and strings.

```
Bonus: Using .index() in a String

python
CopyEdit

message = "hello world"

print(message.index("o"))
Output:
```

CopyEdit

Works the same way for strings — first "o" is at index 4.

Assume you are expert in python and Problem solver then provide definition, syntax, Parameter uses, then examples by providing creative arguments to the count method.

Absolutely! Let's dive deep into the **count() method** for Python **lists**, breaking it down like an expert problem solver  $\mathscr{A}$ 

## Definition of count() in Python

The count() method returns the number of times a specified element appears in the list.



python CopyEdit

list.count(element)



#### Parameter Description

element Required. The item to search for and count in the list.

It can be of any data type: string, number, boolean, object, etc.

## 🧠 Internal Working & Use Case

Under the hood, count() iterates through the list and increments a counter each time it finds an element equal to the given parameter using ==.

Useful when you want to:

- Check for frequency of values
- Validate duplicates
- Analyze survey data
- Clean/normalize data

# Examples with Creative Arguments

1. Count occurrences of a fruit in a fruit basket

```
python
CopyEdit
fruits = ['apple', 'banana', 'orange', 'apple', 'kiwi', 'banana',
'apple']
print(fruits.count('apple')) # Output: 3
```

## 2. Count number of failed tests (represented as False)

python

CopyEdit

```
test_results = [True, False, True, False, False]
print(test_results.count(False)) # Output: 3
```

# ✓ 3. Count how many times the number 0 occurs (good for checking missing data)

```
python
CopyEdit
data = [0, 1, 2, 0, 3, 0, 4]
print(data.count(0)) # Output: 3
```

## ✓ 4. Count how many times a character appears in a list.

python

CopyEdit

```
chars = ['a', 'b', 'c', 'a', 'd', 'e', 'a']
print(chars.count('a')) # Output: 3
```

## **5.** Count a tuple in a list of coordinates

python

CopyEdit

```
coordinates = [(0, 0), (1, 2), (0, 0), (3, 4)]
print(coordinates.count((0, 0))) # Output: 2
```

6. Count a custom object in a list using overridden \_\_eq\_\_

python

CopyEdit

class Student:

```
def __init__(self, name):
        self.name = name
    def __eq__(self, other):
        return self.name == other.name

s1 = Student("Alice")
s2 = Student("Bob")
s3 = Student("Alice")

students = [s1, s2, s3]
print(students.count(Student("Alice"))) # Output: 2
```

## **7.** Count a specific sentence in survey feedback

```
python
CopyEdit
feedback = ["Great course", "Too long", "Great course", "Loved it",
"Great course"]
print(feedback.count("Great course")) # Output: 3
```

## Quick Challenges to Practice

- 1. Count how many zeros are in a binary list.
- 2. Count how many times your name appears in a list of attendees.
- 3. Count how many times an item was bought from a shopping cart.

Assume you are expert in python and Problem solver then provide solution for Append single vs multiple items • Insert at different positions • Remove by value and by index • Handle exceptions when pop() or index() fails

Sure! Let's walk through **Python list operations** including:

- 1. Appending single vs multiple items
- 2. Inserting at different positions
- 3. Removing items by value and by index
- 4. Handling exceptions when pop() or index() fails

I'll provide simple examples and explanations for each.

## 1. Append Single vs Multiple Items

```
python
CopyEdit
# Append a single item
fruits = ['apple', 'banana']
fruits.append('cherry')  # Adds one item
print(f"After appending single item: {fruits}")

# Append multiple items - WRONG way (nested list)
fruits.append(['orange', 'grape'])
print(f"After appending a list: {fruits}")

# Correct way to add multiple items
fruits = ['apple', 'banana']
fruits.extend(['orange', 'grape'])  # Adds multiple items individually
print(f"After extending with multiple items: {fruits}")
```

## 2. Insert at Different Positions

```
python
CopyEdit
numbers = [10, 20, 30, 40]
# Insert at beginning
numbers.insert(0, 5)
# Insert at middle
```

```
numbers.insert(2, 15)

# Insert at end (like append)
numbers.insert(len(numbers), 50)
print(f"After inserts: {numbers}")
```

## 3. Remove by Value and by Index

```
python
CopyEdit
items = ['pen', 'pencil', 'eraser', 'pen']

# Remove by value (removes first occurrence)
items.remove('pen')
print(f"After removing 'pen' by value: {items}")

# Remove by index
del items[1] # Removes item at index 1
print(f"After removing by index: {items}")
```

## 4. Handle Exceptions: pop() and index()

```
pop() fails if list is empty
```

```
index() fails if value not found
python
CopyEdit
# pop() with exception handling
my_list = []

try:
    my_list.pop()
except IndexError as e:
    print(f"pop() failed: {e}")

# index() with exception handling
```

```
names = ['Alice', 'Bob']

try:
    idx = names.index('Charlie')
    print(f"Index of Charlie: {idx}")

except ValueError as e:
    print(f"index() failed: {e}")
```

## Summary Table

Operation	Method	Handles
Append single item	append()	One element
Append multiple	extend()	List/Iterable
Insert item	<pre>insert(i,x)</pre>	Position-based
Remove by value	remove(x)	First match
Remove by index	<pre>del list[i] or pop(i)</pre>	By position
Safe pop	try-except	Handle empty
Safe index lookup	try-except	Handle missing