

Assume you are good problem solver in dictionary of java programming language and good guide in explaining in terms of comments in codes from beginner to advance then provide examples related to method "**put(K key, V value)**". Where you response must have definition, syntax, arguments it takes, return types, and creative way of providing different arguments value

Absolutely! Let's go step-by-step through the `put(K key, V value)` method in Java's `Map` interface (commonly used via `HashMap`, `TreeMap`, etc.) and then I'll provide examples from **beginner to advanced** level with creative use cases and **detailed comments**.

✓ Definition

`put(K key, V value)` is a method in Java's `Map` interface (like `HashMap`) used to **insert a key-value pair** into the map.

If the key **already exists**, the method **updates** the value and returns the **previous value**.

✓ Syntax

```
V put(K key, V value);
```

✓ Parameters

- `K key` – the key with which the specified value is to be associated
- `V value` – the value to be associated with the specified key

✓ Return Type

- Returns the **previous value** associated with the key, or `null` if there was **no mapping** for the key.

🚀 Examples from Beginner to Advanced with Comments

📖 1. Beginner Level – Basic Insertion with Integer and String

```
import java.util.HashMap;

public class BeginnerExample {

    public static void main(String[] args) {

        HashMap<Integer, String> map = new HashMap<>();

        // Adding new key-value pairs to the map

        map.put(1, "Apple");    // key: 1, value: "Apple"

        map.put(2, "Banana");   // key: 2, value: "Banana"

        // Displaying the map

        System.out.println(map); // Output: {1=Apple, 2=Banana}

    }

}
```

2. Intermediate – Updating Values and Checking Return

```
import java.util.HashMap;
```

```
public class UpdateExample {  
    public static void main(String[] args) {  
        HashMap<String, Integer> map = new HashMap<>();  
        map.put("Java", 10); // Initial value  
  
        // Updating the value for existing key "Java"  
        Integer oldValue = map.put("Java", 20); // returns 10  
  
        System.out.println("Old value: " + oldValue); // Output: Old value: 10  
        System.out.println("Updated map: " + map);    // Output: {Java=20}  
    }  
}
```

3. Creative – Using Different Data Types (Custom Class as Value)

```
import java.util.HashMap;
```

```
class Student {  
    String name;  
    int grade;
```

```

Student(String name, int grade) {

    this.name = name;

    this.grade = grade;

}

public String toString() {

    return name + " (Grade: " + grade + ")";

}

}

public class CustomObjectExample {

    public static void main(String[] args) {

        HashMap<Integer, Student> studentMap = new HashMap<>();

        // Using student roll number as key, Student object as value

        studentMap.put(101, new Student("Alice", 85));

        studentMap.put(102, new Student("Bob", 90));

        System.out.println(studentMap);

        // Output: {101=Alice (Grade: 85), 102=Bob (Grade: 90)}

    }

}

```



4. Creative – Dynamic Key-Value Insertion via Loop

```
import java.util.HashMap;
```

```
public class LoopInsertExample {  
  
    public static void main(String[] args) {  
  
        HashMap<String, Integer> map = new HashMap<>();  
  
        // Insert keys "Day1", "Day2", ..., "Day5" with increasing values  
        for (int i = 1; i <= 5; i++) {  
            map.put("Day" + i, i * 100);  
        }  
  
        System.out.println(map);  
  
        // Output: {Day1=100, Day2=200, Day3=300, Day4=400, Day5=500}  
    }  
}
```



5. Advanced – Nested HashMaps

```
import java.util.HashMap;
```

```
public class NestedMapExample {  
  
    public static void main(String[] args) {
```

```
HashMap<String, HashMap<String, Integer>> countryData = new HashMap<>();
```

```
HashMap<String, Integer> indiaStats = new HashMap<>();
```

```
indiaStats.put("Population", 1400000000);
```

```
indiaStats.put("GDP", 3000);
```

```
HashMap<String, Integer> usaStats = new HashMap<>();
```

```
usaStats.put("Population", 330000000);
```

```
usaStats.put("GDP", 21000);
```

```
// Putting country and its stats into main map
```

```
countryData.put("India", indiaStats);
```

```
countryData.put("USA", usaStats);
```

```
System.out.println(countryData);
```

```
/*
```

```
Output: {
```

```
    India={Population=1400000000, GDP=3000},
```

```
    USA={Population=330000000, GDP=21000}
```

```
}
```

```
*/
```

```
}
```

```
}
```

Summary Table

Use Case	Key Type	Value Type	Purpose
Basic Insert	<code>Integer</code>	<code>String</code>	Just storing basic data
Update Existing	<code>String</code>	<code>Integer</code>	Shows return of old value
Custom Object	<code>Integer</code>	<code>Student</code> (class)	Storing user-defined objects
Dynamic via Loop	<code>String</code>	<code>Integer</code>	Shows programmatic insertion
Nested Maps	<code>String</code>	<code>HashMap</code>	Storing complex structured data

Would you like me to include real-world examples like tracking inventory, student marks, or login sessions using `put()`?

`get(Object key)`

Absolutely, let's dive deep into the `get(Object key)` method in Java's `Map` interface, especially focusing on the `HashMap` implementation. I'll explain **definition**, **syntax**, **arguments**, **return type**, and provide **beginner to advanced examples**, all with **detailed inline comments** to make learning smooth and clear.

Method: `get(Object key)`

✔ Definition:

The `get(Object key)` method in Java is used to **retrieve the value** associated with a specified key in a map (like `HashMap`, `TreeMap`, etc.).



Syntax:

`V get(Object key)`



Parameters:

- `key` – the key whose associated value is to be returned (of type `Object`).
-



Return Type:

- Returns the value to which the specified key is mapped.
 - Returns `null` if the map contains no mapping for the key.
-



Beginner-Friendly Example

```
import java.util.HashMap;

public class GetMethodExample1 {
    public static void main(String[] args) {
        // Create a HashMap with String keys and Integer values
        HashMap<String, Integer> marks = new HashMap<>();

        // Adding key-value pairs using put()
        marks.put("Alice", 85);
        marks.put("Bob", 92);

        // Retrieve values using get()
        System.out.println("Alice's Marks: " + marks.get("Alice")); // 85
        System.out.println("Bob's Marks: " + marks.get("Bob"));    // 92
    }
}
```



```
        // Try to get value for a key that doesn't exist
        System.out.println("Eve's Marks: " + marks.get("Eve"));    // null
    }
}
```

Intermediate Example with Multiple Data Types

```
import java.util.HashMap;

public class GetMethodExample2 {
    public static void main(String[] args) {
        // HashMap with Integer keys and String values
        HashMap<Integer, String> idToName = new HashMap<>();
        idToName.put(101, "Laptop");
        idToName.put(102, "Keyboard");

        // HashMap with Boolean keys
        HashMap<Boolean, String> boolMap = new HashMap<>();
        boolMap.put(true, "Enabled");
        boolMap.put(false, "Disabled");

        // Getting values
        System.out.println("Product 101: " + idToName.get(101));    // Laptop
        System.out.println("Is Feature On? " + boolMap.get(true));  // Enabled
    }
}
```

Advanced Example with Custom Object as Key

```
import java.util.HashMap;
import java.util.Objects;

class Employee {
    int id;
    String name;

    Employee(int id, String name) {
        this.id = id;
        this.name = name;
    }
}
```

```

    }

    // Override equals() and hashCode() for correct get() behavior
    @Override
    public boolean equals(Object o) {
        if (this == o) return true;
        if (!(o instanceof Employee)) return false;
        Employee e = (Employee) o;
        return id == e.id && Objects.equals(name, e.name);
    }

    @Override
    public int hashCode() {
        return Objects.hash(id, name);
    }
}

public class GetMethodExample3 {
    public static void main(String[] args) {
        // Create a HashMap with custom Employee objects as keys
        HashMap<Employee, String> empRoles = new HashMap<>();


        // Create employee objects
        Employee emp1 = new Employee(1, "John");
        Employee emp2 = new Employee(2, "Jane");

        // Put roles
        empRoles.put(emp1, "Developer");
        empRoles.put(emp2, "Manager");

        // Retrieve roles using get()
        System.out.println("John's Role: " + empRoles.get(emp1)); // Developer
        System.out.println("Jane's Role: " + empRoles.get(emp2)); // Manager

        // Get using new object with same data
        Employee empClone = new Employee(1, "John");
        System.out.println("Clone John's Role: " + empRoles.get(empClone)); // Developer
    }
}

```


 **Why it works:** We override `equals()` and `hashCode()` so `get()` can correctly find the key even with a new object that has the same content.

Creative Variations of `get()` Arguments

```
HashMap<Object, String> mixedMap = new HashMap<>();
```

```
mixedMap.put(10, "Ten");           // Integer key
mixedMap.put("Ten", "String Ten"); // String key
mixedMap.put(10.5, "Double Ten Point Five"); // Double key
mixedMap.put(true, "Boolean True"); // Boolean key
mixedMap.put('A', "Character A");   // Character key

System.out.println(mixedMap.get(10)); // "Ten"
System.out.println(mixedMap.get("Ten")); // "String Ten"
System.out.println(mixedMap.get(10.5)); // "Double Ten Point Five"
System.out.println(mixedMap.get(true)); // "Boolean True"
System.out.println(mixedMap.get('A')); // "Character A"
```

 **Takeaway:** You can use **any object** as a key, including different types in the same map — just make sure they're distinct and hashable.

Would you like a challenge question or quiz next to practice the `get()` method?

containsKey(Object key)

Absolutely! Let's dive into the `containsKey(Object key)` method in Java's `Map` (especially `HashMap`) with **clear comments**, **creative examples**, and a **structured breakdown** — from **beginner** to **advanced level**.

◆ Definition:

The `containsKey(Object key)` method checks whether a specified **key** exists in the map.

◆ Syntax:

map.containsKey(Object key)

◆ Parameters:

- **key** – The **key object** whose presence in the map is to be tested.
-

◆ Return Type:

- Returns **true** if the map contains a mapping for the specified key, else **false**.
-

◆ Beginner Example: Using String keys

```
import java.util.HashMap;

public class ContainsKeyExample {
    public static void main(String[] args) {
        // Create a simple HashMap with String keys and Integer values
        HashMap<String, Integer> map = new HashMap<>();

        // Adding some key-value pairs
        map.put("apple", 10);
        map.put("banana", 20);

        // Check if certain keys exist
        System.out.println("Has key 'apple'? " + map.containsKey("apple")); // true
        System.out.println("Has key 'grape'? " + map.containsKey("grape")); // false
    }
}
```

What You Learn Here:

- Basic usage with **String** keys.

- Simple true/false return values.
-

◆ Intermediate Example: Using Integer keys and dynamic input

```
import java.util.HashMap;
import java.util.Scanner;

public class ContainsKeyWithIntegers {
    public static void main(String[] args) {
        HashMap<Integer, String> students = new HashMap<>();

        students.put(101, "Alice");
        students.put(102, "Bob");
        students.put(103, "Charlie");

        Scanner sc = new Scanner(System.in);
        System.out.print("Enter student roll number: ");
        int rollNo = sc.nextInt();

        // containsKey used to check if student exists
        if (students.containsKey(rollNo)) {
            System.out.println("Student Found: " + students.get(rollNo));
        } else {
            System.out.println("Student Not Found");
        }
    }
}
```

What You Learn Here:

- `containsKey` can be used with **dynamic input**.
 - Works with any object as key – not just strings.
-

◆ Advanced Example: Custom Object as Key (with hashCode and equals)

```
import java.util.HashMap;
import java.util.Objects;
```

```
class Book {
    String title;
    int id;

    Book(String title, int id) {
        this.title = title;
        this.id = id;
    }

    // Overriding hashCode and equals so it works in HashMap
    @Override
    public int hashCode() {
        return Objects.hash(title, id);
    }

    @Override
    public boolean equals(Object obj) {
        if (this == obj) return true;
        if (!(obj instanceof Book)) return false;
        Book other = (Book) obj;
        return this.id == other.id && this.title.equals(other.title);
    }
}

public class ContainsKeyWithCustomObject {
    public static void main(String[] args) {
        HashMap<Book, String> library = new HashMap<>();

        Book b1 = new Book("Java Basics", 1);
        Book b2 = new Book("Advanced Java", 2);

        library.put(b1, "Available");
        library.put(b2, "Issued");

        // Checking if a book exists (even if we create a new instance with same content)
        Book searchBook = new Book("Java Basics", 1);

        System.out.println("Is book present? " + library.containsKey(searchBook)); // true
    }
}
```

```
}  
}
```

What You Learn Here:

- `containsKey()` works properly only if `hashCode()` and `equals()` are overridden correctly.
- Allows searching even if object references differ but content is same.

◆ Creative Variations of Arguments

Argument Type	Example Key	Notes
<code>String</code>	<code>"name"</code>	Most common
<code>Integer</code>	<code>1001</code>	Roll numbers, IDs
<code>Character</code>	<code>'A'</code>	Grade mapping
<code>Double</code>	<code>99.9</code>	For percentile maps
<code>null</code>	<code>map.containsKey(null)</code>	<code>HashMap</code> allows 1 null key
<code>Custom Object</code>	<code>new Book("Java", 1)</code>	Must override <code>equals()</code> and <code>hashCode()</code>

◆ Bonus: `containsKey` with null key

```
import java.util.HashMap;  
  
public class NullKeyExample {  
    public static void main(String[] args) {  
        HashMap<String, String> map = new HashMap<>();  
  
        map.put(null, "Null Key Value");  
  
        // Check for null key
```

```
        System.out.println("Has null key? " + map.containsKey(null)); // true
    }
}
```

Would you like a **quick quiz or task** to test your understanding of `containsKey()`?

Assume you are good problem solver in dictionary of java programming language and **good guide in explaining for a beginner** in terms of comments in codes from beginner to advance then provide examples related to method "**containsValue(Object value)**". Where you response must have definition, syntax, arguments it takes, return types, and creative way of providing different arguments value

Absolutely! Let's dive deep into the Java `containsValue(Object value)` method from the **Map interface** (typically used with `HashMap`, `TreeMap`, etc.), and break it down in a way that's beginner-friendly — complete with well-commented code examples that go from basic to advanced.

Definition

The `containsValue(Object value)` method is used to **check if a specific value exists** in the map.

Syntax

```
map.containsValue(Object value)
```

Parameters

- **value**: The value you want to check for presence in the map. It can be of **any object type**, including **String**, **Integer**, custom objects, etc.
-

Return Type

- **boolean**: Returns **true** if the map **contains the specified value**, otherwise returns **false**.
-

Basic Example with Comments

```
import java.util.HashMap;

public class ContainsValueExample {
    public static void main(String[] args) {
        // Step 1: Create a HashMap with Integer keys and String values
        HashMap<Integer, String> map = new HashMap<>();

        // Step 2: Put some key-value pairs
        map.put(1, "Apple");
        map.put(2, "Banana");
        map.put(3, "Cherry");

        // Step 3: Use containsValue to check if a value exists
        System.out.println(map.containsValue("Banana")); // true
        System.out.println(map.containsValue("Mango")); // false
    }
}
```

Example Using Different Data Types

```
import java.util.HashMap;

public class DifferentDataTypes {
    public static void main(String[] args) {
        // Using Integer keys and Boolean values
        HashMap<Integer, Boolean> map1 = new HashMap<>();
        map1.put(1, true);
    }
}
```

```

map1.put(2, false);
System.out.println(map1.containsValue(true)); // true
System.out.println(map1.containsValue(null)); // false

// Using String keys and Double values
HashMap<String, Double> map2 = new HashMap<>();
map2.put("pi", 3.14);
map2.put("gravity", 9.8);
System.out.println(map2.containsValue(9.8)); // true
System.out.println(map2.containsValue(1.0)); // false
}
}

```

Creative Use with Custom Objects

```

import java.util.HashMap;
import java.util.Objects;

class Student {
    String name;
    int id;

    Student(String name, int id) {
        this.name = name;
        this.id = id;
    }

    // Overriding equals() and hashCode() is necessary for correct containsValue behavior
    @Override
    public boolean equals(Object obj) {
        if (this == obj) return true;
        if (!(obj instanceof Student)) return false;
        Student other = (Student) obj;
        return this.id == other.id && this.name.equals(other.name);
    }

    @Override
    public int hashCode() {
        return Objects.hash(name, id);
    }
}

public class CustomObjectValue {

```

```

public static void main(String[] args) {
    HashMap<Integer, Student> studentMap = new HashMap<>();
    studentMap.put(101, new Student("Alice", 1));
    studentMap.put(102, new Student("Bob", 2));

    // We need to use a NEW object with same data to test containsValue
    System.out.println(studentMap.containsValue(new Student("Alice", 1))); // true
    System.out.println(studentMap.containsValue(new Student("Tom", 3))); // false
}
}

```

Things to Remember

- `containsValue()` checks using `.equals()` method. If you're using custom objects, override `equals()` and `hashCode()`.
 - It can be **less efficient** for large maps because it must check all values (O(n) complexity).
 - It's **case-sensitive** when dealing with `String`.
-

Creative/Advanced Tips

```

import java.util.HashMap;

public class CreativeUsage {
    public static void main(String[] args) {
        HashMap<Integer, String> bookMap = new HashMap<>();
        bookMap.put(1, "Java Programming");
        bookMap.put(2, "Python Tricks");
        bookMap.put(3, "C++ Primer");

        // Using toLowerCase() and stream-like loop to simulate containsIgnoreCase
        String search = "java programming";

        boolean found = bookMap.values().stream()
            .anyMatch(val -> val.equalsIgnoreCase(search));
        System.out.println(found); // true
    }
}

```

Would you like a practice quiz or assignment based on `containsValue()` to test your understanding?

isEmpty()

Absolutely! Let's dive into the `isEmpty()` method in **Java**, with a beginner-friendly, well-commented, and progressively advanced explanation using `Map` (i.e., dictionary in Java).

✓ Definition of `isEmpty()`

The `isEmpty()` method in Java is used to check whether a collection (like a `Map`) is **empty or not** — meaning it contains **no key-value pairs**.

✓ Syntax

```
map.isEmpty();
```

✓ Arguments it takes

- It does not take any arguments.
-

✓ Return Type

- Returns a **boolean**:
 - `true` → if the map has no key-value mappings.
 - `false` → if there is at least one key-value mapping.

✓ Beginner to Advanced Examples with Comments

🧠 Example 1: Basic `isEmpty()` usage on an empty `HashMap`

```
import java.util.HashMap;

public class IsEmptyExample1 {
    public static void main(String[] args) {
        // Creating an empty HashMap
        HashMap<String, String> map = new HashMap<>();

        // Checking if the map is empty
        System.out.println("Is the map empty? " + map.isEmpty()); // true
    }
}
```

🧠 Example 2: Add data, then use `isEmpty()`

```
import java.util.HashMap;

public class IsEmptyExample2 {
    public static void main(String[] args) {
        HashMap<String, Integer> ageMap = new HashMap<>();

        // Adding some key-value pairs
        ageMap.put("Alice", 25);
        ageMap.put("Bob", 30);

        // Checking if the map is empty
        System.out.println("Is the age map empty? " + ageMap.isEmpty()); // false
    }
}
```

🧠 Example 3: Clear the map and check again

```
import java.util.HashMap;

public class IsEmptyExample3 {
    public static void main(String[] args) {
```

```

HashMap<Integer, String> students = new HashMap<>();

students.put(1, "Kiran");
students.put(2, "Ravi");

// Now clearing all entries
students.clear();

// After clearing, checking if map is empty
System.out.println("Is student map empty? " + students.isEmpty()); // true
}
}

```

Example 4: Use `isEmpty()` creatively with conditional checks

```

import java.util.HashMap;

public class IsEmptyExample4 {
    public static void main(String[] args) {
        HashMap<String, String> tasks = new HashMap<>();

        if (tasks.isEmpty()) {
            System.out.println("You have no tasks to complete! Chill 🧘");
        } else {
            System.out.println("Tasks to complete: " + tasks);
        }
    }
}

```

Example 5: Custom method using `isEmpty()` for logging

```

import java.util.HashMap;

public class IsEmptyExample5 {
    public static void checkMapStatus(HashMap<?, ?> map) {
        // Generic method to check status of any map
        if (map.isEmpty()) {
            System.out.println("⚠️ The map is currently empty.");
        } else {
            System.out.println("✅ The map contains data: " + map);
        }
    }
}

```

```

    }

    public static void main(String[] args) {
        HashMap<String, String> userMap = new HashMap<>();
        checkMapStatus(userMap); // empty

        userMap.put("username", "kiran123");
        checkMapStatus(userMap); // not empty
    }
}

```

Example 6: Test with different data types in Map (String, Integer, Custom Object)

```

import java.util.HashMap;

class Product {
    String name;
    int price;

    Product(String name, int price) {
        this.name = name;
        this.price = price;
    }

    public String toString() {
        return name + " - ₹" + price;
    }
}

public class IsEmptyExample6 {
    public static void main(String[] args) {
        // Using custom object as value
        HashMap<String, Product> productMap = new HashMap<>();

        // Initially empty
        System.out.println("Empty? " + productMap.isEmpty()); // true

        // Add product
        productMap.put("laptop", new Product("Dell XPS", 80000));

        // Check again
        System.out.println("Empty? " + productMap.isEmpty()); // false
    }
}

```

```
}  
}
```

Summary (Revision Flash Notes):

Feature	Description
Method Name	<code>isEmpty()</code>
Belongs To	<code>Map</code> , <code>Set</code> , <code>List</code> , and other collections
Arguments	None
Return Type	<code>boolean</code>
<code>true</code> Value	Collection is empty
<code>false</code> Value	Collection has at least 1 element

Would you like the same kind of deep-dive explanation for any other Map or Collection method like `containsKey()`, `keySet()`, or `size()`?

size()

Absolutely! Let's break down the `**size()` method in **Java** (when used with a `HashMap`, `Hashtable`, `TreeMap`, or any class that implements the `Map interface`) in a way that's beginner-friendly but also touches on advanced concepts.

Definition of `size()` Method in Java Dictionary (Map Interface)

The `size()` method **returns the number of key-value mappings** (entries) present in the map.

Syntax

```
map.size();
```

Parameters

- The `size()` method **does not take any arguments**.

Return Type

- It returns an `int` representing the **total number of key-value pairs** in the map.

Concept Behind It

Imagine a dictionary where you store words (keys) and meanings (values). The `size()` method just counts **how many entries** are in that dictionary.

Examples from Beginner to Advanced with Comments

1. Beginner Level – Basic `HashMap` Example

```
import java.util.HashMap;
```

```
public class BeginnerExample {
    public static void main(String[] args) {
        // Creating a HashMap of students and their scores
        HashMap<String, Integer> studentScores = new HashMap<>();

        // Adding key-value pairs to the HashMap
        studentScores.put("Alice", 85);
        studentScores.put("Bob", 90);
        studentScores.put("Charlie", 75);

        // Using size() to get the number of entries in the map
        int numberOfStudents = studentScores.size();

        // Printing the size
        System.out.println("Total students: " + numberOfStudents); // Output: 3
    }
}
```

```
}  
}
```

2. Intermediate Level – After Removing Elements

```
import java.util.HashMap;  
  
public class IntermediateExample {  
    public static void main(String[] args) {  
        HashMap<String, String> countryCapitals = new HashMap<>();  
  
        countryCapitals.put("India", "New Delhi");  
        countryCapitals.put("USA", "Washington D.C.");  
        countryCapitals.put("UK", "London");  
  
        System.out.println("Original size: " + countryCapitals.size()); // Output: 3  
  
        // Remove one entry  
        countryCapitals.remove("UK");  
  
        // Size after removing one entry  
        System.out.println("Size after removing UK: " + countryCapitals.size()); // Output: 2  
    }  
}
```

3. Advanced Level – Handling Custom Object Keys

```
import java.util.HashMap;  
  
class Book {  
    String title;  
    int id;  
  
    Book(String title, int id) {  
        this.title = title;  
        this.id = id;  
    }  
  
    // Must override equals and hashCode for custom object keys in HashMap  
    @Override  
    public boolean equals(Object obj) {
```

```

        if (this == obj) return true;
        if (!(obj instanceof Book)) return false;
        Book b = (Book) obj;
        return this.id == b.id;
    }

    @Override
    public int hashCode() {
        return id * 31;
    }
}

public class AdvancedExample {
    public static void main(String[] args) {
        HashMap<Book, String> library = new HashMap<>();

        library.put(new Book("Java Basics", 101), "Available");
        library.put(new Book("Advanced Java", 102), "Issued");
        library.put(new Book("Data Structures", 103), "Available");

        System.out.println("Library size: " + library.size()); // Output: 3
    }
}

```

Creative Ways to Provide Different Argument Values (For Learning)

Although `size()` doesn't take parameters, you can creatively:

- Dynamically **change the map** contents using `put()` and `remove()`, and observe how `size()` reflects the change.
- Create **maps with duplicate values** (but unique keys), and see that `size()` still counts entries, not unique values.
- Use **null keys/values** and observe behavior (only `HashMap` allows one null key).
- Create a loop that adds elements and prints size step-by-step.

```

HashMap<Integer, String> dynamicMap = new HashMap<>();
for (int i = 1; i <= 5; i++) {
    dynamicMap.put(i, "Item" + i);
}

```

```
System.out.println("Size after adding item " + i + ": " + dynamicMap.size());  
}
```



Summary Table

Feature	Details
Method Name	<code>size()</code>
Belongs to	<code>Map</code> interface (<code>HashMap</code> , etc.)
Arguments	None
Return Type	<code>int</code>
Purpose	Returns the number of key-value pairs

Would you like me to create a small test-case-based project to explore `size()` dynamically with user input?

remove(Object key)

Certainly! Let's break down the `remove(Object key)` method in the `Java Dictionary` class step by step with comments and code examples to help you understand from a beginner to advanced level.

Definition:

The `remove(Object key)` method is used to remove a key-value pair from a `Dictionary` object in Java. The method searches for the specified key and removes the key-value pair from the dictionary if the key exists. If the key is not found, the dictionary remains unchanged.

Syntax:

```
public abstract V remove(Object key);
```

Arguments it takes:

- **key**: This is the key whose associated key-value pair you want to remove from the dictionary.

Return Type:

- It returns the value associated with the removed key (**V**), or **null** if the key does not exist in the dictionary.

How it works:

- When you call `remove(Object key)`, it looks for the specified key in the dictionary. If found, it removes the key-value pair and returns the corresponding value. If the key is not found, it simply returns **null**.

Code Examples with Detailed Comments:

1. Beginner Example:

In this simple example, we demonstrate the basic use of `remove(Object key)` to remove a key-value pair from a **Dictionary** object.

```
import java.util.*;

public class DictionaryExample {
    public static void main(String[] args) {
        // Creating a Dictionary object
        Dictionary<String, Integer> dict = new Hashtable<>();

        // Adding key-value pairs to the Dictionary
        dict.put("apple", 10);
        dict.put("banana", 20);
        dict.put("orange", 30);

        // Printing the original Dictionary
        System.out.println("Original Dictionary: " + dict);

        // Removing the key "banana"
        Integer removedValue = dict.remove("banana");
```

```

// Printing the Dictionary after removal
System.out.println("After removing 'banana': " + dict);

// Displaying the removed value
System.out.println("Removed value: " + removedValue);
}
}

```

Explanation:

- We create a **Dictionary** called **dict** and add three key-value pairs.
- We use **remove("banana")** to remove the entry with the key **"banana"**.
- The removed value (**20**) is returned by the **remove()** method and displayed.

2. Intermediate Example:

In this example, we show what happens when a key is not present in the dictionary.

```

import java.util.*;

public class DictionaryExample {
    public static void main(String[] args) {
        // Creating a Dictionary object
        Dictionary<String, Integer> dict = new Hashtable<>();

        // Adding key-value pairs to the Dictionary
        dict.put("apple", 10);
        dict.put("banana", 20);

        // Attempt to remove a key that doesn't exist
        Integer removedValue = dict.remove("grape");

        // Printing the Dictionary after removal
        System.out.println("Dictionary after attempting to remove 'grape': " + dict);

        // Displaying the removed value (should be null since 'grape' doesn't exist)
        System.out.println("Removed value for 'grape': " + removedValue);
    }
}

```

Explanation:

- The key "grape" does not exist in the dictionary, so `remove("grape")` returns `null`.
 - The dictionary remains unchanged because "grape" was not found.
-

3. Advanced Example:

This example demonstrates the use of different types of objects as the key and how `remove()` works with more complex keys, such as custom objects.

```
import java.util.*;

class Person {
    String name;
    int age;

    // Constructor
    Person(String name, int age) {
        this.name = name;
        this.age = age;
    }

    // Override equals() to compare Person objects based on name and age
    @Override
    public boolean equals(Object obj) {
        if (this == obj) return true;
        if (obj == null || getClass() != obj.getClass()) return false;
        Person person = (Person) obj;
        return age == person.age && Objects.equals(name, person.name);
    }

    // Override hashCode() for consistent behavior with equals()
    @Override
    public int hashCode() {
        return Objects.hash(name, age);
    }

    @Override
    public String toString() {
```

```

        return "Person{name='" + name + "', age=" + age + "'}";
    }
}

public class DictionaryExample {
    public static void main(String[] args) {
        // Creating a Dictionary object
        Dictionary<Person, String> dict = new Hashtable<>();

        // Creating Person objects
        Person person1 = new Person("Alice", 30);
        Person person2 = new Person("Bob", 25);

        // Adding key-value pairs to the Dictionary with Person as the key
        dict.put(person1, "Engineer");
        dict.put(person2, "Doctor");

        // Printing the original Dictionary
        System.out.println("Original Dictionary: " + dict);

        // Removing a Person object using the remove method
        String removedValue = dict.remove(person1);

        // Printing the Dictionary after removal
        System.out.println("After removing 'Alice': " + dict);

        // Displaying the removed value
        System.out.println("Removed value for 'Alice': " + removedValue);
    }
}

```

Explanation:

- We define a custom `Person` class, override the `equals()` and `hashCode()` methods to compare objects based on their properties.
- We then use `Person` objects as the keys in the dictionary.
- `remove(person1)` removes the key-value pair where the key is the `person1` object.
- The removed value ("`Engineer`") is returned and displayed.

Creative Use of Arguments:

1. Passing Null as a Key:

If `null` is passed as the key, it will throw a `NullPointerException`, as most `Dictionary` implementations do not support `null` keys. But let's demonstrate what happens:

```
import java.util.*;

public class DictionaryExample {
    public static void main(String[] args) {
        // Creating a Dictionary object
        Dictionary<String, Integer> dict = new Hashtable<>();

        // Adding key-value pairs to the Dictionary
        dict.put("apple", 10);
        dict.put("banana", 20);

        // Attempting to remove a null key (will throw NullPointerException)
        try {
            dict.remove(null);
        } catch (NullPointerException e) {
            System.out.println("Caught NullPointerException when removing null key!");
        }
    }
}
```

Explanation:

- The code attempts to remove a `null` key, but since `Hashtable` doesn't allow `null` keys, it throws a `NullPointerException`.

Summary:

- The `remove(Object key)` method is useful for removing key-value pairs from a `Dictionary`.

- It returns the value associated with the key, or `null` if the key is not found.
- Different types of keys can be used, including custom objects, but ensure proper `equals()` and `hashCode()` implementations.

This should provide you with a solid understanding of the `remove(Object key)` method in `Dictionary` from basic to advanced examples. Feel free to experiment with other custom types as keys to enhance your understanding!

clear()

The `clear()` method is an essential function in the Java `Dictionary` interface, which is a part of the `java.util` package. It is used to remove all key-value pairs from the dictionary, essentially clearing the dictionary's contents.

Definition:

The `clear()` method removes all the elements from the dictionary, leaving it empty.

Syntax:

```
public void clear();
```

Arguments:

- The `clear()` method does not take any arguments.

Return Type:

- It has a `void` return type, meaning it does not return any value.

Example Code with Detailed Comments (from beginner to advanced):

```
import java.util.Hashtable;
```

```
public class DictionaryClearExample {
```

```

public static void main(String[] args) {

    // Step 1: Creating a dictionary (Hashtable in this case)
    // A Hashtable is a concrete implementation of the Dictionary interface.
    Hashtable<String, String> dictionary = new Hashtable<>();

    // Step 2: Adding key-value pairs to the dictionary
    dictionary.put("Apple", "A fruit that is round and often red or green.");
    dictionary.put("Banana", "A long, curved fruit with a yellow skin.");
    dictionary.put("Carrot", "A root vegetable, usually orange in color.");

    // Printing the dictionary before calling clear()
    System.out.println("Dictionary before clear(): " + dictionary);

    // Step 3: Using the clear() method to remove all key-value pairs
    // The clear() method will remove all entries from the dictionary.
    dictionary.clear();

    // Printing the dictionary after calling clear()
    System.out.println("Dictionary after clear(): " + dictionary);

    // The dictionary is now empty.
    // As the dictionary is cleared, it will print an empty collection: {}.
}
}

```

Explanation:

1. **Creating a Dictionary:** We used `Hashtable` as a concrete implementation of the `Dictionary` interface.
 2. **Adding Key-Value Pairs:** We used `put()` to insert key-value pairs into the dictionary. For example, "Apple" is mapped to its definition.
 3. **Using `clear()`:** The `clear()` method is called to remove all elements in the dictionary.
 4. **Before and After `clear()`:** The dictionary is printed before and after calling `clear()`, showing how all elements are removed.
-

Creative Examples for Different Argument Values:

While `clear()` doesn't take any arguments, we can creatively experiment by adding different data types to the dictionary to see how `clear()` works with them.

Example 1: Clearing a Dictionary with Integer Values

```
import java.util.Hashtable;

public class IntegerDictionaryClear {
    public static void main(String[] args) {
        Hashtable<String, Integer> numberDict = new Hashtable<>();
        numberDict.put("One", 1);
        numberDict.put("Two", 2);
        numberDict.put("Three", 3);

        System.out.println("Number Dictionary before clear(): " + numberDict);

        numberDict.clear(); // Clears the dictionary

        System.out.println("Number Dictionary after clear(): " + numberDict); // Empty dictionary
    }
}
```

Example 2: Clearing a Dictionary with Custom Objects

```
import java.util.Hashtable;

class Person {
    String name;
    int age;

    Person(String name, int age) {
        this.name = name;
        this.age = age;
    }

    @Override
    public String toString() {
        return name + " (" + age + " years old)";
    }
}

public class CustomObjectDictionaryClear {
    public static void main(String[] args) {
```

```

Hashtable<String, Person> peopleDict = new Hashtable<>();
peopleDict.put("Person1", new Person("Alice", 25));
peopleDict.put("Person2", new Person("Bob", 30));

System.out.println("People Dictionary before clear(): " + peopleDict);

peopleDict.clear(); // Clears the dictionary

System.out.println("People Dictionary after clear(): " + peopleDict); // Empty dictionary
}
}

```

Example 3: Clearing a Dictionary with Mixed Data Types (String, Integer, and Object)

```

import java.util.Hashtable;

public class MixedTypeDictionaryClear {
    public static void main(String[] args) {
        Hashtable<String, Object> mixedDict = new Hashtable<>();
        mixedDict.put("Age", 25); // Integer
        mixedDict.put("Name", "Alice"); // String
        mixedDict.put("Address", new String[]{"Street 1", "City"}); // Object (Array)

        System.out.println("Mixed Dictionary before clear(): " + mixedDict);

        mixedDict.clear(); // Clears the dictionary

        System.out.println("Mixed Dictionary after clear(): " + mixedDict); // Empty dictionary
    }
}

```

Key Takeaways:

- **clear()** is a straightforward but useful method to clear all entries in a dictionary (or any implementation of the **Dictionary** interface).
- It doesn't take any arguments and has a void return type.
- You can use this method on any **Dictionary** implementation like **Hashtable** or **Properties**.

This method is crucial when you want to reset the dictionary without creating a new one.