

## 2092. Find All People With Secret

Hard

Topics

Companies

Hint

You are given an integer  $n$  indicating there are  $n$  people numbered from  $0$  to  $n - 1$ . You are also given a **0-indexed** 2D integer array `meetings` where `meetings[i] = [xi, yi, timei]` indicates that person  $x_i$  and person  $y_i$  have a meeting at `timei`. A person may attend **multiple meetings** at the same time. Finally, you are given an integer `firstPerson`.

Person  $0$  has a **secret** and initially shares the secret with a person `firstPerson` at time  $0$ . This secret is then shared every time a meeting takes place with a person that has the secret. More formally, for every meeting, if a person  $x_i$  has the secret at `timei`, then they will share the secret with person  $y_i$ , and vice versa.

The secrets are shared **instantaneously**. That is, a person may receive the secret and share it with people in other meetings within the same time frame.

Return *a list of all the people that have the secret after all the meetings have taken place*. You may return the answer in **any order**.

### Example 1:

**Input:** `n = 6, meetings = [[1,2,5],[2,3,8],[1,5,10]], firstPerson = 1`

**Output:** `[0,1,2,3,5]`

**Explanation:**

At time  $0$ , person  $0$  shares the secret with person  $1$ .

At time  $5$ , person  $1$  shares the secret with person  $2$ .

At time  $8$ , person  $2$  shares the secret with person  $3$ .

At time  $10$ , person  $1$  shares the secret with person  $5$ .

Thus, people  $0, 1, 2, 3$ , and  $5$  know the secret after all the meetings.

### Example 2:

**Input:** `n = 4, meetings = [[3,1,3],[1,2,2],[0,3,3]], firstPerson = 3`

**Output:** `[0,1,3]`

**Explanation:**

At time  $0$ , person  $0$  shares the secret with person  $3$ .

At time  $2$ , neither person  $1$  nor person  $2$  know the secret.

At time  $3$ , person  $3$  shares the secret with person  $0$  and person  $1$ .

Thus, people  $0, 1$ , and  $3$  know the secret after all the meetings.

### Example 3:

**Input:** `n = 5, meetings = [[3,4,2],[1,2,1],[2,3,1]], firstPerson = 1`

**Output:** `[0,1,2,3,4]`

#### Explanation:

At time 0, person 0 shares the secret with person 1.

At time 1, person 1 shares the secret with person 2, and person 2 shares the secret with person 3.

Note that person 2 can share the secret at the same time as receiving it.

At time 2, person 3 shares the secret with person 4.

Thus, people 0, 1, 2, 3, and 4 know the secret after all the meetings.

### Constraints:

- `2 <= n <= 105`
- `1 <= meetings.length <= 105`
- `meetings[i].length == 3`
- `0 <= xi, yi <= n - 1`
- `xi != yi`
- `1 <= timei <= 105`
- `1 <= firstPerson <= n - 1`

## Python:

class Solution:

```
def findAllPeople(self, n: int, meetings: List[List[int]], firstPerson: int) -> List[int]:
```

```
    groups = [i for i in range(n)]
```

```
    groups[firstPerson] = 0
```

```
    meetings.sort(key=lambda x: x[2])
```

```
    size = len(meetings)
```

```
    i = 0
```

```
    while i < size:
```

```
        current_time = meetings[i][2]
```

```
        temp = []
```

```

while i < size and meetings[i][2] == current_time:
    g1 = self.find(groups, meetings[i][0])
    g2 = self.find(groups, meetings[i][1])
    groups[max(g1, g2)] = min(g1, g2)
    temp.extend([meetings[i][0], meetings[i][1]])
    i += 1
for j in temp:
    if self.find(groups, j) != 0:
        groups[j] = j

result = []
for j in range(n):
    if self.find(groups, j) == 0:
        result.append(j)

return result

def find(self, groups: List[int], index: int) -> int:
    while index != groups[index]:
        index = groups[index]
    return index

```

## JavaScript:

```

/**
 * @param {number} n
 * @param {number[][]} meetings
 * @param {number} firstPerson
 * @return {number[]}
 */
var findAllPeople = function(n, meetings, firstPerson) {
    const find = (groups, index) => {
        while (index !== groups[index]) {
            index = groups[index];
        }
        return index;
    };

    let groups = new Array(100000).fill(0).map((_, i) => i);
    let result = [];

    groups[firstPerson] = 0;

    meetings.sort((a, b) => a[2] - b[2]);

```

```

let i = 0;
while (i < meetings.length) {
    let currentTime = meetings[i][2];
    let temp = [];
    while (i < meetings.length && meetings[i][2] === currentTime) {
        let g1 = find(groups, meetings[i][0]);
        let g2 = find(groups, meetings[i][1]);
        groups[Math.max(g1, g2)] = Math.min(g1, g2);
        temp.push(meetings[i][0]);
        temp.push(meetings[i][1]);
        ++i;
    }
    for (let j = 0; j < temp.length; ++j) {
        if (find(groups, temp[j]) !== 0) {
            groups[temp[j]] = temp[j];
        }
    }
}

for (let j = 0; j < n; ++j) {
    if (find(groups, j) === 0) {
        result.push(j);
    }
}

return result;
};

```

## Java:

```

class Solution {
    public List<Integer> findAllPeople(int n, int[][] meetings, int firstPerson) {
        int[] groups = new int[100000];
        List<Integer> result = new ArrayList<>();
        List<Integer> temp = new ArrayList<>();

        for (int i = 0; i < n; ++i) groups[i] = i;
        groups[firstPerson] = 0;

        Arrays.sort(meetings, (a, b) -> Integer.compare(a[2], b[2]));

        int i = 0;
        while (i < meetings.length) {
            int currentTime = meetings[i][2];

```

```

temp.clear();
while (i < meetings.length && meetings[i][2] == currentTime) {
    int g1 = find(groups, meetings[i][0]);
    int g2 = find(groups, meetings[i][1]);
    groups[Math.max(g1, g2)] = Math.min(g1, g2);
    temp.add(meetings[i][0]);
    temp.add(meetings[i][1]);
    ++i;
}
for (int j = 0; j < temp.size(); ++j) {
    if (find(groups, temp.get(j)) != 0) {
        groups[temp.get(j)] = temp.get(j);
    }
}
}

for (int j = 0; j < n; ++j) {
    if (find(groups, j) == 0) result.add(j);
}

return result;
}

private int find(int[] groups, int index) {
    while (index != groups[index]) index = groups[index];
    return index;
}
}

```