

2654. Minimum Number of Operations to Make All Array Elements Equal to 1

Solved 

Medium

 Topics

 Companies

 Hint

You are given a **0-indexed** array `nums` consisting of **positive** integers. You can do the following operation on the array **any** number of times:

- Select an index `i` such that $0 \leq i < n - 1$ and replace either of `nums[i]` or `nums[i+1]` with their gcd value.

Return *the **minimum** number of operations to make all elements of `nums` equal to 1*. If it is impossible, return `-1`.

The gcd of two integers is the greatest common divisor of the two integers.

Example 1:

Input: `nums = [2,6,3,4]`

Output: 4

Explanation: We can do the following operations:

- Choose index `i = 2` and replace `nums[2]` with `gcd(3,4) = 1`.
Now we have `nums = [2,6,1,4]`.
- Choose index `i = 1` and replace `nums[1]` with `gcd(6,1) = 1`.
Now we have `nums = [2,1,1,4]`.
- Choose index `i = 0` and replace `nums[0]` with `gcd(2,1) = 1`.
Now we have `nums = [1,1,1,4]`.
- Choose index `i = 2` and replace `nums[3]` with `gcd(1,4) = 1`.
Now we have `nums = [1,1,1,1]`.

Example 2:

Input: `nums = [2,10,6,14]`

Output: -1

Explanation: It can be shown that it is impossible to make all the elements equal to 1.

Constraints:

- `2 <= nums.length <= 50`
- `1 <= nums[i] <= 106`

Python:

class Solution:

```
def minOperations(self, nums: List[int]) -> int:
    n = len(nums)
    # check if there is 1 in `nums`
    ones = nums.count(1)
    # if so, we can make all the other elements equal to 1 with one operation each
    # e.g. [2,6,1,4] -> [2,1,1,4] -> [1,1,1,4] -> [1,1,1,1]
    # the number of operation to make all equal to 1 is simply n - number of 1s
    if ones: return n - ones
    res = inf
    # try finding the shortest subarray with a gcd equal to 1.
    for i in range(n):
        # subarray starting from i
        g = nums[i]
        # try each element after i
        for j in range(i + 1, n):
            # to calculate gcd
            g = gcd(g, nums[j])
            # if the gcd is 1
            if g == 1:
                # then we calculate the min ops
                res = min(res, j - i)
    # no result -> return -1
    if res == inf: return -1
    # otherwise, return res + n - 1
    # i.e. the min ops to turn the shortest subarray to 1 +
    # use that 1 to convert n - 1 elements to 1
    return res + n - 1
```

JavaScript:

```
var minOperations = function (nums) {
    const n = nums.length;
    let num1 = 0;
    let g = 0;

    const gcd = (a, b) => {
```

```

    while (b !== 0) {
        const temp = b;
        b = a % b;
        a = temp;
    }
    return a;
};

for (const x of nums) {
    if (x === 1) {
        num1++;
    }
    g = gcd(g, x);
}

if (num1 > 0) {
    return n - num1;
}
if (g > 1) {
    return -1;
}

let minLen = n;
for (let i = 0; i < n; i++) {
    let currentGcd = 0;
    for (let j = i; j < n; j++) {
        currentGcd = gcd(currentGcd, nums[j]);
        if (currentGcd === 1) {
            minLen = Math.min(minLen, j - i + 1);
            break;
        }
    }
}
return minLen + n - 2;
};

```

Java:

```

class Solution {
    public int minOperations(int[] nums) {
        int n = nums.length;
        // check if there is 1 in `nums`
        int ones = 0;
        for (int num : nums) {
            if (num == 1) {

```

```

        ones++;
    }
}
// if so, we can make all the other elements equal to 1 with one operation each
// e.g. [2,6,1,4] -> [2,1,1,4] -> [1,1,1,4] -> [1,1,1,1]
// the number of operation to make all equal to 1 is simply n - number of 1s
if (ones > 0) {
    return n - ones;
}
int res = Integer.MAX_VALUE;
// try finding the shortest subarray with a gcd equal to 1.
for (int i = 0; i < n; i++) {
    // subarray starting from i
    int g = nums[i];
    // try each element after i
    for (int j = i + 1; j < n; j++) {
        // to calculate gcd
        g = gcd(g, nums[j]);
        // if the gcd is 1
        if (g == 1) {
            // then we calculate the min ops
            res = Math.min(res, j - i);
        }
    }
}
// no result -> return -1
if (res == Integer.MAX_VALUE) {
    return -1;
}
// otherwise, return res + n - 1
// i.e. the min ops to turn the shortest subarray to 1 +
// use that 1 to convert n - 1 elements to 1
return res + n - 1;
}

private int gcd(int a, int b) {
    if (a == 0) {
        return b;
    }
    return gcd(b % a, a);
}
}

```