

## 2141. Maximum Running Time of N Computers

Solved 

Hard

Topics

Companies

Hint


You have  $n$  computers. You are given the integer  $n$  and a **0-indexed** integer array `batteries` where the  $i^{\text{th}}$  battery can **run** a computer for `batteries[i]` minutes. You are interested in running **all**  $n$  computers **simultaneously** using the given batteries.

Initially, you can insert **at most one battery** into each computer. After that and at any integer time moment, you can remove a battery from a computer and insert another battery **any number of times**. The inserted battery can be a totally new battery or a battery from another computer. You may assume that the removing and inserting processes take no time.

Note that the batteries cannot be recharged.

Return the **maximum** number of minutes you can run **all** the  $n$  computers **simultaneously**.

### Example 1:



**Input:**  $n = 2$ , `batteries = [3,3,3]`

**Output:** 4

#### Explanation:

Initially, insert battery 0 into the first computer and battery 1 into the second computer.


After two minutes, remove battery 1 from the second computer and insert battery 2 instead. Note that battery 1 can still run for one minute.

At the end of the third minute, battery 0 is drained, and you need to remove it from the first computer and insert battery 1 instead.

By the end of the fourth minute, battery 1 is also drained, and the first computer is no longer running.

We can run the two computers simultaneously for at most 4 minutes, so we return 4.

### Example 2:



**Input:** `n = 2, batteries = [1,1,1,1]`

**Output:** `2`

**Explanation:**

Initially, insert battery 0 into the first computer and battery 2 into the second computer.

After one minute, battery 0 and battery 2 are drained so you need to remove them and insert battery 1 into the first computer and battery 3 into the second computer.

After another minute, battery 1 and battery 3 are also drained so the first and second computers are no longer running.

We can run the two computers simultaneously for at most 2 minutes, so we return 2.

**Constraints:**

- `1 <= n <= batteries.length <= 105`
- `1 <= batteries[i] <= 109`

## Python:

class Solution:

```
def maxRunTime(self, n: int, batteries: List[int]) -> int:
```

```
    batteries.sort()
```

```
    extra = sum(batteries[: -n])
```

```
    batteries = batteries[-n:]
```

```
    ans = prefix = 0
```

```
    for i, x in enumerate(batteries):
```

```
        prefix += x
```

```
        if i+1 < len(batteries) and batteries[i+1]*(i+1) - prefix > extra: return (prefix + extra) //
```

```
    (i+1)
```

```
    return (prefix + extra) // n
```

## JavaScript:

```
/**
```

```
 * @param {number} n
```

```
 * @param {number[]} batteries
```

```
 * @return {number}
```

```
*/
```

```

var maxRunTime = function(n, batteries) {
    batteries.sort((a, b) => a - b);
    let left = 1, right = Math.floor(batteries.reduce((a, b) => a + b) / n);
    while (left < right) {
        let target = right - Math.floor((right - left) / 2);
        let total = batteries.reduce((a, b) => a + Math.min(b, target), 0);
        if (total >= target * n) {
            left = target;
        } else {
            right = target - 1;
        }
    }
    return left;
};

```

## Java:

```

class Solution {
    public long maxRunTime(int n, int[] A) {
        Arrays.sort(A);
        long sum = 0;
        for (int a: A)
            sum += a;
        int k = 0, na = A.length;
        while (A[na - 1 - k] > sum / (n - k))
            sum -= A[na - 1 - k++];
        return sum / (n - k);
    }
}

```