

Arrays

1. Array Creation and Accessing Elements Array Creation Arrays in JavaScript are used to store multiple values in a single variable. You can create arrays in several ways: • Using Array Literals:

```
let fruits = ['apple', 'banana', 'cherry'];
```

• Using the Array Constructor:

```
let numbers = new Array(10); // Creates an array with 10 empty slots let colors = new Array('red', 'green', 'blue'); // Creates an array with specified elements
```

Accessing Elements • Access array elements using their index (starting from 0):

```
console.log(fruits[0]); // Output: apple console.log(fruits[2]); // Output: cherry
```

• Modify an element by assigning a new value:

```
fruits[1] = 'mango'; // Changes banana to mango
```

2. Common Array Methods push() • Adds one or more elements to the end of the array. • Returns the new length of the array.

```
let numbers = [1, 2, 3]; numbers.push(4); // [1, 2, 3, 4]
```

pop() • Removes the last element of the array. • Returns the removed element.

```
let numbers = [1, 2, 3, 4]; let last = numbers.pop(); // last = 4, numbers = [1, 2, 3]
```

shift() • Removes the first element of the array. • Returns the removed element.

```
let numbers = [1, 2, 3]; let first = numbers.shift(); // first = 1, numbers = [2, 3]
```

unshift() • Adds one or more elements to the beginning of the array. • Returns the new length of the array.

```
let numbers = [2, 3]; numbers.unshift(1); // [1, 2, 3]
```

3. Iterating Over Arrays forEach() • Executes a provided function once for each array element. • Does not return a new array.

```
let numbers = [1, 2, 3]; numbers.forEach(num => console.log(num)); // Output: 1 2 3
```

map() • Creates a new array by applying a function to each element. • Does not modify the original array.

```
let numbers = [1, 2, 3]; let squares = numbers.map(num => num * num); // [1, 4, 9]
```

`filter()` • Creates a new array with elements that pass the provided condition (test). • Does not modify the original array.

```
let numbers = [1, 2, 3, 4]; let evens = numbers.filter(num => num % 2 === 0); // [2, 4]
```

Method	Purpose	Modifies Original Array?	Returns?
<code>push()</code>	Add elements to the end	Yes	New array length
<code>pop()</code>	Remove the last element	Yes	Removed element
<code>shift()</code>	Remove the first element	Yes	Removed element
<code>unshift()</code>	Add elements to the beginning	Yes	New array length
<code>forEach()</code>	Iterate over elements	No	Undefined
<code>map()</code>	Create a new array with modified values	No	New array
<code>filter()</code>	Create a new array based on a condition	No	New array

-

Using Array Literals:

```
let fruits = ['apple', 'banana', 'cherry'];
```

-

Using the Array Constructor:

```
let numbers = new Array(10); // Creates an array with 10 empty slots
let colors = new Array('red', 'green', 'blue'); // Creates an array with specified elements
```

-

Access array elements using their index (starting from 0):

```
console.log(fruits[0]); // Output: apple
console.log(fruits[2]); // Output: cherry
```

-

Modify an element by assigning a new value:

```
fruits[1] = 'mango'; // Changes banana to mango
```

-

Adds one or more elements to the end of the array.

-

Returns the new length of the array.

```
let numbers = [1, 2, 3];  
numbers.push(4); // [1, 2, 3, 4]
```

-

Removes the last element of the array.

-

Returns the removed element.

```
let numbers = [1, 2, 3, 4];  
let last = numbers.pop(); // last = 4, numbers = [1, 2, 3]
```

-

Removes the first element of the array.

-

Returns the removed element.

```
let numbers = [1, 2, 3];  
let first = numbers.shift(); // first = 1, numbers = [2, 3]
```

-

Adds one or more elements to the beginning of the array.

-

Returns the new length of the array.

```
let numbers = [2, 3];  
numbers.unshift(1); // [1, 2, 3]
```

-

Executes a provided function once for each array element.

-

Does not return a new array.

```
let numbers = [1, 2, 3];  
numbers.forEach(num => console.log(num)); // Output: 1 2 3
```

- Creates a new array by applying a function to each element.
- Does not modify the original array.

```
let numbers = [1, 2, 3];  
let squares = numbers.map(num => num * num); // [1, 4, 9]
```

- Creates a new array with elements that pass the provided condition (test).
- Does not modify the original array.

```
let numbers = [1, 2, 3, 4];  
let evens = numbers.filter(num => num % 2 === 0); // [2, 4]
```