

Assume you are good guide/explainer to the beginner and expert in finding elements in web pages using css selector then provide all possible ways to use **css selector** from beginner to advanced

Absolutely, Routh Kiran! If you're aiming to **master CSS selectors for finding elements on web pages**—especially useful in automation testing (e.g., **Selenium**, **Cypress**, **Playwright**)—here's a **complete guide from beginner to expert level** with syntax, examples, and best practices.

✅ Beginner Level – Basic CSS Selectors

1. Tag Selector

Selects all elements of a given tag.

`input`

✓ Matches all `<input>` elements.

2. ID Selector

Selects an element with a specific `id`.

`#username`

✓ Matches: `<input id="username" />`

3. Class Selector

Selects all elements with a given `class`.

.login-button

✓ Matches: `<button class="login-button">Login</button>`

4. Universal Selector

Selects all elements.

*

✓ Matches everything on the page.

5. Group Selector

Combines multiple selectors using commas.

input, select, textarea

✓ Selects all three input-related fields.

✓ Intermediate Level – Attribute Selectors

6. Element with Attribute

input[type]

✓ Matches any input element with a `type` attribute.

7. Attribute Equals

input[type="text"]

✓ Matches: `<input type="text" />`

8. Attribute Starts With

`input[placeholder^="Enter"]`

✓ Matches: `<input placeholder="Enter your name" />`

9. Attribute Ends With

`input[placeholder$="name"]`

✓ Matches: `<input placeholder="Your name" />`

10. Attribute Contains

`input[placeholder*="user"]`

✓ Matches: `<input placeholder="Enter username" />`

Advanced Level – Combinators and Relationships

11. Descendant Selector

`form input`

✓ Matches all `<input>` inside a `<form>` (any level deep).

12. Child Selector

`form > input`

✓ Matches **only direct** child `<input>` under `<form>`.

13. Adjacent Sibling Selector

label + input

- ✓ Matches the first `<input>` immediately after `<label>`.

14. General Sibling Selector

label ~ input

- ✓ Matches all `<input>` elements that follow a `<label>` (not necessarily immediate).

✓ Expert Level – Pseudo-classes and Functions

15. First Child

ul li:first-child

- ✓ Matches the first `` in every ``.

16. Last Child

ul li:last-child

17. Nth Child

table tr:nth-child(2)

- ✓ Matches the second row of each table.

18. Nth of Type

div p:nth-of-type(2)

- ✓ Second `<p>` under each `<div>` (ignores other tags).
-

19. Not Selector

input:not([type="submit"])

- ✓ Matches all `<input>` elements **except** `type="submit"`.
-

20. Empty Selector

div:empty

- ✓ Matches `<div></div>` with no child nodes or text.
-

Expert++ Level – Multiple Attributes, Complex Chains

21. Multiple Attribute Match

input[type="text"][name="username"]

22. Nested & Hierarchical Selectors

div.container form#loginForm input.login-input[type="text"]

- ✓ Matches very specific element inside a structure.
-

23. Class Selector Chaining

.btn.primary.large

- ✓ Matches element with **all** three classes.
-

24. Combining with `:not()`

`button:not(.disabled):not([type="reset"])`

- ✓ All buttons except those disabled or reset type.
-

25. Complex Example (Real-world usage)

`div#main .card:nth-child(2) > h2.title[role="heading"]`

- ✓ A very specific heading inside the second card of a main div.
-

✓ CSS Selector Best Practices in Automation

Tip	Why
Prefer ID over Class	IDs are unique and faster
Avoid overly complex selectors	They break easily with UI changes
Use <code>data-*</code> attributes if available	Made for testing, e.g., <code>data-test="submit"</code>
Avoid using indexes like <code>nth-child()</code> too much	They are brittle on dynamic pages
Use chaining for precision but avoid too much nesting	Balance between precision and maintainability

✓ Tools to Test CSS Selectors

Chrome DevTools Console:

```
document.querySelector('input[name="email"]')
```

1.

Cypress:

```
cy.get('input[type="text"]')
```

2.

Selenium (Java):

```
driver.findElement(By.cssSelector("input[type='text']"));
```







3.

Playwright:

```
page.locator('button.login')
```

4.

Bonus: CSS Selector vs XPath

Feature	CSS Selector	XPath
Syntax	Simpler	More powerful
Readability	High	Low (for beginners)
Performance	Faster	Slower (usually)
Backward Navigation	 No	 Yes (. . parent)
Starts With / Contains	 Yes	 Yes
Use in Cypress	 Preferred	 Not supported

If you'd like, I can provide **practice questions**, **real-world examples**, or even a **mini-project** where you practice finding elements using all these selectors in a dummy page.

Would you like that?