

## COVERAGE CHART/ESTIMATING GUIDE

1. Figures shown are in pieces - all 12 long<sup>ft</sup> 2. 5% cutting and fitting waste factor included 3. Computations based on minimum overlap of 1-1/4 4. Actual usage subject to variables such as building design and installers


COVERAGE AREA LESS OPENINGS		HARDIPLANK <sup>®</sup> WIDTH									
		(exposure)	5-1/4 (4)	6-1/4 (5)	7-1/4 (6)	7-1/2 (6-1/4)	8 (6-3/4)	8-1/4 (7)	9-1/4 (8)	9-1/2" (8-1/4)	12" (10-3/4)
100 sf	1 SQ		26	21	18	17	16	15	13	13	10
200 sf	2 SQ		53	42	35	34	31	30	26	25	20
300 sf	3 SQ		79	63	53	50	47	45	39	38	29
400 sf	4 SQ		105	84	70	67	62	60	53	51	39
500 sf	5 SQ		131	105	88	84	78	75	66	64	49
600 sf	6 SQ		158	126	105	101	93	90	79	76	59
700 sf	7 SQ		184	147	123	118	109	108	92	89	68
800 sf	8 SQ		210	168	140	134	124	120	105	102	78
900 sf	9 SQ		236	189	158	151	140	135	118	115	88
1000 sf	10 SQ		263	210	175	168	156	150	131	127	98
1100 sf	11 SQ		289	231	193	185	171	165	144	140	107
1200 sf	12 SQ		315	252	210	202	187	180	158	153	117
1300 sf	13 SQ		341	273	228	218	202	195	171	165	127
1400 sf	14 SQ		368	294	245	235	218	210	184	178	137
1500 sf	15 SQ		394	315	263	252	233	225	197	191	147
1600 sf	16 SQ		420	336	280	269	249	240	210	204	156
1700 sf	17 SQ		446	357	298	286	264	255	223	216	166
1800 sf	18 SQ		473	378	315	302	280	270	236	229	176
1900 sf	19 SQ		499	399	333	319	296	285	249	242	186
2000 sf	20 SQ		525	420	350	336	311	300	263	255	195
2100 sf	21 SQ		551	441	368	353	327	315	276	267	205
2200 sf	22 SQ		578	462	385	370	342	330	289	280	215
2300 sf	23 SQ		604	483	403	386	358	345	302	293	225
2400 sf	24 SQ		630	504	420	403	373	360	315	305	234
2500 sf	25 SQ		656	525	438	420	389	375	328	318	244
2600 sf	26 SQ		683	546	455	437	404	390	341	331	254
2700 sf	27 SQ		709	567	473	454	420	405	354	344	264
2800 sf	28 SQ		735	588	490	470	436	420	368	356	273
2900 sf	29 SQ		761	609	508	487	451	435	381	369	283
3000 sf	30 SQ		788	630	525	504	467	450	394	382	293

NOTES AND CALCULATIONS: ((sq ft exposure) x 1.05 = number of boards)

## FINISHING HARDIPLANK:

## Patching:

Dents, chips and cracks can be filled with a cementitious patching compound.



## Caulking:

A high quality, paintable caulk is recommended. For best results use caulks that comply with either ASTM C 834 or ASTM C 920. Caulking should be applied in accordance with caulking manufacturers written instructions. (Leave 1/8" gap at trim for caulk. Caulking at butt joints is optional.)



## Painting:

James Hardie products must be painted. For best results install Hardiplank siding with our exclusive Prime Plus<sup>®</sup> factory priming system and a 100% acrylic topcoat (s). \* If our Prime Plus<sup>®</sup> factory priming is not being used, Hardie recommends the application of an alkali-resistant primer along with 100% acrylic topcoat (s).

(For paint manufacturers paint specifications, refer to JH Technical Bulletin No. S-100.)

\*Note: Please refer to paint manufacturers specifications for application rates.

