Deployment stack, not model: a reproducibility audit harness for LLM-assisted evidence extraction in environmental assessment

Lucas Rover[a,*], Yara de Souza Tadano[a]

[a] *Universidade Tecnológica Federal do Paraná (UTFPR), Curitiba, PR, Brazil*

Abstract

Environmental evidence bases are increasingly assembled with large language models, on the assumption that identical inputs yield identical outputs. We test that assumption with an open audit harness on a screening-and-extraction pipeline over 500 abstracts on fine particulate matter and respiratory health: six deployment stacks, ten runs each (35,636 of 36,000 calls). Local stacks reproduced exactly (Exact Match Rate 1.000); API-served stacks reached 0.150–0.470 on extraction at temperature zero, the most reproducible accepting no seed. Identical LLaMA weights served locally and in the cloud disagreed on 39% of jointly decided abstracts, all in one direction. Neither a fixed-slot prompt nor a decision model returning probabilities removed the variation. Schema conformance was independent of reproducibility (local stacks: 38–43%). A client that logged temperature zero while transmitting 1.0 shows that provenance must record the transmitted payload. Harness, run cards and gold standard (κ=0.529) are released.

Keywords: reproducibility, large language models, deployment stack,

*Corresponding author.

Email address: lucasrover@alunos.utfpr.edu.br (Lucas Rover)

evidence synthesis, quality assurance, provenance, environmental assessment

---

Software and data availability

Name: `llm-repro-harness` — a reproducibility audit harness for LLM-assisted evidence extraction.

Developers: L. Rover and Y. de Souza Tadano, Universidade Tecnológica Federal do Paraná, Curitiba, Brazil. Contact: `lucasrover@alunos.utfpr.edu.br`.

Year first available: 2026.

Hardware required: any POSIX workstation for the audit and analysis layer. Reproducing the local-stack arm additionally requires a machine able to serve 7–9B-parameter models; ours was an Apple M4 with 24 GB unified memory. The API arm requires only network access and provider credentials.

Software required: Python 3.14; Ollama v0.15.5 for the local arm. Dependencies are pinned in `requirements-lock.txt`.

Program language: Python.

Program size: approximately 11,000 lines; the test suite collects 157 cases from 138 test functions.

Availability and cost: free and open source. Code: `https://github.com/Roverlucas/llm-evidence-synthesis-reproducibility` (MIT). Data, run cards and frozen analysis artefacts: OSF project `vr934`, `https://doi.org/10.17605/OSF.IO/VR934` (CC BY 4.0). The human labeling protocol is deposited as an immutable pre-registration, `https://doi.org/10.17605/OSF.IO/FGN3E`.

What the harness does: it wraps any set of LLM endpoints behind one

runner interface, executes a task R times under a declared configuration, and emits a call record per request (a hash of the declared configuration and input, the output hash, timestamps, token counts and, where the runner reads it back from the request body, the temperature actually sent) and a run card per execution. From those cards it computes Exact Match Rate with bootstrap intervals, pairwise disagreement, inter-run Fleiss' κ, schema conformance, and—where the task yields effect estimates—the propagation of run-to-run variation into a pooled meta-analytic result. It is designed to be pointed at a different corpus, a different schema, and a different set of endpoints than the ones audited here; the environmental evidence task in this paper is the demonstration, not the scope.

1. Introduction

1.1. Evidence Pipelines Are Becoming Software

Environmental evidence bases are increasingly assembled by software rather than by hand. Regulatory reviews, exposure assessments and air-quality standards rest on syntheses of primary literature, and the screening and extraction steps that produce them are now routinely delegated to large language models. Work in this journal has begun mapping that shift, scaling open-weight models for regulatory information extraction in the hydropower domain[1] and examining what structured tool interfaces do and do not provide for LLM-driven model calibration.[2]

That first study also illustrates the assumption this paper sets out to test, and it does so in the way the field as a whole does. Its experimental setup fixes temperature at zero *"thereby eliminating sampling variability and facil-*

itating consistent outputs across multiple experimental runs", and executes each model–method permutation once.[1] That is the conventional move: a single execution is treated as sufficient because the decoding parameters are believed to make repetition redundant. The premise is stated openly there, which is what allows it to be tested here; our question is not whether that study was well conducted but whether the premise it shares with the field survives measurement.

Delegating a pipeline step to an LLM makes that step a piece of software, and software in this journal is expected to be verifiable: the scope explicitly covers quality assurance and evaluation of models, data and procedures, backed by quantitative results. Yet the procedure being introduced here carries a property that conventional environmental software does not. A hydrological model run twice on the same inputs returns the same outputs; an LLM endpoint offers no such guarantee, and whether it happens to behave deterministically is a property of how it is served, not of the model named in the methods section. Recent work in this journal has confronted the reproducibility of geoscientific analysis pipelines directly, distinguishing methodological, results and inferential reproducibility, and cataloguing the barriers to each.[3] That catalogue already names the problem we quantify: it lists "non-deterministic model outputs from generative AI" among the barriers to computational reproducibility, and observes that the adoption of large language models introduces reproducibility challenges of a new kind. It does not measure them, and it is not a study designed to. This paper supplies the measurement for one such component, in the dimension that catalogue calls methodological reproducibility—the exact repetition of a procedure given the

same code, data and environment.

Evidence synthesis—screening the literature, extracting effect estimates and pooling them—underpins environmental standards and exposure assessments,[4, 5] and its screening and extraction steps are among the most labour-intensive parts of the work.[6] LLMs now perform those steps with accuracy approaching that of human reviewers,[7–10] and LLM-assisted synthesis is an established methodological line.[11–14] Those evaluations report accuracy from one or two runs; whether a second run returns the same output is what this paper measures. Reporting guidance is beginning to catch up: a 2025 editorial in *Research Synthesis Methods*[15] asks authors of GenAI-assisted syntheses to document random-seed values and, for commercial models, API versions and access dates. What such guidance does not yet establish—and what an audit must supply—is whether documenting those settings buys the determinism their presence implies.

1.2. The Hidden Problem: Non-Determinism

Beneath this promise lies a rarely examined assumption: *if you ask the same question twice, you should get the same answer*. In the context of LLM-assisted evidence synthesis, this means that running the same model with the same prompt, temperature, and random seed on the same abstract should produce identical screening decisions and extraction outputs every time.

This assumption does not hold in practice.

Recent work has demonstrated that commercial LLM APIs exhibit non-deterministic behavior even when configured for maximum reproducibility. Atil et al.[16] showed accuracy variations of up to 15% across repeated identical runs, with best-to-worst performance gaps reaching 70%. Klishe-

vich et al.[17] confirmed that temperature=0 does not guarantee deterministic outputs across any of the major models tested (GPT-4o, Claude 3.5, LLaMA 3.2). At a deeper level, Fu et al.[18] demonstrated that even when surface-level text appears identical, the underlying token probability distributions exhibit substantial instability, suggesting that apparent determinism may mask hidden variation. A philosophical analysis by Karelin et al.[19] traced this non-determinism to three fundamental sources: numerical precision in floating-point operations, architectural choices in distributed inference, and sampling procedures inherent to the generation process.

1.3. Why This Matters for Evidence Synthesis

The consequences of LLM non-determinism are particularly severe in evidence synthesis for three reasons.

First, decisions propagate. A screening decision that flips from "include" to "exclude" in a repeated run does not merely change one data point—it removes an entire study from downstream analysis. In meta-analysis, where pooled effect estimates are sensitive to study composition, a single inclusion change can shift a confidence interval across the null, transforming a statistically significant finding into a non-significant one.[20]

Second, extraction compounds variation. Data extraction involves free-text parsing of complex scientific results—relative risks, confidence intervals, exposure definitions, population characteristics. Even small variations in how an LLM parses "RR=1.05 (95% CI: 1.01–1.09)" can propagate through meta-analytic pooling. Gartlehner et al.[9] reported 95–97% test-retest reliability in LLM extraction, but this still implies 3–5% of extracted values may change between runs—a rate that, across hundreds of data points,

can materially alter pooled estimates.

Third, reproducibility is the foundation of scientific credibility. The broader reproducibility crisis in AI research[21–23] has already eroded trust in computational findings. When LLM-assisted reviews cannot be independently reproduced because the API returns different outputs, the scientific value of those reviews is undermined.[24–26]

1.4. The Gap We Address

Despite the rapid adoption of LLMs in evidence synthesis, **no study has systematically measured how API-level non-determinism propagates through a complete synthesis pipeline**—from abstract screening through data extraction—in an environmental evidence task.

Consider the state of current evidence. Jensen et al.[10] report 94.1% inter-session reproducibility for ChatGPT-4o extraction—an encouraging number. But this was measured with only 2 repetitions and evaluated per-field, not per-output. As we demonstrate below, applying a stricter whole-output metric across 10 repetitions yields extraction EMR as low as 15.0%—approximately 6× lower than what per-field metrics suggest. Similarly, Gartlehner et al.[9] report 95–97% test-retest reliability, but with only 2–3 repetitions and no examination of how variation compounds across pipeline stages. Studies measuring non-determinism[16, 17] do so on general NLP benchmarks, where the structured, multi-field outputs characteristic of evidence synthesis are absent. And the most influential screening evaluations[7, 8, 13] report results from a single run, implicitly assuming that a repeat would yield the same result.

We address this gap with the following contributions:

1. An open audit harness (`llm-repro-harness`) that runs any set of LLM endpoints R times under a declared configuration, emits a per-call record, and computes whole-output Exact Match Rate, pairwise disagreement, inter-run κ and schema conformance;
2. A measurement of run-to-run reproducibility for six deployment stacks over a two-stage environmental evidence pipeline (500 abstracts, 10 runs, 35,636 calls): exact reproduction on the local stacks, extraction EMR of 0.150–0.470 on the API-served stacks at temperature zero;
3. A same-weights comparison (LLaMA-3-8B local vs. cloud) showing that identical weights do not guarantee identical decisions across serving stacks (38.8% disagreement, all in one direction), scoped to what a non-byte-identical request payload allows;
4. Tests of three settings practitioners rely on—a transmitted seed, a fixed-slot output shape, and a decision model that returns probabilities—none of which removed the variation;
5. Evidence that schema conformance and accuracy are separate from reproducibility, and a documented provenance failure in which run cards recorded a temperature the client did not transmit, from which we derive reporting requirements for LLM steps in environmental workflows.

2. Related Work

2.1. LLMs in Systematic Reviews

The application of LLMs to systematic review workflows has accelerated dramatically since 2023. Oami et al.[7] evaluated GPT-4 Turbo for citation screening, reporting sensitivity of 0.75 and specificity of 0.99, with prompt

tuning improving sensitivity to 0.91. Khraisha et al.[8] extended this to multilingual screening and extraction, finding strong specificity (>0.80) but variable sensitivity across languages and review types.

For data extraction, Gartlehner et al.[9] showed that Claude 2 achieved 96.3% accuracy compared to human reviewers, with test-retest reliability of 95–97%. Jensen et al.[10] found that ChatGPT-4o achieves 92.4% extraction accuracy and 94.1% inter-session reproducibility, explicitly noting residual stochasticity across sessions.

More comprehensive pipelines have also been proposed. The TrialMind system[27] demonstrated that human-AI collaboration improved recall by 71.4% and reduced screening time by 44.2% across 100 systematic reviews. Li et al.[11] described an LLM pipeline for health technology assessment, while Matsui et al.[13] showed that a three-layer GPT-3.5/GPT-4 strategy achieved human-comparable sensitivity. Cao et al.[28] presented otto-SR, a system that automates the entire systematic review lifecycle with LLMs, demonstrating near-human performance across screening, extraction, and synthesis—yet without examining run-to-run reproducibility. Khan et al.[29] proposed a collaborative multi-LLM approach for automated data extraction in living systematic reviews, achieving high accuracy but reporting results from single executions. A recent systematic review of automated meta-analysis[30] found that 57% of studies focus on data processing tasks, yet only 2% have attempted full-process automation—underscoring that evidence synthesis remains a multi-stage pipeline where each step introduces potential variation.

A common thread across these studies is that **reproducibility is either assumed or measured only superficially**. Test-retest reliability, when

reported, is based on 2–3 repetitions and does not examine how variation propagates through multi-stage pipelines.

2.2. The Non-Determinism Problem

The phenomenon of LLM non-determinism has received increasing attention. Atil et al.[16] provided the most comprehensive analysis to date, documenting accuracy swings of up to 15% across repeated runs and introducing the TARr@N metric to quantify run-to-run stability. Klishevich et al.[17] confirmed that temperature=0 fails to ensure determinism across GPT-4o, Claude 3.5, and LLaMA 3.2 on code review tasks.

At the token level, Fu et al.[18] showed that apparent text-level agreement masks substantial distributional instability in token probabilities—a finding that suggests surface-level reproducibility metrics may underestimate true variation. Angermeir et al.[31] examined how non-determinism undermines reproducibility in software engineering research, proposing documentation standards to mitigate this.

These studies establish that non-determinism is real, measurable, and consequential. However, they focus on general-purpose tasks (benchmarks, code review, classification). Our study addresses non-determinism specifically in evidence synthesis, where structured, domain-specific outputs amplify the problem.

2.3. Reproducibility in AI Research

The broader AI reproducibility crisis has been documented extensively. Hutson[21] identified unpublished code and sensitivity to training conditions

as primary barriers. Haibe-Kains et al.[22] called for structural reform, advocating for mandatory code and model sharing. Kapoor and Narayanan[23] documented data leakage affecting 294 studies across 17 fields, while Han[24] analyzed reproducibility failures in biomedical AI through the lens of model non-determinism.

Recent frameworks have attempted to systematize reproducibility requirements. Desai et al.[25] proposed a taxonomy of reproducibility types, arguing that LLMs require "conceptual replicability" given their proprietary training data. Semmelrock et al.[26] provided a systematic overview of barriers, and Yu[32] argued that computational reproducibility alone is insufficient for trustworthy AI.

2.4. Provenance and Transparency

Provenance tracking—recording the lineage of data, computations, and decisions—has been identified as a key enabler of AI reproducibility. Longpre et al.[33] audited 1,800+ datasets, finding license omission rates above 70%. Liang et al.[34] analyzed 32,111 model cards on Hugging Face, finding that documentation of limitations and environmental impact remains sparse. The Foundation Model Transparency Index[35] scored 14 major developers across 100 indicators, finding average transparency of only 58/100.

Technical solutions for provenance include the Workflow Run RO-Crate[36] and the W3C Provenance (PROV) Data Model—a W3C Recommendation defining an interoperable standard for representing the entities, activities, and agents involved in producing a piece of data.[37] Longpre et al.[38] argued at ICML 2024 that current practices for data authenticity and provenance are "fundamentally broken," calling for comprehensive reform.

Our provenance approach builds on the lightweight protocol proposed by Rover,[20] using SHA-256 hashing of inputs, outputs, and configurations to create an auditable trail without requiring infrastructure beyond standard file storage.

2.5. Reproducibility of Environmental Modelling Workflows

Work in this journal has approached the same problem from the modelling side. Schlögl et al. distinguish methodological, results and inferential reproducibility in geoscientific analysis and list "non-deterministic model outputs from generative AI" among the barriers, without measuring it.[3] Zhu et al. assess the computational reproducibility of geo-simulation experiments workflow-wide and then process by process, a diagnosis that presumes a process behaves the same way when re-executed.[39] On the LLM side, Yoon et al. scale open-weight models for regulatory information extraction and fix temperature at zero to obtain consistent outputs from a single run,[1] and Park et al. show that a typed, range-validated tool interface gives an LLM agent control and reviewable provenance in SWAT+ calibration without guaranteeing a valid model state.[2] None of these measures whether an LLM-mediated step returns the same output when it is run again, which is the per-process property the present harness measures.

2.6. Positioning: What Existing Studies Do Not Address

Table 1 synthesizes the landscape of prior work and highlights the methodological gaps that motivate our study. Three critical gaps emerge. **First**, studies that evaluate LLMs for evidence synthesis[7, 9, 10, 13] measure accuracy against human judgments but do not measure self-consistency across

repeated runs—or do so with only 2–3 repetitions and per-field metrics that can mask whole-output variation. **Second**, studies that measure LLM non-determinism[16–18] do so on general-purpose benchmarks (classification, code review), not on the structured, domain-specific tasks characteristic of evidence synthesis. **Third**, no prior study examines how non-determinism *propagates* across a multi-stage pipeline—from screening through extraction—or compares local versus cloud deployment as a reproducibility strategy. Our study addresses all three gaps simultaneously.

Table 1: Comparison of our study with prior work. "Runs" indicates the number of repeated executions under identical conditions. "Full pipeline" indicates whether both screening and extraction were evaluated in the same study.

Study	**Domain**	**Task**	**Runs**	**Metric**	**Local**	**Cloud**	**Pipe.**
Oami (2024)	Health	Screening	1	Accuracy	—	✓	—
Oami (2025)	Health	Screening	1	Acc.+cost	✓	✓	—
Khraisha (2024)	Health	Scr.+Extr.	1	Accuracy	—	✓	—
Gartlehner (2024)	Health	Extraction	2–3	Field acc.	—	✓	—
Jensen (2025)	Health	Extraction	2	Field acc.	—	✓	—
Matsui (2024)	Health	Screening	1	Accuracy	—	✓	—
Atil (2024)	General	NLP bench.	10+	Acc. var.	—	✓	—
Klishevich (2025)	Softw.	Code review	5+	Determinism	✓	✓	—
Fu (2026)	General	Token dist.	—	Distrib.	—	✓	—
Li (2025)	Multi	Meta-anal.	—	Survey	—	—	—
Cao (2025)	Health	Full SR	1	Accuracy	—	✓	✓
Khan (2025)	Health	Extraction	1	Field acc.	—	✓	—
This study	**Env. health ($PM_{2.5}$)**	**Scr.+Extr.**	**10**	**EMR+CI**	✓	✓	✓

3. Methods

3.1. Study Design

We designed a repeated-measures experiment to isolate LLM non-determinism as the sole source of variation. We held the corpus, prompts, model configurations, and random seeds constant across all runs. The only element permitted to vary was the model's internal computation—any observed difference in outputs is therefore attributable to non-determinism in the model or its serving infrastructure.

Figure 1 provides an overview of the experimental pipeline.

3.2. Unit of Analysis: Deployment Stacks

We treat the unit of analysis as the *deployment stack*—the tuple (*model_weights*, *provider*, *infras*
rather than the model weights alone. For the three local stacks, every component of the tuple is transparent and pinned: open-weight checkpoints with verifiable hashes (LLaMA 3 8B, Mistral 7B, Gemma 2 9B), served by Ollama v0.15.5 on a single Apple M4 chip (24 GB RAM, single replica, single execution thread), through Ollama's local HTTP endpoint. For the three API-served stacks, only the provider and the client-visible API surface are observable; the underlying weight checkpoint version, GPU topology, batching policy, and intermediate-precision routines are opaque and may change without notice. This framing matters because the local-vs-cloud comparison constitutes a *partial quasi-isolation probe*: when two stacks share approximately matched weights (e.g., `meta-llama/llama-3-8b-instruct` served locally via Ollama and via DeepInfra) but differ in infrastructure and serving layer, any divergence in their outputs is attributable to the non-weight




Figure 1: Experimental pipeline. A 500-abstract PubMed corpus on $PM_{2.5}$ and respiratory health is processed by six deployment stacks: three local Ollama/Apple M4 stacks (LLaMA 3 8B, Mistral 7B, Gemma 2 9B) and three API-served stacks (Claude Sonnet 4.5/Anthropic, Gemini 2.5 Pro/Google, GPT-4.1/OpenAI). Each stack is run 10 times under identical configurations (temperature=0, fixed seed where supported). Stage A (screening) produces binary include/exclude decisions over all 500 abstracts; Stage B (extraction) produces structured JSON over the 100 INCLUDE articles. All outputs are SHA-256-hashed for provenance tracking. Reproducibility is quantified via the Exact Match Rate (EMR) with 95% percentile bootstrap confidence intervals.

components of the tuple. Throughout this paper we use "deployment stack" for the experimental unit and reserve "model" for the weights alone.

3.3. Corpus Construction

We constructed a 500-abstract corpus from PubMed covering the association between $PM_{2.5}$ and respiratory health outcomes (Supplementary Table 26). We chose this domain because it is one of the most extensively studied areas in environmental epidemiology, with Yu et al.[40] estimating approximately 1 million premature deaths annually from short-term $PM_{2.5}$ exposure. This literature is characterized by standardized reporting of relative risks with confidence intervals, well-defined exposure metrics, and time-series study designs—making it an ideal testbed for evaluating LLM extraction reproducibility.[41, 42] Prior work on particulate matter and respiratory morbidity has shown that machine learning models can capture the complex, lagged relationships between PM_{10} concentration and hospital admissions,[43] further motivating a domain where both the epidemiological patterns and the computational methods are well established.

Inclusion criteria required: (1) original epidemiological study, (2) $PM_{2.5}$ as exposure, (3) respiratory hospitalization or emergency-department visit as the outcome—mortality-only studies are *excluded*, (4) time-series or case-crossover design, (5) quantitative risk estimates, and (6) publication in English. These are the criteria as executed: they are the text of the screening prompt in `configs/prompts/screening.txt` and of the human labeling protocol, verbatim in both. Articles were sourced from PubMed using the E-utilities API with a broad query yielding 573 candidate records, supplemented by 475 exclusion candidates and a design-filtered subset of

222 records. The final corpus spans 148 journals and publication years 1994–2026, with a mean abstract length of 1,873 characters.

Gold standard construction. The 200 clear-category abstracts (100 include + 100 exclude) were labeled by an automated classification rule based on inclusion-criteria keyword matching, validated against a held-out 50-abstract validation set. No errors were observed on that set, which by the rule of three bounds the true error rate at ≈6% with 95% confidence and no tighter; we therefore report that bound rather than describing the rule as 100% precise, since zero errors in 50 trials cannot establish a zero error rate. The 300 remaining abstracts received heuristic labels from the same rule operating in low-confidence regions and are explicitly flagged as not human-validated. We do not retroactively present these heuristic labels as a human gold standard, and we therefore *exclude* them from the accuracy, sensitivity and specificity computations rather than reporting them separately: those metrics are computed against the 200 clear-category abstracts only, giving per-stack denominators of 192–200 rather than 500 (Table 3). We also record what this stratum is and is not. Of its 300 abstracts, 260 carry the maximum inclusion score of 5—the same score borne by all 100 clear-includes—and all 300 carry zero exclusion reasons. The label "ambiguous" therefore denotes low rule confidence, not measured human disagreement, and the stratum is closer in composition to the include side than the name suggests.

We additionally conducted a **dual-independent human-labeling validation** on a stratified subset of 100 abstracts (25 clear-include + 25 clear-exclude + 50 ambiguous, stratified by heuristic category × year-tertile, seed=42). The labeling protocol, screening templates, and agreement script were pre-

registered on the Open Science Framework *before* any label was collected (`https://doi.org/10.17605/OSF.IO/FGN3E`, frozen 2026-05-12; the two label sets were returned on 2026-07-15 and 2026-07-29). Two reviewers, each blinded to the other's decisions, independently classified every abstract via the protocol in Supplementary §4; we computed Cohen's κ on the 3-class outcome (include/exclude/uncertain) and on the binary include-vs.-exclude collapse. Agreement fell **below the pre-specified Cochrane target** of $\kappa \geq 0.80$: $\kappa = 0.529$ (SE=0.074, 95% CI [0.383, 0.674]) on the 3-class outcome and $\kappa = 0.556$ (95% CI [0.400, 0.712]) on the binary collapse, with 75% raw agreement and 25 discordant abstracts (confusion matrix and full agreement statistics in Supplementary §4). The shortfall against the target is itself statistically decisive ($z = -3.65$, $p = 1.3 \times 10^{-4}$), whereas $n = 100$ is not sufficient to place κ within a single descriptive band—the interval spans "fair" through "substantial"—so we report the value against the threshold rather than assigning it a label. Two objections can be foreclosed immediately. The low coefficient is not an artefact of skewed marginals: the prevalence index is 0.189 and PABAK (0.558 on the binary collapse) is nearly identical to κ, so the "kappa paradox" is not operating here. Nor is it an artefact of the three-class scale: linearly and quadratically weighted κ (0.541 and 0.548, computed on the ordinal ordering include–uncertain–exclude) move the estimate by less than 0.02. The pre-registration specified in advance what to do in this event—report the value transparently, examine the disagreement pattern qualitatively, amend the protocol to address the ambiguity, and file a sub-registration update—and we followed that sequence rather than revising the target. The disagreement is not diffuse but directional, and this

is testable: the discordant cells of the binary table are 2 versus 19 (exact McNemar p=2.2×10^{-4}), and marginal homogeneity is rejected on the full 3-class table (Stuart–Maxwell $\chi^2(2)$=16.4, p=2.7×10^{-4}), with a bias index of 0.179. One rater is systematically more inclusive than the other, which is the signature of divergent protocol reading rather than of random rater noise. The source is specific: 17 of those 19 asymmetric discordances turn on inclusion criterion 5 (a quantitative effect estimate), whose v1.1 wording supported two defensible readings—requiring the numeric estimate and interval to be present, or accepting an explicit statement that the study reported them. The v1.1 decision table compounded this by specifying outcomes for failure in two or more criteria and for a borderline single criterion, but not for clear failure in exactly one, which is precisely the configuration of those 17 abstracts. Neither rater departed from the protocol; the protocol was underspecified. Protocol v1.2 therefore splits criterion 5 into three levels: values present (criterion satisfied), the effect stated but its values absent (*uncertain*, since abstract-only screening cannot verify what the abstract omits), and no estimate or mention at all (*exclude*, since total absence is reasonable evidence that no extractable estimate exists). The amendment also separates structural criteria (original study, $PM_{2.5}$ exposure, respiratory hospitalization, English), where a single clear failure excludes, from conditional ones (design, effect reporting), where a single failure yields *uncertain* unless the information is absent rather than merely unreported. The 25 discordant items then go through a blinded recalibration. We state what that step can and cannot establish. Because re-measurement is conditioned on prior disagreement, the resulting figure is *not* a second estimate of κ and

we do not report it as one: recomputing a whole-corpus coefficient after selectively re-rating only the discordant items would drive the value upward by construction, and would cross the Cochrane threshold at a resolution rate that carries no evidential content. We therefore report it as post-hoc reconciliation agreement conditional on the initially discordant items, and κ=0.529 remains the study's agreement estimate. Establishing that the v1.2 amendment actually repairs the ambiguity would require a fresh independent sample rather than a re-rating of the same items, which we identify as the appropriate next step rather than claim as a result here. Residual discordances go to a consensus meeting, and items without consensus are settled by the senior author (Y.d.S.T.) as tie-breaker, exactly as pre-registered. Assigning that role to the senior author rather than to the first author is deliberate: the first author developed the pipeline whose outputs are scored against this gold standard, so placing final adjudication with a co-author who did not build it keeps the reference standard independent of the system under evaluation. Tie-breaks apply only to residual discordant items, are adjudicated against the written criteria without access to any model output, and are logged with the criterion invoked, so each adjudicated item remains auditable.

Stratifying agreement exposes something the pooled coefficient hides, and it bears directly on how our accuracy numbers should be read. On the 25 clear-*exclude* abstracts the two raters agreed unanimously (25/25, PABAK=1.00; κ is undefined there because expected agreement equals one—a degenerate-marginals case that is precisely why we report PABAK alongside). On the 25 clear-*include* abstracts agreement was 68% (κ=0.359), and on the 50 ambiguous abstracts 66% (κ=0.398). The automated rule's include

side fares worst under human scrutiny: of the 25 abstracts it called clearly includable, one rater endorsed inclusion for 13 and the other for 21, and 8 of the 25 discordances fall inside that stratum. The gold standard is therefore **asymmetrically valid**. Specificity rests on the unanimous exclude side and is trustworthy; sensitivity rests on include-side labels that the human raters substantially contest, and is correspondingly attenuated. We report this rather than pool it away, and we read all sensitivity figures in this paper as lower bounds.

For extraction, we constructed two independent reference standards: (a) a *silver-internal* consensus from majority vote across all 6 stacks $\times$ 10 runs (60 votes per item), and (b) a *silver-external* consensus from DeepSeek-R1 (5 runs $\times$ 100 items, majority vote per field). DeepSeek-R1 was selected for the silver-external role on three independence axes: (i) it is served by a provider outside the four tested in our main analysis, (ii) it was trained predominantly on a different (Chinese-led, mixed open/closed) corpus, and (iii) it uses an explicit-reasoning decoding paradigm distinct from the standard chat models evaluated here, which together make correlated systematic errors with the evaluated stacks unlikely. Cross-validation between these two silvers yields Spearman ρ=0.845 on `effect_estimate` and 80% agreement across numeric fields (consensus subset, see Supplementary §14), supporting their use as comparative anchors. The dual-human extraction reference is drawn from the INCLUDE items of the human gold standard, not from model output: a subset drawn from the silver-internal standard would be circular, and of the 25 items such a subset contains only 13 are included by first-round human agreement, while 15 abstracts the raters agree on are absent

from it. The overlap is reported as a result in its own right—direct evidence that LLM-based screening admits material that human raters reject—and its final value is fixed once discordance resolution closes the gold standard ([**PENDING: final overlap, rebuilt subset size, and per-field extraction agreement**]).

Because our primary metric (EMR) measures self-consistency rather than accuracy, gold-standard quality affects only the secondary accuracy analysis; we report secondary accuracy against three sources (heuristic, silver-internal, silver-external—the latter computed on the consensus subset only, see Supplementary §14; plus the dual-human gold standard for screening) to triangulate the result. Given the asymmetric validity documented above, we treat the exclude side of every accuracy comparison as firm and the include side as a lower bound.

3.4. Deployment Stacks

We selected six deployment stacks spanning local and API-served paradigms (Table 2). Each stack instantiates the tuple (*model_weights*, *provider*, *infrastructure*, *API_layer*) defined in Section 3.2. The three local stacks cover three open-weight families served on a single device; the three API-served stacks cover three proprietary providers accessed over the public network.

The three local stacks pair open-weight checkpoints—LLaMA 3 8B,[44] Mistral 7B,[45] and Gemma 2 9B[46]—with Ollama v0.15.5 on Apple M4 hardware (24 GB RAM), ensuring single-device deterministic inference with identical seed and temperature settings. The three API-served stacks accessed proprietary weights through their respective providers: Claude Sonnet 4.5[47] via the Anthropic Messages API (no seed parameter available), Gemini 2.5

Table 2: Deployment-stack configurations. The four-component tuple (*weights*, *provider*, *infrastructure*, *API_layer*) is shown across the first four columns. All local stacks were served via Ollama with deterministic settings. Claude does not expose a seed parameter; Gemini accepts seeds but does not guarantee determinism; GPT-4.1 accepts seeds via the API. Local stacks are 7–9B-parameter open-weight checkpoints; API-served weights are proprietary and approximately >100B parameters, so the local-vs-API comparison varies multiple tuple components simultaneously (see Section 4.8 for a single-component probe).

Weights	**Provider**	**Infrastructure**	**API layer**	**Temp. / Seed**	**top_p**	**Max tokens**
LLaMA 3 8B	Meta (open)	Ollama v0.15.5 / Apple M4 / single replica	local HTTP /api/generate	0 / 42	1.0	2,048
Mistral 7B	Mistral (open)	Ollama v0.15.5 / Apple M4 / single replica	local HTTP /api/generate	0 / 42	1.0	2,048
Gemma 2 9B	Google (open)	Ollama v0.15.5 / Apple M4 / single replica	local HTTP /api/generate	0 / 42	1.0	2,048
Claude Sonnet 4.5 (20250929)	Anthropic	opaque (production)	Messages API v1	0‡ / —	1.0	2,048
Gemini 2.5 Pro	Google	opaque (production)	generateContent v1	0 / 42	1.0	8,192†
GPT-4.1	OpenAI	opaque (production)	Chat Completions v1	0 / 42	1.0	2,048

†Gemini requires a higher token budget because its "thinking" tokens consume output capacity.

‡Run on 8 October 2026, with `temperature`=0 recorded per call from the transmitted payload; the five other stacks ran in February–March 2026. An execution of the same stack at the API default temperature of 1.0 is reported in the Supplement as a temperature contrast (Section 5.5).

Pro[48] via the Google AI `generateContent` API (seed set to 42), and GPT-4.1[49] via the OpenAI Chat Completions API (seed set to 42). All stacks were queried via HTTP (urllib-based, no SDK dependencies) to ensure uniform request handling. API calls included up to 2 retries with exponential backoff on timeout or rate-limit errors; retried calls may route to different server nodes, introducing a minor additional source of variation for the API-served stacks.

A decision-model stack on screening. To test whether returning a distribution instead of a sample removes run-to-run variation, we added a decision-model stack to Stage A only: TypeSafe Jev (`typesafe-ai/jev`), a model that does not generate text but answers a typed question with a choice and the probability of every option. It was called through the Vercel AI Gateway (`POST /v1/evaluate`) with the provider pinned to TypeSafe and no fallback, so every answer was served by the model named here. Each call received the same title-and-abstract string as the other stacks and one `choice` question whose instructions are the inclusion and exclusion criteria of the screening prompt, verbatim; the options were the three labels the generative stacks may return (include, exclude, uncertain). The prompt's JSON-formatting instructions were dropped, because they have no meaning for a model that returns a typed answer, and this is the one difference in the request the stack receives. Jev has no extraction mode, so it does not enter Stage B or the meta-analytic propagation. The arm comprised 10 runs $\times$ 500 abstracts, executed on 8 October 2026.

3.5. Sources of Non-Determinism in Distributed Inference

It is useful to distinguish two classes of factors that can plausibly contribute to LLM non-determinism across deployment stacks. *Cloud-deployment factors* are those intrinsic to running a model on hardware accessed over a network: end-to-end network latency, request routing across geographically distributed endpoints, shared physical hardware, and multi-tenancy isolation policies. *Production serving-infrastructure factors* are specific design choices in the LLM inference stack: tensor parallelism with non-deterministic all-reduce, FlashAttention kernel non-determinism, dynamic continuous batching that varies request composition between calls, speculative decoding fast-paths, mixed-precision (BF16/FP16) accumulation, and prefix-caching state shared across requests. These two classes are conceptually distinct: a request that traverses the network can still be served on a deterministic infrastructure, and vice versa, an infrastructure with the non-deterministic features above can be exercised under local-network conditions. Our desconfound experiment (Section 4.8) helps separate them empirically by holding the weights constant while varying the rest of the stack tuple.

Supplementary Table 27 maps six of these mechanisms onto each of the six deployment stacks studied here, classifying each cell as documented (✓), *likely* (consistent with public information from the provider's serving infrastructure), *possible* (compatible with public information but not directly confirmed), or precluded by stack design (—). Attribution is necessarily *inferential* for the API-served stacks because the production serving stacks of OpenAI, Anthropic, and Google are closed-source; the table reflects what is publicly documented or strongly implied by published architecture descrip-

tions, not what we directly measured per request.

The mapping is used in two ways in our discussion. First, the residual disagreement observed in the same-weights cloud experiment (Section 4.8) is most parsimoniously attributable to mechanisms 1–4, because mechanisms 5–6 are not standard for an 8B-parameter model under modest load. Second, the larger gap observed for the three API-served stacks of much-larger proprietary weights is consistent with all six mechanisms being active simultaneously; we therefore do not attempt single-mechanism attribution for those stacks in the present study, and we mark this as a key direction for future work (Section 5.5).

3.6. Prompt Development

Both prompt templates (Listings 1 and 2 in the Supplement) were developed iteratively over two pilot rounds before the main experiment was committed.

Round 1. An initial draft was tested on 10 randomly drawn abstracts from the corpus (5 include + 5 exclude) using LLaMA 3 8B locally. Output JSON validated against the schema for 9 of 10 calls; one failure was due to embedded Markdown code-fences. The failure case motivated the explicit instruction "Respond with a JSON object only. Do not include any text outside the JSON." in both prompts.

Round 2. The revised prompt was tested on the same 10 abstracts plus 10 additional abstracts drawn from the ambiguous stratum. Output validated for 20/20 calls. We additionally manually inspected the rationale text for coherence (no contradictions between rationale and decision); none were identified.

The final prompts were committed to the public repository on 2026-02-11 (commit `75292f2`) and held constant across all 6 stacks and all 120 experimental runs. We did not adapt prompts to individual model capabilities beyond the generic JSON-only constraint, as such adaptation would confound model-level effects with prompt-level optimization. A formal *prompt sensitivity analysis*—varying the structured-output shape (variable-length estimates array vs. fixed-slot single primary estimate)—is reported in Section 4.7.

3.7. Pipeline Stages

Each model was run 10 times through two stages:

Stage A: Abstract Screening. Each of the 500 abstracts was presented with a structured prompt requesting a JSON response containing: a binary decision (`include`/`exclude`), a confidence score (0–1), and a brief rationale. Note that LLaMA consistently processed 480 of 500 abstracts per run (the same 20 abstracts exceeded response length constraints in every run); the remaining models processed all 500. Total: 6 models $\times$ 10 runs $\times$ 500 abstracts = 30,000 screening calls.

Stage B: Data Extraction. The 100 included abstracts were presented with an extraction prompt requesting: study design, location, period, population, sample size, and a structured list of effect estimates (each with effect measure, point estimate, confidence interval, lag period, and exposure increment). LLaMA consistently processed 96 of 100 articles per run (the same 4 articles exceeded response length constraints); the remaining models processed all 100. Total: 6 models $\times$ 10 runs $\times$ 100 articles = 6,000 extraction calls.

In total, the experiment comprised **36,000 LLM calls** across **120 experiment runs**.

3.8. Reproducibility Metrics

3.8.1. Exact Match Rate (EMR)

Our primary metric is the *Exact Match Rate*, defined as the proportion of items (abstracts or articles) that received identical outputs across all 10 runs:

$$\text{EMR} = \frac{1}{N} \sum_{i=1}^{N} \mathbb{1}[\,|\{o_{i,1}, o_{i,2}, \ldots, o_{i,R}\}| = 1\,] \tag{1}$$

where N is the number of successfully processed items, R=10 is the number of runs, $o_{i,r}$ is the output for item i in run r, and $|\cdot|$ denotes the number of distinct values. For screening, $o_{i,r}$ is the binary decision; for extraction, $o_{i,r}$ is the SHA-256 hash of the full JSON output (used as a compact identity check: any character-level difference produces a different hash).

An EMR of 1.0 indicates perfect reproducibility; an EMR of 0.0 indicates that every item received at least one different output across runs. We note that extraction EMR is a strict metric—any variation in any field (including formatting differences such as "Beijing, China" vs. "Beijing") produces a non-match. The field-level analysis in Section 4.4 complements this by isolating which fields drive the variation.

3.8.2. Bootstrap Confidence Intervals

We computed 95% confidence intervals for EMR using the percentile bootstrap method with 10,000 resamples. For each bootstrap sample, we drew N items with replacement and computed the EMR, then reported the 2.5th and 97.5th percentiles of the bootstrap distribution. We note that when

EMR=1.000 (as for all local stacks), the percentile bootstrap trivially returns [1.000, 1.000]. By the rule of three, observing zero non-matches in N=500 items yields a 95% one-sided upper bound on the true non-match rate of 3/500=0.006; thus, we can rule out population-level non-determinism rates above 0.6% for local models, but not lower rates.

3.8.3. Secondary Metrics

- **Flip rate**: $1 - \text{EMR}$ (proportion of items with any variation across runs)
- **Mean agreement**: Average proportion of runs agreeing with the majority decision per item
- **Accuracy vs. gold standard**: Per-run sensitivity, specificity, and accuracy against gold standard labels (noting that 300 of the 500 labels are heuristic-based; see Limitations)
- **Field-level EMR**: For extraction, the proportion of articles with identical values for each individual field across all runs
- **Estimate count stability**: The proportion of articles for which all 10 runs extracted the same number of effect estimates—a measure of structural consistency independent of the specific values extracted

3.9. Provenance Protocol

Scope: client-side observability. The provenance protocol described below is a *client-side* instrument by design. It documents what is observable from the client side—the request payload, the resolved model identifier and

version returned by the API (when available), response headers, the client-recorded API response identifier, end-to-end latency, and the input/output text together with their cryptographic hashes. It does not require provider-side weight hashes, GPU-topology fingerprints, or batching-policy attestation, none of which are returned by any production LLM API at the time of writing. The protocol is therefore not restricted to open-source local stacks: for proprietary API-served stacks, it creates the audit trail that providers' opacity would otherwise make impossible. Its operational value is twofold: (i) *differential diagnosis*—when the same prompt produces different outputs at the same client-pinned snapshot, the logged hashes establish that the divergence is attributable to the deployment stack rather than to client-side drift in prompts, inputs, or configuration; and (ii) *provider-agnostic minimum standard*—adopting the protocol creates a verifiable audit trail across any combination of local and API-served stacks that authors may choose to use. Whether providers extend the protocol with weight-checkpoint hashes or deterministic-execution attestation is a separate question of provider commitment; the protocol functions in either case.

Following Rover,[20] we implemented a lightweight provenance protocol that creates a cryptographic fingerprint of every input-output pair, enabling automated detection of any change across runs:

- **Call-level hashing**: SHA-256 hash of a canonicalized JSON object containing five fields (prompt template, input text, model ID, temperature, seed), serialized with sorted keys and ASCII encoding to ensure deterministic hashing across platforms. Absent parameters (e.g., Claude's seed) are encoded as `null`

- **Output hashing**: SHA-256 hash of the raw response text
- **Run cards**: Structured JSON metadata per run, including timestamps, token counts, success/failure rates, and aggregate output hashes

The call hash covers the declared configuration, not the transmitted request body. For the Claude stack, each call record additionally stores the temperature read back from the request body as sent (`request_temperature`); the runners of the other stacks place the declared temperature in the request body unconditionally. The protocol is the one proposed in our companion paper,[20] which tests it across 8 models with 100 repetitions per condition on a 100-abstract corpus; the present study trades that per-condition depth for pipeline coverage (two stages, meta-analytic propagation, desconfound and fixed-slot conditions) at 10 repetitions.

This protocol enables post-hoc verification: if two runs produce different aggregate hashes, the per-call hashes pinpoint exactly which items changed.

3.10. Software and Reproducibility

All code is available at `https://github.com/Roverlucas/llm-evidence-synthesis-reprodu`

The experiment was conducted in Python 3.14 on macOS (Apple M4, 24 GB RAM). API keys are excluded from the repository; all other materials—including the corpus, prompts, schemas, and raw outputs—are publicly available.

4. Results

4.1. Overview

Local stacks reproduced every screening decision and every extraction across ten runs; API-served stacks did not, and the gap widened from screening (EMR 0.936–0.990) to extraction (0.150–0.470). All 120 experiment runs completed successfully: 60 screening runs (10 per model × 500 abstracts each) and 60 extraction runs (10 per model × 100 articles each), totaling 36,000 LLM calls. LLaMA consistently processed 480/500 screening abstracts and 96/100 extraction articles across all 10 runs—the same 20 screening and 4 extraction items failed every time, producing identical error outputs. These failures are not truncation: the returned text is well under the 2,048-token ceiling, and inspection shows the model emitting a value in its own orthography where the schema fixes the vocabulary (`case-crossover` for `case_crossover`), returning two values where one is allowed, or leaving a typed field null. Because these failures were deterministic (the same items failed identically in every run), they contribute to perfect agreement; EMR was computed over all 500 (screening) and 100 (extraction) items.[1] GPT-4.1 achieved 500/500 screening and 100/100 extraction in all runs, and Claude did the same except for two screening calls in one run that failed on the network and returned no decision; those two abstracts count as non-matches in its EMR. Mistral processed 497/500 screening abstracts and Gemma 493/500, in both cases failing the same items identically in every run,

[1]Computing EMR over only the 480 successfully parsed items yields the same result (EMR=1.000), since the 20 consistently-errored items also agree across runs.

so the footnote above applies to them as well. Gemini achieved 483–500/500 screening and 98–100/100 extraction.

Supplementary Table 28 summarizes the computational resources consumed. The six stacks required 207 hours of inference time and processed 55.8 million tokens. Local stacks were substantially slower per call (mean latency 28–92 seconds) than cloud APIs (3–12 seconds), reflecting the difference between single-device Apple M4 inference and distributed GPU clusters. However, the total cost of local inference was negligible ($0.26 electricity) compared to API costs ($69.38), with Claude Sonnet 4.5 accounting for 66% of the total budget.

4.2. Screening Reproducibility

Important caveat regarding Mistral 7B (Stage A): Although Mistral 7B achieved EMR=1.000 in the screening stage (Table 3), its specificity against the gold standard was 0.240 and its accuracy was 0.628. Inspection of the outputs reveals that Mistral classified 4,660 of its 4,960 parsed screening outputs as "include" (94.0%; 93.2% of the 5,000 attempted)—i.e., a degenerate "always-include" strategy. Any function that returns a constant is trivially reproducible: EMR=1.000 alone is therefore *not* evidence of useful reproducibility. We retain Mistral 7B in our results because this combination (perfect EMR + degenerate specificity) is itself a finding: it warns reviewers that EMR is necessary but not sufficient to characterize a screening tool's utility. We discuss the implications for paired-metric reporting in Section 5.1 of the Discussion.

Table 3 presents the screening reproducibility results.

All three local stacks—LLaMA, Mistral, and Gemma—produced identical

Table 3: Screening reproducibility across 10 runs per deployment stack. LLaMA's 20 consistently-errored abstracts are included in the EMR denominator (see text). For stacks with EMR=1.000, we report the rule-of-three 95% upper bound on the non-match rate ($3/n$, Hanley & Lippman-Hand 1983) instead of the trivial bootstrap interval.

Deployment Stack	**EMR**	**95% UCL***	**Flip Rate**	**Accuracy**	**Sensitivity**	**Specificity**
LLaMA 3 8B / Ollama / M4	1.000	≤0.006	0.0%	0.927	0.928	0.926
Mistral 7B / Ollama / M4	1.000	≤0.006	0.0%	**0.628**	**1.000**	**0.240**‡
Gemma 2 9B / Ollama / M4	1.000	≤0.006	0.0%	0.909	0.969	0.848
Claude Sonnet 4.5 / Anthropic	0.990	[0.980, 0.998]	1.0%	0.935	0.868	1.000
Gemini 2.5 Pro / Google	0.936	[0.914, 0.956]	6.4%	0.964	0.929	1.000
GPT-4.1 / OpenAI	0.970	[0.954, 0.984]	3.0%	0.941	0.882	1.000

*For EMR=1.000: 95% rule-of-three upper bound on non-match rate, $3/n$=3/500=0.006. For EMR<1.000: percentile bootstrap CI.

‡Mistral 7B exhibits a degenerate "always-include" strategy (sens=1.000, spec=0.240). EMR=1.000 is trivial here; see warning box.

screening decisions across all 10 runs for every successfully processed abstract (EMR=1.000), so no run-to-run variation was observed (non-match rate ≤0.6%, rule of three). Among the cloud APIs, Claude showed a 1.0% flip rate (5 abstracts, two of them the network failures noted above; as for every stack, a failed call counts as a non-match, and without those two the rate is 0.6%), GPT-4.1 3.0% (15 abstracts), and Gemini 6.4% (32 abstracts).

Notably, accuracy and reproducibility behaved as independent properties: Gemini achieved the highest accuracy (0.964) but the lowest reproducibility (EMR=0.936), while Mistral had perfect reproducibility but the lowest accuracy (0.628) due to an include-biased strategy (sensitivity=1.000, specificity=0.240). This illustrates that a model can be accurate on average yet inconsistent across individual runs, and conversely, that perfect repro-

ducibility does not imply high accuracy.

Inter-run agreement (Fleiss' κ). As a chance-corrected complement to EMR, we computed Fleiss' κ across the 10 runs on the 3-class screening decision (include/exclude/uncertain) for each deployment stack. Inter-run Fleiss' κ for screening ranged from 0.974 (GPT-4.1, "almost perfect") to 1.000 (all three local stacks); the cloud APIs were κ=0.995 (Claude), 0.975 (Gemini), and 0.974 (GPT-4.1). These values quantify self-consistency across repetitions of the same stack and are not directly comparable to the Cochrane $\kappa \geq 0.80$ guideline for agreement between two human reviewers,[4] which measures a different construct (see Section 5.1). For whole-output extraction (each unique output hash as a distinct rating category), the picture is dramatically different: Claude's inter-run κ=0.757 ("substantial" on Landis & Koch's scale), Gemini's κ=0.505 ("moderate"), and GPT-4.1's κ=0.512 ("moderate"); local stacks retain κ=1.000. Full Fleiss' κ values with 95% CIs and per-categorical-field decompositions are reported in Supplementary Table 19.

4.3. Extraction Reproducibility

The extraction results reveal a dramatically larger reproducibility gap (Table 4).

While screening EMR remained above 0.93 for all models, extraction EMR dropped for all three cloud APIs: **0.150 for GPT-4.1** (only 15 of 100 articles produced identical extraction outputs across all 10 runs), **0.200 for Gemini** (20 of 100), and **0.470 for Claude** (47 of 100). All three local stacks again achieved perfect extraction reproducibility (EMR=1.000). Claude showed the highest estimate count stability (0.978), followed by GPT-4.1 (0.922)

Table 4: Extraction reproducibility across 10 runs per deployment stack. The "Pairwise" column reports the mean fraction of pairs (across $\binom{10}{2}$=45 run-pairs per article) producing different outputs—a more powerful indicator than EMR alone of how dispersed flipping items are. For EMR=1.000 cells we report the rule-of-three upper bound (3/100=0.030).

Deployment Stack	**EMR**	**95% UCL***	**Pairwise**	**Estimate Stability**
LLaMA 3 8B / Ollama / M4	1.000	≤0.030	0.0000	1.000
Mistral 7B / Ollama / M4	1.000	≤0.030	0.0000	1.000
Gemma 2 9B / Ollama / M4	1.000	≤0.030	0.0000	1.000
Claude Sonnet 4.5 / Anthropic	0.470	[0.370, 0.570]	0.241	0.978
Gemini 2.5 Pro / Google	0.200	[0.120, 0.280]	**0.493**	0.735
GPT-4.1 / OpenAI	0.150	[0.080, 0.220]	0.486	0.922

*95% rule-of-three upper bound on non-match rate when EMR=1.000.

and Gemini (0.735): for Claude and GPT-4.1, the outputs varied while the structural composition of the extractions stayed largely fixed.

We emphasize that extraction EMR is computed over the full JSON output hash, so any character-level variation counts as a mismatch. To assess practical significance, we examine field-level variation below.

4.4. Field-Level Analysis

Not all extraction fields are equally affected (Supplementary Table 29). A clear pattern emerges: **categorical fields** (study design, study period) are highly reproducible even for API models (EMR≥0.990), while **free-text fields** (study location) and **numerical extractions** (effect estimates) show the greatest variation. GPT-4.1 is notable for achieving perfect location reproducibility (1.000) while showing variation in categorical fields like study

design and period (0.990 each)—a different instability profile from Claude and Gemini, where location is the most variable field.

The estimate count stability metric reveals that 26.5% of Gemini's articles with extractable estimates, 7.8% of GPT-4.1's, and 2.2% of Claude's received a different number of effect estimates across runs.[2] This structural variation directly affects any downstream meta-analysis.

4.5. Semantic Equivalence Analysis

The hash-based EMR reported in Table 4 (0.150 for GPT-4.1, 0.200 for Gemini, 0.470 for Claude) treats any character-level difference in the *full JSON output*—including all numeric effect estimates, confidence intervals, and variable-length estimate arrays—as a mismatch. To disentangle variation in the five metadata fields from variation in numeric estimates, and to assess whether metadata variation is merely cosmetic (formatting, abbreviation) or genuinely semantic, we applied three progressively relaxed equivalence criteria to the metadata fields only (Supplementary Table 30).

1. **Exact match**: character-identical outputs (equivalent to SHA-256 hash comparison).
2. **Normalized match**: after lowercasing, whitespace normalization, punctuation stripping, and abbreviation expansion (e.g., "U.S." → "United States").

[2]Estimate count stability is computed over articles that produced at least one estimate in all 10 runs, yielding denominators of 83 (Gemini), 90 (GPT-4.1), and 89 (Claude) rather than the full 100. The meta-analytic "Varying" column in Supplementary Table 20 uses the full 100-article denominator, producing different percentages (20%, 5%, 1%), since both the numerator and the denominator change.

3. **Fuzzy match**: Levenshtein similarity ratio ≥ 0.90 between all normalized pairwise comparisons across runs.
4. **BERTScore**: Embedding-based semantic similarity using `roberta-large`, computing the F1 score across all $\binom{10}{2}=45$ unique run pairs per article (4,500 pairs per model).

Four findings emerge from this multi-level analysis.

First, the gap between metadata-field EMR and hash-based EMR quantifies how much variation resides in the numeric estimate arrays versus the text metadata. For Claude, 93% of articles had identical metadata across all runs, but only 47% had identical *complete* outputs; for GPT-4.1, 88% had identical metadata but only 15% had identical complete outputs; for Gemini, 62% and 20% respectively. In all three cases, the variable-length estimate arrays (effect sizes, confidence intervals) are the primary source of non-reproducibility.

Second, within the metadata fields, normalization and fuzzy matching improved EMR by at most 1 percentage point (Gemini: 0.620 $\rightarrow$ 0.630; Claude: 0.930 and GPT-4.1: 0.880 unchanged), confirming that the variation is predominantly semantic, not cosmetic. That the Claude and GPT-4.1 metadata EMR do not move under normalization and fuzzy matching indicates that when their metadata fields vary, the variation is genuinely semantic rather than attributable to formatting differences.

Third, BERTScore embedding similarity computed across all $\binom{10}{2}=45$ unique run pairs per article (4,500 pairs per model) was near-perfect for all API models: GPT-4.1 averaged F_1=1.000 $\pm$ 0.004, Claude F_1=0.999 $\pm$ 0.004, and Gemini F_1=0.997 $\pm$ 0.022, with 100%, 100%, and 98.5% of pairs

exceeding $F_1 \geq 0.95$, respectively. This creates an apparent paradox: the models produce *semantically near-identical* metadata text, yet 53–85% of their complete extraction outputs are non-identical. The resolution lies in the numeric estimates—the effect sizes, confidence intervals, and variable-length estimate arrays that hold hash-based EMR at 0.150–0.470. Even when a model describes a study in nearly the same words, it may extract a different number of effect estimates or parse "RR=1.05 (95% CI: 1.01–1.09)" with subtly different numeric precision. Concrete, verbatim side-by-side excerpts of an exact-match local-stack output and a near-miss API-stack output (with the divergence located in the variable-length `estimates` array rather than in the metadata fields) are reproduced as JSON listings in Supplementary §5.

Fourth, the three API models exhibit distinct instability profiles. Claude shows the highest metadata stability (exact EMR=0.930) and the highest hash-based EMR (0.470), yet more than half of its complete outputs still differ across runs, which places its residual variation in the numeric layer. GPT-4.1 shows high metadata stability (0.880) and the highest BERTScore (F_1=1.000), yet its hash-based EMR (0.150) is the lowest of the three, so numeric extraction drives its variation even more strongly. Gemini shows the lowest minimum BERTScore (F_1=0.754) and highest standard deviation (0.022), indicating that some articles receive genuinely divergent interpretations across runs—not merely numeric rounding differences.

4.6. Downstream Propagation

An audit of an extraction step is only as interesting as what the step feeds. We therefore propagated each run's extracted estimates into a pooled analysis, to ask whether run-to-run variation survives aggregation or is averaged

away.

Over the full corpus it is largely averaged away: pooled estimates are stable across runs and no run pair reverses the aggregate conclusion. The variation surfaces at small k, which is the regime most environmental syntheses actually occupy. Resampling subsets of ten studies, the share of subsets whose conclusion flips depending on which run supplied the inputs reaches at most 2.0% under DerSimonian–Laird and as much as 45.0% under the Hartung–Knapp–Sidik–Jonkman correction, both on the Gemini stack; for GPT-4.1 the HKSJ figure is 21.5%, and for Claude and the three local stacks no subset flips. A second, quieter effect is that k itself moves with the run—on the Gemini stack between 39 and 45 articles yield a usable estimate depending on the execution—so non-determinism changes not only the numbers entering the pool but how many there are.

Because the pooling machinery is peripheral to the audit itself, the full analysis, the per-run inputs and the heterogeneity statistics are reported in Supplementary §19.

4.7. Fixed-Slot Extraction Sensitivity

To test whether the variable-length `estimates` array structurally amplifies cloud API non-determinism, we re-ran the extraction stage on the three cloud models with a fixed-slot prompt that requests *exactly one* primary estimate (lag 0–1 if multiple lags are reported, single-pollutant model preferred, all-respiratory preferred over subgroups, normalized to per 10 μg/m^3). All other parameters were held identical to the variable-length design: temperature=0, seed=42 where the API accepts one, same 100 INCLUDE articles, three runs per model.

Table 5: Fixed-slot extraction EMR against a run-count-matched variable-length baseline. Both columns are 3-run EMR: the fixed-slot condition as executed, and the baseline averaged over all $\binom{10}{3}$=120 three-run subsets of the 10 variable-length runs. Coverage differs slightly by stack—the fixed-slot arm returned usable output for 100 articles on Claude and 99 on Gemini and GPT-4.1—and each EMR is computed over the articles present in all runs of its own arm.

Deployment Stack	**Var-length, 3-run**	**Fixed-slot, 3-run**	**Relative change**
Claude Sonnet 4.5 / Anthropic	0.660	0.640	−3.0%
Gemini 2.5 Pro / Google	0.349	0.182	**−47.9%**
GPT-4.1 / OpenAI	0.359	**0.444**	+23.8%

The baseline must be matched on run count. EMR is monotonically non-increasing in the number of runs, since each additional run is another opportunity for an item to differ. The fixed-slot condition was executed with 3 runs while the variable-length baseline has 10, so comparing them directly credits the fixed-slot prompt with a difference that is partly an artefact of fewer repetitions. We therefore compute the baseline over all $\binom{10}{3}$=120 three-run subsets and average, which is what Table 5 reports. Against the unmatched 10-run baseline the same data would read +36.2%, −9.1% and +196.3%; the matched comparison is the defensible one, and it changes both the magnitude and, for Claude, the sign of the conclusion.

The result is *not* a uniform improvement. Fixed-slot prompting *degraded* reproducibility on Gemini by 48%, improved it on GPT-4.1 by 24% rather than the near-tripling the unmatched comparison suggested, and left Claude essentially unchanged (−3%). This refutes the expectation that "fixed-slot extraction will resolve cloud non-determinism": constraining the output shape

does not fix the problem in general, and its effect runs from harm to help depending on the stack. The result converges with one obtained independently in this journal, on a different environmental task and from the opposite starting point. Constraining an LLM agent to operate SWAT+ exclusively through a typed, range-validated tool interface shortened its calibration path substantially (21.9 versus 62.0 model evaluations) and produced reviewable operational provenance—so the structure delivered on control. What it did not deliver was validity: an acceptable goodness-of-fit score did not guarantee hydrological quality, and a held-out corruption task showed that logs and range constraints alone could not detect a physically corrupted model state.[2] Their conclusion and ours describe the same boundary from either side. Constraining the interface buys control and auditability and does not buy correctness, and the layer that would have to be added is not the interface layer. The effect of prompt design is real but **model-specific**, and for two of three stacks the dominant source of variation lies elsewhere (see Section 4.8).

4.8. Deployment-vs.-Model-Size Desconfound Experiment

Throughout the comparisons above, the local versus cloud difference is confounded with model size: our three local models are 7–9B-parameter open-weight models, while the three cloud APIs are estimated at >100B parameters and trained with proprietary procedures. To isolate the deployment effect, we ran a seventh experimental condition: the identical `meta-llama/llama-3-8b-instruct` model—same weights, same tokenizer, same architecture—served via cloud (OpenRouter routing pinned to the DeepInfra provider) at temperature=0 and seed=42. Ten cloud runs ×

500 abstracts mirror the local experimental design.

The two arms hold constant the model weights, the prompt source file, the decoding temperature and the seed, but they do not issue a byte-identical request payload, and we state the difference rather than let the word "identical" carry it. The local harness interpolates the article into the prompt template before the call and the serving layer then appends the article text again, whereas the cloud harness transmits the uninterpolated template and the article as separate message parts; the two were additionally configured with different output-token ceilings (2,048 local, 512 cloud). Measured over the deposited call records, the arms differ by 34.2% in mean input tokens (1,279.3 local vs. 842.3 cloud) and share *none* of the 500 canonical call hashes. This condition therefore holds the weights constant while varying the remainder of the deployment stack *including its request-rendering layer*, and we scope the inference accordingly: it demonstrates that identical weights do not guarantee identical behaviour across serving stacks, and it does not isolate the serving infrastructure from the payload construction that stack imposes. Output truncation is excluded as a contributor by direct measurement: all 4,266 completed cloud calls returned `finish_reason=stop`, none hitting the 512-token ceiling.

Three findings stand out.

First, infrastructure introduces non-determinism in a small-parameter model. Local LLaMA 3 8B is bit-deterministic (EMR=1.000 over 10 runs and 500 abstracts). The same model served via cloud is *not*: 2.04% of items receive different decisions in at least one run-pair (mean pairwise disagreement 0.79%). Model size therefore does not explain the gap: a 7–9B

Table 6: Same-weights, different-stack comparison. Two deployment stacks share the `meta-llama/llama-3-8b-instruct` weights but differ in the remaining tuple components: local stack = (weights, Meta/open, Ollama v0.15.5/Apple M4/single replica, local HTTP); cloud stack = (weights, Meta-via-DeepInfra, OpenRouter routing/opaque GPU pool, OpenRouter Chat Completions). Ten runs each, same prompt source file, seed=42, temperature=0; the request payloads are not byte-identical (see text).

Quantity	**Local stack (Ollama / M4)**	**Cloud stack (DeepInf**
EMR within deployment	1.000	0.992*
Mean pairwise disagreement	0.0000	0.0079
% items with any pair-disagreement	0.00%	2.04%
Cross-deployment agreement (all run pairs)	—	59.7%
Items where local=include / cloud=exclude	—	167
Items where local=exclude / cloud=include	—	**0**

*Pairwise-mean-based estimate; 2 of 10 cloud runs had transient infrastructure failures that reduced their valid-item counts (45 and 221, vs. ∼491 in the other 8 runs).

model became non-deterministic when served through a different stack, with weights, prompt source, seed and temperature held fixed. Because the two stacks also render the request differently, the result does not separate serving infrastructure from payload construction.

Second, cloud and local produce systematically different outputs. Even within the runs where the cloud was internally consistent, mean pairwise agreement with the local deployment was 59.7%. Of 430 items where both deployments produced a valid decision, 167 (38.8%) showed a different decision under cloud than under local.

Third, the discordance is asymmetric. Of those 167 discordant items, **all 167** were cases where the local model said *include* but the cloud said *exclude*; the reverse direction (local exclude / cloud include) occurred zero times. The cloud deployment is systematically more conservative. We do not identify the mechanism. Serving-side numerics and the request-rendering difference (the local payload carries the article text twice) are both candidates, and this design does not discriminate between them.

We additionally observed an operational reliability finding: 2 of 10 cloud runs (`run_005`, `run_006`) experienced transient infrastructure failures that reduced their successful-call counts substantially (45/500 and 221/500 versus the ∼491/500 baseline of the other eight runs). This pattern was absent from all 10 local Ollama runs, all of which had identical 480/500 success. Cloud reliability is therefore a second property to report alongside reproducibility.

4.9. A Decision Model on the Screening Stage

The generative stacks sample one answer per call. A decision model returns the whole distribution, and a natural expectation is that a stack

which never samples should never disagree with itself. The Jev arm tests that expectation on Stage A.

It completed 4,998 of 5,000 calls; the two failures were a server error and a dropped connection. Screening EMR was 0.956 (95% CI [0.938, 0.972]): 20 abstracts received a different decision in at least one run and the two failed calls add two non-matches, placing the decision model between Gemini (0.936) and GPT-4.1 (0.970) and below Claude (0.990). Against the same gold standard as Table 3, accuracy was 0.888, specificity 1.000 and sensitivity 0.776, the lowest sensitivity of any stack in Table 3.

The probabilities show where the variation comes from. The probability of the chosen option varied across the ten runs by 0.039 on average, reached 0.20, and was zero for only 29.8% of abstracts. Per option the picture is the same. For the same abstract and the same question, the probability Jev assigned to *include* was identical across all ten runs for only 31.4% of abstracts; its range across runs averaged 0.037 and reached 0.19, and over all three options the largest range was 0.20. Most of this movement does not change the decision, because the modal option carried a mean probability of 0.865 and fell below 0.5 for 4.4% of abstracts. Returning the distribution therefore does not remove run-to-run variation; it exposes it, and that exposure is the property a review team could use, since an abstract whose probabilities move between runs can be flagged for a human reader before any decision is recorded. We make no calibration claim from these data: the human-labelled subset (n=100) is too small to estimate one. Call-level details are in Supplementary §24.

4.10. Schema Conformance: A Second Axis of Reliability

EMR asks whether repeated runs agree with one another. It is silent on whether what they agree upon is usable. These are separable properties, and separating them changes how the local stacks should be read.

Table 7: Share of returned outputs validating against the study's JSON schema, over all runs. Calls that returned nothing are excluded from the denominator and counted separately. Conformance is independent of EMR: a stack can reproduce a non-conforming output perfectly.

Deployment Stack	**Screening**	**Extraction**
LLaMA 3 8B / Ollama / M4	87.0%	38.0%
Mistral 7B / Ollama / M4	84.2%	43.0%
Gemma 2 9B / Ollama / M4	96.2%	40.0%
Claude Sonnet 4.5 / Anthropic	100.0%	72.4%
Gemini 2.5 Pro / Google	99.7%	**2.6%**
GPT-4.1 / OpenAI	100.0%	64.9%

Two readings follow, and they cut in opposite directions.

The first tempers the local-stack result. The three local stacks reach EMR=1.000 on extraction while returning schema-conforming output in only 38–43% of calls. Their perfect reproducibility is therefore reproducibility of a set that includes a majority of records a review team would have to repair by hand. This does not overturn the reproducibility finding—an unusable output that is identical across runs is still identical, and repair effort is at least predictable—but it does mean that "deterministic" and "ready to use" are not the same claim, and this paper only establishes the first.

The second sharpens the cloud result. Gemini validates on 2.6% of extraction calls, 951 of its failures being a null in a field the schema types as a string. The meta-analytic propagation in Section 4.6 nonetheless harvests 39–45 estimates per Gemini run, drawn from outputs its own validator rejects in 97 of every 100 cases. A pipeline reporting only pooled effect sizes would surface none of this.

Conformance is thus a reliability axis orthogonal to EMR, cheap to measure, and absent from the studies in Table 1. We report it because the pairing is what carries the lesson: Mistral shows that perfect EMR can accompany a degenerate decision rule, and the local extraction stacks show that it can accompany a largely non-conforming output. Neither is visible if reproducibility is measured alone.

4.11. Summary Comparison

Figure 2 visualizes the EMR comparison across models and stages, and Figure 3 displays the field-level variation as a heatmap.

The results reveal three key patterns: (1) a sharp reproducibility gap between local and API-served deployment stacks, with all three local stacks achieving EMR=1.000 while all three API-served stacks reach at most 0.470 for extraction; (2) a dramatic amplification of non-determinism when moving from simple binary screening decisions to complex structured extraction outputs; and (3) distinct instability profiles among API-served stacks, with the Claude / Anthropic stack showing the highest metadata and structural stability but still returning a different complete output in more than half of the articles.




Figure 2: Exact Match Rate (EMR) by deployment stack and pipeline stage. Six deployment stacks are shown: three local Ollama/Apple M4 stacks (LLaMA 3 8B, Mistral 7B, Gemma 2 9B) and three API-served stacks (Claude Sonnet 4.5/Anthropic, Gemini 2.5 Pro/Google, GPT-4.1/OpenAI). Error bars represent 95% percentile bootstrap confidence intervals over 10,000 resamples; for stacks with EMR=1.000, the displayed upper bound is the rule-of-three $3/n$ instead of the trivial bootstrap interval. The dashed line indicates perfect reproducibility (EMR=1.0).




Figure 3: Field-level EMR heatmap for extraction outputs across the six deployment stacks (three local Ollama/Apple M4 stacks on the left columns; three API-served stacks—Claude/Anthropic, Gemini/Google, GPT-4.1/OpenAI—on the right). Darker cells indicate lower reproducibility. Categorical fields (study design, study period) remain stable across all stacks, while free-text fields (study location) and the variable-length structured estimates array show the greatest variation in the three API-served stacks.

5. Discussion

5.1. Principal Findings

Our study provides a systematic quantification of LLM non-determinism across a complete evidence synthesis pipeline—to our knowledge, the first to combine whole-output metrics, multi-run repetition, and pipeline propagation analysis in this domain. Nine findings emerge, after one reframing.

Reframing: the object of reproducibility variation is the deployment stack, not the model. A first-principles consequence of our results is that "which model" is the wrong level of abstraction for talking about LLM reproducibility. A deployment stack—the tuple of weights, provider, infrastructure, and API layer (Section 3.2)—is the unit through which an LLM actually generates an answer, and it is the unit at which reproducibility is

preserved or destroyed. Two stacks that share weights can diverge by tens of percentage points if their infrastructure or serving layer differs (Table 6); two stacks that differ in weights but share a deterministic local infrastructure can both achieve EMR=1.000 (Tables 3, 4). Reporting only the model name in an LLM-assisted SR therefore underspecifies the experimental condition: the same weights on a different stack will not reliably reproduce the same outputs. This reframing motivates the recommendations in Section 5.6.

Finding 1: Deployment infrastructure—not parameter count—drives the local-vs-cloud reproducibility gap. All three local stacks—LLaMA 3 8B, Mistral 7B, and Gemma 2 9B served via Ollama on a single device—produced identical outputs across all 10 runs in both screening and extraction. All three cloud-based APIs (Claude, Gemini, GPT-4.1) exhibited measurable non-determinism despite transmitting temperature=0 and, where the API accepts one, a fixed seed. The desconfound experiment in Section 4.8 establishes that this gap is *not* attributable to model size: serving the identical `meta-llama/llama-3-8b-instruct` via cloud (DeepInfra) introduces 2% pairwise disagreement and 39% systematic disagreement with the local deployment of the same weights—asymmetrically, with the cloud always more conservative. The gap is consistent with floating-point non-associativity under multi-GPU serving,[19] where partial sums are reduced in an order that can change between calls, whereas a single device with a single execution thread repeats the same order; the design does not isolate that mechanism. This determinism guarantee is configuration-specific, however. The same model on different hardware, driver versions, or Ollama versions would likely produce different baseline outputs. Determinism holds within

each configuration, not across configurations.

Finding 2: Extraction amplifies non-determinism dramatically, and the variation is semantic. Claude's EMR dropped from 0.990 (screening) to 0.470 (extraction); GPT-4.1's from 0.970 to 0.150; Gemini's from 0.936 to 0.200. Screening requires a binary decision (a single token effectively determines the output), while extraction generates complex structured JSON with multiple fields. Our four-tier semantic equivalence analysis (Section 4.5) confirms that this gap is not an artifact of strict string matching. BERTScore embedding similarity across all 4,500 pairwise comparisons per model averaged $F_1 \geq 0.997$—near-perfect semantic agreement on metadata text—yet hash-based EMR remained at 0.150–0.470. This paradox reveals that the variation concentrates in the numeric extraction layer: the models describe studies in nearly the same words but extract different numbers of effect estimates and parse numeric values with different precision. Even the residual metadata variation is genuinely semantic (fuzzy matching recovers at most 1 percentage point), not cosmetic. The practical implication depends on context: the high BERTScore ($F_1 \geq 0.997$) indicates that API models describe studies in near-identical terms, and for applications requiring only qualitative summaries, this level of consistency may be acceptable. However, for quantitative evidence synthesis—where exact numeric values feed directly into meta-analytic pooling—the hash-based EMR of 0.15–0.47 represents a genuine threat to reproducibility.

Finding 3: API-served stacks exhibit distinct instability profiles. Claude achieved the highest metadata stability among API models (exact EMR=0.930), the smallest structural variation (Δk=2 estimates across runs)

and the highest hash-based extraction EMR (0.470), yet more than half of its complete outputs still differed across runs. GPT-4.1 paired high metadata stability (0.880, BERTScore F_1=1.000) and a small structural swing (Δk=4) with the lowest hash-based EMR (0.150), while Gemini showed the widest structural swing (Δk=17) and the most extreme semantic divergence (minimum BERTScore F_1=0.754). These distinct profiles suggest that nondeterminism manifests differently across API providers—some vary primarily in numeric precision, others in structural composition, and others in semantic interpretation.

Finding 4: Accuracy and reproducibility are independent properties; report them as a paired tuple. Gemini achieved the highest screening accuracy (0.964) but the lowest screening reproducibility (0.936), while Mistral had perfect reproducibility (EMR=1.000) but a degenerate "always-include" strategy (specificity=0.240, accuracy=0.628). The Mistral case is a stark warning: a constant function is trivially reproducible, so EMR alone is not evidence of useful reproducibility. This independence means that **accuracy evaluations from a single run cannot detect reproducibility problems**, and **reproducibility evaluations without accuracy cannot detect degenerate strategies**. Future studies should report EMR and accuracy (against a human-labeled ground truth) as a paired tuple, never EMR alone.

Finding 5: Prompt design is a contributor to extraction nondeterminism, but the effect is model-specific. The fixed-slot sensitivity analysis (Section 4.7), read against a run-count-matched baseline, degraded extraction reproducibility on one API-served stack (Gemini −47.9%),

improved it on another (GPT-4.1 +23.8%) and left the third essentially unchanged (Claude −3.0%). Against an unmatched 10-run baseline the same data would read −9.1%, +196.3% and +36.2% in the same order; the matched comparison changes both the magnitude and, for Claude, the sign, and it is the defensible one. This refines the assumption that "fixed-slot will fix it": prompt structure matters, but the dominant source of variation differs across providers. For Claude in particular, simplifying the output shape barely moved EMR (0.660 to 0.640), which places its residual non-determinism in the deployment stack rather than in prompt-induced array variability.

Finding 6: Neither a transmitted seed nor temperature zero delivers determinism. Recent reporting guidance for GenAI-assisted evidence syntheses asks authors to document random-seed values and, for commercial models, API versions and access dates;[15] it does not establish whether a documented seed delivers determinism.

The cleanest evidence is within-stack and needs no cross-provider comparison. Gemini and GPT-4.1 both expose a seed parameter, both received seed=42 on every one of their 6,000 calls, and both were verified to have transmitted `temperature`=0. Under those conditions—the exact configuration a practitioner would adopt believing it buys reproducibility—their extraction EMR was 0.200 and 0.150 respectively, against 1.000 for local stacks holding the same nominal settings. A documented, accepted, transmitted seed therefore does not make an API-served extraction pipeline reproducible.

The data also contain an observation that runs against the seed's reputation, and we state it with its limit. The most reproducible API-served

stack on extraction was the one that accepts no seed at all: Claude, at temperature=0 and without a seed, reached 0.470 against 0.200 and 0.150 for the two seeded stacks. That is a contrast between stacks that differ simultaneously in provider, infrastructure and API layer, so it is not an estimate of the seed's effect—our own unit-of-analysis argument in Section 3.2 forbids that reading—but it is incompatible with the seed being what separates reproducible from non-reproducible API stacks. What our design does *not* support is an estimate of how much the seed contributes on its own. Such an estimate requires a within-stack ablation—the same stack, same provider, same infrastructure, run with and without the seed—and we did not execute one.

Temperature behaves the same way. An execution of the Claude stack at the API default of 1.0 provides a contrast (Supplementary §23): moving to 0 raised its extraction EMR from 0.050 to 0.470 and its screening EMR from 0.974 to 0.990, yet more than half of the articles still received a different complete extraction across runs. The two executions are eight months apart (Section 5.5), so the contrast combines the temperature change with any provider-side change in between. Temperature zero reduces the variation and does not remove it, and the lever is closing: the provider's documentation states that its newer models return an error when `temperature` is set to a non-default value,[3] so on those models a practitioner can no longer request 0 at all.

Finding 7: A model that returns probabilities instead of a sam-

[3] `https://platform.claude.com/docs/en/about-claude/model-deprecations`, accessed 9 October 2026.

ple still varies, and the variation becomes visible. The decision model (Section 4.9) never samples text, yet its screening EMR (0.956) sits inside the range of the generative API stacks, and the probability it assigns to the same option for the same abstract moved between identical calls for most abstracts. Non-determinism is therefore not a by-product of sampling that a different output format removes; it reaches a stack that returns distributions as well. What the distribution adds is a signal the generative stacks do not provide: an abstract whose option probabilities move across runs is identifiable from the output itself, which is the information a review team needs to route that abstract to a human reader.

Finding 8: Reproducible is not the same as usable. The three local stacks reach EMR=1.000 on extraction while returning schema-conforming output on 38–43% of calls (Section 4.10), and Mistral reproduces a degenerate screening rule perfectly (Finding 4). Reproducibility and usability are separable, cheap to measure together, and measured together in no study in Table 1.

Finding 9: A run card can record a configuration that was not executed. In the Claude execution at 1.0, the client attached the `temperature` field only when the requested value exceeded zero, so a request for 0 was sent without it and ran at the API default, while the run cards recorded `temperature: 0.0` because the call hash covered the requested value rather than the transmitted payload. A single conditional, invisible in the configuration table, the run card and the hash, detached the executed configuration from the declared one. Provenance that records what was requested cannot detect this; provenance that records what was transmitted

can.

5.2. Implications for Evidence Synthesis Practice

For systematic reviewers: If using cloud-based LLMs for screening or extraction, results from a single run should be treated as one sample from a distribution of possible outputs, not as a definitive answer. Running multiple repetitions and reporting variation metrics should become standard practice, analogous to how human inter-rater reliability is routinely measured. It is tempting to place the models' screening EMR of 0.94–0.99 next to the Cochrane expectation of $\kappa \geq 0.80$ for human screening agreement[4] and read the comparison as favourable, and we resist that reading for two reasons. First, the quantities are not commensurable: EMR and inter-run Fleiss' κ measure how consistently a *single* rater reproduces itself across repetitions, whereas Cohen's κ measures whether *two different* raters reach the same conclusion. A system can be perfectly self-consistent and consistently wrong—in this corpus Mistral-7B achieves EMR=1.000 at a specificity of 0.240 (Table 3), which is the cleanest possible demonstration that self-consistency is not accuracy. Second, on this same corpus our own two human raters reached κ=0.529 (95% CI [0.383, 0.674]; Section 3.3), so the 0.80 figure functions here as an aspirational guideline rather than as a measured property of human screening. The honest comparison is therefore not "models versus the threshold" but "models and humans each measured, on different constructs, against a threshold that neither was shown to meet." Extraction EMR (0.15–0.47), by contrast, requires no such careful framing: it falls below any reliability standard on any construct.

For journal editors and reviewers: Papers reporting LLM-assisted

evidence synthesis should be expected to disclose: (a) the exact model version, (b) all inference parameters, (c) whether results were verified across multiple runs, and (d) provenance information enabling independent replication.

For tool developers: Open-weight models have already been scaled in this journal for regulatory information extraction in the hydropower domain;[1] our result adds a property to that choice which cost and control arguments do not cover, since the local single-device arm is the only configuration here that returned bit-identical output across all ten runs. The large difference in extraction EMR between local and cloud deployment suggests that deterministic local inference should be the default for reproducibility-critical applications. Local inference on consumer hardware (Apple M4, 24 GB RAM) cost $0.26 total for 174 hours across three models, versus $69.38 for 32 hours of API inference—a 266× advantage in total outlay. Normalised per hour of inference the gap is far wider still ($0.0015/h local vs. $2.14/h API, ≈1,400×), since the local stacks ran five times longer for that outlay. Either way the cost advantage compounds with the reproducibility benefit. Where cloud APIs must be used, every reported output should come with its run-to-run variation; whether majority voting across runs restores a stable output was not measured here.

5.3. Relationship to Prior Work

Our results both corroborate and significantly extend prior findings (see Table 1 for a systematic comparison).

Our screening flip rates (1.0% for Claude, 3.0% for GPT-4.1, 6.4% for Gemini) are consistent with the accuracy variations reported by Atil et al.[16]

on general benchmarks, confirming that the phenomenon documented in controlled settings translates directly to real-world evidence synthesis tasks. However, we reveal that **structured extraction amplifies non-determinism by an order of magnitude**—a finding invisible to benchmark-level analyses. Defining amplification as the ratio of extraction flip rate to screening flip rate, Claude's non-match rate increased from 1.0% to 53.0% (53.0×; ≈88× if its two failed screening calls are not counted as non-matches), GPT-4.1's from 3.0% to 85.0% (28.3×), and Gemini's from 6.4% to 80.0% (12.5×). This amplification pattern—consistent across all three API providers—has not been previously documented.

The comparison with Jensen et al.[10] is particularly instructive. Their reported 94.1% inter-session reproducibility for ChatGPT-4o extraction appears to align with our API screening EMR (93.6–99.0%), creating the impression that API-based extraction is reasonably stable. However, their metric measures per-field agreement across 2 sessions, while our EMR measures whole-output identity across 10 runs. When we apply our stricter metric, extraction reproducibility drops to 15.0–47.0%—**between two and six times lower than what per-field metrics suggest**. This discrepancy is not an artifact; it reflects a genuine measurement gap. Per-field metrics miss the combinatorial explosion of variation: when 5 fields each have 97% individual reproducibility, the probability that *all* fields match simultaneously is only $0.97^5 = 0.859$—and this is before accounting for the variable-length effect estimate lists that drive most of our observed non-matches.

Similarly, Gartlehner et al.'s[9] 95–97% test-retest reliability with Claude 2 was measured over 2–3 repetitions. Our 10-run design with output hashing

reveals instability that shorter test-retest windows cannot detect, because some items change in only 1–2 of 10 runs—a frequency that 2-run comparisons would miss entirely.

The meta-analytic propagation experiment (Section 4.6) provides the most direct evidence of downstream impact. For Gemini, the number of usable effect estimates varied from 154 to 171 across runs—an 11.0% swing in the evidence base feeding the pooled result. For GPT-4.1 the swing was 2.3% (176–180), and even the most stable API model, Claude, showed a 1.0% swing (195–197). Across API models, 1–20% of articles produced a different number of effect estimates depending on the run, meaning that **the composition of a meta-analysis is not fixed when an LLM extracts the data**. Importantly, the overall pooled conclusion remained stable across all runs in our corpus—a finding we attribute to the large k and strong aggregate effect, which buffer against compositional variation. This stability should not be misread as evidence that non-determinism is inconsequential; it reflects the large k of the full corpus. The per-run pooling here uses a fixed-effect model; the random-effects re-analysis in the Supplement widens the intervals 2.2–2.7× without changing any full-corpus conclusion, and it is at small k that run dependence appears (Section 4.6).

5.4. Structured-Output and Tool-Use Modes as Potential Mitigations

The three commercial APIs in our study all offer "structured output" or "tool-use" modes that constrain output format more strictly than free-form JSON: Anthropic's tool-use API enforces a Pydantic-like schema server-side, OpenAI's `response_format=json_schema` similarly constrains the output token distribution, and Gemini's function-calling enforces argument types in

the response.

Whether these modes reduce run-to-run non-determinism in extraction is an open question that our study did not directly address—we used the standard Chat Completions endpoints with prompt-level JSON instruction, matching the most common practice in the LLM-SR literature as of late 2025. Two hypotheses are testable in future work. First, structured outputs may reduce *parsing* variation (no more "Markdown code-fence around JSON" edge cases) without reducing the underlying semantic non-determinism (the model still chooses among multiple valid outputs). Second, structured outputs with strict enums (e.g., `lag` restricted to `lag0, lag1, lag0-1, lag2`) may push semantic variation toward the specific sub-fields with the most uncertainty, but bounded EMR may improve. We recommend that future LLM-SR studies report results in both unstructured and structured-output modes when comparing across commercial APIs, because the deployment paradigm explicitly affects which output channels are available.

5.5. Limitations

The results are bounded by the limitations below; for each we state what it prevents us from concluding.

Timing of the Claude stack. The Claude stack was run on 8 October 2026, eight months after the other five stacks, on a snapshot that Anthropic had announced for retirement (deprecated 30 September 2026, retirement 30 November 2026).[4] Provider-side changes to the serving stack in

[4] `https://platform.claude.com/docs/en/about-claude/model-deprecations`, accessed 9 October 2026.

that window cannot be excluded, so differences between Claude and the other API stacks cannot be attributed to the provider alone, and the temperature contrast of Finding 6 cannot be read as a pure temperature effect.

Stack sample. Six stacks—three local 7–9B models on one device, three proprietary API-served models—are not a sample of deployment practice. The local-versus-API contrast varies weights, infrastructure and serving layer together, and the one same-weights comparison does not hold the request payload constant. We therefore cannot attribute the gap to a specific serving component, nor claim that other hardware, other runtime versions or other API stacks behave the same way. Further same-weights pairs can be run through the harness as configuration changes.

Ten runs per condition. With R=10, a per-item non-match probability of 0.30 or higher is detected with $\geq$95% power under a binomial model, while rarer instability (per-item $p<0.05$) is under-detected; the local EMR of 1.000 bounds the non-match rate at $\leq$0.6% (screening) and $\leq$3% (extraction) and does not exclude lower rates. EMR values here are not comparable with EMR computed over a different number of runs. Increasing R is a configuration change in the harness.

No within-stack seed ablation. Our data show that a transmitted seed does not buy determinism (Finding 6) and do not estimate how much the seed contributes on its own; that estimate needs one stack run with and without the seed, which we did not execute.

An agreement coefficient below its target. Two blinded raters working from a pre-registered protocol reached κ=0.529 (95% CI [0.383, 0.674]) against a target of 0.80, and the shortfall is statistically decisive ($z = -3.65$).

We did not raise the target, drop a rater, or recompute the coefficient after selectively re-rating the discordant items, each of which would have produced a number above the threshold with no evidential content behind it. The disagreement is located: it is directional (exact McNemar p=2.2×10^{-4}), and 17 of the 19 asymmetric discordances turn on a single inclusion criterion whose original wording admitted two defensible readings; showing that the amended criterion repairs it requires a fresh independent sample. This prevents us from reporting sensitivity as more than a lower bound or certifying the reference standard; it does not affect EMR, which needs no reference.

Usability of the local outputs. The three local stacks reach EMR=1.000 on extraction while returning schema-conforming output on 38–43% of calls. This paper therefore does not show that local stacks yield usable extractions.

Screening EMR covers the decision only. It ignores confidence scores and rationales, so it does not measure their variation; a full-output screening EMR could only be equal or lower.

Corpus composition. Sixty per cent of the corpus comes from the rule's low-confidence stratum. It would be tempting to read these flip rates as upper bounds for standard workloads, on the reasoning that a typical review contains fewer borderline cases. That reading does not survive inspection of the stratum: 260 of its 300 abstracts carry the maximum inclusion score of 5, the same score borne by every clear-include, and all 300 carry zero exclusion reasons. The stratum marks where the automated rule was unconfident, which is not the same as where a human reader would hesitate, and its composition sits closer to the include side than to a genuine borderline. We therefore make no directional claim about how these rates transfer to other

corpora. Whether a review with fewer such abstracts would flip less often is untested here, and the enrichment fraction is a property of our sampling frame rather than a calibrated difficulty setting.

Snapshot validity. For the three API-served stacks, the infrastructure and intermediate-precision routines—GPU topology, batching policy, weight checkpoint version, internal post-training—are opaque to the client and may change silently. The main stacks ran within a 3-week window (February 11–March 2, 2026), the desconfound cloud stack in April 2026, and the Claude and Jev arms on 8 October 2026. Our API results describe the snapshots observed in those windows and cannot be extrapolated to later provider versions. Re-running the same configuration at intervals would measure drift.

Single corpus and domain. All measurements come from one 500-abstract corpus on $PM_{2.5}$ and respiratory hospitalization, a literature that reports effects formulaically (RR per 10 $\mu g/m^3$ with 95% CI). We therefore cannot say whether the extraction EMR values or the screening-to-extraction amplification hold for less standardized environmental literatures, for other periods, or for other domains. Applying the harness to a second corpus changes the corpus and schema configuration, not the code.

Single local device. The local EMR=1.000 was obtained on one device (Apple M4, 24 GB RAM, macOS Darwin 24.6.0, Ollama v0.15.5). We cannot claim that the same local stacks are deterministic on other hardware or runtime versions, nor that they reproduce these exact outputs there.

Pre-registration disclosure. This study is partly pre-registered, and we state precisely which parts, because the distinction matters for how much weight each result can carry. The original analyses (Sections 4.4–4.6) are

exploratory: the choice of 10 repetitions, whole-output hash EMR, four semantic-tier definitions, and fixed-effect meta-analytic propagation were made during analysis design but without an Open Science Framework or AsPredicted submission. The dual-human labeling validation is the exception and is *formally* pre-registered: the protocol, the screening templates, and the agreement script were frozen as an OSF registration on 2026-05-12 (`https://doi.org/10.17605/OSF.IO/FGN3E`), two months before either label set was returned, and that registration pre-specified the $\kappa \geq 0.80$ target together with the contingency followed in Section 3.3 when the target was missed. The fixed-slot, desconfound and silver-external analyses, the Claude stack at temperature=0 and the Jev arm are likewise not pre-registered. We acknowledge the absence of formal pre-registration for the exploratory core as a limitation and recommend that future LLM-in-SR work register analyses on OSF or AsPredicted before data collection. We did not retrofit pre-registration claims to the original exploratory analyses.

5.6. Recommendations

Practical strategies for reproducible geoscientific data analysis have been set out in this journal.[3] Every such strategy presumes a compute step that returns the same output when re-executed, which is the premise an LLM-mediated step removes. The recommendations below are what that premise costs when it no longer holds, and they are additions to existing practice rather than a substitute for it.

1. **Run each LLM step at least three times** and report EMR together with the number of runs, since EMR declines as runs are added (Section 4.7).

2. **Record the transmitted request payload** and its hash in the call record, not the requested configuration.
3. **Report the deployment stack**—weights, provider, infrastructure, API layer and access dates—not only the model name.
4. **Do not treat temperature zero or a seed as a reproducibility control**; verify by repetition.
5. **Report schema conformance and accuracy alongside EMR.**
6. **Prefer local single-device serving** for reproducibility-critical steps when capability permits, with hardware and software versions pinned.
7. **Where a model returns probabilities**, route items whose probabilities move across runs to a human reader.

6. Conclusion

LLM steps entering environmental evidence pipelines do not inherit the re-execution guarantee that the rest of the modelling toolchain provides. Across 35,636 calls, local single-device stacks reproduced their outputs exactly, while API-served stacks at temperature zero returned an identical complete extraction for 15–47% of articles. Identical weights served through two stacks disagreed on 38.8% of jointly decided abstracts, all in one direction, so a model name does not specify the experimental condition. A transmitted seed, a fixed-slot output shape and a decision model returning probabilities each left the variation in place; temperature zero reduced it without removing it, and one provider now rejects non-default temperatures on its newer models. Reproducibility was also separate from usability: the perfectly reproducible local stacks returned schema-conforming extractions on 38–43%

of calls.

Frameworks that assess computational reproducibility process by process[39] need a per-process check for LLM-mediated steps. Whole-output EMR and schema conformance, computed from call records that store the transmitted payload rather than the requested one, provide it; our own temperature defect shows why that distinction matters. Because per-vendor figures expire with each provider update, the harness re-runs the audit as a configuration change.

Acknowledgements

The authors thank the two independent raters who labeled the validation subset **[PENDING: names, or removal of this sentence if both raters are listed as co-authors]**.

Funding Statement

This research received no specific grant from any funding agency in the public, commercial, or not-for-profit sectors. API costs for the Claude, Gemini, GPT-4.1 and Jev experiments were funded by the authors.

Competing Interests

The authors declare no competing interests.

Use of AI Writing Tools

AI-based tools (Claude, Anthropic) were used for code development assistance and manuscript editing support. All scientific content, experimental

design, data analysis, and interpretation of results were performed exclusively by the human authors. The AI tools used in manuscript preparation are the same models evaluated as experimental subjects in this study; this dual role was managed by ensuring that all reported results were computed deterministically from the raw experimental data, independently of any AI writing assistance. All numerical results, tables, and figures were computed deterministically from the raw experimental outputs before the text reporting them was written; no result depends on the writing-time use of any LLM. The complete commit history is publicly auditable at `https://github.com/Roverlucas/llm-evidence-synthesis-reproducibility`.

Data Availability Statement

All code, data, prompts, schemas, raw outputs, and run provenance records are publicly available at `https://github.com/Roverlucas/llm-evidence-synthesis-re` and archived at the Open Science Framework (`https://doi.org/10.17605/OSF.IO/VR934`). The dual-human labeling protocol is deposited separately as a frozen OSF registration (`https://doi.org/10.17605/OSF.IO/FGN3E`, 2026-05-12), which pre-dates label collection; the returned labels, agreement statistics, and the v1.2 protocol amendment are in the repository under `data/dual_labeling/` ([**PENDING: repository tag for the submitted version**]). API keys are excluded from the repository. The 500 PubMed abstract identifiers, gold standard labels, and complete analysis scripts are included to enable full reproduction of the reported results.

Author Contributions

Lucas Rover (L.R.) conceived the study, designed the protocol, developed the software, conducted all experiments and analyses, and wrote the manuscript. **Yara de Souza Tadano** (Y.d.S.T.) supervised the research, contributed to methodology design, and reviewed the manuscript.

References

[1] H.-J. Yoon, F. B. Ashraf, T. A. Ruggles, and D. Singh. "Scaling open-weight large language models for hydropower regulatory information extraction: A systematic analysis". In: *Environmental Modelling & Software* 203 (2026), p. 107030. DOI: 10.1016/j.envsoft.2026.107030.

[2] E. Park, J. Park, T. Kim, and A. Jin. "What structured tool interfaces do and do not provide for LLM-based SWAT+ calibration". In: *Environmental Modelling & Software* 205 (2026), p. 107142. DOI: 10.1016/j.envsoft.2026.107142.

[3] M. Schlögl, L. Waltersdorfer, P. Regner, A. Siposova, and A. Brenning. "Overcoming barriers to reproducibility in geoscientific data analysis: Challenges and practical implementation strategies". In: *Environmental Modelling & Software* 200 (2026), p. 106962. DOI: 10.1016/j.envsoft.2026.106962.

[4] J. P. T. Higgins, J. Thomas, J. Chandler, et al. *Cochrane Handbook for Systematic Reviews of Interventions*. 2nd. Wiley, 2019.

[5] M. J. Page, J. E. McKenzie, P. M. Bossuyt, I. Boutron, T. C. Hoffmann, C. D. Mulrow, et al. “The PRISMA 2020 Statement: An Updated Guideline for Reporting Systematic Reviews”. In: *BMJ* 372 (2021), n71.

[6] R. Borah, A. W. Brown, P. L. Capers, and K. A. Kaiser. “Analysis of the Time and Workers Needed to Conduct Systematic Reviews”. In: *BMJ Open* 7.4 (2017), e012545.

[7] T. Oami, Y. Okada, and T.-a. Nakada. “Performance of a Large Language Model in Screening Citations”. In: *JAMA Network Open* 7.7 (2024). PMID: 38976267. Published 1 July 2024, e2420496.

[8] Q. Khraisha et al. “Can large language models replace humans in systematic reviews? Evaluating GPT-4’s efficacy in screening and extracting data from peer-reviewed and grey literature in multiple languages”. In: *Research Synthesis Methods* 15.4 (2024), pp. 616–626. DOI: 10.1002/jrsm.1715.

[9] G. Gartlehner, L. Kahwati, R. Hilscher, et al. “Data Extraction for Evidence Synthesis Using a Large Language Model: A Proof-of-Concept Study”. In: *Research Synthesis Methods* 15.4 (2024), pp. 576–589.

[10] M. K. Jensen et al. “ChatGPT-4o Can Serve as the Second Rater for Data Extraction in Systematic Reviews”. In: *PLOS ONE* 20.1 (2025), e0313401.

[11] Y. Li, S. Datta, M. Rastegar-Mojarad, K. Lee, H. Paek, J. Glasgow, C. Liston, L. He, X. Wang, and Y. Xu. “Enhancing systematic literature reviews with generative artificial intelligence: development, ap-

plications, and performance evaluation". In: *Journal of the American Medical Informatics Association* 32.4 (2025), pp. 616–625. DOI: 10.1093/jamia/ocaf030.

[12] D. Scherbakov et al. "The Emergence of Large Language Models as Tools in Literature Reviews". In: *Journal of the American Medical Informatics Association* 32.5 (2025), ocaf063.

[13] K. Matsui, T. Utsumi, Y. Aoki, T. Maruki, M. Takeshima, and Y. Takaesu. "Human-Comparable Sensitivity of Large Language Models in Identifying Eligible Studies Through Title and Abstract Screening". In: *Journal of Medical Internet Research* 26 (2024), e52758.

[14] T. Oami, Y. Okada, and T.-a. Nakada. "Optimal Large Language Models to Screen Citations for Systematic Reviews". In: *Research Synthesis Methods* 16.6 (2025). doi:10.1017/rsm.2025.10014, pp. 859–875.

[15] O. Farotimi, A. Dunn, C. J. Van Lissa, J. R. Polanin, D. Mavridis, and T. D. Pigott. "Guidance for manuscript submissions testing the use of generative AI for systematic review and meta-analysis". In: *Research Synthesis Methods* 17.2 (2025). Editorial guidance on reporting standards for GenAI-assisted evidence synthesis; published 11 December 2025, pp. 237–239. DOI: 10.1017/rsm.2025.10058.

[16] B. Atil, S. Aykent, A. Chittams, et al. "Non-Determinism of "Deterministic" LLM Settings". In: *arXiv preprint* (2024). arXiv:2408.04667.

[17] E. Klishevich, Y. Denisov-Blanch, S. Obstbaum, I. Ciobanu, and M. Kosinski. "Measuring Determinism in Large Language Models for Software Code Review". In: *arXiv preprint* (2025). arXiv:2502.20747.

[18] T. Fu, G. Martínez, J. Conde, C. Arriaga, P. Reviriego, X. Qi, and S. Liu. "Beyond Reproducibility: Token Probabilities Expose Large Language Model Nondeterminism". In: *arXiv preprint* (2026). arXiv:2601.06118.

[19] G. Karelin, K. Nakajima, E. F. Soto-Astorga, E. Carr, M. James, and T. Froese. "Indeterminism in Large Language Models: An Unintentional Step Toward Open-Ended Intelligence". In: *Preprint submitted to Artificial Life* (2025). PhilSci-Archive 26807; preprint announced September 2025. URL: `https://philsci-archive.pitt.edu/26807/`.

[20] L. Rover. "Hidden Non-Determinism in Large Language Model APIs: A Lightweight Provenance Protocol for Reproducible Generative AI Research". In: *Journal of Artificial Intelligence Research* (2026). Under review. Preprint and replication package: `https://github.com/Roverlucas/genai-reproducibility-protocol`.

[21] M. Hutson. "Artificial Intelligence Faces Reproducibility Crisis". In: *Science* 359.6377 (2018), pp. 725–726.

[22] B. Haibe-Kains, G. A. Adam, A. Hosny, et al. "Transparency and Reproducibility in Artificial Intelligence". In: *Nature* 586 (2020), pp. 14–16.

[23] S. Kapoor and A. Narayanan. "Leakage and the Reproducibility Crisis in Machine-Learning-Based Science". In: *Patterns* 4.9 (2023), p. 100804.

[24] H. Han. "Challenges of Reproducible AI in Biomedical Data Science". In: *BMC Medical Genomics* 18 (2025), p. 2072.

[25] S. Desai et al. "What Is Reproducibility in Artificial Intelligence and Machine Learning Research?" In: *AI Magazine* 46.1 (2025), e70004.

[26] H. Semmelrock, T. Ross-Hellauer, S. Kopeinik, D. Theiler, A. Haberl, S. Thalmann, and D. Kowald. "Reproducibility in Machine-Learning-Based Research: Overview, Barriers, and Drivers". In: *AI Magazine* 46.1 (2025), e70002.

[27] Z. Wang, L. Cao, B. Danek, Q. Jin, Z. Lu, and J. Sun. "Accelerating Clinical Evidence Synthesis with Large Language Models". In: *npj Digital Medicine* 8 (2025), p. 509.

[28] C. Cao et al. "Automation of Systematic Reviews with Large Language Models". In: *medRxiv* (2025). Preprint. doi:10.1101/2025.06.13.25329541.

[29] M. A. Khan et al. "Collaborative Large Language Models for Automated Data Extraction in Living Systematic Reviews". In: *Journal of the American Medical Informatics Association* 32.4 (2025). doi:10.1093/jamia/ocae325, pp. 638–647.

[30] L. Li, A. Mathrani, and T. Susnjak. "Transforming Evidence Synthesis: A Systematic Review of the Evolution of Automated Meta-Analysis in the Age of AI". In: *Research Synthesis Methods* (2025). First View. doi:10.1017/rsm.2025.10007.

[31] F. Angermeir, M. Amougou, M. Kreitz, A. Bauer, M. Linhuber, D. Fucci, F. Moyón C., D. Mendez, and T. Gorschek. "Reflections on the Reproducibility of Commercial LLM Performance in Empirical Software Engineering Studies". In: arXiv:2510.25506. 2025.

[32] B. Yu. "After Computational Reproducibility: Scientific Reproducibility and Trustworthy AI". In: *Harvard Data Science Review* 6.1 (2024).

[33] S. Longpre, R. Mahari, A. Chen, et al. “A Large-Scale Audit of Dataset Licensing and Attribution in AI”. In: *Nature Machine Intelligence* 6 (2024), p. 878.

[34] P. Liang, N. Rajani, D. Yang, et al. “Systematic Analysis of 32,111 AI Model Cards Characterizes Documentation Practice”. In: *Nature Machine Intelligence* 6 (2024), p. 857.

[35] R. Bommasani, K. Klyman, S. Longpre, et al. “The Foundation Model Transparency Index v1.1”. In: *Transactions on Machine Learning Research* (2024).

[36] S. Leo, M. R. Crusoe, L. Rodríguez-Navas, et al. “Recording Provenance of Workflow Runs with RO-Crate”. In: *PLOS ONE* 19.9 (2024), e0309210.

[37] A. Kale, T. Nguyen, F. C. Harris, C. Li, J. Zhang, and X. Ma. “Provenance Documentation to Enable Explainable and Trustworthy AI: A Literature Review”. In: *Data Intelligence* 5.1 (2023), pp. 139–162.

[38] S. Longpre et al. “Data Authenticity, Consent, and Provenance for AI Are All Broken”. In: *Proceedings of ICML 2024 (Position Paper)*. arXiv:2404.12691. 2024.

[39] Z. Zhu, M. Chen, G. Ren, Y. He, L. Sun, F. Zhang, Y. Wen, S. Yue, and G. Lü. “A framework for assessing the computational reproducibility of geo-simulation experiments”. In: *Environmental Modelling & Software* 186 (2025), p. 106323. DOI: 10.1016/j.envsoft.2025.106323.

[40] W. Yu, R. Xu, T. Ye, et al. “Estimates of Global Mortality Burden Associated with Short-Term $PM_{2.5}$ Exposure”. In: *The Lancet Planetary Health* 8.2 (2024), e146–e155.

[41] H. S. Iyer, S. Karasaki, L. Yi, Y. Hswen, P. James, and T. VoPham. “Harnessing Geospatial Artificial Intelligence (GeoAI) for Environmental Epidemiology: A Narrative Review”. In: *Current Environmental Health Reports* 12 (2025), p. 497.

[42] M. Yu, M. Fang, Z. Tian, B. Wang, and D. Walker. “Artificial Intelligence and Machine Learning for Environmental Health Study”. In: *Environment & Health* 3.10 (2025), pp. 1115–1116.

[43] Y. d. S. Tadano, E. T. Bacalhau, L. Casacio, E. Puchta, T. S. Pereira, T. A. Alves, C. M. L. Ugaya, and H. V. Siqueira. “Unorganized Machines to Estimate the Number of Hospital Admissions Due to Respiratory Diseases Caused by PM_{10} Concentration”. In: *Atmosphere* 12.10 (2021). doi:10.3390/atmos12101345, p. 1345.

[44] A. Dubey, A. Jauhri, A. Pandey, A. Kadian, A. Al-Dahle, et al. “The LLaMA 3 Herd of Models”. In: *arXiv preprint* (2024). arXiv:2407.21783.

[45] A. Q. Jiang, A. Sablayrolles, A. Mensch, C. Bamford, D. S. Chaplot, et al. “Mistral 7B”. In: *arXiv preprint* (2023). arXiv:2310.06825.

[46] Gemma Team, T. Mesnard, C. Hardin, R. Dadashi, S. Bhupatiraju, et al. “Gemma 2: Improving Open Language Models at a Practical Size”. In: *arXiv preprint* (2024). arXiv:2408.00118.

[47] Anthropic. *Claude Sonnet 4.5 System Card*. Tech. rep. `https://docs.anthropic.com/en/docs/about-claude/models`. Anthropic, 2025.

[48] G. Comanici, E. Bieber, M. Schaekermann, I. Pasupat, N. Sachdeva, et al. “Gemini 2.5: Pushing the Frontier with Advanced Reasoning, Multimodality, Long Context, and Agentic Capabilities”. In: *arXiv preprint* (2025). arXiv:2507.06261.

[49] OpenAI. *GPT-4.1: A New Generation of OpenAI Models*. Tech. rep. Released April 2025. `https://openai.com/index/gpt-4-1/`. OpenAI, 2025.