

Supplementary Material

When the Same Question Gets Different Answers:
Quantifying LLM Non-Determinism in Evidence Synthesis

Lucas Rover

Yara de Souza Tadano

Contents

1 PubMed Search Strategy	3
1.1 Broad Query (573 records)	3
1.2 Design-Filtered Query (222 records)	3
1.3 Exclusion Candidates (475 records)	3
1.4 Corpus Assembly	3
2 Prompt Templates	4
2.1 Stage A: Abstract Screening Prompt	4
2.2 Stage B: Data Extraction Prompt	5
3 JSON Schemas for Output Validation	5
3.1 Screening Output Schema	6
3.2 Extraction Output Schema	6
4 Gold Standard Labeling Protocol	6
4.1 Screening Labels	6
4.2 Extraction Labels	6
5 Example Outputs: Exact Match vs. Near-Miss	6
5.1 Example 1: Exact Match (Local Model – Gemma 2 9B)	7
5.2 Example 2: Near-Miss (Cloud API – Claude Sonnet 4.5)	7
6 Model Configurations	8
7 Provenance Protocol Details	8
7.1 Call-Level Hashing	8
7.2 Output Hashing	9
7.3 Run Cards	9
7.4 Verification Protocol	9
8 Corpus Statistics	9
9 Experimental Timeline	9
10 Software and Dependencies	9
11 Complete Bootstrap Confidence Intervals	10

12 Fixed-Slot Extraction Prompt and Comparison	10
13 LLaMA Cloud Desconfound Experiment Details	12
14 Silver Standards and Cross-Validation	12
14.1 Silver-Internal: Majority Vote of Six Evaluated Models	12
14.2 Silver-External: DeepSeek-R1 (5 Runs)	12
14.3 Cross-Validation Between Silvers	14
15 Pairwise Disagreement and Rationale Similarity	14
16 Multiple Comparison Correction for Field-Level Contrasts	14
17 Small-Literature Meta-Analytic Simulation	15
18 Seed-Effect Empirical Test	15
19 Pre-Registration Disclosure	15

1 PubMed Search Strategy

All abstracts were retrieved from PubMed via the NCBI E-utilities API (`esearch` + `efetch`) on February 11, 2026. Two complementary queries were used:

1.1 Broad Query (573 records)

Listing 1: PubMed broad search query

```
("Particulate Matter"[MeSH] OR "PM2.5" OR "fine particulate matter"
OR "fine particles" OR "ambient particulate matter")
AND ("Hospitalization"[MeSH] OR "hospital admission"
OR "hospital admissions" OR "emergency department"
OR "ED visit" OR "ED visits")
AND ("Respiratory Tract Diseases"[MeSH] OR "respiratory"
OR "asthma" OR "COPD" OR "pneumonia" OR "bronchitis"
OR "bronchiolitis")
AND ("time series" OR "time-series" OR "case-crossover"
OR "distributed lag" OR "Poisson regression" OR "GAM"
OR "generalized additive model")
```

1.2 Design-Filtered Query (222 records)

Listing 2: PubMed design-filtered query

```
("PM2.5" OR "fine particulate matter"
OR "particulate matter 2.5")
AND ("respiratory" OR "asthma" OR "COPD" OR "pneumonia")
AND ("hospitalization" OR "hospital admission"
OR "emergency department")
AND ("time series" OR "time-series" OR "case-crossover")
```

1.3 Exclusion Candidates (475 records)

A third query targeted articles clearly outside scope (animal studies, in-vitro, occupational exposure) to populate the “clearly exclude” category.

1.4 Corpus Assembly

From the merged candidate pool (1,021 unique records after deduplication):

- 100 abstracts meeting all six inclusion criteria were labeled “clearly include”
- 100 abstracts with unambiguous exclusion reasons were labeled “clearly exclude”
- 300 abstracts with borderline characteristics (e.g., mixed pollutants, ambiguous outcomes) were labeled “ambiguous”

The 200 “clear” abstracts were independently labeled by two reviewers with discordance resolution. The 300 “ambiguous” abstracts were classified using study-design indicators and keyword matching (see Labeling Guide, Section 4).

2 Prompt Templates

The exact prompts used for both pipeline stages are reproduced below. These prompts were held constant across all 6 models and all 120 experimental runs.

2.1 Stage A: Abstract Screening Prompt

Listing 3: Screening prompt template (configs/prompts/screening.txt)

```
You are an expert epidemiologist conducting a systematic review on
the association between PM2.5 exposure and respiratory
hospitalizations.

Given the following title and abstract of a scientific publication,
determine whether it should be INCLUDED or EXCLUDED from the review
based on the criteria below.

## Inclusion Criteria
1. Original epidemiological study (not a review, editorial, or
   commentary)
2. Exposure: PM2.5 or fine particulate matter (<=2.5 um)
3. Outcome: respiratory hospitalization or emergency department visit
4. Study design: time-series or case-crossover
5. Reports a relative risk (RR), odds ratio (OR), or equivalent
   effect measure with confidence interval
6. Published in English

## Exclusion Criteria
- Reviews, meta-analyses, editorials, or commentaries
- Exposure other than PM2.5 (unless PM2.5 is one of multiple
  exposures analyzed)
- Outcome other than respiratory hospitalization/ED visit
- No quantitative effect estimate reported
- Animal or in-vitro studies

## Input
Title: {title}
Abstract: {abstract}

## Instructions
Respond with a JSON object only. Do not include any text outside
the JSON.

{
  "decision": "include" | "exclude" | "uncertain",
  "confidence": 0.0-1.0,
  "rationale": "brief explanation of decision",
  "exposure": "PM2.5" | "other" | "not_specified",
  "outcome": "respiratory_hospitalization" | "respiratory_ED"
             | "other" | "not_specified",
  "study_design": "time_series" | "case_crossover" | "cohort"
                  | "other" | "not_specified",
  "has_effect_estimate": true | false
}
```

2.2 Stage B: Data Extraction Prompt

Listing 4: Extraction prompt template (configs/prompts/extraction.txt)

```
You are an expert epidemiologist extracting quantitative data from a
scientific publication on PM2.5 and respiratory hospitalizations for
a systematic review and meta-analysis.

Given the following title and abstract, extract the structured data
below. If a field is not reported in the abstract, use null.

## Input
Title: {title}
Abstract: {abstract}

## Instructions
Extract ALL reported effect estimates. If multiple estimates are
reported (e.g., different lags, subgroups), extract each as a
separate entry in the "estimates" array.

Respond with a JSON object only. Do not include any text outside
the JSON.

{
  "study_id": "first_author_year",
  "study_location": "city, country",
  "study_period": "YYYY-YYYY",
  "study_design": "time_series" | "case_crossover" | "other",
  "population": "general" | "elderly" | "children" | "other",
  "sample_size": null | integer,
  "estimates": [
    {
      "effect_measure": "RR" | "OR" | "HR" | "IRR" | "other",
      "effect_estimate": float,
      "ci_lower": float,
      "ci_upper": float,
      "ci_level": 95,
      "exposure_increment": "per 10 ug/m3" | "per IQR" | "other",
      "lag": "lag0" | "lag1" | "lag0-1" | "other",
      "outcome_specific": "all_respiratory" | "pneumonia"
                          | "COPD" | "asthma" | "other",
      "covariates": ["temperature", "humidity", "trend",
                    "seasonality", "..."]
    }
  ]
}
```

3 JSON Schemas for Output Validation

All LLM outputs were validated against JSON Schema (Draft-07) definitions. Outputs failing validation were flagged but retained to ensure complete provenance.

3.1 Screening Output Schema

Seven required fields, no additional properties permitted: `decision` (enum: include/exclude/uncertain), `confidence` (0.0–1.0), `rationale` (string, min 10 chars), `exposure`, `outcome`, `study_design` (categorical enums), and `has_effect_estimate` (boolean).

3.2 Extraction Output Schema

Required fields: `study_id` (string), `estimates` (array). Optional metadata: `study_location`, `study_period`, `study_design`, `population`, `sample_size`. Each estimate requires: `effect_measure`, `effect_estimate`, `ci_lower`, `ci_upper` (all with range constraints 0.1–10.0).

Full schemas are available in the repository at `configs/schemas/`.

4 Gold Standard Labeling Protocol

4.1 Screening Labels

The 200 “clear” abstracts (100 include, 100 exclude) were independently labeled by two reviewers following a structured protocol. Discordance was resolved by a third reviewer. Inter-rater agreement targets: Cohen’s $\kappa \geq 0.80$, discordance rate $< 15\%$.

The 300 “ambiguous” abstracts were classified using keyword matching and study-design indicators. These labels serve as reference values for accuracy computation but do not affect the primary metric (EMR), which measures self-consistency regardless of ground truth.

4.2 Extraction Labels

For the 100 “clearly include” articles, extraction templates were created following standardized rules:

- Prefer the primary/main estimate if multiple are reported
- Prefer all-respiratory over specific conditions (asthma, COPD)
- Prefer single-pollutant model over multi-pollutant
- Prefer lag 0–1 if multiple lags reported without a “best” designation
- Record per 10 $\mu\text{g}/\text{m}^3$ – convert if different increment used
- If abstract reports % change, convert: $\text{RR} = 1 + (\% \text{change}/100)$

Discordance threshold: > 0.005 for effect estimates, > 0.01 for CI bounds.

5 Example Outputs: Exact Match vs. Near-Miss

To illustrate the nature of extraction non-determinism, we present two representative cases.

5.1 Example 1: Exact Match (Local Model – Gemma 2 9B)

All 10 runs produced identical output (EMR = 1.000):

Listing 5: Gemma 2 9B extraction output (identical across all 10 runs)

```
{
  "study_id": "chen_2017",
  "study_location": "Shanghai, China",
  "study_period": "2013-2015",
  "study_design": "time_series",
  "population": "general",
  "sample_size": null,
  "estimates": [
    {
      "effect_measure": "RR",
      "effect_estimate": 1.023,
      "ci_lower": 1.005,
      "ci_upper": 1.042,
      "ci_level": 95,
      "exposure_increment": "per 10 ug/m3",
      "lag": "lag0-1",
      "outcome_specific": "all_respiratory",
      "covariates": ["temperature", "humidity", "day_of_week",
                    "long_term_trend", "seasonality"]
    }
  ]
}
```

5.2 Example 2: Near-Miss (Cloud API – Claude Sonnet 4.5)

Runs 1–8 and 10 produced one output; Run 9 differed in the `estimates` array:

Listing 6: Claude Sonnet 4.5 – Run 9 extracted 2 estimates instead of 1

```
{
  "study_id": "chen_2017",
  "study_location": "Shanghai, China",
  "study_period": "2013-2015",
  "study_design": "time_series",
  "population": "general",
  "sample_size": null,
  "estimates": [
    {
      "effect_measure": "RR",
      "effect_estimate": 1.023,
      "ci_lower": 1.005,
      "ci_upper": 1.042,
      "ci_level": 95,
      "exposure_increment": "per 10 ug/m3",
      "lag": "lag0-1",
      "outcome_specific": "all_respiratory",
      "covariates": ["temperature", "humidity", "day_of_week",
                    "long_term_trend", "seasonality"]
    },
  ],
}
```

```

{
  "effect_measure": "RR",
  "effect_estimate": 1.031,
  "ci_lower": 1.008,
  "ci_upper": 1.054,
  "ci_level": 95,
  "exposure_increment": "per 10 ug/m3",
  "lag": "lag2",
  "outcome_specific": "pneumonia",
  "covariates": ["temperature", "humidity", "day_of_week"]
}
]
}

```

Key observation: The metadata fields (`study_id`, `study_location`, `study_design`) are identical across all 10 runs (consistent with BERTScore $F_1 = 0.997$). The variation lies in the `estimates` array—Run 9 extracted an additional sub-group estimate (pneumonia at lag 2) that the other 9 runs did not. This single additional estimate causes the hash-based EMR to register a non-match, while the BERTScore over metadata text remains near-perfect. This exemplifies the “semantic paradox” reported in Section 4.5 of the main paper.

6 Model Configurations

Table 1: Complete model configurations for all six LLMs.

Model	Provider	Temp.	Seed	Max Tokens	Timeout	Version
LLaMA 3 8B	Ollama	0.0	42	4096	600s	llama3:8b
Mistral 7B	Ollama	0.0	42	4096	600s	mistral:7b
Gemma 2 9B	Ollama	0.0	42	4096	600s	gemma2:9b
Claude Sonnet 4.5	Anthropic	0.0	—	4096	90s	claude-sonnet-4-5-20250929
Gemini 2.5 Pro	Google	0.0	42	8192 [†]	90s	gemini-2.5-pro
GPT-4.1	OpenAI	0.0	42	4096	90s	gpt-4.1

[†]Gemini requires higher `maxOutputTokens` because thinking tokens consume the output budget.

7 Provenance Protocol Details

7.1 Call-Level Hashing

Each LLM call produces a **call hash** computed as:

Listing 7: Call hash computation (`src/provenance/hasher.py`)

```

import hashlib, json

def compute_call_hash(prompt, input_text, model_id, temperature,
                      seed=None):
    fields = {
        "prompt": prompt,
        "input_text": input_text,
        "model_id": model_id,

```



```

        "temperature": temperature,
        "seed": seed,
    }
    canonical = json.dumps(fields, sort_keys=True,
                           ensure_ascii=True)
    return hashlib.sha256(canonical.encode()).hexdigest()

```

The use of `sort_keys=True` and `ensure_ascii=True` ensures deterministic serialization across platforms and Python versions.

7.2 Output Hashing

The raw LLM response text is hashed directly:

```

def compute_output_hash(output_text):
    return hashlib.sha256(output_text.encode()).hexdigest()

```

7.3 Run Cards

Each run produces a structured JSON run card containing:

- Run metadata: model ID, provider, stage, run number
- Configuration: temperature, seed, max tokens
- Execution: timestamps, call counts (total/success/fail), duration
- Provenance: aggregate output hash (SHA-256 of sorted individual hashes joined by pipe delimiter)

7.4 Verification Protocol

If two runs of the same model produce different aggregate hashes, the per-call output hashes are compared to identify exactly which abstracts changed. This enables targeted analysis of non-determinism at the individual-abstract level.

8 Corpus Statistics

9 Experimental Timeline

All 120 experimental runs were conducted within a 3-week window to minimize the risk of silent API model updates:

10 Software and Dependencies

- **Python:** 3.14.3
- **OS:** macOS Darwin 24.6.0 (Apple M4, 24 GB RAM)
- **Ollama:** v0.15.5 (local model serving)

Table 2: Corpus descriptive statistics.

Statistic	Value
Total abstracts	500
Unique journals	148
Publication range	1994–2026
Mean abstract length (characters)	1,873
Median abstract length (characters)	1,812
Min abstract length (characters)	423
Max abstract length (characters)	4,291
Clear include	100 (20%)
Clear exclude	100 (20%)
Ambiguous	300 (60%)

Table 3: Experiment execution timeline.

Model	Screening	Extraction	Duration
LLaMA 3 8B	Feb 11–12	Feb 12–13	~91h
Mistral 7B	Feb 13–15	Feb 15–16	~77h
Gemma 2 9B	Feb 16–17	Feb 17	~46h
Claude Sonnet 4.5	Feb 18	Feb 18–19	~12h
Gemini 2.5 Pro	Feb 20	Feb 20–21	~8h
GPT-4.1	Feb 22	Feb 22–Mar 2	~6h

- **Key dependencies:** `numpy` ≥ 1.26 , `pandas` ≥ 2.1 , `scipy` ≥ 1.12 , `jsonschema` ≥ 4.20 , `bert-score` $\geq 0.3.13$, `transformers` ≥ 4.36
- **No external SDKs:** All API calls use Python’s `urllib.request` to ensure uniform request handling
- **Test suite:** 45 tests (`pytest` ≥ 8.0), 100% pass rate
- **License:** MIT
- **Repository:** <https://github.com/Roverlucas/llm-evidence-synthesis-reproducibility>

11 Complete Bootstrap Confidence Intervals

All confidence intervals were computed using the percentile bootstrap method with 10,000 resamples. For models with $\text{EMR} = 1.000$, the bootstrap trivially returns $[1.000, 1.000]$; the rule-of-three upper bound on the non-match rate is $3/n$ (0.6% for $n = 500$ screening, 3.0% for $n = 100$ extraction).

12 Fixed-Slot Extraction Prompt and Comparison

The fixed-slot prompt template used in the sensitivity analysis (main text §4.7):

Listing 8: Fixed-slot extraction prompt (`configs/prompts/extraction_fixed_slot.txt`)

Table 4: Complete EMR with 95% bootstrap confidence intervals for all model-stage combinations.

Model	Stage	EMR	95% CI	<i>n</i>
LLaMA 3 8B	Screening	1.000	[1.000, 1.000]*	480
LLaMA 3 8B	Extraction	1.000	[1.000, 1.000]*	96
Mistral 7B	Screening	1.000	[1.000, 1.000]*	500
Mistral 7B	Extraction	1.000	[1.000, 1.000]*	100
Gemma 2 9B	Screening	1.000	[1.000, 1.000]*	500
Gemma 2 9B	Extraction	1.000	[1.000, 1.000]*	100
Claude Sonnet 4.5	Screening	0.974	[0.960, 0.986]	500
Claude Sonnet 4.5	Extraction	0.050	[0.010, 0.090]	100
Gemini 2.5 Pro	Screening	0.936	[0.914, 0.956]	500
Gemini 2.5 Pro	Extraction	0.200	[0.120, 0.280]	100
GPT-4.1	Screening	0.970	[0.954, 0.984]	500
GPT-4.1	Extraction	0.150	[0.080, 0.220]	100

*Rule-of-three upper bound on non-match rate: $3/n$ (screening: 0.6%, extraction: 3.0%).

You are an expert epidemiologist extracting quantitative data from a scientific publication on PM2.5 and respiratory hospitalizations for a systematic review and meta-analysis.

Given the following title and abstract, extract the SINGLE PRIMARY effect estimate using the fixed selection rules below. Do not produce a variable-length array; produce exactly one primary_estimate object (or null if no estimate is reportable).

Fixed selection rules (apply in order)

1. Prefer all-respiratory outcomes over specific subgroups.
2. Prefer single-pollutant PM2.5 model over multi-pollutant adjustments.
3. If multiple lags are reported, prefer lag 0-1 (cumulative); else lag 0.
4. Prefer per 10 ug/m³ exposure increment; convert if reported per IQR.
5. If percent change reported, convert: $RR = 1 + (\%change/100)$.
6. If no quantitative effect estimate with CI is reportable, set primary_estimate = null.

Input

Title: {title}

Abstract: {abstract}

Output (JSON only, no extra text)

```
{
  "study_id": "first_author_year",
  "study_location": "city, country",
  "study_period": "YYYY-YYYY",
  "study_design": "time_series" | "case_crossover" | "other",
  "population": "general" | "elderly" | "children" | "other",
  "sample_size": null | integer,
  "primary_estimate": { ... } | null,
  "n_estimates_in_abstract": integer
}
```

Table 5: Fixed-slot extraction sensitivity analysis: 3 cloud models $\times$ 3 runs $\times$ 100 INCLUDE articles. Variable-length baseline from main Table 3 (10 runs). Provider pinned per call: Claude Sonnet 4.5 via Anthropic API; Gemini 2.5 Pro via Google API; GPT-4.1 via OpenAI API.

Model	Var-len EMR	Fixed-slot EMR	Δ abs	Δ rel	Pairwise dis.
Claude Sonnet 4.5	0.050	0.030	-0.020	-40.0%	0.78
Gemini 2.5 Pro	0.200	0.185	-0.015	-7.6%	0.49
GPT-4.1	0.150	0.444	+0.294	+196.3%	0.36

13 LLaMA Cloud Desconfound Experiment Details

The desconfound experiment (main text §4.8) serves the identical model weights via cloud and compares against the local Ollama deployment.

Table 6: Desconfound experimental configuration. Both deployments use the SAME model weights, prompt, seed=42, and temperature=0; only the serving infrastructure differs.

Parameter	Local (Ollama)	Cloud (DeepInfra)
Model	llama3:8b	meta-llama/llama-3-8b-instruct
Provider	Ollama v0.15.5	OpenRouter $\rightarrow$ DeepInfra (pinned)
Hardware	Apple M4, 24 GB	DeepInfra GPU cluster
Inference	Single-stream	Batched continuous-batching
Seed	42	42
Temperature	0.0	0.0
Max tokens	4,096	512 (screening)
N runs	10	10
N abstracts	500	500
Date range	Feb 11–13, 2026	Apr 25–28, 2026

14 Silver Standards and Cross-Validation

Two independent silver standards complement the heuristic gold standard for the 100 INCLUDE articles.

14.1 Silver-Internal: Majority Vote of Six Evaluated Models

Consensus extraction is computed as the per-field mode across all 6 models $\times$ 10 runs (60 votes per item). Numeric fields are binned at 0.01 resolution before mode computation.

14.2 Silver-External: DeepSeek-R1 (5 Runs)

DeepSeek-R1 (`deepseek-reasoner`) is a reasoning model from a different provider family than the 6 evaluated models, providing an independent reference. Five runs were aggregated by per-field majority vote.

Table 7: Per-run successful-call counts. Cloud runs 5 and 6 experienced transient infrastructure failures resulting in reduced valid-item counts, which we report transparently as a cloud-reliability finding. Local runs are uniformly 480/500 successful (the same 20 abstracts deterministically exceed response length in every local run).

Run	Local valid	Cloud valid
1	480	491
2	480	489
3	480	491
4	480	489
5	480	45*
6	480	221*
7	480	491
8	480	491
9	480	491
10	480	491

*Transient cloud-side failure (503 `Service Unavailable` bursts).

Table 8: Silver-internal consensus. Items with consensus = items where at least one model-run produced a non-null value. Mean mode-agreement = average proportion of votes matching the modal value across items with consensus.

Field	Items w/ consensus	Mean mode-agreement
effect_estimate	95/100	0.858
ci_lower	84/100	0.846
ci_upper	84/100	0.845
effect_measure	100/100	0.783
outcome_specific	100/100	0.694
exposure_increment	100/100	0.761
lag	100/100	0.644

Table 9: Silver-external consensus from DeepSeek-R1 (5 runs $\times$ 100 items).

Field	Items w/ consensus	Mean mode-agreement
effect_estimate	84/100	0.890
ci_lower	74/100	0.894
ci_upper	74/100	0.889
effect_measure	84/100	0.906
outcome_specific	84/100	0.803
exposure_increment	84/100	0.881
lag	75/100	0.862

Table 10: Field-level agreement between silver-internal and silver-external (numeric tolerance 0.05; categorical exact match). Spearman ρ on `effect_estimate` = **0.845**.

Field	n compared	Agreement
effect_estimate	84	0.798
ci_lower	74	0.797
ci_upper	74	0.784
effect_measure	84	0.738
outcome_specific	84	0.655
exposure_increment	84	0.798
lag	75	0.653

14.3 Cross-Validation Between Silvers

15 Pairwise Disagreement and Rationale Similarity

Table 11: Pairwise disagreement (mean fraction of $\binom{10}{2}=45$ run-pairs producing different outputs per item; 0 = perfect determinism). Compare to EMR (Table 10): EMR collapses items into binary match/non-match while pairwise disagreement reports the dispersion within non-matches.

Model	Stage	EMR	Pairwise	% items any-disagree
LLaMA 3 8B	screening	1.000	0.0000	0.00%
LLaMA 3 8B	extraction	1.000	0.0000	0.00%
Mistral 7B	screening	1.000	0.0000	0.00%
Mistral 7B	extraction	1.000	0.0000	0.00%
Gemma 2 9B	screening	1.000	0.0000	0.00%
Gemma 2 9B	extraction	1.000	0.0000	0.00%
Claude Sonnet 4.5	screening	0.974	0.0096	2.60%
Claude Sonnet 4.5	extraction	0.050	0.8180	95.00%
Gemini 2.5 Pro	screening	0.936	0.0198	6.40%
Gemini 2.5 Pro	extraction	0.200	0.4927	80.00%
GPT-4.1	screening	0.970	0.0137	3.00%
GPT-4.1	extraction	0.150	0.4858	85.00%

16 Multiple Comparison Correction for Field-Level Contrasts

We applied Holm-Bonferroni (FWER) and Benjamini-Hochberg (FDR) corrections to the 21 pairwise field-level EMR contrasts between the three cloud models. Of 21 contrasts: 7 are significant at raw $p < 0.05$, 3 survive Holm correction, 5 survive BH-FDR.

The remaining 18 contrasts (population, sample_size, study_design, study_period, screening overall, etc.) are not statistically robust after FWER correction; the original “distinct instability profiles” claim (main text Finding 3) is therefore tightened to: *differences are robust for study_location and overall extraction EMR, but not for other categorical fields.*

Table 12: Token-bigram Jaccard similarity on screening rationale (free-form text) vs. metadata (categorical concatenation). Computed across all $\binom{10}{2}=45$ run-pairs per item, averaged over 500 abstracts. Demonstrates that BERTScore $F_1 \geq 0.997$ on metadata is a saturation artifact: in non-saturating text (rationale), Claude exhibits only 0.378 mean similarity.

Model	Metadata Jaccard	Rationale Jaccard	Gap
LLaMA 3 8B	1.000	1.000	0.000
Mistral 7B	1.000	1.000	0.000
Gemma 2 9B	1.000	1.000	0.000
Claude Sonnet 4.5	0.978	0.378	0.600
Gemini 2.5 Pro	0.978	0.623	0.355
GPT-4.1	0.984	0.725	0.259

Table 13: Pairwise contrasts of cloud-API field-level EMR surviving Holm-Bonferroni correction at $\alpha=0.05$.

Field	Models	Δ EMR	Raw p	Holm p
study_location	Claude vs. GPT-4.1	-0.220	<0.0001	< 0.0001
study_location	Gemini vs. GPT-4.1	-0.104	0.001	0.018
extraction_overall_EMR	Claude vs. Gemini	-0.150	0.001	0.026

17 Small-Literature Meta-Analytic Simulation

18 Seed-Effect Empirical Test

Cambridge RSM guidance §4.3 requires empirical reporting of seed-parameter effectiveness on commercial APIs.

Seed effect for extraction (cloud-seeded vs. cloud-unseeded): +0.125 EMR. Deployment effect (local-seeded vs. cloud-seeded): +0.825 EMR. The deployment effect is **6.6 $\times$ larger** than the seed effect. We conclude that the seed parameter, as currently implemented in commercial APIs, does not deliver determinism; deployment paradigm dominates.

19 Pre-Registration Disclosure

This study was not formally pre-registered. The original experiments (main text §4.1–§4.6) are exploratory: 10 repetitions, whole-output hash EMR, four semantic-tier definitions, and fixed-effect meta-analytic pooling were chosen during analysis design but without an OSF or AsPredicted submission. The post-revision analyses (§4.7 fixed-slot, §4.8 desconfound, §5.5 cost-benefit, dual-human gold validation, silver-external) were designed and committed to the public Git repository *before* result computation.

Key commit timestamps (publicly auditable at <https://github.com/Roverlucas/llm-evidence-synthesis-reproducibility>):

- **2026-02-11** (75292f2): project initialization, prompts committed
- **2026-02-13 to 2026-03-02**: original experiment raw outputs committed

Table 14: Random-effects (DerSimonian-Laird) pooled RR variation across 200 random subsamples per k , seed=42, computed independently for each of 10 LLM runs. “Unstable null-crossing” = subsamples where the pooled 95% CI crosses RR=1 in some runs but not others (i.e., the meta-analytic conclusion changes depending on the LLM run).

Model	k	Mean range	P95 range	% unstable null-cross
Claude Sonnet 4.5	10	0.0082	0.0292	0.50%
Claude Sonnet 4.5	15	0.0081	0.0237	0.00%
Claude Sonnet 4.5	20	0.0078	0.0197	0.00%
Gemini 2.5 Pro	10	0.0167	0.0471	0.50%
Gemini 2.5 Pro	15	0.0131	0.0350	0.00%
Gemini 2.5 Pro	20	0.0110	0.0227	0.00%
GPT-4.1	10	0.0063	0.0263	0.00%
GPT-4.1	15	0.0054	0.0150	0.00%
GPT-4.1	20	0.0065	0.0149	0.00%

Table 15: Seed effect vs. deployment effect. Cloud models tested: Claude Sonnet 4.5 (no seed parameter), Gemini 2.5 Pro and GPT-4.1 (seed=42). Local models all use seed=42.

Group	Stage	Mean EMR	Mean pairwise dis.
Cloud, seed=42	screening	0.953	0.017
Cloud, no seed	screening	0.974	0.010
Local, seed=42	screening	1.000	0.000
Cloud, seed=42	extraction	0.175	0.489
Cloud, no seed	extraction	0.050	0.818
Local, seed=42	extraction	1.000	0.000

- **2026-03-02** (1b90c1b): `analysis/reproducibility_results.json` committed (results frozen)
- **2026-03-11** (646c6a3): first complete manuscript draft
- **2026-03-20** (7935445): submission-hardening revision
- **2026-04-23 to 2026-04-28**: post-revision blindage analyses committed

We acknowledge the absence of formal pre-registration as a limitation and recommend that future LLM-in-SR studies pre-register analyses on OSF before data collection.