

Deep Generative Models: Discrete Latent Variables

Bryan Eikema and Wilker Aziz

<https://vitutorial.github.io/tour/ua2020>



UNIVERSITY OF AMSTERDAM
Institute for Logic, Language and Computation



Discrete Latent Variables

- Language is an inherently discrete structure.

Discrete Latent Variables

- Language is an inherently discrete structure.
- Many structures used to describe language are discrete, e.g. trees, graphs, tags, etc.

- 1 First Attempt: Wake-Sleep
- 2 Neural Variational Inference and Learning
- 3 Score Function Estimator

Generative Models

Joint distribution over observed data x and latent variables z .

$$p(x, z|\theta) = \underbrace{p(z)}_{\text{prior}} \underbrace{p(x|z, \theta)}_{\text{likelihood}}$$

The likelihood and prior are often standard distributions (Gaussian, Bernoulli) with simple dependence on conditioning information.

Deep generative models

Joint distribution with **deep observation model**

$$p(x, z|\theta) = \underbrace{p(z)}_{\text{prior}} \underbrace{p(x|z, \theta)}_{\text{likelihood}}$$

mapping from z to $p(x|z, \theta)$ is a neural network with parameters θ

Deep generative models

Joint distribution with **deep observation model**

$$p(x, z|\theta) = \underbrace{p(z)}_{\text{prior}} \underbrace{p(x|z, \theta)}_{\text{likelihood}}$$

mapping from z to $p(x|z, \theta)$ is a neural network with parameters θ

Marginal likelihood

$$p(x|\theta) = \int p(x, z|\theta) \, dz = \int p(z)p(x|z, \theta) \, dz$$

intractable in general

Goals

We want

- richer probabilistic models

Goals

We want

- richer probabilistic models
- complex observation models
parameterised by neural networks

Goals

We want

- richer probabilistic models
- complex observation models
parameterised by neural networks

but we can't perform gradient-based MLE

Goals

We want

- richer probabilistic models
- complex observation models
parameterised by neural networks

but we can't perform gradient-based MLE

We need **approximate inference** techniques!

ELBO recap

And we've developed the ELBO

$$\log p(x) = \log \int p(z, x) dz$$

ELBO recap

And we've developed the ELBO

$$\log p(x) = \log \int p(z, x) dz = \log \int q(z|x) \frac{p(z, x)}{q(z|x)} dz$$

ELBO recap

And we've developed the ELBO

$$\begin{aligned}\log p(x) &= \log \int p(z, x) dz = \log \int q(z|x) \frac{p(z, x)}{q(z|x)} dz \\ &\stackrel{\text{JL}}{\geq} \underbrace{\mathbb{E}_{q(z|x)} \left[\log \frac{p(z, x)}{q(z|x)} \right]}_{\text{ELBO}}\end{aligned}$$

ELBO recap

And we've developed the ELBO

$$\begin{aligned}\log p(x) &= \log \int p(z, x) dz = \log \int q(z|x) \frac{p(z, x)}{q(z|x)} dz \\ &\stackrel{\text{JL}}{\geq} \underbrace{\mathbb{E}_{q(z|x)} \left[\log \frac{p(z, x)}{q(z|x)} \right]}_{\text{ELBO}} \\ \text{ELBO} &= \mathbb{E}_{q(z|x)} \left[\log \frac{p(z|x)p(x)}{q(z|x)} \right]\end{aligned}$$

ELBO recap

And we've developed the ELBO

$$\log p(x) = \log \int p(z, x) dz = \log \int q(z|x) \frac{p(z, x)}{q(z|x)} dz$$

$$\stackrel{\text{JL}}{\geq} \underbrace{\mathbb{E}_{q(z|x)} \left[\log \frac{p(z, x)}{q(z|x)} \right]}_{\text{ELBO}}$$

$$\begin{aligned} \text{ELBO} &= \mathbb{E}_{q(z|x)} \left[\log \frac{p(z|x)p(x)}{q(z|x)} \right] \\ &= - \underbrace{\text{KL} (q(z|x) \parallel p(z|x))}_{\text{gap}} + \log p(x) \end{aligned}$$

- 1 First Attempt: Wake-Sleep
- 2 Neural Variational Inference and Learning
- 3 Score Function Estimator

Wake-Sleep Algorithm

- Generalise latent variables to neural networks.
- Train generative neural model.
- Use variational inference! (kind of)
- Hinton et al. (1995)

Wake-Sleep Architecture

2 neural networks:

Wake-Sleep Architecture

2 neural networks:

- A generation network to model the data (the one we want to optimise) – parameters: θ

Wake-Sleep Architecture

2 neural networks:

- A generation network to model the data (the one we want to optimise) – parameters: θ
- An inference (recognition) network (to model the latent variable) – parameters: λ

Wake-Sleep Architecture

2 neural networks:


- A generation network to model the data (the one we want to optimise) – parameters: θ
- An inference (recognition) network (to model the latent variable) – parameters: λ
- Original setting: binary hidden units

Wake-Sleep Architecture


2 neural networks:

- A generation network to model the data (the one we want to optimise) – parameters: θ
- An inference (recognition) network (to model the latent variable) – parameters: λ
- Original setting: binary hidden units
- Training is performed in a “hard EM” fashion

Generator



Inference Network



Wake-sleep Training

Wake Phase

- Use inference network to sample hidden unit setting z from $q(z|x, \lambda)$
- Update generation parameters θ to maximize joint log-likelihood of data and latents $p(x, z|\theta)$

Wake-sleep Training

Wake Phase


- Use inference network to sample hidden unit setting z from $q(z|x, \lambda)$
- Update generation parameters θ to maximize joint log-likelihood of data and latents $p(x, z|\theta)$

Sleep Phase

- Produce dream sample \tilde{x} from random hidden unit z
- Update inference parameters λ to maximize probability of latent state $q(z|\tilde{x}, \lambda)$


Wake Phase Sampling

Sampling $z \sim q(z|x, \lambda)$




Wake Phase Sampling

Sampling $z \sim q(z|x, \lambda)$




Wake Phase Sampling

Sampling $z \sim q(z|x, \lambda)$




Wake Phase Sampling

Sampling $z \sim q(z|x, \lambda)$



Wake Phase Update

Compute $\log p(x, z|\theta)$ and update θ




Sleep Phase Sampling

Sampling $(z, \tilde{x}) \sim p(x, z|\theta)$




Sleep Phase Sampling

Sampling $(z, \tilde{x}) \sim p(x, z|\theta)$




Sleep Phase Sampling

Sampling $(z, \tilde{x}) \sim p(x, z|\theta)$



Sleep Phase Update

Compute $\log q(z|\tilde{x}, \lambda)$ and update λ



Wake Phase Objective

Objective

$$\arg \min_{\theta} \mathbb{E}_{p(x)} [\text{KL}(q(z|x, \lambda) || p(z|x, \theta))]$$

Wake Phase Objective

Objective

$$\begin{aligned} & \arg \min_{\theta} \mathbb{E}_{p(x)} [\text{KL}(q(z|x, \lambda) \parallel p(z|x, \theta))] \\ &= \arg \max_{\theta} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x) - \log p(x|\theta)] \end{aligned}$$

Wake Phase Objective

Objective

$$\begin{aligned} & \arg \min_{\theta} \mathbb{E}_{p(x)} [\text{KL}(q(z|x, \lambda) \parallel p(z|x, \theta))] \\ &= \arg \max_{\theta} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x) - \log p(x|\theta)] \end{aligned}$$

Approximation: optimize the lower-bound alone.

Wake Phase Objective

Objective

$$\begin{aligned} & \arg \max_{\theta} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x)] \\ &= \arg \max_{\theta} \mathbb{E}_{p(x)} [\mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \mathbb{H}[q(z|x, \lambda)]] \end{aligned}$$

Wake Phase Objective

Objective

$$\begin{aligned} & \arg \max_{\theta} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x)] \\ &= \arg \max_{\theta} \mathbb{E}_{p(x)} [\mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \mathbb{H}[q(z|x, \lambda)]] \end{aligned}$$

Gradient wrt θ for $x \sim p(x)$

$$\nabla_{\theta} \mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \nabla_{\theta} \mathbb{H}[q(z|x, \lambda)]$$

Wake Phase Objective

Objective

$$\begin{aligned} & \arg \max_{\theta} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x)] \\ &= \arg \max_{\theta} \mathbb{E}_{p(x)} [\mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \mathbb{H}[q(z|x, \lambda)]] \end{aligned}$$

Gradient wrt θ for $x \sim p(x)$

$$\begin{aligned} & \nabla_{\theta} \mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \nabla_{\theta} \mathbb{H}[q(z|x, \lambda)] \\ &= \mathbb{E}_{q(z|x, \lambda)} [\nabla_{\theta} \log p(z, x|\theta)] \end{aligned}$$

Wake Phase Objective

Objective

$$\begin{aligned} \arg \max_{\theta} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x)] \\ = \arg \max_{\theta} \mathbb{E}_{p(x)} [\mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \mathbb{H}[q(z|x, \lambda)]] \end{aligned}$$

Gradient wrt θ for $x \sim p(x)$

$$\begin{aligned} \nabla_{\theta} \mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \nabla_{\theta} \mathbb{H}[q(z|x, \lambda)] \\ = \mathbb{E}_{q(z|x, \lambda)} [\nabla_{\theta} \log p(z, x|\theta)] \\ \stackrel{\text{MC}}{\approx} \nabla_{\theta} \log p(z, x|\theta) \quad \text{where } z \sim q(z|x, \lambda) \end{aligned}$$

Wake Phase Objective

Assumes z to be fixed random draw from $q(z|x, \lambda)$
and maximises $\log p(z, x|\theta)$.

This is simply supervised learning with imputed latent data!

Sleep Phase Objective

Objective

$$\begin{aligned} & \arg \max_{\lambda} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x)] \\ &= \arg \max_{\lambda} \mathbb{E}_{p(x)} [\mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \mathbb{H}[q(z|x, \lambda)]] \end{aligned}$$

Sleep Phase Objective

Objective

$$\begin{aligned} \arg \max_{\lambda} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x)] \\ = \arg \max_{\lambda} \mathbb{E}_{p(x)} [\mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \mathbb{H}[q(z|x, \lambda)]] \end{aligned}$$

Gradient wrt λ for $x \sim p(x)$

$$\nabla_{\lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \nabla_{\lambda} \mathbb{H}[q(z|x, \lambda)]$$

Sleep Phase Objective

Objective

$$\begin{aligned} \arg \max_{\lambda} \mathbb{E}_{p(x)} [\text{ELBO}(\theta, \lambda|x)] \\ = \arg \max_{\lambda} \mathbb{E}_{p(x)} [\mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \mathbb{H}[q(z|x, \lambda)]] \end{aligned}$$

Gradient wrt λ for $x \sim p(x)$

$$\nabla_{\lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(z, x|\theta)] + \nabla_{\lambda} \mathbb{H}[q(z|x, \lambda)]$$

Let's change the objective!

Sleep Phase (Convenient) Objective

Flip the direction of the KL

$$\arg \min_{\lambda} \mathbb{E}_{p(x)} [\text{KL} (p(z|x, \theta) || q(z|x, \lambda))]$$

Sleep Phase (Convenient) Objective

Flip the direction of the KL

$$\begin{aligned} & \arg \min_{\lambda} \mathbb{E}_{p(x)} [\text{KL} (p(z|x, \theta) \parallel q(z|x, \lambda))] \\ &= \arg \min_{\lambda} \mathbb{E}_{p(x)} \mathbb{E}_{p(z|x, \theta)} [\log p(z|x, \theta) - \log q(z|x, \lambda)] \end{aligned}$$

Sleep Phase (Convenient) Objective

Flip the direction of the KL

$$\begin{aligned}
 & \arg \min_{\lambda} \mathbb{E}_{p(x)} [\text{KL} (p(z|x, \theta) \parallel q(z|x, \lambda))] \\
 &= \arg \min_{\lambda} \mathbb{E}_{p(x)} \mathbb{E}_{p(z|x, \theta)} [\log p(z|x, \theta) - \log q(z|x, \lambda)] \\
 &\stackrel{\text{asm}}{=} \arg \max_{\lambda} \mathbb{E}_{p(x, z|\theta)} [\log q(z|x, \lambda)] - \underbrace{\mathbb{E}_{p(x, z|\theta)} [\log p(z|x, \theta)]}_{\text{constant}}
 \end{aligned}$$

Sleep Phase (Convenient) Objective

Flip the direction of the KL

$$\begin{aligned}
 & \arg \min_{\lambda} \mathbb{E}_{p(x)} [\text{KL} (p(z|x, \theta) \parallel q(z|x, \lambda))] \\
 &= \arg \min_{\lambda} \mathbb{E}_{p(x)} \mathbb{E}_{p(z|x, \theta)} [\log p(z|x, \theta) - \log q(z|x, \lambda)] \\
 &\stackrel{\text{asm}}{=} \arg \max_{\lambda} \mathbb{E}_{p(x, z|\theta)} [\log q(z|x, \lambda)] - \underbrace{\mathbb{E}_{p(x, z|\theta)} [\log p(z|x, \theta)]}_{\text{constant}}
 \end{aligned}$$

Gradient wrt λ

$$\nabla_{\lambda} \mathbb{E}_{p(x, z|\theta)} [\log q(z|x, \lambda)]$$

Sleep Phase (Convenient) Objective

Flip the direction of the KL

$$\begin{aligned}
 & \arg \min_{\lambda} \mathbb{E}_{p(x)} [\text{KL} (p(z|x, \theta) \parallel q(z|x, \lambda))] \\
 &= \arg \min_{\lambda} \mathbb{E}_{p(x)} \mathbb{E}_{p(z|x, \theta)} [\log p(z|x, \theta) - \log q(z|x, \lambda)] \\
 &\stackrel{\text{asm}}{=} \arg \max_{\lambda} \mathbb{E}_{p(x, z|\theta)} [\log q(z|x, \lambda)] - \underbrace{\mathbb{E}_{p(x, z|\theta)} [\log p(z|x, \theta)]}_{\text{constant}}
 \end{aligned}$$

Gradient wrt λ

$$\begin{aligned}
 & \nabla_{\lambda} \mathbb{E}_{p(x, z|\theta)} [\log q(z|x, \lambda)] \\
 &= \mathbb{E}_{p(x, z|\theta)} [\nabla_{\lambda} \log q(z|x, \lambda)]
 \end{aligned}$$

Sleep Phase (Convenient) Objective

Flip the direction of the KL

$$\begin{aligned}
 & \arg \min_{\lambda} \mathbb{E}_{p(x)} [\text{KL} (p(z|x, \theta) \parallel q(z|x, \lambda))] \\
 &= \arg \min_{\lambda} \mathbb{E}_{p(x)} \mathbb{E}_{p(z|x, \theta)} [\log p(z|x, \theta) - \log q(z|x, \lambda)] \\
 &\stackrel{\text{asm}}{=} \arg \max_{\lambda} \mathbb{E}_{p(x, z|\theta)} [\log q(z|x, \lambda)] - \underbrace{\mathbb{E}_{p(x, z|\theta)} [\log p(z|x, \theta)]}_{\text{constant}}
 \end{aligned}$$

Gradient wrt λ

$$\begin{aligned}
 & \nabla_{\lambda} \mathbb{E}_{p(x, z|\theta)} [\log q(z|x, \lambda)] \\
 &= \mathbb{E}_{p(x, z|\theta)} [\nabla_{\lambda} \log q(z|x, \lambda)] \\
 &\stackrel{\text{MC}}{\approx} \nabla_{\lambda} \log q(z|\tilde{x}, \lambda) \quad \text{where } z \sim p(z|\theta)
 \end{aligned}$$

$$\tilde{x} \sim p(x|z, \theta)$$

Sleep Phase (Convenient) Objective

Assumes **fake data** \tilde{x} and latent variables z to be fixed random draws from $p(x, z|\theta)$ via

$$z \sim p(z|\theta)$$

$$\tilde{x} \sim p(x|z, \theta)$$

and maximises $\log q(z|\tilde{x}, \lambda)$.

Wake-sleep Algorithm

Advantages

- Simple layer-wise updates
- Amortised inference: all latent variables are inferred from the same weights λ

Wake-sleep Algorithm

Advantages

- Simple layer-wise updates
- Amortised inference: all latent variables are inferred from the same weights λ

Drawbacks

- Inference and generative networks are trained on different objectives
- Inference weights λ are updated on fake data \tilde{x}
- Generative weights are bad initially, giving wrong signal to the updates of λ

- 1 First Attempt: Wake-Sleep
- 2 Neural Variational Inference and Learning
- 3 Score Function Estimator

Variational Inference Learning (NVIL)

Generative model with NN likelihood

Variational Inference Learning (NVIL)

Generative model with NN likelihood

Let us consider a latent factor model for topic modelling:

Variational Inference Learning (NVIL)

Generative model with NN likelihood

Let us consider a latent factor model for topic modelling:

- a document $x = (x_1, \dots, x_N)$ consists of n i.i.d. categorical draws from that model

Variational Inference Learning (NVIL)

Generative model with NN likelihood

Let us consider a latent factor model for topic modelling:

- a document $x = (x_1, \dots, x_N)$ consists of n i.i.d. categorical draws from that model
- the categorical distribution in turn depends on binary latent factors $z = (z_1, \dots, z_K)$ which are also i.i.d.

Latent factor model

$$Z_j \sim \text{Bernoulli}(\alpha) \quad (1 \leq k \leq K)$$


$$X_i|z \sim \text{Categorical}(f(z; \theta)) \quad (1 \leq i \leq N)$$

Here $0 < \alpha < 1$ specifies a Bernoulli prior and $f(\cdot; \theta)$ is a function computed by a neural network with softmax output, e.g.

$$f(z; \theta) = \text{softmax}(Wz + b)$$


$$\theta = \{W, b\}$$

Example Model



Joint distribution: independent latent variables


Example Model



Posterior: latent variables are marginally dependent.

For our variational distribution we are going to assume that they are not (recall: mean field assumption).

Mean Field Inference



The inference network needs to predict K Bernoulli parameters b_1^K . Any neural network with sigmoid output will do that job.

Inference Network

$$q(z|x, \lambda) = \prod_{k=1}^K \text{Bern}(z_k | b_k)$$

where $b_1^K = g(x; \lambda)$

Example architecture

$$h = \frac{1}{N} \sum_{i=1}^N E_{x_i} \quad b_1^K = \text{sigmoid}(Mh + c)$$

$$\lambda = \{E, M, c\}$$

Objective

$$\text{ELBO} = \mathbb{E}_{q(z|x, \lambda)} [\log p(x, z|\theta)] + \mathbb{H}(q(z|x, \lambda))$$

Objective

$$\begin{aligned}\text{ELBO} &= \mathbb{E}_{q(z|x, \lambda)} [\log p(x, z|\theta)] + \mathbb{H}(q(z|x, \lambda)) \\ &= \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \text{KL}(q(z|x, \lambda) \parallel p(z))\end{aligned}$$

Objective

$$\begin{aligned}\text{ELBO} &= \mathbb{E}_{q(z|x, \lambda)} [\log p(x, z|\theta)] + \mathbb{H}(q(z|x, \lambda)) \\ &= \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \text{KL}(q(z|x, \lambda) \parallel p(z))\end{aligned}$$

Parameter estimation

$$\arg \max_{\theta, \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \text{KL}(q(z|x, \lambda) \parallel p(z))$$

KL

KL between K independent Bernoulli distributions is tractable

$$\text{KL} (q(z|x, \lambda) \parallel p(z|\alpha)) = \sum_{k=1}^K \text{KL} (q(z_k|x, \lambda) \parallel p(z_k|\alpha))$$

KL

KL between K independent Bernoulli distributions is tractable

$$\begin{aligned}\text{KL}(q(z|x, \lambda) \parallel p(z|\alpha)) &= \sum_{k=1}^K \text{KL}(q(z_k|x, \lambda) \parallel p(z_k|\alpha)) \\ &= \sum_{k=1}^K \text{KL}(\text{Bernoulli}(b_k) \parallel \text{Bernoulli}(\alpha))\end{aligned}$$

KL

KL between K independent Bernoulli distributions is tractable

$$\begin{aligned}
 \text{KL}(q(z|x, \lambda) \parallel p(z|\alpha)) &= \sum_{k=1}^K \text{KL}(q(z_k|x, \lambda) \parallel p(z_k|\alpha)) \\
 &= \sum_{k=1}^K \text{KL}(\text{Bernoulli}(b_k) \parallel \text{Bernoulli}(\alpha)) \\
 &= \sum_{k=1}^K b_k \log \frac{b_k}{\alpha} + (1 - b_k) \log \frac{1 - b_k}{1 - \alpha}
 \end{aligned}$$

Generative Network Gradient

$$\frac{\partial}{\partial \theta} \left(\mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \overbrace{\text{KL}(q(z|x, \lambda) || p(z))}^{\text{constant wrt } \theta} \right)$$

Generative Network Gradient

$$\begin{aligned}
 & \frac{\partial}{\partial \theta} \left(\mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \overbrace{\text{KL}(q(z|x, \lambda) || p(z))}^{\text{constant wrt } \theta} \right) \\
 &= \underbrace{\mathbb{E}_{q(z|x, \lambda)} \left[\frac{\partial}{\partial \theta} \log p(x|z, \theta) \right]}_{\text{expected gradient :)}}
 \end{aligned}$$

Generative Network Gradient

$$\begin{aligned}
 & \frac{\partial}{\partial \theta} \left(\mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \overbrace{\text{KL}(q(z|x, \lambda) || p(z))}^{\text{constant wrt } \theta} \right) \\
 &= \underbrace{\mathbb{E}_{q(z|x, \lambda)} \left[\frac{\partial}{\partial \theta} \log p(x|z, \theta) \right]}_{\text{expected gradient :)}}
 \end{aligned}$$

$$\stackrel{\text{MC}}{\approx} \frac{1}{S} \sum_{s=1}^S \frac{\partial}{\partial \theta} \log p(x|z^{(s)}, \theta) \quad \text{where } z^{(s)} \sim q(z|x, \lambda)$$

Inference Network Gradient

$$\frac{\partial}{\partial \lambda} \left(\mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \overbrace{\text{KL} (q(z|x, \lambda) || p(z))}^{\text{analytical}} \right)$$

Inference Network Gradient

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \left(\mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \overbrace{\text{KL}(q(z|x, \lambda) || p(z))}^{\text{analytical}} \right) \\
 &= \frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \underbrace{\frac{\partial}{\partial \lambda} \text{KL}(q(z|x, \lambda) || p(z))}_{\text{analytical computation}}
 \end{aligned}$$

Inference Network Gradient

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \left(\mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \overbrace{\text{KL}(q(z|x, \lambda) || p(z))}^{\text{analytical}} \right) \\
 &= \frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] - \underbrace{\frac{\partial}{\partial \lambda} \text{KL}(q(z|x, \lambda) || p(z))}_{\text{analytical computation}}
 \end{aligned}$$

The first term again requires approximation by sampling, but there is a problem

Inference Network Gradient

$$\frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)]$$

Inference Network Gradient

$$\begin{aligned} & \frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)] \\ &= \frac{\partial}{\partial \lambda} \sum_z q(z|x, \lambda) \log p(x|z, \theta) \end{aligned}$$

Inference Network Gradient

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)] \\
 &= \frac{\partial}{\partial \lambda} \sum_z q(z|x, \lambda) \log p(x|z, \theta) \\
 &= \underbrace{\sum_z \frac{\partial}{\partial \lambda} (q(z|x, \lambda)) \log p(x|z, \theta)}_{\text{not an expectation}}
 \end{aligned}$$

Inference Network Gradient

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)] \\
 &= \frac{\partial}{\partial \lambda} \sum_z q(z|x, \lambda) \log p(x|z, \theta) \\
 &= \underbrace{\sum_z \frac{\partial}{\partial \lambda} (q(z|x, \lambda)) \log p(x|z, \theta)}_{\text{not an expectation}}
 \end{aligned}$$

- MC estimator is non-differentiable

Inference Network Gradient

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)] \\
 &= \frac{\partial}{\partial \lambda} \sum_z q(z|x, \lambda) \log p(x|z, \theta) \\
 &= \underbrace{\sum_z \frac{\partial}{\partial \lambda} (q(z|x, \lambda)) \log p(x|z, \theta)}_{\text{not an expectation}}
 \end{aligned}$$

- MC estimator is non-differentiable
- Differentiating the expression does not yield an expectation: cannot approximate via MC

Score Function Estimator

We can again use the log identity for derivatives

$$\begin{aligned} & \frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)] \\ &= \sum_z \frac{\partial}{\partial \lambda} (q(z|x, \lambda)) \log p(x|z, \theta) \end{aligned}$$

Score Function Estimator

We can again use the log identity for derivatives

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)] \\
 &= \sum_z \frac{\partial}{\partial \lambda} (q(z|x, \lambda)) \log p(x|z, \theta) \\
 &= \sum_z q(z|x, \lambda) \frac{\partial}{\partial \lambda} (\log q(z|x, \lambda)) \log p(x|z, \theta)
 \end{aligned}$$

Score Function Estimator

We can again use the log identity for derivatives

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \mathbb{E}_{q_{\lambda}(z|x)} [\log p_{\theta}(x|z)] \\
 &= \sum_z \frac{\partial}{\partial \lambda} (q(z|x, \lambda)) \log p(x|z, \theta) \\
 &= \sum_z q(z|x, \lambda) \frac{\partial}{\partial \lambda} (\log q(z|x, \lambda)) \log p(x|z, \theta) \\
 &= \underbrace{\mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right]}_{\text{expected gradient :)}}
 \end{aligned}$$

Score Function Estimator

We can now build an MC estimator

$$\begin{aligned} & \frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] \\ &= \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right] \end{aligned}$$


Score Function Estimator

We can now build an MC estimator

$$\begin{aligned}
 & \frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] \\
 &= \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right] \\
 &\stackrel{\text{MC}}{\approx} \frac{1}{S} \sum_{s=1}^S \log p(x|z^{(s)}, \theta) \frac{\partial}{\partial \lambda} \log q(z^{(s)}|x, \lambda)
 \end{aligned}$$

where $z^{(s)} \sim q(z|x, \lambda)$


Computation Graph



inference model


Computation Graph

$$z \sim \text{Bernoulli}(b)$$



inference model


Computation Graph



inference model

generation model


Computation Graph



inference model

generation model

Computation Graph



inference model

generation model

Score Function Estimator: Variance

$$\frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] = \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right]$$

Score Function Estimator: Variance

$$\frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] = \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right]$$

Empirically this estimator often exhibits high variance.

Score Function Estimator: Variance

$$\frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] = \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right]$$

Empirically this estimator often exhibits high variance.

- the magnitude of $\log p(x|z, \theta)$ varies widely

Score Function Estimator: Variance

$$\frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] = \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right]$$

Empirically this estimator often exhibits high variance.

- the magnitude of $\log p(x|z, \theta)$ varies widely
- the model likelihood does not contribute to direction of gradient

Score Function Estimator: Variance

We could:

Score Function Estimator: Variance

We could:

- sample more (better MC estimates)

Score Function Estimator: Variance

We could:

- sample more (better MC estimates)
- use variance reduction techniques (e.g. baselines and control variates)

Score Function Estimator: Variance

Idea: standardise the “reward” $r(z) := \log p(x|z, \theta)$ to have a mean at 0 and a variance of 1

Score Function Estimator: Variance

Idea: standardise the “reward” $r(z) := \log p(x|z, \theta)$ to have a mean at 0 and a variance of 1

- Keep a moving average of the mean and variance $\log p(x|z, \theta)$: $\hat{\mu}$ and $\hat{\sigma}^2$.

Score Function Estimator: Variance

Idea: standardise the “reward” $r(z) := \log p(x|z, \theta)$ to have a mean at 0 and a variance of 1

- Keep a moving average of the mean and variance $\log p(x|z, \theta)$: $\hat{\mu}$ and $\hat{\sigma}^2$.
- $\hat{r}(z) = \frac{\log p(x|z, \theta) - \hat{\mu}}{\hat{\sigma}^2}$

Score Function Estimator: Variance

Idea: standardise the “reward” $r(z) := \log p(x|z, \theta)$ to have a mean at 0 and a variance of 1

- Keep a moving average of the mean and variance $\log p(x|z, \theta)$: $\hat{\mu}$ and $\hat{\sigma}^2$.
- $\hat{r}(z) = \frac{\log p(x|z, \theta) - \hat{\mu}}{\hat{\sigma}^2}$

$$\frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] = \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right]$$

Score Function Estimator: Variance

Idea: standardise the “reward” $r(z) := \log p(x|z, \theta)$ to have a mean at 0 and a variance of 1

- Keep a moving average of the mean and variance $\log p(x|z, \theta)$: $\hat{\mu}$ and $\hat{\sigma}^2$.
- $\hat{r}(z) = \frac{\log p(x|z, \theta) - \hat{\mu}}{\hat{\sigma}^2}$

$$\begin{aligned} \frac{\partial}{\partial \lambda} \mathbb{E}_{q(z|x, \lambda)} [\log p(x|z, \theta)] &= \mathbb{E}_{q(z|x, \lambda)} \left[\log p(x|z, \theta) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right] \\ &\approx \mathbb{E}_{q(z|x, \lambda)} \left[\hat{r}(z) \frac{\partial}{\partial \lambda} \log q(z|x, \lambda) \right] \end{aligned}$$

Score Function Estimator: Variance

- We can show that using these *baselines* do not bias the estimator.

Score Function Estimator: Variance

- We can show that using these *baselines* do not bias the estimator.
- We can add more advanced *control variates* and other *baselines* to further reduce variance.

Score Function Estimator: Variance

- We can show that using these *baselines* do not bias the estimator.
- We can add more advanced *control variates* and other *baselines* to further reduce variance.
- More about this tomorrow!

Pros and Cons

Pros:

- Applicable to all distributions
- Many libraries come with samplers for common distributions

Pros and Cons

Pros:

- Applicable to all distributions
- Many libraries come with samplers for common distributions

Cons:

- High Variance!

Summary

- Wake-Sleep: train inference and generation networks with separate objectives

Summary

- Wake-Sleep: train inference and generation networks with separate objectives
- NVIL: a single objective (ELBO) for both models

Summary

- Wake-Sleep: train inference and generation networks with separate objectives
- NVIL: a single objective (ELBO) for both models
- Use score function estimator

Summary

- Wake-Sleep: train inference and generation networks with separate objectives
- NVIL: a single objective (ELBO) for both models
- Use score function estimator
- Always use baselines for variance reduction!

Implementation

Check one of our notebooks, e.g.

- inducing rationales for sentiment classification
github.com/vitutorial/exercises/tree/master/SST

Literature I

- G. E. Hinton, P. Dayan, B. J. Frey, and R. M. Neal. The wake-sleep algorithm for unsupervised neural networks. *Science*, 268:1158–1161, 1995. URL <http://www.gatsby.ucl.ac.uk/~dayan/papers/hdfn95.pdf>.
- Ronald J. Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine Learning*, 8(3-4):229–256, 1992. URL <https://doi.org/10.1007/BF00992696>.

Literature II

Andriy Mnih and Karol Gregor. Neural variational inference and learning in belief networks. In *Proceedings of the 31st International Conference on International Conference on Machine Learning - Volume 32*, ICML'14, pages II-1791-II-1799. JMLR.org, 2014. URL <http://dl.acm.org/citation.cfm?id=3044805.3045092>.

Rajesh Ranganath, Sean Gerrish, and David Blei. Black Box Variational Inference. In Samuel Kaski and Jukka Corander, editors, *AISTATS*, pages 814-822, 2014. URL <http://proceedings.mlr.press/v33/ranganath14.pdf>.