


HDC Connections Chamber side

From	Cable colour / size AWG	Length mm	To Pin
Chamber Heater L	Brown Silicone 600V /18	500	1
Chamber Heater N	Blue Silicone 600V /18	500	2
Chamber Heater E	Green Silicone 600V /18	500	3
N/C			4
N/C			5
N/C			6


HDC 1 Male



Screw terminals view

From	Cable colour / size AWG	Length mm	To pin
N/C			1
N/C			2
Fan Chamber Tacho	yellow/22	500	3
Fan Chamber PWM	Blue/ 22	500	4
Fan Chamber +12	Red /18	500	5
Fan Chamber gnd	Black/18	500	6


HDC 2 Female




Screw terminal view

From	Cable colour / size AWG	Length mm	To Pin
Heated Bed L	Used Supplied? Via thermal Fuse	500	1
Heated Bed N	Used Supplied	500	2
Aluminium Bed	Green silicion 600V /18	500	3
N/C			4
N/C			5
Heater Bed Thermistor	Used Supplied	500	6
Heater Bed Thermistor	Used Supplied	500	7
N/C			8
Tool Sensor	white/22	800	9
Tool Sensor	white/22	800	10

HDC 3 Female



Screw terminal view




HDC, 1 2 3

Place a blob of RTV over the L and N connections , safety precaution in case the screws come loose!

HDC Connections Buddy side


HDC 1 Female



Screw terminal view

From pin	Cable colour/size AWG	Length mm	To
1	Brown Silicone 600V / 18	700	SSR Chamber Terminal 2
2	Blue Silicone 600V / 18	400	Blue Terminal Block
3	Green Silicone 600V / 18	400	Earth Terminal Block
4			N/C
5			N/C
6			N/C


HDC 2 Male



Screw terminals view


FromPin	Cable colour/size AWG	Length mm	To
1			N/C
2			N/C
3	yellow/22	700	out6.tach
4	Blue/ 22	700	out6_out
5	Red /18	400	Yellow Terminal Block
6	Black/18	400	Black Terminal Block

HDC 3 Male



Screw terminals view

From Pin	Cable colour/size AWG	Length mm	To
1	Brown Silicone 600V / 18	700	SSR BED Terminal 2
2	Blue Silicone 600V / 18	400	Blue Terminal Block
3	Green Silicone 600V / 18	400	Earth Terminal Block
4			N/C
5			N/C
6	yellow / 22	700	TENP 3/VSSA
7	yellow / 22	700	TENP 3/temp3
8			N/C
9	white / 22	700	IO_4/io4in
10	white / 22	700	IO_4/GND



HDC, 1 2 3

Place a blob of RTV over the L and N connections , safety precaution in case the screws come loose!