


GX20 Duet 6HC Connections

GX20 10 M



Plug viewed from solder side

From Pin Num	Device	Wire Col/Size	Length	To Duet
1	N/C			N/C
2	N/C			N/C
3	Pt1000 Temperature sensor	White/24	600mm	TEMP0/VSSA
4	PT1000 Temperature sensor	White/24	600mm	TEMP0/temp0
5	Thermistor extruder	Blue/24	600mm	TEMP1/VSSA
6	Thermistor extruder	Blue//24	600mm	TEMP1/VSSA
7	Thermistor CPAP Air	Red/22/	600mm	IO_5_in/io5.in
8	Thermistor CPAP Air	Black/22	600mm	IO_5_gnd/GND
9	Flint Zone Probe	White/22	600mm	IO_4_in/io4.in
10	Flint Zone Probe	White/22	600mm	IO4_gnd/GND

GX20 6 M



Plug viewed from solder side

From Pim Num	Device	Wire Col/Size	Length	To Duet
1	Heater Cartridge +	White/18	600mm	OUT1/V_Fused
2	Heater Cartridge -	White/18	600mm	OUT1/out1
3	Stepper motor A2	Black/ 18	600mm	Driver2/A2
4	Stepper motor A1	Green/18	600mm	Driver2/A1
5	Stepper motor B1	Blue/18	600mm	Driver2/B1
6	Stepper motor B2	Red/18	600mm	Driver2/B2

Max wire size for:-
6 Pin 16 AWG
10 Pin 20 AWG