


GX20 Male wiring to Duet V1


GX20 10 M



Plug viewed from
solder side

1	Fan Extruder +	Red/22awg	600mm	Duet connection
2	Fan Extruder -	Black/22awg	600mm	NC
3	Pt1000 Temperature sensor	white/24awg	600mm	NC
4	PT1000 Temperature sensor	white/24awg	600mm	TEMP0/VSSA
5	thermistor extruder	blue/24awg	600mm	TEMP0/temp0
6	thermistor extruder	blue//24awg	600mm	TEMP1/VSSA
7	Part cooling Fan +	Red/22/awg	600mm	TEMP1/VSSA
8	Part cooling Fan -	Black/22awg	600mm	N/C
9	Flint Zone Probe	White/22awg	600mm	N/C
10	Flint Zone Probe	White/22awg	600mm	IO_4_in/io4.in
				IO4_gnd/GND

GX20 6 M



Plug viewed from
solder side

				Duet Connection
1	Heater Cartridge +	white/18awg	600mm	OUT1/V_Fused
2	Heater Cartridge -	white/18awg	600mm	OUT1/out1
3	Stepper motor A2	Black/ 18awg	600mm	Driver2/A2
4	Stepper motor A1	Green/18awg	600mm	Driver2/A1
5	Stepper motor B1	Blue/18awg	600mm	Driver2/B1
6	Stepper motor B2	Red/18awg	600mm	Driver2/B2

Max wire size for:-

6 Pin 16 AWG

10 Pin 20 AWG